

System F Language Specification

Syntax

| | | | |
|--------|------|---|--|
| e | $:=$ | lit eid (e) $e[\tau]$ $e_1 e_2$ $(\overline{e})^{(\geq 2)}$ $e_1 \text{ op } e_2$ $\Lambda \overline{tid}^{(\geq 1)}. e$ $\lambda \overline{eid} : \tau^{(\geq 1)}. e$ $\text{if } e_1 \text{ then } e_2 \text{ else } e_3$ $\text{let } eid : \tau = e_1 \text{ in } e_2$ $\text{match } e \text{ with } \overline{pat} => e^+$ | literals expression identifier parenthesized type application application tuples infix operation parametric polymorphism anonymous function if expression let binding pattern destructing |
| τ | $:=$ | tid (τ) $\tau_1 \tau_2$ $\tau_1 * \tau_2$ $\tau_1 \rightarrow \tau_2$ $\forall \overline{tid}^{(\geq 1)}. \tau$ $\text{Int} \mid \text{Bool} \mid \text{Unit}$ | type identifier parenthesized type application tuple types arrow types universal types built-in types |
| lit | $:=$ | null $\text{true} \mid \text{false}$ $\dots \mid \sim 2 \mid \sim 1 \mid 0 \mid 1 \mid 2 \mid \dots$ | unit literal boolean literals 64 bit signed integers |
| pat | $:=$ | $-$ $\overline{eid} : \tau$ $(\overline{pat})^{(\geq 2)}$ | wildcard, producing no bindings binds a single expression destructs a tuple |

Multiple argument λ 's (and \forall 's) are syntactic sugar for nested functions. For instance,

$$\lambda x: \text{int}, y: \text{int}. x + y \stackrel{\text{def}}{=} \lambda x: \text{int}. \lambda y: \text{int}. x + y$$

Semantics:

CBV big step semantics with capture-avoiding substitution.

When a bound variable is bound again, the new binding takes over.

There is no one-type tuples

Lexical scope.