

Run system panic diagnostics

ONTAP Systems

Martin Houser September 28, 2021

This PDF was generated from https://docs.netapp.com/us-en/ontap-systems/platform-supplemental/sldiag-system-panic-diagnostics.html on October 26, 2021. Always check docs.netapp.com for the latest.

Table of Contents

un system panic diagnostics

Run system panic diagnostics

Running diagnostics after your storage system suffers a system panic can help you to identify the possible cause of the panic.

- 1. At the storage system prompt, switch to the LOADER prompt: halt
- Enter the following command at the LOADER prompt: boot_diags



You must run this command from the LOADER prompt for system-level diagnostics to function properly. The boot_diags command starts special drivers designed specifically for system-level diagnostics.

- Run diagnostics on all the devices by entering the following command: sldiag device run
- 4. View the status of the test by entering the following command: sldiag device status

Your storage system provides the following output while the tests are still running:

```
There are still test(s) being processed.
```

After all the tests are complete, you receive the following default response:

```
*> <SLDIAG:_ALL_TESTS_COMPLETED>
```

5. Identify the cause of the system panic by entering the following command: sldiag device status -long -state failed

The following example shows how the full status of the failures is displayed in a test run without the appropriate hardware:

```
DEVTYPE: fcal
NAME: Fcal Loopback Test
START DATE: Sat Jan 3 23:10:56 GMT 2009
STATUS: Completed
Starting test on Fcal Adapter: Ob
Started gathering adapter info.
Adapter get adapter info OK
Adapter fc data link rate: 1Gib
Adapter name: QLogic 2532
Adapter firmware rev: 4.5.2
Adapter hardware rev: 2
Started adapter get WWN string test.
Adapter get WWN string OK wwn str: 5:00a:098300:035309
Started adapter interrupt test
Adapter interrupt test OK
Started adapter reset test.
Adapter reset OK
Started Adapter Get Connection State Test.
Connection State: 5
Loop on FC Adapter Ob is OPEN
Started adapter Retry LIP test
Adapter Retry LIP OK
ERROR: failed to init adaptor port for IOCTL call
ioctl status.class type = 0x1
ioctl status.subclass = 0x3
ioctl status.info = 0x0
Started INTERNAL LOOPBACK:
INTERNAL LOOPBACK OK
Error Count: 2 Run Time: 70 secs
>>>> ERROR, please ensure the port has a shelf or plug.
END DATE: Sat Jan 3 23:12:07 GMT 2009
LOOP: 1/1
TEST END -----
```

If the system-level diagnostics tests	Then
Were completed without any failures	There are no hardware problems and your storage system returns to the prompt.
	a. Clear the status logs by entering the following command: sldiag device clearstatus
	b. Verify that the log is cleared by entering the following command: sldiag device status
	The following default response is displayed:
	SLDIAG: No log messages are present.
	c. Exit Maintenance mode by entering the following command: halt
	d. Enter the following command at the Loader prompt to boot the storage system: boot_ontap You have completed system-level diagnostics.
Resulted in some test failures	Determine the cause of the problem.
	a. Exit Maintenance mode by entering the following command: halt
	b. Perform a clean shutdown and disconnect the power supplies.
	c. Verify that you have observed all the considerations identified for running system-level diagnostics, that cables are securely connected, and that hardware components are properly installed in the storage system.
	d. Reconnect the power supplies and power on the storage system.
	e. Repeat Steps 1 through 5 of Running system panic diagnostics.

If the failures persist after repeating the steps, you need to replace the hardware.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.