

Java Message Service

The JMS API is an API for accessing enterprise messaging systems from Java programs

Version 2.0 (Public Draft – unreleased draft)

Mark Hapner, Rich Burrige, Rahul Sharma, Joseph Fialli, Kate Stout
Sun Microsystems
(Version 1.1)

Nigel Deakin
Oracle
(Version 2.0)

5 September 2012

Please send comments to users@jms-spec.java.net
For information about how to contribute to JMS 2.0
visit <http://jms-spec.java.net>

License

Specification: JSR-343 Java Message Service 2.0 ("Specification")

Version: 2.0

Status: Public Draft Review

Release: 14 April 2012

Copyright 2012 Oracle America, Inc.

500 Oracle Parkway, Redwood City, California 94065, U.S.A.

All rights reserved.

NOTICE

The Specification is protected by copyright and the information described therein may be protected by one or more U.S. patents, foreign patents, or pending applications. Except as provided under the following license, no part of the Specification may be reproduced in any form by any means without the prior written authorization of Oracle America, Inc. ("Oracle") and its licensors, if any. Any use of the Specification and the information described therein will be governed by the terms and conditions of this Agreement.

Subject to the terms and conditions of this license, including your compliance with Paragraphs 1 and 2 below, Oracle hereby grants you a fully-paid, non-exclusive, non-transferable, limited license (without the right to sublicense) under Oracle's intellectual property rights to:

1. Review the Specification for the purposes of evaluation. This includes: (i) developing implementations of the Specification for your internal, non-commercial use; (ii) discussing the Specification with any third party; and (iii) excerpting brief portions of the Specification in oral or written communications which discuss the Specification provided that such excerpts do not in the aggregate constitute a significant portion of the Technology.

2. Distribute implementations of the Specification to third parties for their testing and evaluation use, provided that any such implementation:

(i) does not modify, subset, superset or otherwise extend the Licensor Name Space, or include any public or protected packages, classes, Java interfaces, fields or methods within the Licensor Name Space other than those required/authorized by the Specification or Specifications being implemented;

(ii) is clearly and prominently marked with the word "UNTESTED" or "EARLY ACCESS" or "INCOMPATIBLE" or "UNSTABLE" or "BETA" in any list of available builds and in proximity to every link initiating its download, where the list or link is under Licensee's control; and

(iii) Includes the following notice:

"This is an implementation of an early-draft specification developed under the Java Community Process (JCP) and is made available for testing and evaluation purposes only. The code is not compatible with any specification of the JCP."

The grant set forth above concerning your distribution of implementations of the specification is contingent upon your agreement to terminate development and distribution of your "early draft" implementation as soon as feasible following final completion of the specification. If you fail to do so, the foregoing grant shall be considered null and void.

No provision of this Agreement shall be understood to restrict your ability to make and distribute to third parties applications written to the Specification.

Other than this limited license, you acquire no right, title or interest in or to the Specification or any other Oracle intellectual property, and the Specification may only be used in accordance with the license terms set forth herein. This license will expire on the earlier of: (a) two (2) years from the date of Release listed above; (b) the date on which the final version of the Specification is publicly released; or (c) the date on which the Java Specification Request (JSR) to which the Specification corresponds is withdrawn. In addition, this license will terminate immediately without notice from Oracle if you fail to comply with any provision of this license. Upon termination, you must cease use of or destroy the Specification.

"Licensor Name Space" means the public class or interface declarations whose names begin with "java", "javax", "com.oracle" or their equivalents in any subsequent naming convention adopted by Oracle through the Java Community Process, or any recognized successors or replacements thereof

TRADEMARKS

No right, title, or interest in or to any trademarks, service marks, or trade names of Oracle or Oracle's licensors is granted hereunder. Oracle, the Oracle logo, Java are trademarks or registered trademarks of Oracle USA, Inc. in the U.S. and other countries.

DISCLAIMER OF WARRANTIES

THE SPECIFICATION IS PROVIDED "AS IS" AND IS EXPERIMENTAL AND MAY CONTAIN DEFECTS OR DEFICIENCIES WHICH CANNOT OR WILL NOT BE CORRECTED BY ORACLE. ORACLE MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT THAT THE CONTENTS OF THE SPECIFICATION ARE

SUITABLE FOR ANY PURPOSE OR THAT ANY PRACTICE OR IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADE SECRETS OR OTHER RIGHTS. This document does not represent any commitment to release or implement any portion of the Specification in any product.

THE SPECIFICATION COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION THEREIN; THESE CHANGES WILL BE INCORPORATED INTO NEW VERSIONS OF THE SPECIFICATION, IF ANY. ORACLE MAY MAKE IMPROVEMENTS AND/OR CHANGES TO THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THE SPECIFICATION AT ANY TIME. Any use of such changes in the Specification will be governed by the then-current license for the applicable version of the Specification.

LIMITATION OF LIABILITY

TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL ORACLE OR ITS LICENSORS BE LIABLE FOR ANY DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUE, PROFITS OR DATA, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF OR RELATED TO ANY FURNISHING, PRACTICING, MODIFYING OR ANY USE OF THE

SPECIFICATION, EVEN IF ORACLE AND/OR ITS LICENSORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You will hold Oracle (and its licensors) harmless from any claims based on your use of the Specification for any purposes other than the limited right of evaluation as described above, and from any claims that later versions or releases of any Specification furnished to you are incompatible with the Specification provided to you under this license.

RESTRICTED RIGHTS LEGEND

If this Software is being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), then the Government's rights in the Software and accompanying documentation shall be only as set forth in this license; this is in accordance with 48 C.F.R. 227.7201 through 227.7202-4 (for Department of Defense (DoD) acquisitions) and with 48 C.F.R. 2.101 and 12.212 (for non-DoD acquisitions).

REPORT

You may wish to report any ambiguities, inconsistencies or inaccuracies you may find in connection with your evaluation of the Specification ("Feedback"). To the extent that you provide Oracle with any Feedback, you hereby: (i) agree that such Feedback is provided on a non-proprietary and non-confidential basis, and (ii) grant Oracle a perpetual, non-exclusive, worldwide, fully paid-up, irrevocable license, with the right to sublicense through multiple levels of sublicensees, to incorporate, disclose, and use without limitation the Feedback for any purpose related to the Specification and future versions, implementations, and test suites thereof.

GENERAL TERMS

Any action related to this Agreement will be governed by California law and controlling U.S. federal law. The U.N. Convention for the International Sale of Goods and the choice of law rules of any jurisdiction will not apply.

The Specification is subject to U.S. export control laws and may be subject to export or import regulations in other countries. Licensee agrees to comply strictly with all such laws and regulations and acknowledges that it has the responsibility to obtain such licenses to export, re-export or import as may be required after delivery to Licensee.

This Agreement is the parties' entire agreement relating to its subject matter. It supersedes all prior or contemporaneous oral or written communications, proposals, conditions, representations and warranties and prevails over any conflicting or additional terms of any quote, order, acknowledgment, or other communication between the parties relating to its subject matter during the term of this Agreement. No modification to this Agreement will be binding, unless in writing and signed by an authorized representative of each party.

Contents

| | |
|--|-----------|
| License | 2 |
| Contents | 5 |
| 1. Introduction | 12 |
| 1.1. Abstract | 12 |
| 1.2. Overview | 12 |
| 1.2.1. Is this a mail API? | 12 |
| 1.2.2. Existing messaging systems | 12 |
| 1.2.3. JMS objectives | 13 |
| 1.2.4. What JMS does not include | 14 |
| 1.3. What is required by JMS | 15 |
| 1.4. Relationship to other Java APIs | 15 |
| 1.4.1. Java DataBase Connectivity (JDBC™) software | 15 |
| 1.4.2. JavaBeans™ components | 15 |
| 1.4.3. Enterprise JavaBeans™ component model | 15 |
| 1.4.4. Java Transaction API (JTA) | 15 |
| 1.4.5. Java Transaction Service (JTS) | 15 |
| 1.4.6. Java Naming and Directory Interface™ (JNDI) API | 16 |
| 1.4.7. Java Platform, Enterprise Edition (Java EE) | 16 |
| 1.4.8. Contexts and dependency injection (CDI) | 16 |
| 1.5. What is new in JMS 1.1? | 16 |
| 1.6. What is new in JMS 2.0? | 17 |
| 2. Architecture | 18 |
| 2.1. Overview | 18 |
| 2.2. What is a JMS application? | 18 |
| 2.3. Administration | 18 |
| 2.4. Two messaging styles | 19 |
| 2.5. JMS interfaces | 19 |
| 2.6. Developing a JMS application | 20 |
| 2.6.1. Developing a JMS client | 21 |
| 2.7. Security | 21 |
| 2.8. Multi-threading | 21 |
| 2.9. Triggering clients | 22 |
| 2.10. Request/reply | 22 |
| 3. JMS message model | 23 |
| 3.1. Background | 23 |
| 3.2. Goals | 23 |
| 3.3. JMS messages | 23 |
| 3.4. Message header fields | 24 |
| 3.4.1. JMSDestination | 24 |
| 3.4.2. JMSDeliveryMode | 24 |
| 3.4.3. JMSMessageID | 24 |
| 3.4.4. JMSTimestamp | 25 |
| 3.4.5. JMSCorrelationID | 25 |
| 3.4.6. JMSReplyTo | 26 |
| 3.4.7. JMSRedelivered | 26 |
| 3.4.8. JMSType | 26 |
| 3.4.9. JMSExpiration | 26 |
| 3.4.10. JMSPriority | 27 |
| 3.4.11. How message header values are set | 27 |

| | | |
|-----------|---|-----------|
| 3.4.12. | Overriding message header fields | 28 |
| 3.4.13. | JMSDeliveryTime | 28 |
| 3.5. | Message properties | 29 |
| 3.5.1. | Property names | 29 |
| 3.5.2. | Property values | 29 |
| 3.5.3. | Using properties | 29 |
| 3.5.4. | Property value conversion | 29 |
| 3.5.5. | Property values as objects | 30 |
| 3.5.6. | Property iteration | 30 |
| 3.5.7. | Clearing a message's property values | 30 |
| 3.5.8. | Non-existent properties | 30 |
| 3.5.9. | JMS defined properties | 30 |
| 3.5.10. | Provider-specific properties | 32 |
| 3.5.11. | JMSXDeliveryCount | 32 |
| 3.6. | Message acknowledgment | 32 |
| 3.7. | The Message interface | 32 |
| 3.8. | Message selection | 33 |
| 3.8.1. | Message selector | 33 |
| 3.9. | Access to sent messages | 38 |
| 3.10. | Changing the value of a received message | 38 |
| 3.11. | JMS message body | 38 |
| 3.11.1. | Clearing a message body | 39 |
| 3.11.2. | Read-only message body | 39 |
| 3.11.3. | Conversions provided by StreamMessage and MapMessage | 39 |
| 3.11.4. | Messages for non-JMS clients | 40 |
| 3.12. | Provider implementations of JMS message interfaces | 40 |
| 4. | JMS common facilities | 42 |
| 4.1. | Overview | 42 |
| 4.2. | Administered objects | 42 |
| 4.2.1. | Destination | 42 |
| 4.2.2. | ConnectionFactory | 43 |
| 4.3. | Connection | 43 |
| 4.3.1. | Authentication | 43 |
| 4.3.2. | Client identifier | 44 |
| 4.3.3. | Connection setup | 44 |
| 4.3.4. | Pausing delivery of incoming messages | 45 |
| 4.3.5. | Closing a Connection | 45 |
| 4.3.6. | Sessions | 46 |
| 4.3.7. | ConnectionMetaData | 46 |
| 4.3.8. | ExceptionListener | 47 |
| 4.4. | Session | 47 |
| 4.4.1. | Closing a Session | 48 |
| 4.4.2. | MessageProducer and MessageConsumer Creation | 49 |
| 4.4.3. | Creating temporary destinations | 49 |
| 4.4.4. | Creating Destination objects | 49 |
| 4.4.5. | Optimized message implementations | 49 |
| 4.4.6. | Conventions for using a session | 50 |
| 4.4.7. | Transactions | 51 |
| 4.4.8. | Distributed transactions | 51 |
| 4.4.9. | Multiple sessions | 52 |
| 4.4.10. | Message order | 52 |
| 4.4.11. | Message acknowledgment | 53 |
| 4.4.12. | Duplicate delivery of messages | 53 |
| 4.4.13. | Duplicate production of messages | 54 |
| 4.4.14. | Serial execution of client code | 54 |
| 4.4.15. | Concurrent message delivery | 54 |

| | | |
|-----------|--|-----------|
| 4.5. | MessageConsumer | 55 |
| 4.5.1. | Synchronous delivery | 55 |
| 4.5.2. | Asynchronous delivery | 55 |
| 4.6. | MessageProducer | 55 |
| 4.6.1. | Synchronous send | 56 |
| 4.6.2. | Asynchronous send | 56 |
| 4.7. | Message delivery mode | 59 |
| 4.8. | Message time-to-live | 59 |
| 4.9. | Exceptions | 59 |
| 4.10. | Reliability | 60 |
| 4.11. | Method inheritance across messaging domains | 61 |
| 4.12. | Delivery delay | 61 |
| 5. | JMS point-to-point model | 62 |
| 5.1. | Overview | 62 |
| 5.2. | Queue management | 62 |
| 5.3. | Queue | 63 |
| 5.4. | TemporaryQueue | 63 |
| 5.5. | QueueConnectionFactory | 63 |
| 5.6. | QueueConnection | 63 |
| 5.7. | QueueSession | 63 |
| 5.8. | QueueReceiver | 63 |
| 5.9. | QueueBrowser | 64 |
| 5.10. | QueueRequestor | 64 |
| 5.11. | Reliability | 64 |
| 6. | JMS publish/subscribe model | 65 |
| 6.1. | Overview | 65 |
| 6.2. | Pub/sub latency | 65 |
| 6.3. | Durable subscription | 66 |
| 6.4. | Topic management | 66 |
| 6.5. | Topic | 66 |
| 6.6. | TemporaryTopic | 67 |
| 6.7. | TopicConnectionFactory | 67 |
| 6.8. | TopicConnection | 67 |
| 6.9. | TopicSession | 67 |
| 6.10. | TopicPublisher | 67 |
| 6.11. | TopicSubscriber | 68 |
| 6.11.1. | Unshared non-durable subscriptions | 68 |
| 6.11.2. | Shared non-durable subscriptions | 69 |
| 6.11.3. | Durable subscriptions | 70 |
| 6.12. | Recovery and redelivery | 71 |
| 6.13. | Administering subscriptions | 71 |
| 6.14. | TopicRequestor | 71 |
| 6.15. | Reliability | 72 |
| 7. | JMS exceptions | 73 |
| 7.1. | Overview | 73 |
| 7.2. | The JMSEException | 73 |
| 7.3. | Standard exceptions | 73 |
| 8. | JMS application server facilities | 75 |
| 8.1. | Overview | 75 |
| 8.2. | Concurrent processing of a subscription's messages | 75 |
| 8.2.1. | Session | 75 |
| 8.2.2. | ServerSession | 76 |
| 8.2.3. | ServerSessionPool | 76 |

| | | |
|------------|--|-----------|
| 8.2.4. | ConnectionConsumer | 76 |
| 8.2.5. | How a ConnectionConsumer uses a ServerSession..... | 76 |
| 8.2.6. | How an application server implements a ServerSession..... | 77 |
| 8.2.7. | The result | 77 |
| 8.3. | XAConnectionFactory | 79 |
| 8.4. | XAConnection | 79 |
| 8.5. | XASession | 79 |
| 8.6. | JMS application server interfaces..... | 80 |
| 9. | JMS example code | 81 |
| 9.1. | Preparing to send and receive messages | 81 |
| 9.1.1. | Getting a ConnectionFactory | 81 |
| 9.1.2. | Getting a Destination | 82 |
| 9.1.3. | Creating a Connection | 82 |
| 9.1.4. | Creating a Session | 82 |
| 9.1.5. | Creating a MessageProducer | 83 |
| 9.1.6. | Creating a MessageConsumer | 83 |
| 9.1.7. | Starting message delivery..... | 83 |
| 9.1.8. | Using a TextMessage | 83 |
| 9.2. | Sending and receiving messages | 84 |
| 9.2.1. | Sending a message | 84 |
| 9.2.2. | Receiving a message synchronously..... | 84 |
| 9.2.3. | Unpacking a TextMessage | 84 |
| 9.3. | Other messaging features | 84 |
| 9.3.1. | Receiving messages asynchronously | 85 |
| 9.3.2. | Using message selection..... | 85 |
| 9.3.3. | Using durable subscriptions | 86 |
| 9.4. | JMS message types | 87 |
| 9.4.1. | Creating a TextMessage | 88 |
| 9.4.2. | Unpacking a TextMessage | 88 |
| 9.4.3. | Creating a BytesMessage | 88 |
| 9.4.4. | Unpacking a BytesMessage..... | 88 |
| 9.4.5. | Creating a MapMessage | 88 |
| 9.4.6. | Unpacking a MapMessage | 89 |
| 9.4.7. | Creating a StreamMessage | 89 |
| 9.4.8. | Unpacking a StreamMessage..... | 90 |
| 9.4.9. | Creating an ObjectMessage..... | 91 |
| 9.4.10. | Unpacking an ObjectMessage | 91 |
| 10. | Use of JMS API in Java EE applications | 93 |
| 10.1. | Overview | 93 |
| 10.2. | Restrictions on the use of JMS API in the Java EE web or EJB container..... | 93 |
| 10.3. | Behaviour of JMS sessions in the Java EE web or EJB container | 95 |
| 10.3.1. | MDB topic subscriptions Error! Bookmark not defined. | |
| 11. | Simplified JMS API | 98 |
| 11.1. | Goals of the simplified API..... | 99 |
| 11.2. | Key features of the simplified API..... | 99 |
| 11.2.1. | JMSContext | 99 |
| 11.2.2. | Static constants for session mode | 101 |
| 11.2.3. | Creating messages..... | 101 |
| 11.2.4. | Sending messages | 101 |
| 11.2.5. | Consuming messages | 103 |
| 11.2.6. | Closing the JMSContext..... | 105 |

| | | |
|------------|---|------------|
| 11.2.7. | Automatic start of message delivery..... | 106 |
| 11.2.8. | Threading restrictions on a JMSContext..... | 106 |
| 11.2.9. | Exceptions | 107 |
| 11.3. | Injection of JMSContext objects | 107 |
| 11.3.1. | Support for injection | 107 |
| 11.3.2. | Container-managed and application-managed JMSContexts | 107 |
| 11.3.3. | Injection syntax..... | 108 |
| 11.3.4. | Scope of injected JMSContext objects | 109 |
| 11.3.5. | Restrictions on use of injected JMSContext objects | 110 |
| 11.4. | Examples using the simplified API | 110 |
| 11.4.1. | Sending a message (Java EE) | 110 |
| 11.4.2. | Sending a message (Java SE) | 111 |
| 11.4.3. | Sending a message with properties (Java SE) | 112 |
| 11.4.4. | Receiving a message synchronously (Java EE) | 113 |
| 11.4.5. | Receiving a message synchronously (Java SE)..... | 115 |
| 11.4.6. | Receiving a message synchronously from a durable subscription (Java EE)..... | 116 |
| 11.4.7. | Receiving messages asynchronously (Java SE) | 117 |
| 11.4.8. | Receiving a message asynchronously from a durable subscription (Java SE)..... | 118 |
| 11.4.9. | Receiving messages in multiple threads (Java SE) | 119 |
| 11.4.10. | Receiving synchronously and sending a message in the same local transaction (Java SE)..... | 121 |
| 11.4.11. | Request/reply pattern using a TemporaryQueue (Java EE)..... | 123 |
| 12. | Resource Adapter | 131 |
| 12.1. | ActivationSpec properties | 131 |
| A. | Resolved issues | 134 |
| A.1.1 | JDK 1.1.x compatibility | 134 |
| A.1.1 | Distributed Java event model | 134 |
| A.1.2 | Should the two JMS domains, PTP and pub/sub, be merged? | 134 |
| A.1.3 | Should JMS specify a set of JMS JavaBeans? | 134 |
| A.1.4 | Alignment with the CORBA notification service | 134 |
| A.1.5 | Should JMS provide end-to-end synchronous message delivery and notification of delivery? | 134 |
| A.1.6 | Should JMS provide a send-to-list mechanism? | 135 |
| A.1.7 | Should JMS provide subscription notification? | 135 |
| A.2. | Unresolved issues in the JMS 2.0 Early Draft | 135 |
| A.2.1 | Simplified API: Injecting a JMSContext | 135 |
| B. | Change history | 137 |
| B.1. | Version 1.0.1 | 137 |
| B.1.1 | JMS exceptions | 137 |
| B.2. | Version 1.0.2 | 137 |
| B.2.1 | The multiple topic subscriber special case..... | 137 |
| B.2.2 | Message selector comparison of exact and inexact numeric values | 137 |
| B.2.3 | Connection and session close | 137 |
| B.2.4 | Creating a session on an active connection..... | 137 |
| B.2.5 | Delivery mode and message retention | 138 |
| B.2.6 | The ‘single thread’ use of sessions | 138 |
| B.2.7 | Clearing a message’s properties and body | 138 |
| B.2.8 | Message selector numeric literal syntax | 138 |

| | | |
|--------|---|-----|
| B.2.9 | Comparison of boolean values in message selectors.... | 138 |
| B.2.10 | Order of messages read from a queue..... | 138 |
| B.2.11 | Null values in messages | 138 |
| B.2.12 | Closing constituents of closed connections and sessions | 138 |
| B.2.13 | The termination of a pending receive on close | 138 |
| B.2.14 | Incorrect entry in Stream and Map Message conversion table | 138 |
| B.2.15 | Inactive durable subscription..... | 138 |
| B.2.16 | Read-only message body..... | 139 |
| B.2.17 | Changing header fields of a received message..... | 139 |
| B.2.18 | Null/missing message properties and message fields... | 139 |
| B.2.19 | JMS source errata..... | 139 |
| B.2.20 | JMS source Java API documentation errata..... | 139 |
| B.2.21 | JMS source Java API documentation clarifications | 139 |
| B.3. | Version 1.0.2b | 140 |
| B.3.1 | JMS API specification, version 1.0.2: errata and clarifications | 141 |
| B.3.2 | JMS API Java API documentation, version 1.0.2a: major errata..... | 142 |
| B.3.3 | JMS API Java API documentation, version 1.0.2a: lesser errata | 143 |
| B.4. | Version 1.1 | 144 |
| B.4.1 | Unification of messaging domains | 144 |
| B.4.2 | JMS API specification, version 1.1: domain unification..... | 144 |
| B.4.3 | JMS API specification, version 1.1: updates and clarifications | 145 |
| B.4.4 | JMS API Java API documentation, version 1.1: domain unification | 147 |
| B.4.5 | JMS API documentation, version 1.1: changes..... | 149 |
| B.5. | Version 2.0 | 151 |
| B.5.1 | Re-ordering of chapters..... | 151 |
| B.5.2 | JMS providers must implement both P2P and Pub-Sub (JMS_SPEC-50)..... | 151 |
| B.5.3 | Use of JMS API in Java EE applications (JMS_SPEC-45 and JMS_SPEC-27)..... | 151 |
| B.5.4 | New methods to create a session (JMS_SPEC-45) | 152 |
| B.5.5 | Multiple consumers now allowed on the same topic subscription (JMS_SPEC-40)..... | 152 |
| B.5.6 | Delivery delay (JMS_SPEC-44)..... | 152 |
| B.5.7 | Sending messages asynchronously (JMS_SPEC-43) ... | 153 |
| B.5.8 | Use of AutoCloseable (JMS_SPEC-53)..... | 153 |
| B.5.9 | JMSXDeliveryCount (JMS_SPEC-42)..... | 153 |
| B.5.10 | Client ID optional on Durable subscriptions (JMS_SPEC-39)..... | 154 |
| B.5.11 | New createDurableConsumer methods (JMS_SPEC-51)..... | 154 |
| B.5.12 | Simplified API (JMS_SPEC-64) | 154 |
| B.5.13 | Clarification: message may be sent using any session (JMS_SPEC-52)..... | 155 |
| B.5.14 | Clarification: use of ExceptionListener (JMS_SPEC-49)..... | 155 |
| B.5.15 | Clarification: use of stop or close from a message listener (JMS_SPEC-48) | 156 |
| B.5.16 | Clarification: use of noLocal when creating a durable subscription (JMS_SPEC-65)..... | 156 |

| | | |
|--------|--|-----|
| B.5.17 | Clarification: message headers that are intended to be set by the JMS provder (JMS_SPEC-34)..... | 156 |
| B.5.18 | Clarification: Session methods createQueue and createTopic (JMS_SPEC-31) | 157 |
| B.5.19 | Correction: Reconnecting to a durable subscription (JMS_SPEC-80)..... | 157 |

1. Introduction

1.1. Abstract

This specification describes the objectives and functionality of the Java™ Message Service (JMS).

JMS provides a common way for Java programs to create, send, receive and read an enterprise messaging system's messages.

1.2. Overview

Enterprise messaging products (or as they are sometimes called, Message Oriented Middleware products) are becoming an essential component for integrating intra-company operations. They allow separate business components to be combined into a reliable, yet flexible, system.

In addition to the traditional MOM vendors, enterprise messaging products are also provided by several database vendors and a number of internet related companies.

Java language clients and Java language middle tier services must be capable of using these messaging systems. JMS provides a common way for Java language programs to access these systems.

JMS is a set of interfaces and associated semantics that define how a JMS client accesses the facilities of an enterprise messaging product.

Since messaging is peer-to-peer, all users of JMS are referred to generically as *clients*. A JMS *application* is made up of a set of application defined messages and a set of clients that exchange them.

Products that implement JMS do this by supplying a *provider* that implements the JMS interfaces.

1.2.1. Is this a mail API?

The term *messaging* is quite broadly defined in computing. It is used for describing various operating system concepts; it is used to describe email and fax systems; and here, it is used to describe asynchronous communication between enterprise applications.

Messages, as described here, are asynchronous requests, reports or events that are consumed by enterprise applications, not humans. They contain vital information needed to coordinate these systems. They contain precisely formatted data that describe specific business actions. Through the exchange of these messages each application tracks the progress of the enterprise.

1.2.2. Existing messaging systems

Messaging systems are peer-to-peer facilities. In general, each client can send messages to, and receive messages from any client. Each client connects to a messaging agent which provides facilities for creating, sending and receiving messages.

Each system provides a way of addressing messages. Each provides a way to create a message and fill it with data.

Some systems are capable of broadcasting a message to many destinations. Others only support sending a message to a single destination.

Some systems provide facilities for asynchronous receipt of messages (messages are delivered to a client as they arrive). Others support only synchronous receipt (a client must request each message).

Each messaging system typically provides a range of service that can be selected on a per message basis. One important attribute is the lengths to which the system will go to ensure delivery. This varies from simple best effort to guaranteed, only once delivery. Other important attributes are message time-to-live, priority and whether a response is required.

1.2.3. *JMS objectives*

If JMS provided a union of all the existing features of messaging systems it would be much too complicated for its intended users. On the other hand, JMS is more than an intersection of the messaging features common to all products. It is crucial that JMS include the functionality needed to implement sophisticated enterprise applications.

JMS defines a common set of enterprise messaging concepts and facilities. It attempts to minimize the set of concepts a Java language programmer must learn to use enterprise messaging products. It strives to maximize the portability of messaging applications.

1.2.3.1. *JMS provider*

As noted earlier, a JMS provider is the entity which implements JMS for a messaging product.

Ideally, JMS providers will be written in 100% Pure Java so they can run in applets; simplify installation; and, work across architectures and OS's.

An important goal of JMS is to minimize the work needed to implement a provider.

1.2.3.2. *JMS messages*

JMS defines a set of message interfaces.

Clients use the message implementations supplied by their JMS provider.

A major goal of JMS is that clients have a consistent API for creating and working with messages which is independent of JMS provider.

1.2.3.3. *JMS domains*

Messaging products can be broadly classified as either *point-to-point* or *publish-subscribe* systems.

Point-to-point (PTP) products are built around the concept of message queues. Each message is addressed to a specific queue; clients extract messages from the queue(s) established to hold their messages.

Publish and subscribe (Pub/Sub) clients address messages to some node in a content hierarchy. Publishers and subscribers are generally anonymous and may dynamically publish or subscribe to the content hierarchy. The

system takes care of distributing the messages arriving from a node's multiple publishers to its multiple subscribers.

JMS provides a set of interfaces that allow the client to send and receive messages in both domains, while supporting the semantics of each domain. JMS also provides client interfaces tailored for each domain. Prior to version 1.1 of the JMS specification, only the client interfaces that were tailored to each domain were available. These interfaces continue to be supported to provide backward compatibility for those who have already implemented JMS clients using them. The preferred approach for implementing clients is to use the domain-independent interfaces. These interfaces, referred to as the "common interfaces", are parents of the domain-specific interfaces.

1.2.3.4. Portability

The primary portability objective is that new, JMS only, applications are portable across products within the same messaging domain.

This is in addition to the expected portability of a JMS client across machine architectures and operating systems (when using the same JMS provider).

Although JMS is designed to allow clients to work with existing message formats used in a mixed language application, portability of such clients is not generally achievable (porting a mixed language application from one product to another is beyond the scope of JMS).

1.2.4. What JMS does not include

JMS does not address the following functionality:

- Load Balancing/Fault Tolerance - Many products provide support for multiple, cooperating clients implementing a critical service. The JMS API does not specify how such clients cooperate to appear to be a single, unified service.
- Error/Advisory Notification - Most messaging products define system messages that provide asynchronous notification of problems or system events to clients. JMS does not attempt to standardize these messages. By following the guidelines defined by JMS, clients can avoid using these messages and thus prevent the portability problems their use introduces.
- Administration - JMS does not define an API for administering messaging products.
- Security - JMS does not specify an API for controlling the privacy and integrity of messages. It also does not specify how digital signatures or keys are distributed to clients. Security is considered to be a JMS provider-specific feature that is configured by an administrator rather than controlled via the JMS API by clients.
- Wire Protocol - JMS does not define a wire protocol for messaging.
- Message Type Repository - JMS does not define a repository for storing message type definitions and it does not define a language for creating message type definitions.

1.3. *What is required by JMS*

The functionality discussed in the specification is required of all JMS providers unless it is explicitly noted otherwise.

JMS is also used within the Java Platform, Enterprise Edition (Java EE). See section 1.4 "Relationship to other Java APIs" for additional requirements for JMS when it is integrated into a Java EE environment.

1.4. *Relationship to other Java APIs*

1.4.1. *Java DataBase Connectivity (JDBCTM) software*

JMS clients may also use the JDBC API. They may desire to include the use of both the JDBC API and the JMS API in the same transaction. In most cases, this will be achieved automatically by implementing these clients as Enterprise JavaBeansTM components. It is also possible to do this directly with the Java Transaction API (JTA).

1.4.2. *JavaBeansTM components*

JavaBeans components can use a JMS session to send/receive messages. JMS itself is an API and the interfaces it defines are not designed to be used directly as JavaBeans components.

1.4.3. *Enterprise JavaBeansTM component model*

The JMS API is an important resource available to Enterprise Java Beans (EJBTM) component developers. It can be used in conjunction with other resources like JDBC to implement enterprise services.

The EJB specification defines beans that are invoked synchronously via method calls from EJB clients. It also defines a form of asynchronous bean that is invoked when a JMS client sends it a message, called a message-driven bean. The EJB specification supports both synchronous and asynchronous message consumption. In addition, EJB specifies how the JMS API participates in bean-managed or container-managed transactions. The EJB specification restricts how to use JMS interfaces when implementing EJB clients. Refer to the EJB specification for the details.

1.4.4. *Java Transaction API (JTA)*

The *javax.transaction* package provides a client API for delimiting distributed transactions and an API for accessing a resource's ability to participate in a distributed transaction.

A JMS client may use JTA to delimit distributed transactions; however, this is a function of the transaction environment the client is running in. It is not a feature of JMS.

A JMS provider can optionally support distributed transactions via JTA.

1.4.5. *Java Transaction Service (JTS)*

JMS can be used in conjunction with JTS to form distributed transactions that combine message sends and receives with database updates and other JTS aware services. This should be handled automatically when a JMS client is run from within an application server such as an Enterprise

JavaBeans server; however, it is also possible for JMS clients to program this explicitly.

1.4.6. *Java Naming and Directory InterfaceTM (JNDI) API*

JMS clients look up configured JMS objects using the JNDI API. JMS administrators use provider-specific facilities for creating and configuring these objects.

This division of work maximizes the portability of clients by delegating provider specific work to the administrator. It also leads to more administrable applications because clients do not need to embed administrative values in their code.

1.4.7. *Java Platform, Enterprise Edition (Java EE)*

The JavaTM Platform, Enterprise Edition (Java EE) Specification, v7 requires support for the JMS API as part of the Java EE platform. The Java EE platform specification places certain additional requirements on the implementation and use of the JMS API. The most important requirements are described in chapter 10 "Use of JMS API in Java EE applications".

1.4.8. *Contexts and dependency injection (CDI)*

This specification defines how `JMSContext` objects may be injected into Java EE web or EJB applications. See section 11.3 "Injection of `JMSContext` objects" for more information. The CDI (Contexts and dependency injection) specification defines the concepts and technology on which this is based.

1.5. *What is new in JMS 1.1?*

In previous versions of JMS, client programming for the Point-to-Point and Pub/Sub domains was done using similar but separate class hierarchies. In JMS 1.1, there is now a domain-independent approach to programming the client application. This provides several benefits:

- For the client programmer, a simpler programming model
- The ability to engage queues and topics in the same transaction, now that they can be created in the same session
- For the JMS provider, increased opportunity to optimize implementations by pooling thread management
- To take advantage of these features, the developer of JMS clients needs to use the domain-independent or "common" APIs. In the future, some of the domain-specific APIs may be deprecated.

In JMS 1.1, all of the classes and methods from JMS 1.0.2b are retained to provide backward compatibility. The semantics of the two messaging domains are retained; the expected behavior of a Point-to-Point domain and a Pub/Sub domain remain the same, as described in chapter 5 "JMS point-to-point model" and chapter 6 "JMS publish/subscribe model"

To see details of the changes made to this specification, see chapter B "Change history".

1.6. What is new in JMS 2.0?

A full list of the new features, changes and clarifications introduced in JMS 2.0 is given in section B.5 "Version 2.0" of the "Change history" chapter. Here is a summary:

The JMS 2.0 specification now requires JMS providers to implement both P2P and Pub-Sub.

The following new messaging features have been added in JMS 2.0:

- Delivery delay: a message producer can now specify that a message must not be delivered until after a specified time interval.
- New send methods have been added to allow an application to send messages asynchronously.
- JMS providers must now set the `JMSXDeliveryCount` message property.

Several changes have been made to the JMS API to make it simpler and easier to use:

- `Connection`, `Session` and other objects with a `close()` method now implement the `java.lang.AutoCloseable` interface to allow them to be used in a Java SE 7 try-with-resources statement.
- A new "simplified API" has been added which offers a simpler alternative to the standard API, especially in Java EE applications.
- New methods have been added to create a session without the need to supply redundant arguments.
- Client ID is now optional when creating a durable subscription

The following change has been made to aid scalability:

- Applications are now permitted to create multiple consumers on the same durable or non-durable topic subscription. In previous versions of JMS only a single consumer was permitted.

A new chapter has been added which describes some additional restrictions and behaviour which apply when using the JMS API in the Java EE web or EJB container. This information was previously only available in the EJB and Java EE platform specifications.

New methods have been added to `Session` which return a `MessageConsumer` on a durable topic subscription. Applications could previously only obtain a domain-specific `TopicSubscriber`, even though its use was discouraged.

The specification has been clarified in various places.

2. *Architecture*

2.1. *Overview*

This chapter describes the environment of message based applications and the role JMS plays in this environment.

2.2. *What is a JMS application?*

A JMS application is composed of the following parts:

- JMS Clients - These are the Java language programs that send and receive messages.
- Non-JMS Clients - These are clients that use a message system's native client API instead of JMS. If the application predated the availability of JMS it is likely that it will include both JMS and non-JMS clients.
- Messages - Each application defines a set of messages that are used to communicate information between its clients.
- JMS Provider - This is a messaging system that implements JMS in addition to the other administrative and control functionality required of a full featured messaging product.
- Administered Objects - Administered objects are preconfigured JMS objects created by an administrator for the use of clients.

2.3. *Administration*

It is expected that each JMS provider will differ significantly in its underlying messaging technology. It is also expected there will be major differences in how a provider's system is installed and administered.


If JMS clients are to be portable, they must be isolated from these proprietary aspects of a provider. This is done by defining JMS administered objects that are created and customized by a provider's administrator and later used by clients. The client uses them through JMS interfaces that are portable. The administrator creates them using provider-specific facilities.

There are two types of JMS administered objects:

- `ConnectionFactory` - This is the object a client uses to create a connection with a provider.
- `Destination` - This is the object a client uses to specify the destination of messages it is sending and the source of messages it receives.

Administered objects are placed in a JNDI namespace by an administrator. A JMS client typically notes in its documentation the JMS administered objects it requires and how the JNDI names of these objects should be provided to it. Figure 2.1 illustrates how JMS administration ordinarily works.

Figure 2.1 JMS Administration



2.4. Two messaging styles

A JMS application can use either the point-to-point (PTP) and the publish-and-subscribe (pub/sub) style of messaging, which are described in more detail later in this specification. An application can also combine both styles of messaging in one application. These two styles of messaging are often referred to as messaging domains. JMS provides these two messaging domains because they represent two common models for messaging.

When using the JMS API, a developer can use interfaces and methods that support both models of messaging. When using these interfaces, the behavior of the messaging system may be somewhat different, because the two messaging domains have different semantics. These semantic differences are described in Chapter 5 "JMS point-to-point model" and Chapter 6 "JMS publish/subscribe model".

2.5. JMS interfaces

JMS is based on a set of common messaging concepts. Each JMS messaging domain - PTP and Pub/Sub - define their customized set of interfaces for these concepts.

Table 2.1 Relationship of PTP and Pub/Sub Interfaces

| JMS Common Interfaces | PTP-specific Interfaces | Pub/Sub-specific interfaces |
|-----------------------|--------------------------------|-----------------------------|
| ConnectionFactory | QueueConnectionFactory | TopicConnectionFactory |
| Connection | QueueConnection | TopicConnection |
| Destination | Queue | Topic |
| Session | QueueSession | TopicSession |
| MessageProducer | QueueSender | TopicPublisher |
| MessageConsumer | QueueReceiver, QueueBrowser | TopicSubscriber |

The JMS common interfaces provide a domain-independent view of the PTP and Pub/Sub messaging domains. JMS client programmers are encouraged to use these interfaces to create their client programs.

The following list provides a brief definition of these JMS concepts. See Chapter 4 "JMS common facilities" for more details about these concepts.

For the details about the differences in the two messaging domains, see Chapter 5 "JMS point-to-point model" and Chapter JMS publish/subscribe model, "JMS Publish/Subscribe Model."

- **ConnectionFactory** - an administered object used by a client to create a **Connection**
- **Connection** - an active connection to a JMS provider
- **Destination** - an administered object that encapsulates the identity of a message destination
- **Session** - a single-threaded context for sending and receiving messages
- **MessageProducer** - an object created by a **Session** that is used for sending messages to a destination
- **MessageConsumer** - an object created by a **Session** that is used for receiving messages sent to a destination

Figure 2.2 Overview of JMS object relationships



The term *consume* is used in this document to mean the receipt of a message by a JMS client; that is, a JMS provider has received a message and has given it to its client. Since JMS supports both synchronous and asynchronous receipt of messages, the term *consume* is used when there is no need to make a distinction between them.

The term *produce* is used as the most general term for sending a message. It means giving a message to a JMS provider for delivery to a destination.

2.6. Developing a JMS application

Broadly speaking, a JMS application is one or more JMS clients that exchange messages. The application may also involve non-JMS clients; however, these clients use the JMS provider's native API in place of JMS.

A JMS application can be architected and deployed as a unit. In many cases, JMS clients are added incrementally to an existing application.

The message definitions used by an application may originate with JMS or they may have been defined by the non-JMS part of the application.

2.6.1. *Developing a JMS client*

A typical JMS client executes the following JMS setup procedure:

- Use JNDI to find a `ConnectionFactory` object
- Use JNDI to find one or more `Destination` objects
- Use the `ConnectionFactory` to create a JMS `Connection` with message delivery inhibited
- Use the `Connection` to create one or more JMS `Sessions`
- Use a `Session` and the `Destinations` to create the `MessageProducers` and `MessageConsumers` needed
- Tell the `Connection` to start delivery of messages

At this point a client has the basic JMS setup needed to produce and consume messages.

2.7. *Security*

JMS does not provide features for controlling or configuring message integrity or message privacy.

It is expected that many JMS providers will provide such features. It is also expected that configuration of these services will be handled by provider-specific administration tools. Clients will get the proper security configuration as part of the administered objects they use.

2.8. *Multi-threading*

JMS could have required that all its objects support concurrent use. Since support for concurrent access typically adds some overhead and complexity, the JMS design restricts its requirement for concurrent access to those objects that would naturally be shared by a multi-threaded client. The remainder are designed to be accessed by one logical thread of control at a time.

Table 2.2 JMS objects that support concurrent use

| JMS Object | Supports Concurrent Use |
|-------------------|-------------------------|
| Destination | YES |
| ConnectionFactory | YES |
| Connection | YES |
| Session | NO |
| MessageProducer | NO |
| MessageConsumer | NO |

JMS defines some specific rules that restrict the concurrent use of Sessions. Since they require more knowledge of JMS specifics than we have presented at this point, they will be described later. Here we will describe the rationale for imposing them.

There are two reasons for restricting concurrent access to Sessions. First, Sessions are the JMS entity that supports transactions. It is very difficult to implement transactions that are multi-threaded. Second, Sessions support asynchronous message consumption. It is important that JMS *not* require that client code used for asynchronous message consumption be capable of handling multiple, concurrent messages. In addition, if a Session has been set up with multiple, asynchronous consumers, it is important that the client is not forced to handle the case where these separate consumers are concurrently executing. These restrictions make JMS easier to use for typical clients. More sophisticated clients can get the concurrency they desire by using multiple sessions.

2.9. *Triggering clients*

Some clients are designed to periodically wake up and process messages waiting for them. A message-based application triggering mechanism is often used with this style of client. The trigger is typically a threshold of waiting messages, etc.

JMS does not provide a mechanism for triggering the execution of a client. Some providers may supply such a triggering mechanism via their administrative facilities.

2.10. *Request/reply*

JMS provides the `JMSReplyTo` message header field for specifying the Destination where a reply to a message should be sent. The `JMSCorrelationID` header field of the reply can be used to reference the original request. See Section 3.4 "Message header fields" for more information.

In addition, JMS provides a facility for creating temporary queues and topics that can be used as a unique destination for replies.

Enterprise messaging products support many styles of request/reply, from the simple "one message request yields a one message reply" to "one message request yields streams of messages from multiple respondents." Rather than architect a specific JMS request/reply abstraction, JMS provides the basic facilities on which many can be built.

For convenience, JMS defines request/reply helper classes (classes written using JMS) for both the PTP and Pub/Sub domains that implement a basic form of request/reply. JMS providers and clients may provide more specialized implementations.

3. *JMS message model*

3.1. *Background*

Enterprise messaging products treat messages as lightweight entities that consist of a header and a body. The header contains fields used for message routing and identification; the body contains the application data being sent.

Within this general form, the definition of a message varies significantly across products. There are major differences in the content and semantics of headers. Some products use a self describing, canonical encoding of message data; others treat data as completely opaque. Some products provide a repository for storing message descriptions that can be used to identify and interpret message content; others don't.

It would be quite difficult for JMS to capture the breadth of this, sometimes conflicting, union of message models.

3.2. *Goals*

The JMS message model has the following goals:

- Provide a single, unified message API
- Provide an API suitable for creating messages that match the format used by existing, non-JMS applications
- Support the development of heterogeneous applications that span operating systems, machine architectures, and computer languages
- Support messages containing Java objects
- Support messages containing Extensible Markup Language pages (see <http://www.w3.org/XML>).

3.3. *JMS messages*

JMS messages are composed of the following parts:

- Header - All messages support the same set of header fields. Header fields contain values used by both clients and providers to identify and route messages.
- Properties - In addition to the standard header fields, messages provide a built-in facility for adding optional header fields to a message.
 - Application-specific properties - In effect, this provides a mechanism for adding application specific header fields to a message.
 - Standard properties - JMS defines some standard properties that are, in effect, optional header fields.
 - Provider-specific properties - Integrating a JMS client with a JMS provider native client may require the use of provider-specific properties. JMS defines a naming convention for these.

- Body - JMS defines several types of message body which cover the majority of messaging styles currently in use.

3.4. *Message header fields*

The following subsections describe each JMS message header field. A message's complete header is transmitted to all JMS clients that receive the message. JMS does not define the header fields transmitted to non-JMS clients.

3.4.1. *JMSDestination*

The *JMSDestination* header field contains the destination to which the message is being sent.

When a message is sent this value is ignored. After completion of the send it holds the destination object specified by the sending method.

When a message is received, its destination value must be equivalent to the value assigned when it was sent.

3.4.2. *JMSDeliveryMode*

The *JMSDeliveryMode* header field contains the delivery mode specified when the message was sent.

When a message is sent this value is ignored. After completion of the send, it holds the delivery mode specified by the sending method.

See Section 4.7 "Message delivery mode" for more information.

3.4.3. *JMSMessageID*

The *JMSMessageID* header field contains a value that uniquely identifies each message sent by a provider.

When a message is sent, *JMSMessageID* is ignored. When the send method returns it contains a provider-assigned value.

A *JMSMessageID* is a *String* value which should function as a unique key for identifying messages in a historical repository. The exact scope of uniqueness is provider defined. It should at least cover all messages for a specific installation of a provider where an installation is some connected set of message routers.

All *JMSMessageID* values must start with the prefix 'ID:'. Uniqueness of message ID values across different providers is not required.

Since message IDs take some effort to create and increase a message's size, some JMS providers may be able to optimize message overhead if they are given a hint that message ID is not used by an application. Both *MessageProducer* and *JMSProducer* provide a method *setDisableMessageID* which allows the application to provide a hint to disable message ID. When an application sets a producer to disable message ID, it is saying that it does not depend on the value of message ID for the messages it produces. If the JMS provider accepts this hint, these messages must have the message ID set to null; if the provider ignores the hint, the message ID must be set to its normal unique value.

3.4.4. *JMSTimestamp*

The `JMSTimestamp` header field contains the time a message was handed off to a provider to be sent. It is not the time the message was actually transmitted because the actual send may occur later due to transactions or other client side queueing of messages.

When a message is sent, `JMSTimestamp` is ignored. When the send method returns, the field contains a time value somewhere in the interval between the call and the return. It is in the format of a normal Java millis time value.

Since timestamps take some effort to create and increase a message's size, some JMS providers may be able to optimize message overhead if they are given a hint that timestamp is not used by an application. Both `MessageProducer` and `JMSProducer` provide a method `setDisableMessageTimestamp` which allows the application to provide a hint to disable timestamps. When an application sets a producer to disable timestamps it is saying that it does not depend on the value of timestamp for the messages it produces. If the JMS provider accepts this hint, these messages must have the timestamp set to zero; if the provider ignores the hint, the timestamp must be set to its normal value.

3.4.5. *JMSCorrelationID*

A client can use the `JMSCorrelationID` header field to link one message with another. A typical use is to link a response message with its request message.

`JMSCorrelationID` can hold one of the following:

- A provider-specific message ID
- An application-specific `String`
- A provider-native `byte[]` value.

Since each message sent by a JMS provider is assigned a message ID value it is convenient to link messages via message ID. All message ID values must start with the 'ID:' prefix.

In some cases, an application (made up of several clients) needs to use an application-specific value for linking messages. For instance, an application may use `JMSCorrelationID` to hold a value referencing some external information. Application-specified values must not start with the 'ID:' prefix; this is reserved for provider-generated message ID values.

If a provider supports the native concept of correlation ID, a JMS client may need to assign specific `JMSCorrelationID` values to match those expected by non-JMS clients. A `byte[]` value is used for this purpose. JMS providers without native correlation ID values are not required to support `byte[]` values¹ The use of a `byte[]` value for `JMSCorrelationID` is non-portable.

¹ Their implementation of `setJMSCorrelationIDAsBytes()` and `getJMSCorrelationIDAsBytes()` may throw `java.lang.UnsupportedOperationException`.

3.4.6. *JMSReplyTo*

The `JMSReplyTo` header field contains a Destination supplied by a client when a message is sent. It is the destination where a reply to the message should be sent.

Messages sent with a null `JMSReplyTo` value may be a notification of some event or they may just be some data the sender thinks is of interest.

Messages sent with a `JMSReplyTo` value are typically expecting a response. A response may be optional; it is up to the client to decide.

3.4.7. *JMSRedelivered*

If a client receives a message with the `JMSRedelivered` indicator set, it is likely, but not guaranteed, that this message was delivered but not acknowledged in the past. In general, a provider must set the `JMSRedelivered` message header field of a message whenever it is redelivering a message. If the field is set to true, it is an indication to the consuming application that the message may have been delivered in the past and that the application should take extra precautions to prevent duplicate processing. See Section 4.4.11 "Message acknowledgment" for more information.

This header field has no meaning on send and is left unassigned by the sending method.

The JMS-defined message property `JMSXDeliveryCount` will be set to the number of times a particular message has been delivered. See section 3.5.11 "`JMSXDeliveryCount`" for more information.

3.4.8. *JMSType*

The `JMSType` header field contains a message type identifier supplied by a client when a message is sent.

Some JMS providers use a message repository that contains the definitions of messages sent by applications. The *type* header field may reference a message's definition in the provider's repository.

JMS does not define a standard message definition repository nor does it define a naming policy for the definitions it contains.

Some messaging systems require that a message type definition for each application message be created and that each message specify its type. In order to work with such JMS providers, JMS clients should assign a value to `JMSType` whether the application makes use of it or not. This insures that the field is properly set for those providers that require it.

To ensure portability, JMS clients should use symbolic values for `JMSType` that can be configured at installation time to the values defined in the current provider's message repository. If string literals are used they may not be valid type names for some JMS providers.

3.4.9. *JMSExpiration*

When a message is sent, its expiration time is calculated as the sum of the time-to-live value specified on the send method and the current GMT value. On return from the send method, the message's `JMSExpiration` header field contains this value. When a message is received its `JMSExpiration` header field contains this same value.

If the time-to-live is specified as zero, expiration is set to zero to indicate that the message does not expire.

When GMT is later than an undelivered message's expiration time, the message should be destroyed. JMS does not define a notification of message expiration.

Clients should not receive messages that have expired; however, JMS does not guarantee that this will not happen.

3.4.10. *JMSPriority*

The `JMSPriority` header field contains the message's priority.

When a message is sent this value is ignored. After completion of the send it holds the value specified by the method sending the message.

JMS defines a ten level priority value with 0 as the lowest priority and 9 as the highest. In addition, clients should consider priorities 0-4 as gradations of *normal* priority and priorities 5-9 as gradations of *expedited* priority.

JMS does not require that a provider strictly implement priority ordering of messages; however, it should do its best to deliver expedited messages ahead of normal messages.

3.4.11. *How message header values are set*

The following table lists the message header fields supported by JMS and whether they are set by the JMS provider or by the client application.

Table 3.1 Message header field values

| Header Fields | Set By | Setter method |
|-------------------------------|-----------------------------|---|
| <code>JMSDestination</code> | JMS provider send method | <code>setJMSDestination</code> (not for client use) |
| <code>JMSDeliveryMode</code> | JMS provider send method | <code>setJMSDeliveryMode</code> (not for client use) |
| <code>JMSExpiration</code> | JMS provider send method | <code>setJMSExpiration</code> (not for client use) |
| <code>JMSDeliveryTime</code> | JMS provider send method | <code>setJMSDeliveryTime</code> (not for client use) |
| <code>JMSPriority</code> | JMS provider send method | <code>setJMSPriority</code> (not for client use) |
| <code>JMSMessageID</code> | JMS provider send method | <code>setJMSMessageID</code> (not for client use) |
| <code>JMSTimestamp</code> | JMS provider send method | <code>setJMSTimestamp</code> (not for client use) |
| <code>JMSCorrelationID</code> | Client application | <code>setJMSCorrelationID</code> , <code>setJMSCorrelationIDAsBytes</code> |
| <code>JMSReplyTo</code> | Client application | <code>setJMSReplyTo</code> |
| <code>JMSType</code> | Client application | <code>setJMSType</code> |

| | | |
|----------------|--------------------------------------|---|
| JMSRedelivered | JMS provider prior to delivery | setJMSRedelivered (not for client use) |
|----------------|--------------------------------------|---|

Message header fields that are defined as being set by the "client application" in the above table may be set by the client application, using the appropriate setter method, before the message is sent.

Message header fields that are defined as being set by the "JMS provider on send" will be available on the sending client as well as on the receiving client. If a message is sent synchronously (see section 4.6.1 "Synchronous send") then these message header fields may be accessed on the sending client when the send method returns. If a message is sent asynchronously (see section 4.6.2 "Asynchronous send") then these message header fields may be accessed on the sending client only after the completion listener has been invoked. The JMS provider sets these header fields using the appropriate setter methods. These setter methods are public to allow a JMS provider to set these fields when handling a message whose implementation is not its own. Client applications should not use these setter methods. Any values set by calling these methods prior to sending a message will be ignored and overwritten.

A client application may specify the delivery mode, priority, time to live and delivery delay of a message using appropriate methods on the `MessageProducer` or `JMSContext` object, but not by methods on the `Message` object itself.

Message header fields that are defined as being set by the "JMS provider prior to delivery" will be set by the JMS provider on the message delivered to the receiving client.

3.4.12. *Overriding message header fields*

JMS permits an administrator to configure JMS to override the client specified values for delivery mode, priority, time to live and delivery delay. If this is done, the `JMSDeliveryMode`, `JMSPriority`, `JMSExpiration` and `JMSDeliveryTime` header field value must reflect the administratively specified value.

JMS does not define specifically how an administrator overrides these header field values. A JMS provider is not required to support this administrative option.

3.4.13. *JMSDeliveryTime*

When a message is sent, its delivery time is calculated as the sum of the delivery delay value specified on the send method and the current GMT value. On return from the send method, the message's `JMSDeliveryTime` header field contains this value. When a message is received its `JMSDeliveryTime` header field contains this same value.

A message's delivery time is the earliest time when a provider may make the message visible on the target destination and available for delivery to consumers.

Clients must not receive messages before the delivery time has been reached.

3.5. Message properties

In addition to the header fields defined here, the `Message` interface contains a built-in facility for supporting property values. In effect, this provides a mechanism for adding optional header fields to a message.

Properties allow a client, via message selectors (see Section 3.8 "Message selection"), to have a JMS provider select messages on its behalf using application-specific criteria.

3.5.1. Property names

Property names must obey the rules for a message selector identifier. See Section 3.8 "Message selection" for more information.

3.5.2. Property values

Property values can be boolean, byte, short, int, long, float, double, and String.

3.5.3. Using properties

Property values are set prior to sending a message. When a client receives a message, its properties are in read-only mode. If a client attempts to set properties at this point, a `MessageNotWriteableException` is thrown.

A property value may duplicate a value in a message's body or it may not. Although JMS does not define a policy for what should or should not be made a property, application developers should note that JMS providers will likely handle data in a message's body more efficiently than data in a message's properties. For best performance, applications should only use message properties when they need to customize a message's header. The primary reason for doing this is to support customized message selection.

See Section 3.8 "Message selection" for more information about JMS message properties.

3.5.4. Property value conversion

Properties support the following conversion table. The marked cases must be supported. The unmarked cases must throw the JMS `MessageFormatException`. The String to numeric conversions must throw the `java.lang.NumberFormatException` if the numeric's `valueOf()` method does not accept the String value as a valid representation. Attempting to read a null value as a Java primitive type must be treated as calling the primitive's corresponding `valueOf(String)` conversion method with a null value.

A value set as the row type can be read as the column type.

Table 3.2 Property value conversion

| | boolean | byte | short | int | long | float | double | String |
|---------|---------|------|-------|-----|------|-------|--------|--------|
| boolean | X | | | | | | | X |
| byte | | X | X | X | X | | | X |
| short | | | X | X | X | | | X |
| int | | | | X | X | | | X |
| long | | | | | X | | | X |

| | | | | | | | | |
|--------|---|---|---|---|---|---|---|---|
| float | | | | | | X | X | X |
| double | | | | | | | X | X |
| String | X | X | X | X | X | X | X | X |

3.5.5. *Property values as objects*

In addition to the type-specific set/get methods for properties, JMS provides the `setObjectProperty/getObjectProperty` methods. These support the same set of property types using the objectified primitive values. Their purpose is to allow the decision of property type to be made at execution time rather than at compile time. They support the same property value conversions.

The `setObjectProperty` method accepts values of `Boolean`, `Byte`, `Short`, `Integer`, `Long`, `Float`, `Double` and `String`. An attempt to use any other class must throw a `JMS MessageFormatException`.

The `getObjectProperty` method only returns values of `null`, `Boolean`, `Byte`, `Short`, `Integer`, `Long`, `Float`, `Double` and `String`. A `null` value is returned if a property by the specified name does not exist.

3.5.6. *Property iteration*

The order of property values is not defined. To iterate through a message's property values, use `getPropertyNames` to retrieve a property name enumeration and then use the various property get methods to retrieve their values.

The `getPropertyNames` method does not return the names of the JMS standard header fields.

3.5.7. *Clearing a message's property values*

A message's properties are deleted by the `clearProperties` method. This leaves the message with an empty set of properties. New property entries can then be both created and read.

Clearing a message's property entries does not clear the value of its body.

JMS does not provide a way to remove an individual property entry once it has been added to a message.

3.5.8. *Non-existent properties*

Getting a property value for a name which has not been set is handled as if the property exists with a `null` value.

3.5.9. *JMS defined properties*

JMS reserves the 'JMSX' property name prefix for JMS defined properties. The full set of these properties is provided in Table 3.3. This table defines:

- The name of the property
- The type of the property (integer or string)
- Whether support for the property is mandatory or optional.
- Whether the property is set by the sending client, by the provider when the message is sent, or by the provider when the message is received.

- The purpose of the property

New JMS defined properties may be added in later versions of JMS.

The Enumeration `ConnectionMetaData.getJMSXPropertyNames()` method returns the names of the JMSX properties supported by a connection.

JMSX properties may be referenced in message selectors whether or not they are supported by a connection. If they are not present in a message, they are treated like any other absent property. The effect of setting a message selector on a property which is set by the provider on receive is undefined.

The existence, in a particular message, of optional JMS defined properties that are set by a JMS Provider depends on how a particular provider controls use of the property. It may choose to include them in some messages and omit them in others depending on administrative or other criteria.

Table 3.3 JMS defined properties

| Name | Type | Optional or mandatory | Set By | Use |
|-------------------|--------|-----------------------|---------------------|---|
| JMSXUserID | String | Optional | Provider on Send | The identity of the user sending the message |
| JMSXAppID | String | Optional | Provider on Send | The identity of the application sending the message |
| JMSXDeliveryCount | int | Mandatory | Provider on Receive | The number of message delivery attempts. See section 3.5.11 "JMSXDeliveryCount". |
| JMSXGroupID | String | Optional | Client | The identity of the message group this message is part of |
| JMSXGroupSeq | int | Optional | Client | The sequence number of this message within the group; the first message is 1, the second 2,... |
| JMSXProducerTXID | String | Optional | Provider on Send | The transaction identifier of the transaction within which this message was produced |
| JMSXConsumerTXID | String | Optional | Provider on Receive | The transaction identifier of the transaction within which this message was consumed |
| JMSXRcvTimestamp | long | Optional | Provider on Receive | The time JMS delivered the message to the consumer |
| JMSXState | int | Optional | Provider | Assume there exists a message warehouse that contains a separate copy of each message sent to each consumer and that these copies exist from the time the original message was sent. Each copy's state is one of: 1(waiting), 2(ready), 3(expired) or 4(retained) Since state is of no interest to producers and consumers it is not provided to either. It is only of relevance to messages looked up in a warehouse and JMS provides no API for this. |

JMSX properties 'set by provider on send' are available to both the producer and the consumers of the message. JSMX properties set by the provider on receive are only available to the consumers. JMSXGroupID and JMSXGroupSeq are standard properties clients should use if they want to group messages. All providers must support them.

The case of these JMSX property names must be as defined in the table above.

Unless specifically noted, the values and semantics of the JMSX properties are undefined.

3.5.10. *Provider-specific properties*

JMS reserves the 'JMS_<vendor_name>' property name prefix for provider-specific properties. Each provider defines their own value of <vendor_name>. This is the mechanism a JMS provider uses to make its special per message services available to a JMS client.

The purpose of provider-specific properties is to provide special features needed to support JMS use with provider-native clients. They should not be used for JMS to JMS messaging.

3.5.11. *JMSXDeliveryCount*

When a client receives a message the mandatory JMS-defined message property JMSXDeliveryCount will be set to the number of times the message has been delivered. The first time a message is received it will be set to 1, so a value of 2 or more means the message has been redelivered.

If the JMSRedelivered message header value is set then the JMSXDeliveryCount property must always be 2 or more. See section 3.4.7 "JMSRedelivered" for more information about the JMSRedelivered message header,

The purpose of the JMSXDeliveryCount property is to allow consuming applications to identify whether a particular message is being repeatedly redelivered and take appropriate action.

The value of the JMSXDeliveryCount property is not guaranteed to be exactly correct. The JMS provider is not expected to persist this value to ensure that its value is not lost in the event of a failure.

3.6. *Message acknowledgment*

All JMS messages support the acknowledge method for use when a client has specified that a JMS consumer's messages are to be explicitly acknowledged.

If a client uses automatic acknowledgment, calls to acknowledge are ignored.

See Section 4.4.11 "Message acknowledgment" for more information.

3.7. *The Message interface*

The Message interface is the root interface for all JMS messages. It defines the JMS message header fields, property facility and the acknowledge method used for all messages.

3.8. *Message selection*

Many messaging applications need to filter and categorize the messages they produce.

In the case where a message is sent to a single receiver, this can be done with reasonable efficiency by putting the criteria in the message and having the receiving client discard the ones it's not interested in.

When a message is broadcast to many clients, it becomes useful to place the criteria into the message header so that it is visible to the JMS provider. This allows the provider to handle much of the filtering and routing work that would otherwise need to be done by the application.

JMS provides a facility that allows clients to delegate message selection to their JMS provider. This simplifies the work of the client and allows JMS providers to eliminate the time and bandwidth they would otherwise waste sending messages to clients that don't need them.

Clients attach application-specific selection criteria to messages using message properties. Clients specify message selection criteria using JMS *message selector* expressions.

3.8.1. *Message selector*

A JMS message selector allows a client to specify, by message header, the messages it's interested in. Only messages whose headers and properties match the selector are delivered. The semantics of *not delivered* differ a bit depending on the `MessageConsumer` being used. See Section 5.8 "QueueReceiver" and Section 6.11 "TopicSubscriber" for more details.

Message selectors cannot reference message body values.

A message selector matches a message when the selector evaluates to true when the message's header field and property values are substituted for their corresponding identifiers in the selector.

3.8.1.1. *Message selector syntax*

A message selector is a `String` whose syntax is based on a subset of the SQL92² conditional expression syntax.

If the value of a message selector is an empty string, the value is treated as a null and indicates that there is no message selector for the message consumer.

The order of evaluation of a message selector is from left to right within precedence level. Parentheses can be used to change this order.

Predefined selector literals and operator names are written here in upper case; however, they are case insensitive.

A selector can contain:

- Literals:

² See X/Open CAE Specification Data Management: Structured Query Language (SQL), Version 2, ISBN: 1-85912-151-9 March 1996.

- A string literal is enclosed in single quotes, with an included single quote represented by doubled single quote; for example, 'literal' and 'literal' 's'. Like Java String literals, these use the Unicode character encoding.
- An exact numeric literal is a numeric value without a decimal point, such as 57, -957, +62; numbers in the range of Java long are supported. Exact numeric literals use the Java integer literal syntax.
- An approximate numeric literal is a numeric value in scientific notation, such as 7E3 and -57.9E2, or a numeric value with a decimal, such as 7., -95.7, and +6.2; numbers in the range of Java double are supported. Approximate literals use the Java floating-point literal syntax.
- The boolean literals TRUE and FALSE.
- Identifiers:
 - An identifier is an unlimited-length character sequence that must begin with a Java identifier start character; all following characters must be Java identifier part characters. An identifier start character is any character for which the method `Character.isJavaIdentifierStart` returns true. This includes '_' and '\$'. An identifier part character is any character for which the method `Character.isJavaIdentifierPart` returns true.
 - Identifiers cannot be the names NULL, TRUE, or FALSE.
 - Identifiers cannot be NOT, AND, OR, BETWEEN, LIKE, IN, IS, or ESCAPE.
 - Identifiers are either header field references or property references. The type of a property value in a message selector corresponds to the type used to set the property. If a property that does not exist in a message is referenced, its value is NULL. The semantics of evaluating NULL values in a selector are described in Section 3.8.1.2 "Null values".
 - The conversions that apply to the get methods for properties do not apply when a property is used in a message selector expression. For example, suppose you set a property as a string value, as in the following:


```
myMessage.setStringProperty("NumberOfOrders", "2");
```

The following expression in a message selector would evaluate to false, because a string cannot be used in an arithmetic expression:

```
"NumberOfOrders > 1"
```
 - Identifiers are case sensitive.
 - Message header field references are restricted to JMSDeliveryMode, JMSPriority, JMSMessageID, JMSTimestamp, JMSCorrelationID, and JMSType. JMSMessageID, JMSCorrelationID, and JMSType values may be null and if so are treated as a NULL value.

- Any name beginning with 'JMSX' is a JMS defined property name.
- Any name beginning with 'JMS_' is a provider-specific property name.
- Any name that does not begin with 'JMS' is an application-specific property name.
- Whitespace is the same as that defined for Java: space, horizontal tab, form feed and line terminator.
- Expressions:
 - A selector is a conditional expression; a selector that evaluates to `true` matches; a selector that evaluates to `false` or `unknown` does not match.
 - Arithmetic expressions are composed of themselves, arithmetic operations, identifiers with numeric values, and numeric literals.
 - Conditional expressions are composed of themselves, comparison operations, logical operations, identifiers with boolean values, and boolean literals.
- Standard bracketing () for ordering expression evaluation is supported.
- Logical operators in precedence order: NOT, AND, OR
- Comparison operators: =, >, >=, <, <=, <> (not equal)
 - Only like type values can be compared. One exception is that it is valid to compare exact numeric values and approximate numeric values (the type conversion required is defined by the rules of Java numeric promotion). If the comparison of non-like type values is attempted, the value of the operation is `false`. If either of the type values evaluates to `NULL`, the value of the expression is `unknown`.
 - String and Boolean comparison is restricted to = and <>. Two strings are equal if and only if they contain the same sequence of characters.
- Arithmetic operators in precedence order:
 - +, - (unary)
 - *, / (multiplication and division)
 - +, - (addition and subtraction)
 - Arithmetic operations must use Java numeric promotion.
- *arithmetic-expr1* [NOT] BETWEEN *arithmetic-expr2* and *arithmetic-expr3* (comparison operator)
 - "age BETWEEN 15 AND 19" is equivalent to "age >= 15 AND age <= 19"
 - "age NOT BETWEEN 15 AND 19" is equivalent to "age < 15 OR age > 19"

- *identifier* [NOT] IN (*string-literal1*, *string-literal2*, ...) (comparison operator where *identifier* has a String or NULL value).
 - "Country IN (' UK', 'US', 'France')" is true for 'UK' and false for 'Peru'; it is equivalent to the expression (Country = ' UK') OR (Country = ' US') OR (Country = ' France')
 - Country NOT IN (' UK', 'US', 'France') is false for 'UK' and true for 'Peru'; it is equivalent to the expression "NOT ((Country = ' UK') OR (Country = ' US') OR (Country = ' France'))"
 - If identifier of an IN or NOT IN operation is NULL, the value of the operation is unknown.
- *identifier* [NOT] LIKE *pattern-value* [ESCAPE *escape-character*] (comparison operator, where *identifier* has a String value; *pattern-value* is a string literal where '_' stands for any single character; '%' stands for any sequence of characters, including the empty sequence, and all other characters stand for themselves. The optional *escape-character* is a single-character string literal whose character is used to escape the special meaning of the '_' and '%' in pattern-value.)
 - "phone LIKE '12%3'" is true for '123' or '12993' and false for '1234'
 - "word LIKE 'l_se'" is true for 'lose' and false for 'loose'
 - "underscored LIKE '_%' ESCAPE '\'" is true for '_foo' and false for 'bar'
 - "phone NOT LIKE '12%3'" is false for '123' and '12993' and true for '1234'
 - If *identifier* of a LIKE or NOT LIKE operation is NULL, the value of the operation is unknown.
- *identifier* IS NULL (comparison operator that tests for a null header field value or a missing property value)
 - "prop_name IS NULL"
- *identifier* IS NOT NULL (comparison operator that tests for the existence of a non-null header field value or property value)
 - "prop_name IS NOT NULL"

JMS providers are required to verify the syntactic correctness of a message selector at the time it is presented. A method providing a syntactically incorrect selector must result in a JMS `InvalidSelectorException`. JMS providers may also optionally provide some semantic checking at the time the selector is presented. Not all semantic checking can be performed at the time a message selector is presented, because property types are not known.

The following message selector selects messages with a message type of *car* and color of *blue* and weight greater than 2500 lbs:

"JMSType = 'car' AND color = 'blue' AND weight > 2500"

3.8.1.2. Null values

As noted above, header fields and property values may be NULL. The evaluation of selector expressions containing NULL values is defined by SQL 92 NULL semantics. A brief description of these semantics is provided here.

SQL treats a NULL value as unknown. Comparison or arithmetic with an unknown value always yields an unknown value.

The IS NULL and IS NOT NULL operators convert an unknown header or property value into the respective TRUE and FALSE values.

The boolean operators use three-valued logic as defined by the following tables:

Table 3.4 The definition of the AND operator

| AND | T | F | U |
|-----|---|---|---|
| T | T | F | U |
| F | F | F | F |
| U | U | F | U |

Table 3.5 The definition of the OR operator

| OR | T | F | U |
|----|---|---|---|
| T | T | T | T |
| F | T | F | U |
| U | T | U | U |

Table 3.6 The definition of the NOT operator

| NOT | |
|-----|---|
| T | F |
| F | T |
| U | U |

3.8.1.3. Special notes

When used in a message selector *JMSDeliveryMode* is treated as having the values 'PERSISTENT' and 'NON_PERSISTENT'.

Date and time values should use the standard Java long millisecond value. When a date or time literal is included in a message selector, it should be an integer literal for a millisecond value. The standard way to produce millisecond values is to use `java.util.Calendar`.

Although SQL supports fixed decimal comparison and arithmetic, JMS message selectors do not. This is the reason for restricting exact numeric literals to those without a decimal (and the addition of numerics with a decimal as an alternate representation for approximate numeric values).

SQL comments are not supported.

3.9. *Access to sent messages*

After sending a message, a client may retain and modify it without affecting the message that has been sent. The same message object may be sent multiple times.

During the execution of its sending method, the message must not be changed by the client. If it is modified, the result of the send is undefined.

3.10. *Changing the value of a received message*

When a message is received, its header field values can be changed; however, its property entries and its body are read-only, as specified in this chapter.

The rationale for the read-only restriction is that it gives JMS Providers more freedom in how they implement the management of received messages. For instance, they may return a message object that references property entries and body values that reside in an internal message buffer rather than being forced to make a copy.

A consumer can modify a received message after calling either the `clearBody` or `clearProperties` method to make the body or properties writable. If the consumer modifies a received message, and the message is subsequently redelivered, the redelivered message must be the original, unmodified message (except for headers and properties modified by the JMS provider as a result of the redelivery, such as the `JMSRedelivered` header and the `JMSXDeliveryCount` property).

3.11. *JMS message body*

JMS provides five forms of message body. Each form is defined by a message interface:

- `StreamMessage` - a message whose body contains a stream of Java primitive values. It is filled and read sequentially.
- `MapMessage` - a message whose body contains a set of name-value pairs where names are `String` objects and values are Java primitive types. The entries can be accessed sequentially by enumerator or randomly by name. The order of the entries is undefined.
- `TextMessage` - a message whose body contains a `java.lang.String`. The inclusion of this message type is based on our presumption that `String` messages will be used extensively. One reason for this is that XML will likely become a popular mechanism for representing the content of JMS messages.
- `ObjectMessage` - a message that contains a serializable Java object. If a collection of Java objects is needed, one of the collection classes provided in JDK 1.2 can be used.
- `BytesMessage` - a message that contains a stream of uninterpreted bytes. This message type is for literally encoding a body to match an existing message format. In many cases, it will be possible to use one of the other, self-defining, message types instead. *Although JMS allows the use of message properties with byte messages it is typically not done since the inclusion of properties may affect the format.*

3.11.1. Clearing a message body

The `clearBody` method of `Message` resets the value of the message body to the 'empty' initial message value as set by the message type's `create` method provided by `Session`. Clearing a message's body does not clear its property entries.

3.11.2. Read-only message body

When a message is received, its body is read only. If an attempt is made to change the body a `MessageNotWriteableException` must be thrown. If its body is subsequently cleared, the body is in the same state as an empty body in a newly created message.

3.11.3. Conversions provided by `StreamMessage` and `MapMessage`

Both `StreamMessage` and `MapMessage` support the same set of primitive data types.

The types can be read or written explicitly using methods for each type. They may also be read or written generically as objects. For instance, a call to `MapMessage.setInt("foo", 6)` is equivalent to `MapMessage.setObject("foo", new Integer(6))`. Both forms are provided because the explicit form is convenient for static programming and the object form is needed when types are not known at compile time.

Both `StreamMessage` and `MapMessage` support the following conversion table. The marked cases must be supported. The unmarked cases must throw a `JMS MessageFormatException`. The `String` to numeric conversions must throw a `java.lang.NumberFormatException` if the numeric's `valueOf()` method does not accept the `String` value as a valid representation.

`StreamMessage` and `MapMessage` must implement the `String` to `boolean` conversion as specified by the `valueOf(String)` method of `Boolean` as defined by the Java language.

Attempting to read a null value as a Java primitive type must be treated as calling the primitive's corresponding `valueOf(String)` conversion method with a null value. Since `char` does not support a `String` conversion, attempting to read a null value as a `char` must throw `NullPointerException`.

Getting a `MapMessage` field for a field name that has not been set is handled as if the field exists with a null value.

If a read method of `StreamMessage` or `BytesMessage` throws a `MessageFormatException` or `NumberFormatException`, the current position of the read pointer must not be incremented. A subsequent read must be capable of recovering from the exception by rereading the data as a different type.

A value written as the row type can be read as the column type

Table 3.7 Conversions for `StreamMessage` and `MapMessage`

| | <code>boolean</code> | <code>byte</code> | <code>short</code> | <code>char</code> | <code>int</code> | <code>long</code> | <code>float</code> | <code>double</code> | <code>String</code> | <code>byte[]</code> |
|----------------------|----------------------|-------------------|--------------------|-------------------|------------------|-------------------|--------------------|---------------------|---------------------|---------------------|
| <code>boolean</code> | X | | | | | | | | X | |
| <code>byte</code> | | X | X | | X | X | | | X | |

| | | | | | | | | | | |
|--------|---|---|---|---|---|---|---|---|---|---|
| short | | | X | | X | X | | | X | |
| char | | | | X | | | | | X | |
| int | | | | | X | X | | | X | |
| long | | | | | | X | | | X | |
| float | | | | | | | X | X | X | |
| double | | | | | | | | X | X | |
| String | X | X | X | | X | X | X | X | X | |
| byte[] | | | | | | | | | | X |

3.11.4. Messages for non-JMS clients

A number of enterprise messaging systems support some form of self-defining stream and/or map native message type. Although clients could use `BytesMessage` to construct native messages of this form, JMS provides the `StreamMessage` and `MapMessage` types as a more convenient API.

For instance, when a client is using a JMS provider that supports a native map message; and, it wishes to send a map message that can be read by both JMS and native clients, it uses a `MapMessage`. When the message is sent, the provider translates it into its native form. Native clients can then receive it. If a JMS provider receives it, the provider translates it back into a `MapMessage`.

Even when a new JMS application with newly defined messages is written, the application may choose to use `StreamMessage` and `MapMessage` to ensure that later, non-JMS clients will be able to read them.

If a JMS client sends a `StreamMessage` or `MapMessage`, it must be translated by a receiving JMS provider into an equivalent `StreamMessage` or `MapMessage`. When passed between JMS clients, a message must always retain its full form. For instance, a message sent as `MapMessage` must not arrive at a JMS client as a `BytesMessage`.

If a JMS provider receives a message created by a native client, the provider should do its best to transform it into the ‘best’ JMS message type. For instance, if it is a native stream message it should be transformed into a `StreamMessage`. If this is not possible, the provider is always able to transform it into a `BytesMessage`.

3.12. Provider implementations of JMS message interfaces

JMS provides a set of message interfaces that define the JMS message model. It does not provide implementations of these interfaces.

Each JMS provider provides its own implementation of its Session’s message creation methods. This allows a provider to use message implementations that are tailored to its needs.

A provider must be prepared to accept, from a client, a message whose implementation is *not* one of its own. A message with a ‘foreign’ implementation may not be handled as efficiently as a provider’s own implementation; however, it must be handled.

The JMS message interfaces provide write/set methods for setting object values in a message body and message properties. All of these methods must be implemented to copy their input objects into the message. The value of an input object is allowed to be null and will return null when accessed.

One exception to this is that `BytesMessage` does not support the concept of a null stream and attempting to write a null into it must throw `java.lang.NullPointerException`.

The JMS message interfaces provide read/get methods for accessing objects in a message body and message properties. All of these methods must be implemented to return a copy of the accessed message objects.

4. *JMS common facilities*

4.1. *Overview*

This chapter describes the JMS facilities that are shared by both the PTP and Pub/Sub domains.

4.2. *Administered objects*

JMS administered objects are objects containing JMS configuration information that are created by a JMS administrator and later used by JMS clients. They make it practical to administer JMS applications in the enterprise.

Although the interfaces for administered objects do not explicitly depend on JNDI, JMS establishes the convention that JMS clients find them by looking them up in a namespace using JNDI.

An administrator can place an administered object anywhere in a namespace. JMS does not define a naming policy.

This strategy of partitioning JMS and administration provides several benefits:

- It hides provider-specific configuration details from JMS clients.
- It abstracts JMS administrative information into Java objects that are easily organized and administered from a common management console.
- Since there will be JNDI providers for all popular naming services, this means JMS providers can deliver one implementation of administered objects that will run everywhere.

An administered object should not hold on to any remote resources. Its lookup should not use remote resources other than those used by JNDI itself.

Clients should think of administered objects as local Java objects. Looking them up should not have any hidden side effects or use surprising amounts of local resources.

JMS defines two administered objects, `Destination` and `ConnectionFactory`.

It is expected that JMS providers will provide the tools an administrator needs to create and configure administered objects in a JNDI namespace. JMS provider implementations of administered objects should be both `javax.naming.Referenceable` and `java.io.Serializable` so that they can be stored in all JNDI naming contexts. In addition, it is recommended that these implementations follow the JavaBeans™ design patterns.

4.2.1. *Destination*

JMS does not define a standard address syntax. Although this was considered, it was decided that the differences in address semantics between existing enterprise messaging products was too wide to bridge

with a single syntax. Instead, JMS defines the `Destination` object which encapsulates provider-specific addresses.

Since `Destination` is an administered object it may also contain provider-specific configuration information in addition to its address.

JMS also supports a client's use of provider-specific address names. See Section 4.4.4 "Creating `Destination` objects" for more information.

`Destination` objects support concurrent use.

4.2.2. *ConnectionFactory*

A `ConnectionFactory` encapsulates a set of connection configuration parameters that has been defined by an administrator. A client uses it to create a `Connection` with a JMS provider.

`ConnectionFactory` objects support concurrent use.

4.3. *Connection*

A JMS `Connection` is a client's active connection to its JMS provider. It will typically allocate provider resources outside the Java virtual machine.

`Connection` objects support concurrent use.

A `Connection` serves several purposes:

- It encapsulates an open connection with a JMS provider. It typically represents an open TCP/IP socket between a client and a provider's service daemon.
- Its creation is where client authentication takes place.
- It can specify a unique client identifier.
- It creates `Session` objects.
- It provides `ConnectionMetaData`.
- It supports an optional `ExceptionListener`.

Due to the authentication and communication setup done when a `Connection` is created, a `Connection` is a relatively heavyweight JMS object. Most clients will do all their messaging with a single `Connection`. Other more advanced applications may use several `Connection` objects. JMS does not architect a reason for using multiple connections (other than when a client acts as a gateway between two different providers); however, there may be operational reasons for doing so.

4.3.1. *Authentication*

When creating a connection, a client may specify its credentials as name/password.

If no credentials are specified, the current thread's credentials are used. At this point, the JDK does not define the concept of a thread's default credentials; however, it is likely this will be defined in the near future. For now, the identity of the user under which the JMS client is running should be used.

4.3.2. *Client identifier*

The preferred way to assign a client's client identifier is for it to be configured in a client-specific `ConnectionFactory` and transparently assigned to the connection it creates. Alternatively, a client can set a connection's client identifier using a provider-specific value. The facility to explicitly set a connection's client identifier is not a mechanism for overriding the identifier that has been administratively configured. It is provided for the case where no administratively specified identifier exists. If one does exist, an attempt to change it by setting it must throw a `IllegalStateException`.

An application may explicitly set a connection's client identifier by calling the `setClientID` method on the `Connection` object or, if the simplified API is being used, on the `JMSContext`.

If a client explicitly sets a connection's client identifier it must do so immediately after creating the `Connection` or `JMSContext` and before any other action on the `Connection` or `JMSContext` is taken. After this point, setting the client identifier is a programming error that should throw an `IllegalStateException`.

The purpose of client identifier is to associate a connection and its objects with a state maintained on behalf of the client by a provider. By definition, the client state identified by a client identifier can only be 'in use' by only one client at a time. A JMS provider must prevent concurrently executing clients from using it.

This prevention may take the form of `JMSExceptions` thrown when such use is attempted; it may result in the offending client being blocked; or some other solution. A JMS provider must insure that such attempted 'sharing' of an individual client state does not result in messages being lost or doubly processed.

The only use of a client identifier defined by JMS is its optional use in identifying a durable subscription.

4.3.3. *Connection setup*

A JMS client typically creates a `Connection`; one or more `Session` objects; and a number of `MessageProducer` and `MessageConsumer` objects. When a `Connection` is created, it is in *stopped* mode. That means that no messages are being delivered to it.

It is typical to leave the `Connection` in stopped mode until setup is complete. At that point the connection's `start()` method is called and messages begin arriving at the connection's consumers. This setup convention minimizes any client confusion that may result from asynchronous message delivery while the client is still in the process of setting itself up.

A `Connection` can be started immediately and the setup can be done afterwards. Clients that do this must be prepared to handle asynchronous message delivery while they are still in the process of setting up.

A `MessageProducer` can send messages while a `Connection` is stopped.

It is important to note that clients rely on the fact that no messages are delivered by a connection until it has been started. JMS Providers must ensure that this is the case.

4.3.4. *Pausing delivery of incoming messages*

A connection's delivery of incoming messages can be temporarily stopped using its `stop` method. It can be restarted using its `start` method. When stopped, delivery to all the connection's `MessageConsumer` objects is inhibited: synchronous receives block, and messages are not delivered to any message listeners.

Stopping a connection has no affect on its ability to send messages. Stopping a stopped connection and starting a started connection are ignored.

A `stop` method call must not return until delivery of messages has paused. This means a client can rely on the fact that none of its message listeners will be called and all threads of control waiting for receive to return will not return with a message until the connection is restarted. The receive timers for a stopped connection continue to advance so receives may time out and return a null message while the connection is stopped.

If any message listeners are running when `stop` is invoked, `stop` must wait until all of them have returned before it may return. While these message listeners are completing, they must have the full services of the connection available to them.

A message listener must not attempt to stop its own connection as this would lead to deadlock. The JMS provider must detect this and throw a `javax.jms.IllegalStateException`.

4.3.5. *Closing a Connection*

Since a provider typically allocates significant resources outside the JVM on behalf of a connection, clients should close them when they are not needed. Relying on garbage collection to eventually reclaim these resources may not be timely enough.

A close terminates all pending message receives on the connection's session's consumers. The receives may return with a message or null depending on whether there was a message or not available at the time of the close.

Note that in this case, the message consumer will likely get an exception if it is attempting to use the facilities of the now closed connection while processing its last message. A developer must take this 'last message' case into account when writing a message consumer. It bears repeating that the message consumer cannot rely on a null return value to indicate this 'last message' case.

If one or more of the connection's session's message listeners is processing a message at the point when connection close is invoked, all the facilities of the connection and its sessions must remain available to those listeners until they return control to the JMS provider.

When connection close is invoked it should not return until message processing has been shut down in an orderly fashion. This means that all message listeners that may have been running have returned, and that all pending receives have returned.

A message listener must not attempt to close its own connection as this would lead to deadlock. The JMS provider must detect this and throw a `javax.jms.IllegalStateException`.

If a connection is closed, there is no need to close its constituent sessions, message producers, message consumers or queue browsers. The connection close is sufficient to signal the JMS provider that all resources for the connection should be released.

The `Connection` interface extends the `java.lang.AutoCloseable` interface. This means that applications which create the connection in a `try-with-resources` statement do not need to call the `close` method when the connection is no longer needed. Instead the connection will be closed automatically at the end of the statement. The use of a `try-with-resources` statement also simplifies the handling of any exceptions thrown by the `close` method. See the Java Tutorials³ for more information about the `try-with-resources` statement.

Closing a connection must rollback the transactions in progress on its transacted sessions⁴. Closing a connection does NOT force an acknowledge of client acknowledged sessions. Invoking the `acknowledge` method of a received message from a closed connection's sessions must throw an `IllegalStateException`. These semantics insure that closing a connection does not cause messages to be lost for queues and durable subscriptions which require reliable processing by a subsequent execution of their JMS client.

Once a connection has been closed, an attempt to use it or its sessions or their message consumers and producers must throw an `IllegalStateException` (calls to the `close` method of these objects must be ignored). It is valid to continue to use message objects created or received via the connection with the exception of a received message's `acknowledge` method.

Closing a closed connection must NOT throw an exception.

4.3.6. *Sessions*

A `Connection` is a factory for `Session` objects that use its underlying connection to a JMS provider for producing and consuming messages.

4.3.7. *ConnectionMetaData*

A `Connection` provides a `ConnectionMetaData` object. This object provides the latest version of JMS supported by the provider as well as the provider's product name and version.

It also provides a list of the JMS defined property names supported by the connection.

³ The Java Tutorials may be found at <http://docs.oracle.com/javase/tutorial/index.html>.

⁴ The term 'transacted session' refers to the case where a session's commit and rollback methods are used to demarcate a transaction local to the session. In the case where a session's work is coordinated by an external transaction manager, a session's commit and rollback methods are not used and the result of a closed session's work is determined later by the transaction manager.

4.3.8. *ExceptionListener*

If a JMS provider detects a problem with a connection, it will inform the connection's `ExceptionListener`, if one has been registered. To retrieve an `ExceptionListener`, the JMS provider calls the connection's `getExceptionListener()` method. This method returns the `ExceptionListener` for the connection. If no `ExceptionListener` is registered, the value `null` is returned. The connection can then use the listener by calling the listener's `onException()` method, passing it a `JMSEException` describing the problem.

This allows a client to be asynchronously notified of a problem. Some connections only consume messages, so they would have no other way to learn their connection has failed.

A `Connection` serializes execution of its `ExceptionListener`. This means that if a connection encounters multiple problems and therefore needs to call its `ExceptionListener` multiple times, then it will only invoke `onException` from one thread at a time. However if the same `ExceptionListener` is registered with multiple connections then it is undefined whether these connections could call `onException` from different threads simultaneously.

A JMS provider should attempt to resolve connection problems itself prior to notifying the client of them.

The exceptions delivered to `ExceptionListener` are those that have no other place to be reported. If an exception is thrown on a JMS call it, by definition, must not be delivered to an `ExceptionListener` (in other words, `ExceptionListener` is not for the purpose of monitoring all exceptions thrown by a connection).

There is no restriction on the use of the JMS API by the listener's `onException` method. However since that method will only be called when there is a serious problem with the connection, any attempt to use that connection may fail and cause exceptions.

4.4. *Session*

A JMS `Session` is a single threaded context⁵ for producing and consuming messages. Although it may allocate provider resources outside the Java virtual machine, it is considered a light-weight JMS object.

A `Session` serves several purposes:

- It is a factory for `MessageProducer` and `MessageConsumer` objects.
- It is a factory for `TemporaryTopic` and `TemporaryQueue` objects.

⁵ There are no restrictions on the number of threads that can use a `Session` object or those it creates. The restriction is that the resources of a `Session` should not be used concurrently by multiple threads. It is up to the user to ensure that this concurrency restriction is met. The simplest way to do this is to use one thread. In the case of asynchronous delivery, use one thread for setup in stopped mode and then start asynchronous delivery. In more complex cases the user must provide explicit synchronization.

- It provides a way to create `Queue` or `Topic` objects for those clients that need to dynamically manipulate provider-specific destination names.
- It supplies provider-optimized message factories.
- It supports a single series of transactions that combine work spanning this session's producers and consumers into atomic units.
- It defines a serial order for the messages it consumes and the messages it produces.
- It retains messages it consumes until they have been acknowledged.
- It serializes execution of `MessageListener` objects registered with it.
- It is a factory for `QueueBrowser` objects.

4.4.1. *Closing a Session*

Since a provider may allocate some resources on behalf of a session outside the JVM, clients should close them when they are not needed. Relying on garbage collection to eventually reclaim these resources may not be timely enough. The same is true for the `MessageProducer` and `MessageConsumer` objects created by a session.

Session close terminates all message processing on the session. It must handle the shutdown of pending receives by the session's consumers or a running message listener as described in *Closing a Connection*.

Session close is the only session method that may be invoked from a thread of control separate from the one which is currently controlling the session.

When session close is invoked it should not return until its message processing has been shut down in an orderly fashion. This means that none of its message listeners are running, and that if there is a pending receive, it has returned with either null or a message.

A message listener must not attempt to close its own session as this would lead to deadlock. The JMS provider must detect this and throw a `javax.jms.IllegalStateException`.

When a session is closed, there is no need to close its constituent message producers, message consumers or queue browsers. The session close is sufficient to signal the JMS provider that all resources for the session should be released.

Note that closing a connection will cause any sessions created from it to be closed, so, although a session should be closed when no longer needed, there is no need to close a session immediately prior to closing its connection.

The `Session` interface extends the `java.lang.AutoCloseable` interface. This means that applications which create the session in a `try-with-resources` statement do not need to call the `close` method when the connection is no longer needed. Instead the session will be closed automatically at the end of the statement. The use of a `try-with-resources` statement also simplifies the handling of any exceptions thrown by the `close` method.

Closing a transacted session must rollback its transaction in progress.
Closing a client-acknowledged session does NOT force an acknowledge.

Once a session has been closed, an attempt to use it or its message consumers and producers must throw an `IllegalStateException` (calls to the `close` method of these objects must be ignored). It is valid to continue to use message objects created or received via the session with the exception of a received message's `acknowledge` method.

Closing a closed session must NOT throw an exception.

4.4.2. *MessageProducer and MessageConsumer Creation*

A session can create and service multiple `MessageProducer` and `MessageConsumer` objects. See Section 4.5 "MessageConsumer" and Section 4.6 "MessageProducer" for information on their creation and use.

Although a session may create multiple producers and consumers, they are restricted to serial use. In effect, only a single logical thread of control can use them. This is explained in more detail later.

4.4.3. *Creating temporary destinations*

Although sessions are used to create temporary destinations, this is only for convenience. Their scope is actually the entire connection. Their lifetime is that of their connection and any of the connection's sessions are allowed to create a `MessageConsumer` for them.

Temporary destinations (`TemporaryQueue` or `TemporaryTopic` objects) are destinations that are system-generated uniquely for their connection. Only their own connection is allowed to create `MessageConsumer` objects for them.

One typical use for a `TemporaryDestination` is as the `JMSReplyTo` destination for service requests.

Each `TemporaryQueue` or `TemporaryTopic` object is unique. It cannot be copied.

Since temporary destinations may allocate resources outside the JVM, they should be deleted if they are no longer needed. They will be automatically deleted when they are garbage collected or when their connection is closed.

4.4.4. *Creating Destination objects*

Most clients will use `Destination` objects that are JMS administered objects that they have looked up via JNDI. This is the most portable approach.

Some specialized clients may need to create `Destination` objects by dynamically manufacturing one using a provider specific destination name. Sessions provide a JMS provider-specific method for doing this.

4.4.5. *Optimized message implementations*

A session provides the following methods to create messages:
`createMessage`, `createBytesMessage`, `createMapMessage`,
`createObjectMessage`, `createStreamMessage` and
`createTextMessage`.

These methods allow the JMS provider to create message implementations which are optimized for that particular provider and allow the provider to minimize its overhead for handling messages.

However the fact that these methods are provided on a session does not mean that messages must be sent using a message producer created from the same session. Messages may be sent using any session, not just the session used to create the message.

Furthermore, sessions must be capable of sending all JMS messages regardless of how they may be implemented. See section 3.12 "Provider implementations of JMS message interfaces".

4.4.6. *Conventions for using a session*

Sessions are designed for serial use by one thread at a time. The only exception to this occurs during the orderly shutdown of the session or its connection. See Section 4.3.5 "Closing a Connection" and Section 4.4.1 "Closing a Session" for further details.

One typical use is to have a thread block on a synchronous `MessageConsumer` until a message arrives. The thread may then use one or more of the session's `MessageProducer` objects.

It is erroneous for a client to use a thread of control to attempt to synchronously receive a message if there is already a client thread of control waiting to receive a message in the same session.

Another typical use is to have one thread set up a session by creating its producers and one or more asynchronous consumers. In this case, the message producers are exclusively for the use of the consumer's message listeners. Since the session serializes execution of its consumers' message listeners, they can safely share the resources of their session.

If a connection is left in stopped mode while its sessions are being set up, a client does not have to deal with messages arriving before the client is fully prepared to handle them. This is the preferred strategy because it eliminates the possibility of unanticipated conflicts between setup and message processing. It is possible to create and set up a session while a connection is receiving messages. In this case, more care is required to ensure that a session's message producers, message consumers and message listeners are created in the right order. For instance, a bad order may cause a `MessageListener` to use a `MessageProducer` that has yet to be created; or messages may arrive in the wrong order due to the order in which `MessageListener` objects are registered.

If a client desires to have one thread producing messages while others consume them, the client should use a separate session for its producing thread.

Once a connection has been started, all its sessions with a registered message listener are dedicated to the thread of control that delivers messages to them. It is erroneous for client code to use such a session from another thread of control. The only exception to this is the use of the session or connection close method.

One consequence of the session's single-thread-of-control restriction is that a session with message listeners cannot also be used to synchronously receive messages. Either the session is dedicated to the thread of control used for delivery to message listeners, or it is dedicated to a thread of

control initiated by client code. It is erroneous to attempt to combine both in the same session.

Another consequence is that a connection must be in stopped mode to set up a session with more than one message listener. The reason is that when a connection is actively delivering messages, once the first message listener for a session has been registered, the session is now controlled by the thread of control that delivers messages to it. At this point a client thread of control cannot be used to further configure the session.

It should be natural for most clients to partition their work into sessions. This model allows clients to start simply and incrementally add message processing complexity as their need for concurrency grows.

Since a `JMSContext` incorporates a `Session` it is subject to the same threading restrictions as a `Session`. For more information, and an exception to this, see section 11.2.8 "Threading restrictions on a `JMSContext`".

Additional threading restrictions apply to applications which perform an asynchronous send. See section 4.6.2 "Asynchronous send" and in particular section 4.6.2.6 "Restrictions on threading"

4.4.7. Transactions

A `Session` may be optionally specified as *transacted*. Each transacted session supports a single series of transactions. Each transaction groups a set of produced messages and a set of consumed messages into an atomic unit of work. In effect, transactions organize a session's input message stream and output message stream into series of atomic units. When a transaction commits, its atomic unit of input is acknowledged and its associated atomic unit of output is sent. If a transaction rollback is done, its produced messages are destroyed and its consumed messages are automatically recovered. For more information on session recovery see Section 4.4.11 "Message acknowledgment".

A transaction is completed using either its session's `commit()` or `rollback()` method. The completion of a session's current transaction automatically begins the next. The result is that a transacted session always has a current transaction within which its work is done.

JTS or some other transaction monitor facility may be used to combine a session's transaction with transactions on other resources (databases, other JMS Sessions, etc.). Since Java distributed transactions are controlled via the JTA transaction demarcation API, use of the session's `commit` and `rollback` methods in this context throws a `JMSTransactionInProgressException`.

4.4.8. Distributed transactions

JMS does not require that a provider support distributed transactions; however, it does define that if a provider supplies this support it should be done via the JTA `XAResource` API.

A JMS provider may also be a distributed transaction monitor. If it is, it should provide control of the transaction via the JTA API.

Although it is possible for a JMS client to handle distributed transactions directly, it is recommended that JMS clients avoid doing this. JMS clients that use the XA-based interfaces described in Chapter 8 "JMS application server facilities" may not be portable across different JMS

implementations, because these interfaces are optional. Support for JTA in JMS is targeted at systems vendors who will be integrating JMS into their application server products. See Chapter 8 "JMS application server facilities" for more information.

4.4.9. *Multiple sessions*

A client may create multiple sessions. Each session is an independent producer and consumer of messages.

For Pub/Sub, if two sessions each have a `TopicSubscriber` that subscribes to the same topic, each subscriber is given each message. Delivery to one subscriber does not block if the other gets behind.

For PTP, JMS does not specify the semantics of concurrent `QueueReceiver` objects for the same queue; however, JMS does not prohibit a provider from supporting this. Therefore, message delivery to multiple `QueueReceiver` objects will depend on the JMS provider's implementation. Applications that depend on delivery to multiple `QueueReceiver` objects are not portable

4.4.10. *Message order*

JMS clients need to understand when they can depend on message order and when they cannot.

4.4.10.1. *Order of message receipt*

Messages consumed by a session define a serial order. This order is important because it defines the effect of message acknowledgment. See Section 4.4.11 "Message acknowledgment" for more details. The messages for each of a session's consumers are interleaved in a session's input message stream.

JMS defines that messages sent by a session to a destination must be received in the order in which they were sent (see Section 4.4.10.2 "Order of message sends" for a few qualifications). This defines a partial ordering constraint on a session's input message stream.

JMS does not define order of message receipt across destinations or across a destination's messages sent from multiple sessions. This aspect of a session's input message stream order is timing-dependent. It is not under application control.

4.4.10.2. *Order of message sends*

Although clients loosely view the messages they produce within a session as forming a serial stream of sent messages, the total ordering of this stream is not significant. The only ordering that is visible to receiving clients is the order of messages a session sends to a particular destination. Several things can affect this order:

- Messages of higher priority may jump ahead of previous lower-priority messages.
- Messages with a later delivery time may be delivered after messages with an earlier delivery time.
- A client may not receive a `NON_PERSISTENT` message due to a JMS provider failure.

- If both `PERSISTENT` and `NON_PERSISTENT` messages are sent to a destination, order is only guaranteed within delivery mode. That is, a later `NON_PERSISTENT` message may arrive ahead of an earlier `PERSISTENT` message; however, it will never arrive ahead of an earlier `NON_PERSISTENT` message with the same priority.
- A client may use a transacted session to group its sent messages into atomic units (the producer component of a JMS transaction). A transaction's order of messages to a particular destination is significant. The order of sent messages across destinations is not significant. See Section 4.4.7 "Transactions" for more information.

4.4.11. *Message acknowledgment*

If a session is transacted, message acknowledgment is handled automatically by `commit`, and recovery is handled automatically by `rollback`.

If a session is not transacted, there are three acknowledgment options and recovery is handled manually:

- `DUPS_OK_ACKNOWLEDGE` - This option instructs the session to lazily acknowledge the delivery of messages. This is likely to result in the delivery of some duplicate messages if JMS fails, it should only be used by consumers that are tolerant of duplicate messages. Its benefit is the reduction of session overhead achieved by minimizing the work the session does to prevent duplicates.
- `AUTO_ACKNOWLEDGE` - With this option, the session automatically acknowledges a client's receipt of a message when it has either successfully returned from a call to receive or the message listener it has called to process the message successfully returns.
- `CLIENT_ACKNOWLEDGE` - With this option, a client acknowledges a message by calling the message's `acknowledge` method. Acknowledging a consumed message automatically acknowledges the receipt of all messages that have been delivered by its session.

When `CLIENT_ACKNOWLEDGE` mode is used, a client may build up a large number of unacknowledged messages while attempting to process them. A JMS provider should provide administrators with a way to limit client over-run so that clients are not driven to resource exhaustion and ensuing failure when some resource they are using is temporarily blocked.

A session's `recover` method is used to stop a session and restart it with its first unacknowledged message. In effect, the session's series of delivered messages is reset to the point after its last acknowledged message. The messages it now delivers may be different from those that were originally delivered due to message expiration, the arrival of higher-priority messages, or the delivery of messages which could not previously be delivered as they had not reached their specified delivery time.

A session must set the `JMSRedelivered` header and increment the `JMSXDeliveryCount` property of messages it redelivers due to a recovery

4.4.12. *Duplicate delivery of messages*

A JMS provider must never deliver a second copy of an acknowledged message.

When a client uses the `AUTO_ACKNOWLEDGE` mode, it is not in direct control of message acknowledgment. Since such clients cannot know for certain if a particular message has been acknowledged, they must be prepared for redelivery of the last consumed message. This can be caused by the client completing its work just prior to a failure that prevents the message acknowledgment from occurring. Only a session's last consumed message is subject to this ambiguity. The `JMSRedelivered` message header field will be set for a message redelivered under these circumstances, and the `JMSXDeliveryCount` property will be incremented.

4.4.13. *Duplicate production of messages*

JMS providers must never produce duplicate messages. This means that a client that produces a message can rely on its JMS provider to ensure that consumers of the message will receive it only once. No client error can cause a provider to duplicate a message.

If a failure occurs between the time a client commits its work on a Session and the commit method returns, the client cannot determine if the transaction was committed or rolled back. The same ambiguity exists when a failure occurs between the non-transactional send of a `PERSISTENT` message and the return from the sending method.

It is up to a JMS application to deal with this ambiguity. In some cases, this may cause a client to produce functionally duplicate messages.

A message that is redelivered due to session recovery is not considered a duplicate message.

4.4.14. *Serial execution of client code*

Even though the Java language provides built-in support for multithreading, writing multithreaded programs is still more difficult than writing singlethreaded ones.

For this reason, JMS does not cause concurrent execution of client code unless a client explicitly requests it. One way this is done is to define that a session serializes all asynchronous delivery of messages.

To receive messages asynchronously, a client registers an object that implements the `JMS MessageListener` interface with a `MessageConsumer` or `JMSConsumer`. *In effect, a session uses a single thread to run all its message listeners.* While the thread is busy executing one listener, all other messages to be asynchronously delivered to the session must wait.

4.4.15. *Concurrent message delivery*

Clients that desire concurrent delivery can use multiple sessions. In effect, each session's listener thread runs concurrently. While a listener on one session is executing, a listener on another session may also be executing.

Note that JMS itself does not provide the facilities for concurrently processing a topic's message set (the messages delivered to a single consumer). A client could use a single consumer and implement all the multithreading logic needed to concurrently process the messages; however, it is not possible to do this reliably, because JMS does not have the transaction facilities needed to handle the concurrent transactions this would require.

4.5. *MessageConsumer*

A client uses a `MessageConsumer` to receive messages from a destination. A `MessageConsumer` is created by passing a `Queue` or `Topic` to a session's `createConsumer` method.

A consumer can be created with a message selector. This allows the client to restrict the messages delivered to the consumer to those that match the selector. See Section 3.8.1 "Message selector" for more information.

A client may either synchronously receive a consumer's messages or have the provider asynchronously deliver them as they arrive.

4.5.1. *Synchronous delivery*

A client can request the next message from a `MessageConsumer` using one of its `receive` methods. There are several variations of `receive` that allow a client to poll or wait for the next message.

4.5.2. *Asynchronous delivery*

A client can register an object that implements the JMS `MessageListener` interface with a `MessageConsumer`. As messages arrive for the consumer, the provider delivers them by calling the listener's `onMessage` method.

It is possible for a listener to throw a `RuntimeException`; however, this is considered a client programming error. Well behaved listeners should catch such exceptions and attempt to divert messages causing them to some form of application-specific 'unprocessible message' destination.

The result of a listener throwing a `RuntimeException` depends on the session's acknowledgment mode.

- `AUTO_ACKNOWLEDGE` or `DUPS_OK_ACKNOWLEDGE` - the message will be immediately redelivered. The number of times a JMS provider will redeliver the same message before giving up is provider-dependent. The `JMSRedelivered` message header field will be set, and the `JMSXDeliveryCount` message property incremented, for a message redelivered under these circumstances.
- `CLIENT_ACKNOWLEDGE` - the next message for the listener is delivered. If a client wishes to have the previous unacknowledged message redelivered, it must manually recover the session.
- `Transacted Session` - the next message for the listener is delivered. The client can either commit or roll back the session (in other words, a `RuntimeException` does not automatically rollback the session).

JMS providers should flag clients with message listeners that are throwing `RuntimeException` as possibly malfunctioning.

See Section 4.4.14 "Serial execution of client code" for information about how `onMessage` calls are serialized by a session.

4.6. *MessageProducer*

A client uses a `MessageProducer` to send messages to a `Destination`. A `MessageProducer` is created by passing a `Queue` or `Topic` to a session's `createProducer` method.

A client also has the option of creating a producer without supplying a destination. In this case, a destination must be input on every send operation. A typical use for this style of producer is to send replies to requests using the request's `JMSReplyTo` destination.

A client may send a message either synchronously or asynchronously. For more details see sections 4.6.1 "Synchronous send" and 4.6.2 "Asynchronous send".

A client can specify a default delivery mode, priority, time-to-live and delivery delay for messages sent by a producer.

A client can also specify delivery mode, priority, and time-to-live per message.

Each time a client creates a `MessageProducer`, it defines a new sequence of messages that have no ordering relationship with the messages it has previously sent.

See Section 3.4.9 "JMSExpiration" for more information on time-to-live. See Section 3.4.10 "JMSPriority" for more information on priority. See Section 3.4.13 "JMSDeliveryTime" for more information on delivery delay.

4.6.1. *Synchronous send*

The following methods on `MessageProducer` may be used to send a message synchronously:

```
void send(Message message)

void send(Destination destination, Message message)

void send(Destination destination, Message message, int
deliveryMode, int priority, long timeToLive)

void send(Message message, int deliveryMode, int
priority, long timeToLive)
```

These methods will block until the message has been sent. If necessary the call will block until a confirmation message has been received back from the JMS server.

4.6.2. *Asynchronous send*

Clients may alternatively send a message using the following methods which permit the JMS provider to perform part of the work involved in sending the message in a separate thread. JMS refers to this as an "asynchronous send".

```
send(Destination destination, Message message,
CompletionListener completionListener)

send(Destination destination, Message message, int
deliveryMode, int priority, long timeToLive,
CompletionListener completionListener)

send(Message message, CompletionListener
completionListener)
```



```
send(Message message, int deliveryMode, int priority,  
long timeToLive, CompletionListener completionListener)
```

When the message has been successfully sent the JMS provider invokes the callback method `onCompletion` on an application-specified `CompletionListener` object. Only when that callback has been invoked can the application be sure that the message has been successfully sent with the same degree of confidence as if a normal synchronous send had been performed. An application which requires this degree of confidence must therefore wait for the callback to be invoked before continuing.

The following information is intended to give an indication of how an asynchronous send would typically be implemented.

In some JMS providers, a normal synchronous send involves sending the message to a remote JMS server and then waiting for an acknowledgement to be received before returning. It is expected that such a provider would implement an asynchronous send by sending the message to the remote JMS server and then returning without waiting for an acknowledgement. When the acknowledgement is received, the JMS provider would notify the application by invoking the `onCompletion` method on the application-specified `CompletionListener` object. If for some reason the acknowledgement is not received the JMS provider would notify the application by invoking the `CompletionListener`'s `onException` method.

In those cases where the JMS specification permits a lower level of reliability, a normal synchronous send might not wait for an acknowledgement. In that case it is expected that an asynchronous send would be similar to a synchronous send: the JMS provider would send the message to the remote JMS server and then return without waiting for an acknowledgement. However the JMS provider would still notify the application that the send had completed by invoking the `onCompletion` method on the application-specified `CompletionListener` object.

It is up to the JMS provider to decide exactly what is performed in the calling thread and what, if anything, is performed asynchronously, so long as it satisfies the requirements given in the following sections:

4.6.2.1. Quality of service

After the send operation is complete, which means that the message has been successfully sent with the same degree of confidence as if a normal synchronous send had been performed, the JMS provider must invoke the `CompletionListener`. The `CompletionListener` must not be invoked earlier than this.

4.6.2.2. Message order

If the same `MessageProducer` or `JMSContext` is used to send multiple messages then JMS message ordering requirements (see section 4.4.10 "Message order") must be satisfied. This applies even if a combination of synchronous and asynchronous sends has been performed. The application is not required to wait for an asynchronous send to complete before sending the next message.

4.6.2.3. Close, commit or rollback

If the session is transacted (uses a local transaction) then when the `commit` or `rollback` method is called the JMS provider must block until any

incomplete send operations have been completed and all callbacks have returned before performing the commit or rollback.

If the `close` method is called on the `MessageProducer`, `Session`, `Connection` or `JMSContext` object then the JMS provider must block until any incomplete send operations have been completed and all callbacks have returned before closing the object and returning.

4.6.2.4. *Restrictions on usage in Java EE*

An asynchronous send is not permitted in a Java EE EJB or web container. If the application component violates this restriction the send method may throw a `JMSEException` or `JMSRuntimeException` (depending on the method signature).

4.6.2.5. *Message headers*

JMS defines a number of message header fields and message properties which must be set by the "JMS provider on send". See section 3.4.11 "How message header values are set" and section 3.5.9 "JMS defined properties". If the send is asynchronous these fields and properties may be accessed on the sending client only after the `CompletionListener` has been invoked. If the `CompletionListener`'s `onException` method is called then the state of these message header fields and properties is undefined. See also section 4.6.2.8 "Restrictions on the use of the Message object" below.

4.6.2.6. *Restrictions on threading*

Applications that perform an asynchronous send must confirm to the threading restrictions defined in section 4.4.6 "Conventions for using a session". This means that the session may be used by only one thread at a time.

Setting a `CompletionListener` does not cause the session to be dedicated to the thread of control which calls the `CompletionListener`. The application thread may therefore continue to use the session after performing an asynchronous send. However the `CompletionListener`'s callback methods must not use the session if an application thread might be using the session at the same time.

4.6.2.7. *Use of the CompletionListener by the JMS provider*

A session will only invoke one `CompletionListener` callback method at a time. For a given `MessageProducer` or `JMSContext`, callbacks will be performed in the same order as the corresponding calls to the asynchronous send method.

A JMS provider must not invoke the `CompletionListener` from the thread that is calling the asynchronous send method.

4.6.2.8. *Restrictions on the use of the Message object*

Applications which perform an asynchronous send must take account of the restriction that a `Message` object is designed to be accessed by one logical thread of control at a time and does not support concurrent use. See section 2.8 "Multi-threading".

After the `send` method has returned, the application must not attempt to read the headers, properties or payload of the `Message` object until the `CompletionListener`'s `onCompletion` or `onException` method has

been called. This is because the JMS provider may be modifying the `Message` object in another thread during this time.

A JMS provider may throw a `JMSEException` if the application attempts to access or modify the `Message` object after the `send` method has returned and before the `CompletionListener` has been invoked. If the JMS provider does not throw an exception then the behaviour is undefined.

4.7. *Message delivery mode*

JMS supports two modes of message delivery.

- The `NON_PERSISTENT` mode is the lowest overhead delivery mode because it does not require that the message be logged to stable storage. A JMS provider failure can cause a `NON_PERSISTENT` message to be lost.
- The `PERSISTENT` mode instructs the JMS provider to take extra care to ensure the message is not lost in transit due to a JMS provider failure.

A JMS provider must deliver a `NON_PERSISTENT` message *at-most-once*. This means it may lose the message, but it must not deliver it twice.

A JMS provider must deliver a `PERSISTENT` message *once-and-only-once*. This means a JMS provider failure must not cause it to be lost, and it must not deliver it twice.

`PERSISTENT` (once-and-only-once) and `NON_PERSISTENT` (at-most-once) message delivery are a way for a JMS client to select between delivery techniques that may lose a messages if a JMS provider dies and those which take extra effort to ensure that messages can survive such a failure. There is typically a performance/reliability trade-off implied by this choice. When a client selects the `NON_PERSISTENT` delivery mode, it is indicating that it values performance over reliability; a selection of `PERSISTENT` reverses the requested trade-off.

The use of `PERSISTENT` messages does not guarantee that all messages are always delivered to every eligible consumer. See Section 4.10 "Reliability" for further discussion on this topic.

4.8. *Message time-to-live*

A client can specify a time-to-live value in milliseconds for each message it sends. This value defines a message expiration time which is the sum of the message's time-to-live and the GMT it is sent (for transacted sends, this is the time the client sends the message, not the time the transaction is committed).

A JMS provider should do its best to accurately expire messages; however, JMS does not define the accuracy provided. It is not acceptable to simply ignore time-to-live.

For more information on message expiration, see Section 3.4.9 "JMSExpiration".

4.9. *Exceptions*

`JMSEException` is the base class for all JMS exceptions. See Chapter 7 "JMS exceptions" for more information.

4.10. Reliability

Most clients should use producers that produce `PERSISTENT` messages. This ensures once-and-only-once message delivery for messages delivered from a queue or a durable subscription.

In some cases, an application may only require at-most-once message delivery for some of its messages. This is accomplished by publishing `NON_PERSISTENT` messages. These messages typically have lower overhead; however, they may be lost if a JMS provider fails. Both `PERSISTENT` and `NON_PERSISTENT` messages can be published to the same destination.

Normally, a consumer fully processes each message before acknowledging its receipt to JMS. This insures that JMS does not discard a partially processed message due to machine failure, etc. A consumer accomplishes this by using either a transacted or `CLIENT_ACKNOWLEDGE` session. Unacknowledged messages redelivered due to system failure must have the `JMSRedelivered` message header field set, and the `JMSXDeliveryCount` incremented, by the JMS provider, as described in sections 3.4.7 "JMSRedelivered" and 3.5.11 "JMSXDeliveryCount"

If a `NON_PERSISTENT` message is delivered to a durable subscription or a queue, delivery is not guaranteed if the durable subscription becomes inactive (that is, if it has no current subscriber) or if the JMS provider is shut down and later restarted.

It is expected that important messages will be produced with a `PERSISTENT` delivery mode within a transaction and will be consumed within a transaction from a nontemporary queue or a durable subscription.

When this is done, applications have the highest level of assurance that a message has been properly produced, reliably delivered, and accurately consumed. Non-transactional production and consumption can also achieve the same level of assurance; however, this requires careful programming.

A JMS provider may have resource restrictions that limit the number of messages that can be held for high-volume destinations or non-responsive clients. If messages are dropped due to resource limits, this is usually a serious administrative issue that needs attention. Correct functioning of JMS requires that clients are responsive and that adequate resources to service them are available.

Once-and-only-once message delivery, as described in this specification, has the important caveat that it does not cover message destruction due to message expiration or other administrative destruction criteria. It also does not cover loss due to resource restrictions. Configuration of adequate resources and processing power for JMS applications is the job of administrators, who must be aware of their JMS provider's reliability features.

`NON_PERSISTENT` messages, nondurable subscriptions, and temporary destinations are by definition unreliable. A JMS provider shutdown or failure will likely cause the loss of `NON_PERSISTENT` messages and the loss of messages held by temporary destinations and nondurable subscriptions. The termination of an application will likely cause the loss of messages held by nondurable subscriptions and temporary destinations of the application.

4.11. Method inheritance across messaging domains

As a result of unifying the domains, some methods that are not appropriate to a domain may be inherited in the domain-specific classes. For example, the `Session` interface has the method `createQueueBrowser`. Since `TopicSession` inherits from the `Session` interface, `TopicSession` inherits the `createQueueBrowser` method, though that method must not be used by a topic, as topics do not support queue browsers. Table 4.1 outlines these instances.

If a application attempts to call any of the methods listed, the JMS provider must throw an `IllegalStateException`.

Table 4.1 methods that throw an `IllegalStateException`

| Interface | Method |
|-----------------|---------------------------------|
| QueueConnection | createDurableConnectionConsumer |
| QueueSession | createDurableSubscriber |
| | createDurableConsumer |
| | createSharedConsumer |
| | createTemporaryTopic |
| | createTopic |
| | unsubscribe |
| TopicSession | createQueueBrowser |
| | createQueue |
| | createTemporaryQueue |

4.12. Delivery delay

A client can specify a delivery delay value in milliseconds for each message it sends. This value defines a message delivery time which is the sum of the message's delivery delay and the GMT it is sent (for transacted sends, this is the time the client sends the message, not the time the transaction is committed).

A message's delivery time is the earliest time when a JMS provider may deliver the message to a consumer. The provider must not deliver messages before the delivery time has been reached.

If a message is published to a topic, it will only be added to a durable or non-durable subscription on that topic if the subscription exists at the time the message is sent.

For more information on message delivery delay, see Section 3.4.13 "JMSDeliveryTime".

5. *JMS point-to-point model*

5.1. *Overview*

Point-to-point systems are about working with queues of messages. They are point-to-point in that a client sends a message to a specific queue. Some PTP systems blur the distinction between PTP and Pub/Sub by providing system clients that automatically distribute messages.

It is common for a client to have all its messages delivered to a single queue.

Like any generic mailbox, a queue can contain a mixture of messages. And, like real mailboxes, creating and maintaining each queue is somewhat costly. Most queues are created administratively and are treated as static resources by their clients.

The JMS PTP model defines how a client works with queues: how it finds them, how it sends messages to them, and how it receives messages from them.

This chapter describes the semantics of the Point-to-Point model. A JMS provider that supports the Point-to-Point model must deliver the semantics described here.

Whether a JMS client program uses the PTP domain-specific interfaces, or the common interfaces that are described in Chapter 4, “JMS Common Facilities, the client program *must* be guaranteed the same behavior.

Table 5.1 shows the interfaces that are specific to the PTP domain and the JMS common interfaces. The common interfaces are preferred for creating JMS application programs, because they are domain-independent.

Table 5.1 PTP domain interfaces and JMS common interfaces

| PTP domain interfaces | JMS common interfaces <i>preferred</i> |
|------------------------------|---|
| QueueConnectionFactory | ConnectionFactory |
| QueueConnection | Connection |
| Queue | Destination |
| QueueSession | Session |
| QueueSender | MessageProducer |
| QueueReceiver | MessageConsumer |

5.2. *Queue management*

JMS does not define facilities for creating, administering, or deleting long-lived queues (it does provide such a mechanism for temporary queues). Since most clients use statically defined queues this is not a problem.

5.3. *Queue*

A *Queue* object encapsulates a provider-specific queue name. It is the way a client specifies the identity of queue to JMS methods.

The actual length of time messages are held by a queue and the consequences of resource overflow are not defined by JMS.

See Section 4.2 "Administered objects" for more information about JMS *Destination* objects.

5.4. *TemporaryQueue*

A *TemporaryQueue* is a unique *Queue* object created for the duration of a *Connection* or *QueueConnection*. It is a system-defined queue that can only be consumed by the *Connection* or *QueueConnection* that created it.

See Section 4.4.3 "Creating temporary destinations" for more information.

5.5. *QueueConnectionFactory*

A client uses a *QueueConnectionFactory* to create *QueueConnection* objects..

See Section 4.2, "Administered Objects" for more information about JMS *ConnectionFactory* objects.

5.6. *QueueConnection*

A *QueueConnection* is an active connection to a JMS PTP provider. A client uses a *QueueConnection* to create one or more *QueueSession* objects for producing and consuming messages.

See Section 4.2 "Administered objects" for more information.

5.7. *QueueSession*

A *QueueSession* provides methods for creating *QueueReceiver*, *QueueSender*, *QueueBrowser* and *TemporaryQueue* objects.

If there are messages that have been received but not acknowledged when a *QueueSession* terminates, these messages must be retained and redelivered when a consumer next accesses the queue.

See Section 4.3 "Connection" for more information.

5.8. *QueueReceiver*

A client uses a *QueueReceiver* for receiving messages that have been delivered to a queue.

Although is possible to have two sessions with a *QueueReceiver* for the same queue, JMS does not define how messages are distributed between the queue receivers.

If a *QueueReceiver* specifies a message selector, the messages that are not selected remain on the queue. By definition, a message selector allows a *QueueReceiver* to skip messages. This means that when the skipped messages are eventually read, the total ordering of the reads does not

retain the partial order defined by each message producer. Only queue receivers without a message selector will read messages in message producer order.

For more information see Section 4.5 "MessageConsumer". If a `MessageConsumer` is consuming messages from a queue, then it behaves as described here in Section 5.8 "QueueReceiver".

A client uses a `MessageProducer` or `QueueSender` to send messages to a queue.

For more information, see Section 4.6 "MessageProducer".

5.9. *QueueBrowser*

A client uses a `QueueBrowser` to look at messages on a queue without removing them. A `QueueBrowser` can be created from a `Session` or a `QueueSession`.

The browse methods return a `java.util.Enumeration` that is used to scan the queue's messages. It may be an enumeration of the entire content of a queue, or it may contain only the messages matching a message selector.

Messages may be arriving and expiring while the scan is done. JMS does not require the content of an enumeration to be a static snapshot of queue content. Whether these changes are visible or not depends on the JMS provider.

A message must not be returned by a `QueueBrowser` before its delivery time has been reached.

5.10. *QueueRequestor*

JMS provides a `QueueRequestor` helper class to simplify making service requests.

The `QueueRequestor` constructor is given a `QueueSession` and a destination queue. It creates a `TemporaryQueue` for the responses and provides a `request` method that sends the request message and waits for its reply.

This is a basic request/reply abstraction that should be sufficient for most uses. JMS providers and clients can create more sophisticated versions.

5.11. *Reliability*

A queue is typically created by an administrator and exists for a long time. It is always available to hold messages sent to it, whether or not the client that consumes its messages is active. For this reason, a client does not have to take any special precautions to ensure it does not miss messages.

6. JMS publish/subscribe model

6.1. Overview

The JMS Pub/Sub model defines how JMS clients publish messages to, and subscribe to messages from, a well-known node in a content-based hierarchy. JMS calls these nodes *topics*.

In this section, the terms *publish* and *subscribe* are used in place of the more generic terms *produce* and *consume* used previously.

A topic can be thought of as a mini message broker that gathers and distributes messages addressed to it. By relying on the topic as an intermediary, message publishers are kept independent of subscribers and vice versa. The topic automatically adapts as both publishers and subscribers come and go.

Publishers and subscribers are *active* when the Java objects that represent them exist. JMS also supports the optional *durability* of subscribers that 'remembers' the existence of them while they are inactive.

This chapter describes the semantics of the Publish/Subscribe model. A JMS provider that supports the Publish/Subscribe model must deliver the semantics described here.

Whether a JMS client program uses the Pub/Sub domain-specific interfaces, or the common interfaces that are described in Chapter 4 "JMS common facilities", the client program *must* be guaranteed the same behavior.

Table 6.1 shows the interfaces that are specific to the PTP domain and the JMS common interfaces. The common interfaces are preferred for creating JMS application programs, because they are domain-independent.

Table 6.1 Pub/sub domain interfaces and JMS common interfaces

| PTP domain interfaces | JMS common interfaces <i>Preferred</i> |
|------------------------|---|
| TopicConnectionFactory | ConnectionFactory |
| TopicConnection | Connection |
| Topic | Destination |
| TopicSession | Session |
| TopicPublisher | MessageProducer |
| TopicSubscriber | MessageConsumer |

6.2. Pub/sub latency

Since there is typically some latency in all pub/sub systems, the exact messages seen by a subscriber may vary depending on how quickly a JMS

provider propagates the existence of a new subscriber and the length of time a provider retains messages in transit.

For instance, some messages from a distant publisher may be missed because it may take a second for the existence of a new subscriber to be propagated system wide. When a new subscriber is created, it may receive messages sent earlier because a provider may still have them available.

JMS does not define the exact semantics that apply during the interval when a pub/sub provider is adjusting to a new client. JMS semantics only apply once the provider has reached a 'steady state' with respect to a new client.

6.3. *Durable subscription*

Nondurable subscriptions last for the lifetime of their subscriber object. This means that a client will only see the messages published on a topic while its subscriber is active. If the subscriber is not active, it is missing messages published on its topic.

At the cost of higher overhead, a subscriber can be made *durable*. A *durable subscriber registers a durable subscription* with a unique identity that is retained by JMS. Subsequent subscriber objects with the same identity resume the subscription in the state it was left by the prior subscriber. If there is no active subscriber for a durable subscription, JMS retains the subscription's messages until they are received by the subscription or until they expire.

All JMS providers must be able to run JMS applications that dynamically create and delete durable subscriptions. Some JMS providers may, in addition, provide facilities to administratively configure durable subscriptions. If a durable subscription has been administratively configured, it is valid for it to silently override the subscription specified by the client.

An *inactive* durable subscription is one that exists but does not currently have a message consumer subscribed to it.

See also section 6.11.3 "Durable subscriptions".

6.4. *Topic management*

Some products require that topics be statically defined with associated authorization control lists, and so on; others don't even have the concept of topic administration.

JMS does not define facilities for creating, administering, or deleting topics.

A special type of topic called a *TemporaryTopic* is provided for creating a *Topic* that is unique to a *TopicConnection*. See Section 6.6 "TemporaryTopic" for more details.

6.5. *Topic*

A *Topic* object encapsulates a provider-specific topic name. It is the way a client specifies the identity of a topic to JMS methods.

Many Pub/Sub providers group topics into hierarchies and provide various options for subscribing to parts of the hierarchy. JMS places no restriction

on what a `Topic` object represents. It might be a leaf in a topic hierarchy or it might be a larger part of the hierarchy (for subscribing to a general class of information).

The organization of topics and the granularity of subscriptions to them is an important part of a pub/sub application's architecture. JMS does not specify a policy for how this should be done. If an application takes advantage of a provider-specific topic grouping mechanism, it should document this. If the application is installed using a different provider, it is the job of the administrator to construct an equivalent topic architecture and create equivalent `Topic` objects.

6.6. *TemporaryTopic*

A `TemporaryTopic` is a unique `Topic` object created for the duration of a `Connection` or `TopicConnection`. It is a system defined `Topic` that can only be consumed only by the `Connection` or `TopicConnection` that created it.

By definition, it does not make sense to create a durable subscription to a temporary topic. To do this is a programming error that may or may not be detected by a JMS Provider.

See Section 4.4.3 "Creating temporary destinations" for more information.

6.7. *TopicConnectionFactory*

A client uses a `TopicConnectionFactory` to create `TopicConnection` objects.

See Section 4.2 "Administered objects" for more information about JMS `ConnectionFactory` objects.

6.8. *TopicConnection*

A `TopicConnection` is an active connection to a JMS Pub/Sub provider. A client uses a `TopicConnection` to create one or more `TopicSession` objects for producing and consuming messages.

See Section 4.3 "Connection" for more information.

6.9. *TopicSession*

A `TopicSession` provides methods for creating `TopicPublisher`, `TopicSubscriber` and `TemporaryTopic` objects. It also provides the `unsubscribe` method for deleting its client's durable subscriptions.

If there are messages that have been received but not acknowledged when a `TopicSession` terminates, a durable `TopicSubscriber` must retain and redeliver them; a nondurable subscriber need not do so.

See Section 4.4 "Session" for more information.

6.10. *TopicPublisher*

A client uses a `TopicPublisher` for publishing messages on a topic. `TopicPublisher` is the Pub/Sub variant of a JMS `MessageProducer`. Messages can also be sent to a topic using a `MessageProducer`. See Section 4.6 "MessageProducer" for a description of its common features.

6.11. TopicSubscriber

A client consumes messages from a topic by creating a subscription on that topic, and creating a `MessageConsumer` or `TopicSubscriber` on that subscription.

In general, a subscription will receive a copy of every message sent to the topic. However if a message selector is specified then only those messages whose properties match the message selector will be added to the subscription.

In addition, the `noLocal` flag may be specified when a `MessageConsumer` or `TopicSubscriber` is created. The effect of setting this flag depends on the type of subscription and is defined in the following sections.

Each copy of the message is treated as a completely separate message. Work done on one copy has no effect on any other; acknowledging one does not acknowledge any other; one message may be delivered immediately, while another waits for its consumer to process messages ahead of it.

Subscriptions may be *durable* or *non-durable*.

A *non-durable subscription* exists only so long as a `MessageConsumer` or `TopicSubscriber` object exists to consume messages from it. A non-durable subscription may be either *unshared* or *shared*.

An *unshared non-durable subscription* does not have a name and may have only a single `MessageConsumer` or `TopicSubscriber` object associated with it. It is created automatically when the `MessageConsumer` or `TopicSubscriber` object is created. It is not persisted and is deleted automatically when it is closed. See section 6.11.1 "Unshared non-durable subscriptions" below.

A *shared non-durable subscription* is identified by name, which may be used to associate several `MessageConsumer` or `TopicSubscriber` objects with it. It is created automatically when the first `MessageConsumer` or `TopicSubscriber` object is created. It is not persisted and is deleted automatically when the last `MessageConsumer` or `TopicSubscriber` object is closed. See section 6.11.2 "Shared non-durable subscriptions" below.

A *durable subscription* is identified by a name and an optional client identifier, which may be used to associate several `MessageConsumer` or `TopicSubscriber` objects with it. A durable subscription is created automatically when the first `MessageConsumer` or `TopicSubscriber` object is created. It is persisted and continues to exist until explicitly deleted, even if there are no `MessageConsumer` or `TopicSubscriber` objects consuming messages from it. See section 6.11.3 "Durable subscriptions" below.

6.11.1. Unshared non-durable subscriptions

An unshared non-durable subscription is the simplest way to consume messages from a topic.

An unshared non-durable subscription is created, and a `MessageConsumer` created on that subscription, using one of the

`createConsumer` methods on `Session`, `JMSContext` or `TopicSession`.

Alternatively an unshared non-durable subscription is created, and a `TopicSubscription` created on that subscription, using one of the `createSubscriber` methods on `TopicSession`.

An unshared non-durable subscription does not have a name. Each call to `createConsumer` or `createSubscriber` creates a new subscription.

An unshared non-durable subscription only exists for as long as the `MessageConsumer` or `TopicSubscriber` exists. This means that any messages sent to the topic will only be added to the subscription whilst the `MessageConsumer` or `TopicSubscriber` is active. The subscription is not persisted and will be deleted (together with any undelivered messages associated with it) when the consumer is closed.

If a message selector is specified then only messages with properties matching the message selector expression will be added to the subscription.

The `noLocal` argument may be used to specify that messages published to the topic by its own connection must not be added to the subscription.

Each unshared non-durable subscription has a single consumer. If the application needs to create multiple consumers on the same subscription then a shared non-durable subscription should be used instead. See section 6.11.2 "Shared non-durable subscriptions".

If the application needs to be able to receive messages that were sent to the topic even when there was no active consumer on it then a durable subscription should be used instead. See section 6.11.3 "Durable subscriptions".

6.11.2. *Shared non-durable subscriptions*

A non-durable shared subscription is used by a client which needs to be able to share the work of receiving messages from a topic subscription amongst multiple consumers. A non-durable shared subscription may therefore have more than one consumer. Each message from the subscription will be delivered to only one of the consumers on that subscription.

A shared non-durable subscription is created, and a `MessageConsumer` created on that subscription, using one of the `createSharedConsumer` methods on `Session`, `JMSContext` or `TopicSession`. The same methods may be used to create a `MessageConsumer` on an existing shared non-durable subscription.

A shared non-durable subscription is identified by a name specified by the client.

A shared non-durable subscription only exists for as long as a `MessageConsumer` or `TopicSubscriber` exists on the subscription. This means that any messages sent to the topic will only be added to the subscription whilst a `MessageConsumer` or `TopicSubscriber` is active. The subscription is not persisted and will be deleted (together with any undelivered messages associated with it) when the last consumer on the subscription is closed.

If a message selector is specified then only messages with properties matching the message selector expression will be added to the subscription.

The `noLocal` argument may be used to specify that messages published to the topic by its own connection must not be added to the subscription.

If there is an active consumer on the non-durable shared subscription (or a consumed message from that subscription is still part of a pending transaction or is not yet acknowledged in the session), and an attempt is made to create an additional consumer, specifying the same name but a different topic or message selector, then a `JMSException` or `JMSRuntimeException` will be thrown.

There is no restriction to prevent a shared non-durable subscription and a durable subscription having the same name. Such subscriptions would be completely separate.

6.11.3. *Durable subscriptions*

A durable subscription is used by a client that needs to receive all the messages published on a topic, including the ones published when there is no consumer associated with it. The JMS provider retains a record of this durable subscription and ensures that all messages from the topic's publishers are retained until they are delivered to, and acknowledged by, a consumer on the durable subscription or until they have expired.

A durable subscription is created, and a `MessageConsumer` created on that durable subscription, using the `createDurableConsumer` methods on a `Session` or `TopicSession`. The same methods may be used to create a `MessageConsumer` on an existing durable subscription.

There are also `createDurableSubscriber` methods which have the same behavior as `createDurableConsumer` but which return a `TopicSubscriber`.

A durable subscription which has a consumer associated with it is described as being active. A durable subscription which has no consumer associated with it is described as being inactive.

A durable subscription may have more than one active consumer (this was not permitted prior to JMS 2.0). Each message from the subscription will be delivered to only one of the consumers on that subscription.

A durable subscription is identified by a name specified by the client and by the client identifier if set. If the client identifier was set when the durable subscription was first created then a client which subsequently wishes to create a consumer on that durable subscription must use the same client identifier.

If there are no active consumers on the durable subscription (and no consumed messages from that subscription are still part of a pending transaction or are not yet acknowledged in the session), and this method is used to create a new consumer on that durable subscription, specifying the same name and client identifier (if set) but a different topic or message selector, or, if the client identifier is set, a different `noLocal` argument, then the durable subscription will be deleted and a new one created.

However if there is an active consumer on the durable subscription (or a consumed message from that subscription is still part of a pending transaction or is not yet acknowledged in the session), and an attempt is

made to create an additional consumer, specifying the same name and client identifier (if set) but a different topic or message selector, or, if the client identifier is set, a different `noLocal` argument, then a `JMSException` or `JMSRuntimeException` will be thrown.

A durable subscription will continue to accumulate messages until it is deleted using the `unsubscribe` method on the `Session`, `TopicSession` or `JMSContext`. This deletes the state being maintained on behalf of the subscriber by its provider. It is erroneous for a client to delete a durable subscription while it has an active consumer or while a message received from it is part of a current transaction or has not been acknowledged in the session.

When a durable subscription is created on a topic, the `noLocal` argument may be used to specify that messages published to the topic by its own connection or any other with the same client identifier will not be added to the durable subscription. If the client identifier is unset then setting `noLocal` to true has no effect.

See also section 6.3 "Durable subscription" and section 4.3.2 "Client identifier".

6.12. *Recovery and redelivery*

Unacknowledged messages of a nondurable subscriber should be able to be recovered for the lifetime of that nondurable subscriber. When a nondurable subscriber terminates, messages waiting for it will likely be dropped whether or not they have been acknowledged.

Only durable subscriptions are reliably able to recover unacknowledged messages.

Sending a message to a topic with a delivery mode of `PERSISTENT` does not alter this model of recovery and redelivery. To ensure delivery, a `TopicSubscriber` should establish a durable subscription.

6.13. *Administering subscriptions*

Ideally, publishers and subscribers are dynamically registered by a provider when they are created. From the client viewpoint this is always the case. From the administrator's viewpoint, other tasks may be needed to support the creation of publishers and subscribers.

The amount of resources allocated for message storage and the consequences of resource overflow are not defined by JMS.

6.14. *TopicRequestor*

JMS provides a `TopicRequestor` helper class to simplify making service requests.

The `TopicRequestor` constructor is given a `TopicSession` and a destination topic. It creates a `TemporaryTopic` for the responses and provides a `request` method that sends the request message and waits for its reply.

This is a basic request/reply abstraction that should be sufficient for most uses. JMS providers and clients are free to create more sophisticated versions.

6.15. Reliability

When all messages for a topic must be received, a durable subscriber should be used. JMS insures that messages published while a durable subscriber is inactive are retained by JMS and delivered when the subscriber subsequently becomes active.

Non-durable subscribers should only be used when missed messages are tolerable.

Table 6.2 Pub/sub reliability

| How Published | Non-Durable Subscriber | Durable Subscriber |
|----------------|--|--------------------|
| NON_PERSISTENT | at-most-once (missed if inactive) | at-most-once |
| PERSISTENT | once-and-only-once (missed if inactive) | once-and-only-once |

7. JMS exceptions

7.1. Overview

This chapter provides an overview of JMS exception handling and defines the standard JMS exceptions.

7.2. The `JMSEException`

JMS defines `JMSEException` as the root class for exceptions thrown by JMS methods. `JMSEException` is a checked exception and catching it provides a generic way of handling all JMS related exceptions. `JMSEException` provides the following information:

- A provider-specific string describing the error - This string is the standard Java exception message, and is available via `getMessage()`.
- A provider-specific string error code
- A reference to another exception - Often a JMS exception will be the result of a lower level problem. If appropriate, this lower level exception can be linked to the JMS exception.

JMS methods only include `JMSEException` in their signatures. JMS methods can throw any JMS standard exception as well as any JMS provider specific exception. **The javadoc for JMS methods documents only the mandatory exception cases.**

7.3. Standard exceptions

In addition to `JMSEException`, JMS defines several additional exceptions that standardize the reporting of basic error conditions.

There are only a few cases where JMS mandates that a specific JMS exception must be thrown. These cases are indicated by the words **must be** in the exception description. **These cases are the only ones on which client logic** should depend on a specific problem resulting in a specific JMS exception being thrown.

In the remainder of cases, it is strongly suggested that JMS providers use one of the standard exceptions where possible. JMS providers may also derive provider-specific exceptions from these if needed.

JMS defines the following standard exceptions:

- `IllegalStateException`: This exception is thrown when a method is invoked at an illegal or inappropriate time or if the provider is not in an appropriate state for the requested operation. For example, this exception **must be** thrown if `Session.commit()` is called on a non-transacted session. This exception is also **must be** called when domain inappropriate method is called, such as calling `TopicSession.CreateQueueBrowser()`.
- `JMSSecurityException`: This exception **must be** thrown when a provider rejects a user name/password submitted by a client. It may

also be thrown for any case where a security restriction prevents a method from completing.

- `InvalidClientIDException`: This exception **must be** thrown when a client attempts to set a connection's client identifier to a value that is rejected by a provider.
- `InvalidDestinationException`: This exception **must be** thrown when a destination is either not understood by a provider or is no longer valid.
- `InvalidSelectorException`: This exception **must be** thrown when a JMS client attempts to give a provider a message selector with invalid syntax.
- `MessageEOFException`: This exception **must be** thrown when an unexpected end of stream has been reached when a `StreamMessage` or `BytesMessage` is being read.
- `MessageFormatException`: This exception **must be** thrown when a JMS client attempts to use a data type not supported by a message or attempts to read data in a message as the wrong type. It must also be thrown when equivalent type errors are made with message property values. For example, this exception **must be** thrown if `StreamMessage.writeObject()` is given an unsupported class or if `StreamMessage.readShort()` is used to read a boolean value. This exception also **must be** thrown if a provider is given a type of message it cannot accept. Note that the special case of a failure caused by attempting to read improperly formatted `String` data as numeric values must throw the `java.lang.NumberFormatException`.
- `MessageNotReadableException`: This exception **must be** thrown when a JMS client attempts to read a write-only message.
- `MessageNotWriteableException`: This exception **must be** thrown when a JMS client attempts to write to a read-only message.
- `ResourceAllocationException`: This exception is thrown when a provider is unable to allocate the resources required by a method. For example, this exception should be thrown when a call to `createTopicConnection` fails due to lack of JMS provider resources.
- `TransactionInProgressException`: This exception is thrown when an operation is invalid because a transaction is in progress. For instance, attempting to call `Session.commit()` when a session is part of a distributed transaction should throw a `TransactionInProgressException`.
- `TransactionRolledBackException`: This exception **must be** thrown when a call to `Session.commit()` results in a rollback of the current transaction.

8. *JMS application server facilities*

8.1. *Overview*

This chapter describes JMS facilities for concurrent processing of a subscription's messages. It also defines how a JMS provider supplies JTS aware sessions. These facilities are primarily intended for the use of the JMS provider.

If JMS clients use the JTS aware facilities a client program may be non-portable code, because JMS providers are not required to support these interfaces.

The facilities described in this chapter are a special category of JMS. They are optional and might only be supported by some JMS providers.

8.2. *Concurrent processing of a subscription's messages*

JMS provides a special facility for creating a `MessageConsumer` that can concurrently consume messages.

This facility partitions the work into three roles:

- JMS provider - its role is to deliver the messages.
- Application Server - its role is to create the consumer and manage the threads used by the concurrent `MessageListener` objects.
- Application - its role is to define a subscription with a destination and optionally a message selector and provide a single threaded `MessageListener` class to consume its messages. An application server will construct multiple objects of this class to concurrently consume messages.

8.2.1. *Session*

Sessions provide the following methods for use by application servers:

- `setMessageListener()` and `getMessageListener()` - a session's `MessageListener` consumes messages that have been assigned to the session by a `ConnectionConsumer`, as described in the next few paragraphs.
- `run()` - causes the messages assigned to its session by a `ConnectionConsumer` to be serially processed by the session's `MessageListener`. When the listener returns from processing the last message, `run()` returns.

An application server would typically be given a `MessageListener` class that contained the single threaded code written by an application programmer to process messages. It would also be given the destination and message selector that specified the messages the listener was to consume.

An application server would take care of creating the JMS `Connection`, `ConnectionConsumer`, and `Session` objects it needs to handle message processing. It would create as many `MessageListener` instances as it needed and register each with its own session.

Since many listeners will need to use the services of its session, the listener is likely to require that its session be passed to it as a constructor parameter.

8.2.2. *ServerSession*

A `ServerSession` is an object implemented by an application server. It is used by an application server to associate a thread with a JMS session.

A `ServerSession` implements two methods:

- `getSession()` - returns the `ServerSession`'s JMS *Session*.
- `start()` - starts the execution of the `ServerSession` thread and results in the execution of the associated JMS *Session*'s run method.

8.2.3. *ServerSessionPool*

A `ServerSessionPool` is an object implemented by an application server to provide a pool of `ServerSession` objects for processing the messages of a `ConnectionConsumer`.

Its only method is `getServerSession()`. This removes a `ServerSession` from the pool and gives it to the caller (which is assumed to be a `ConnectionConsumer`) to use for consuming one or more messages.

JMS does not architect how the pool is implemented. It could be a static pool of `ServerSession` objects or it could use a sophisticated algorithm to dynamically create `ServerSession` objects as needed.

If the `ServerSessionPool` is out of `ServerSession` objects, the `getServerSession()` method may block. If a `ConnectionConsumer` is blocked, it cannot deliver new messages until a `ServerSession` is eventually returned.

8.2.4. *ConnectionConsumer*

For application servers, connections provide a special facility for creating a `ConnectionConsumer`. The messages it is to consume are specified by a destination and a message selector. In addition, a `ConnectionConsumer` must be given a `ServerSessionPool` to use for processing its messages. A `maxMessages` value is specified to limit the number of messages a `ConnectionConsumer` may load at one time into a `ServerSession`'s *Session*.

Normally, when traffic is light, a `ConnectionConsumer` gets a `ServerSession` from its pool; loads its *Session* with a single message; and, starts it. As traffic picks up, messages can back up. If this happens, a `ConnectionConsumer` can load each *Session* with more than one message. This reduces the thread context switches and minimizes resource use at the expense of some serialization of a message processing.

8.2.5. *How a ConnectionConsumer uses a ServerSession*

A `ConnectionConsumer` implemented by a JMS provider uses a `ServerSession` to process one or more messages that have arrived. It does this as follows:

1. It gets a `ServerSession` from the its `ServerSessionPool`

2. It gets the `ServerSession`'s `Session`
3. It loads the `Session` with one or more messages
4. It then starts the `ServerSession` to consume these messages

A `ConnectionConsumer` for a `QueueConnection` will expect to load its messages into a `QueueSession`, as one for a `TopicConnection` would expect to load a `TopicSession`.

Note that JMS does not architect how the `ConnectionConsumer` loads the `Session` with messages. Since both the `ConnectionConsumer` and `Session` are implemented by the same JMS provider, they can accomplish the load using a private mechanism.

8.2.6. *How an application server implements a ServerSession*

JMS does not architect the implementation of a `ServerSession`. A typical implementation is presented here to illustrate the concept:

1. An app server creates a `Thread` for a `ServerSession` registering the `ServerSession`'s `runObject`. The implementation of this `runObject` is private to the app server.
2. The `ServerSession`'s `start` method calls its `Thread`'s `start` method. As with all Java threads, a call to `start` initiates execution of the started thread and calls the thread's `runObject`. The caller to `ServerSession.start` (the `ConnectionConsumer`) and the `ServerSession runObject` are now running in different threads.
3. The `runObject` will do some housekeeping and then call its `Session`'s `run()` method. On return, the `runObject` puts its `ServerSession` back into its `ServerSessionPool` and returns. This terminates execution of the `ServerSession`'s thread and the cycle starts again.

8.2.7. *The result*


JMS has defined a flexible mechanism that partitions the job of concurrent message consumption into roles that are well suited for each participant.

The application programmer provides a simple to write, single threaded implementation of `MessageListener`.


The JMS provider retains control of its messages until they are delivered to the `MessageListener`. This ensures it is under direct control of message acknowledgment.

The application server is in control of setting up the `ConnectionConsumer` and managing all the threads used for executing its `MessageListeners`.

The following diagram illustrates the relationship between the three roles and the objects they implement.



The following diagram illustrates the process a ConnectionConsumer uses to deliver a message to a MessageListener.



8.3. *XAConnectionFactory*

Some application servers provide support for grouping resource use into a distributed transaction. To include JMS transactions in a distributed transaction, an application server requires a Java Transaction API (JTA) capable JMS provider. A JMS provider exposes its JTA support using a JMS *XAConnectionFactory* which an application server uses to create *XAConnection* objects.

XAConnectionFactory provides the same authentication options as *ConnectionFactory*.

XAConnectionFactory objects are JMS administered objects just like *ConnectionFactory* objects. It is expected that application servers will find them using JNDI.

8.4. *XAConnection*

XAConnection extends the capability of *Connection* by providing the ability to create *XASession* objects.

8.5. *XASession*

XASession provides access to what looks like a normal *Session* object and a `javax.transaction.xa.XAResource` object which controls the session's transaction context. The functionality of *XAResource* closely resembles that defined by the standard X/Open XA Resource interface.

An application server controls the transactional assignment of an *XASession* by obtaining its *XAResource*. It uses the *XAResource* to assign the session to a distributed transaction; prepare and commit work on the transaction, and so on.

An *XAResource* provides some fairly sophisticated facilities for interleaving work on multiple transactions, recovering a list of transactions in progress, and so on. A JTA aware JMS provider must fully implement this functionality. This could be done by using the services of a database that supports XA, or a JMS provider may choose to implement this functionality from scratch.

A client of the application server is given the *XASession*'s *Session*. Behind the scenes, the application server controls the transaction management of the underlying *XASession*.

It is important to note that a distributed transaction context does *not* flow with a message; that is, the receipt of the message cannot be part of the same transaction that produced the message. This is the fundamental difference between messaging and synchronized processing. Message producers and consumers use an alternative approach to reliability that is built upon a JMS provider's ability to supply a once-and-only-once message delivery guarantee.

To reiterate, the act of producing and/or consuming messages in a *Session* can be transactional. The act of producing and consuming a specific message across different sessions cannot.

8.6. JMS application server interfaces

Both PTP and Pub/Sub domains provide their own versions of JTS aware JMS facilities.

However, there are common interfaces available, which should be used in preference to the domain-specific interfaces. These are listed as JMS common interfaces in Table 8.1.

Table 8.1 Relationship of optional interfaces in domains

| JMS common Interfaces | PTP interfaces | Pub/sub interfaces |
|------------------------------|----------------------------|----------------------------|
| ServerSessionPool | <i>Not domain-specific</i> | <i>Not domain-specific</i> |
| ServerSession | <i>Not domain-specific</i> | <i>Not domain-specific</i> |
| ConnectionConsumer | <i>Not domain-specific</i> | <i>Not domain-specific</i> |
| XAConnectionFactory | XAQueueConnectionFactory | XATopicConnectionFactory |
| XAConnection | XAQueueConnection | XATopicConnection |
| XASession | XAQueueSession | XATopicSession |

9. *JMS example code*

This chapter gives some code examples that show how a JMS client could use the JMS API. It also demonstrates how to use several message types. The examples use methods that support a unified messaging model: these examples work with either Point-to-Point or Publish/Subscribe messaging. This is the recommended approach to working with the JMS API.

In earlier versions of the JMS Specification, only the separate interfaces for each messaging domain (Point-to-Point or Pub/Sub) were supported, and the client was programmed to use one messaging domain or the other. Now, the JMS client can be programmed using the JMS common interfaces.

In the example program, a client application sends and receives stock quote information. The messages the client application receives are from a stock quote service that sends out stock quote messages. The stock quote service is not described in the example.

To simplify the example, no exception-handling code is included.

This chapter describes the steps for creating the correct environment for sending and receiving a message.

After describing these basic functions, this chapter describes how to perform some other common functions, such as using message selectors.

9.1. *Preparing to send and receive messages*

Here are the basic steps to establish a connection and prepare to send and receive messages.

- Get a `ConnectionFactory` and `Destination`
- Create a `Connection` and `Session`
- Create a `MessageConsumer`
- Create a `MessageProducer`

9.1.1. *Getting a ConnectionFactory*

Both the message producer and message consumer (the sender and receiver) need to get a `ConnectionFactory` and use it to set up both a `Connection` and a `Session`.

An administrator typically has created and configured a `ConnectionFactory` for the JMS client's use. The client program typically uses the JNDI API to look up the `ConnectionFactory`.

```
import javax.naming.*;
import javax.jms.*;

ConnectionFactory connectionFactory;

Context messaging = new InitialContext();
connectionFactory = (ConnectionFactory)
    messaging.lookup("ConnectionFactory");
```

9.1.2. *Getting a Destination*

An administrator has created and configured a `Queue` named “StockSource” which is where stock quote messages are sent and received. Again, the destination can be looked up using the JNDI API.

```
Queue stockQueue;

stockQueue = (Queue)messaging.lookup("StockSource");
```

9.1.3. *Creating a Connection*

Having obtained the `ConnectionFactory`, the client program uses it to create a `Connection`.

```
Connection connection;

connection = connectionFactory.createConnection();
```

A `Connection` must be closed after use. This may be done explicitly using the `close` method:

```
connection.close();
```

Alternatively a connection may be closed automatically using the try-with-resources statement:

```
try (Connection connection =
    connectionFactory.createConnection());{
    // use connection in this try block
    // it will be closed when try block completes
} catch (JMSEException e){
    // exception handling
}
```

9.1.4. *Creating a Session*

Having obtained the `Connection`, the client program uses it to create a `Session`. The `Session` is used to create a `MessageProducer` (to send messages) or a `MessageConsumer` (to receive messages).

There are three `createSession` methods on `Connection`, with different numbers of arguments. Java SE applications such as this example should use the method with one integer argument, `sessionMode`. This single argument indicates

- whether the session will use a local transaction or whether it is non-transacted and,
- if the session is non-transacted, what mode would be used for acknowledging the receipt of messages.

```
Session session;

/* Session is not transacted,
 * uses AUTO_ACKNOWLEDGE for message acknowledgement
 */
session = connection.createSession(
    Session.AUTO_ACKNOWLEDGE);
```

9.1.5. *Creating a MessageProducer*

Having obtained the `Session`, the client program uses the `Session` to create a `MessageProducer`. The `MessageProducer` object is used to send messages to the destination. The `MessageProducer` is created by using the `Session.createProducer` method, supplying as a parameter the destination to which the messages are sent.

```
MessageProducer sender;

/* Value in stockQueue previously looked up in the JNDI
 * createProducer takes a Destination
 */

sender = session.createProducer(stockQueue);
```

9.1.6. *Creating a MessageConsumer*

Messages can be consumed either synchronously or asynchronously. This example shows how to create a message consumer that consumes messages synchronously. See section 9.3.1 "Receiving messages asynchronously" to learn more about consuming messages asynchronously.

A `MessageConsumer` is used to receive messages from the destination, which in this example is the `Queue stockQueue`. A `MessageConsumer` is created using the `Session.createConsumer` method, supplying one parameter, the destination from which messages are received.

```
MessageConsumer receiver;

/* Value in stockQueue previously looked up in the JNDI
 * createConsumer takes a Destination
 */

receiver = session.createConsumer(stockQueue);
```

9.1.7. *Starting message delivery*

Up until this point, delivery of messages has been inhibited so that the preceding setup could be done without being interrupted with asynchronously delivered messages. Now that the setup is complete, the `Connection` is told to begin the delivery of messages to its `MessageConsumer`.

```
connection.start();
```

9.1.8. *Using a TextMessage*

There are several JMS Message formats. For this example, the stock quote information is sent as a text string that is read and displayed by the client.

The following demonstrates how to create such a message:

```
String stockData; /* Stock information as a string */
TextMessage message;

/* Set the message's text to be the stockData string */
message = session.createTextMessage();
message.setText(stockData);
```

9.2. *Sending and receiving messages*

Now that the setup of the `Session` is complete, you can send and receive messages. This section describes how to:

- Create a message
- Send a message
- Receive a message synchronously

9.2.1. *Sending a message*

To send a message, use the `MessageProducer.send` method, supplying a `Message` object for the method's parameter.

```
/* Send the message */
sender.send(message);
```

9.2.2. *Receiving a message synchronously*

To receive the next message in the queue, you can use the `MessageConsumer.receive` method. This call blocks indefinitely until a message arrives on the queue. The same method can be used to receive from a topic.

```
TextMessage stockMessage;
stockMessage = (TextMessage)receiver.receive();
```

To limit the amount of time that the client blocks, use a timeout parameter with the `receive` method. If no messages arrive by the end of the timeout, then the `receive` method returns. The timeout parameter is expressed in milliseconds.

```
TextMessage stockMessage;

/* Wait 4 seconds for a message */
TextMessage = (TextMessage)receiver.receive(4000);
```

9.2.3. *Unpacking a TextMessage*

The stock quote information is sent using a `TextMessage`. To get the information from the message, use the `TextMessage.getText` method. It returns the message content as a string.

```
/* Stock information as a string */
String newStockData;

newStockData = message.getText();
```

9.3. *Other messaging features*

This section goes beyond basic messaging functions, and describes how to perform some other common messaging functions:

- Create an asynchronous `MessageListener`
- Use a message selector to filter message delivery
- Create a durable subscription to a topic
- Re-connect to a topic using a durable subscription

9.3.1. *Receiving messages asynchronously*

In order to receive message asynchronously as they are delivered to the message consumer, the client program needs to create a message listener that implements the `MessageListener` interface. An implementation of the `MessageListener` interface, called `StockListener.java`, might look like this:

```
import javax.jms.*;

public class StockListener implements MessageListener
{
    public void onMessage(Message message) {
        /* Unpack and handle the messages received */
        ...
    }
}
```

The client program registers the `MessageListener` object with the `MessageConsumer` object in the following way:

```
StockListener myListener = new StockListener();

/* Receiver is MessageConsumer object */
receiver.setMessageListener(myListener);
```

The `Connection` must be started for the message delivery to begin. The `MessageListener` is asynchronously notified whenever a message has been published to the queue. This is done via the `onMessage` method in the `MessageListener` interface. It is up to the client to process the message there.

```
public void onMessage(Message message)
{
    String newStockData;

    /* Unpack and handle the messages received */
    newStockData = message.getText();
    if(...)
    {
        /* Logic related to the data */
    }
}
```

9.3.2. *Using message selection*

A client program may be interested in receiving only certain stock quotes. A message selector can be used to achieve this goal. Message selectors work against properties that are assigned to the message.

In this example, the client program is only interested in technology related stocks. The sender of the messages assigns a value to a message property called `StockSector`. The values the sender assigns include "Technology", "Financial", "Manufacturing", "Emerging", and "Global". The message sender assigns these property values by using the `Message.setStringProperty` method.

```
String stockData; /* Stock information as a String */
TextMessage message;
```

```

/* Set the message's text to be the stockData string */

message = session.createTextMessage();
message.setText(stockData);

/* Set the message property 'StockSector' */
message.setStringProperty("StockSector", "Technology");

```

When the client program that receives the stock quote messages creates `MessageConsumer` is created, the client program can create a message selector string to determine which messages it will receive.

```

String selector;

selector = new String("(StockSector = 'Technology')");

```

This string is specified when the `MessageConsumer` is created:

```

MessageConsumer receiver;
receiver = session.createConsumer(stockQueue, selector);

```

The client program receives only messages related to the technology sector.

9.3.3. *Using durable subscriptions*

Durable subscriptions are used to receive messages from a topic. When a JMS client creates a durable subscription, the client can later disconnect from the topic. When the client program re-connects, it can receive the messages that arrived while it was disconnected. In this example, the topic provides information about news updates.

9.3.3.1. *Creating a durable subscription*

The following example sets up durable subscription that gets messages from a topic. First, the client program must perform the usual setup steps of looking up `ConnectionFactory` and a `Destination`, and creating a `Connection` and `Session`, as described in section 9.1 "Preparing to send and receive messages".

```

import javax.naming.*;
import javax.jms.*;

/* Look up connection factory */
ConnectionFactory connectionFactory;
Context messaging = new InitialContext();
connectionFactory =
    (ConnectionFactory)
        Messaging.lookup("ConnectionFactory")

/* Look up destination */
Topic newsFeedTopic;
newsFeedTopic = messaging.lookup("BreakingNews");

/* Create connection and session */
Connection connection;
Session session;
connection = ConnectionFactory.createConnection();
session = connection.createSession(

```

```
Session.AUTO_ACKNOWLEDGE);
```

Having performed the normal setup, the client program can now create a durable subscriber to the destination. To do this, the client program creates a durable `TopicSubscriber`, using `session.CreateDurableSubscriber`. The name "mySubscription" is used as an identifier of the durable subscription.

```
session.createDurableSubscriber(newsFeedTopic,
    "mySubscription");
```

At this point, the client program can start the connection and start to receive messages.

9.3.3.2. *Creating a consumer on an existing durable subscription*

Once a durable subscription has been created it will continue to accumulate messages until the subscription is deleted using the `Session` method `unsubscribe`, even if the original consumer is closed leaving no consumer on the durable subscription.

A client application may create a consumer on an existing durable subscription by calling one of the `Session` methods `createDurableConsumer` or `createDurableSubscriber`, supplying the same parameters that were specified when the durable subscription was first created.

```
/* Create a consumer on an existing durable subscription */
session.createDurableConsumer(newsFeedTopic, "mySubscription");
```

If there were no consumers on the durable subscription prior to calling this method then any messages which were added to the subscription whilst it had no consumers will be delivered.

A durable subscription may have more than one active consumer (this was not permitted prior to JMS 2.0). Each message from the subscription will be delivered to only one of the consumers on that subscription.

When creating a consumer on an existing durable subscription there are some important restrictions to be aware of:

- The `Destination` and subscription name must be the same as when the durable subscription was first created.
- If the connection's client identifier was set when the durable subscription was first created then the same client identifier must be set when subsequently creating a consumer on it.
- If a message selector was specified when the durable subscription was first created then the same message selector must be specified when subsequently creating a consumer on it.

9.4. *JMS message types*

There are five JMS message types. This section provides an example of how to create and unpack each of these types. In each example, the data sent in the message is stock-quote-related data. In all cases, the code that creates the actual content of the messages is omitted.

9.4.1. *Creating a TextMessage*

In this example, the stock quote information is sent as a `TextMessage`. A `TextMessage` carries the message as a text string that can be read by the client.

The following code demonstrates how to create such a message:

```
String stockData; /* Stock information as a string */
TextMessage message;

message = session.createTextMessage();

/* Set the stockData string to the message body */
message.setText(stockData);
```

9.4.2. *Unpacking a TextMessage*

To unpack a `TextMessage`, the client uses the `Message.getText` method.

```
String stockInfo; /* String to hold stock info */

stockInfo = message.getText();
```

9.4.3. *Creating a BytesMessage*

The stock quote information could be in a binary format that the server knows how to construct and that the client program knows how to interpret and display as a stock quote. This is sent as a `BytesMessage`.

Such a message can be constructed in the following way:

```
/* Stock information as a byte array */
byte[] stockData; BytesMessage message;

message = session.createBytesMessage();
message.writeBytes(stockData);
```

9.4.4. *Unpacking a BytesMessage*

When the `BytesMessage` is received, it can be unpacked in the following manner:

```
/* Byte array to hold stock information */
byte[] stockData;

int length;
length = message.readBytes(stockData);
```

The message body is copied to the byte array. The client program can then begin reading and interpreting the data.

9.4.5. *Creating a MapMessage*

Each stock message sent by the server could be a map of various stock quote name/value pairs, using a `MapMessage`. For example, it could contain entries for:

- Stock quote name - represented as a `String`
- Current value - represented as a `double`

- Time of quote - represented as a long
- Last change - represented as a double
- Stock information - represented as a String

To construct the `MapMessage`, the client program uses the various set methods (`setString`, `setLong`, and so forth) that are associated with `MapMessage`, and sets each named value in the `MapMessage`.

```
String stockName; /* Name of the stock */
double stockValue; /* Current value of the stock */
long stockTime; /* Time stock quote was updated */
double stockDiff; /* +/- change in the stock quote*/
String stockInfo; /* Information on this stock */
MapMessage message;
```

```
message = session.createMapMessage();
```

Note that the following can be set in any order.

```
/* First parameter is the name of the map element,
 * second is the value
 */
message.setString("Name", "SUNW");
message.setDouble("Value", stockValue);
message.setLong("Time", stockTime);
message.setDouble("Diff", stockDiff);
message.setString("Info",
    "Recent server announcement causes market interest");
```

9.4.6. *Unpacking a MapMessage*

To unpack the `MapMessage`, the client program uses the various get methods associated with `MapMessage` to get the values in the named `MapMessage` elements. In the following example, the client program expects certain `MapMessage` elements.

```
String stockName; /* Name of the stock */
double stockValue; /* Current value of the stock */
long stockTime; /* Time stock quote was updated */
double stockDiff; /* +/- change in the stock */
String stockInfo; /* Information on this stock */
```

The data is retrieved from the message by using a get method and providing the name of the value desired. The elements from the `MapMessage` can be obtained in any order.

```
stockName = message.getString("Name");
stockDiff = message.getDouble("Diff");
stockValue = message.getDouble("Value");
stockTime = message.getLong("Time");
```

If a client program needs to get a list of the elements in a `MapMessage`, it can use the method `MapMessage.getMapNames`.

9.4.7. *Creating a StreamMessage*

In a similar fashion to the `MapMessage`, an application could send a message consisting of various fields written in sequence to the message, each in their own primitive type. To do this, it would use a

`StreamMessage`. Here's the primitive types assigned to each item in the stock quote message.

- Stock quote name - `String`
- Current value - `double`
- Time of quote - `long`
- Last change - `double`
- Stock information - `String`

The client program might be interested in only some of the message fields, but in the case of a `StreamMessage`, the client has to read and potentially discard each field in turn.

In the following example, the values for each of the following has already been set:

```
String stockName; /* Name of the stock */
double stockValue; /* Current value of the stock */
long stockTime; /* Time stock quote was updated */
double stockDiff; /* +/- change in the stock quote */
String stockInfo; /* Information on this stock*/
StreamMessage message;

/* Create message */
message = session.createStreamMessage();
```

The following elements have to be written to the `StreamMessage` in the order they will be read. Notice that they are not separately named properties, as in `MapMessage`.

```
/* Set data for message */
message.writeString(stockName);
message.writeDouble(stockValue);
message.writeLong(stockTime);
message.writeDouble(stockDiff);
message.writeString(stockInfo);
```

9.4.8. *Unpacking a StreamMessage*

The elements of a `StreamMessage` have to be read in the order they were written.

```
String stockName; /* Name of the stock quote */
double stockValue; /* Current value of the stock */
long stockTime; /* Time stock quote was updated */
double stockDiff; /* +/- change in the stock quote */
String stockInfo; /* Information on this stock */

stockName = message.readString();
stockValue = message.readDouble();
stockTime = message.readLong();
stockDiff = message.readDouble();
stockInfo = message.readString();
```

9.4.9. *Creating an ObjectMessage*

The stock information could be sent in the form of a special `StockObject` Java object. This object can then be sent as the body of a `ObjectMessage`. The `ObjectMessage` can be used to send Java objects.

These values are set using methods that are unique to the `StockObject` implementation. For example, `StockObject` may have methods that set the various data values. An application using `StockObject` might look like this:

```
String stockName; /* Name of the stock quote */
double stockValue; /* Current value of the stock */
long stockTime; /* Time stock quote was updated */
double stockDiff; /* +/- change in the stock quote */
String stockInfo; /* Information on this stock */

/* Create a StockObject */
StockObject stockObject = new StockObject();

/* Establish the values for the StockObject */
stockObject.setName(stockName);
stockObject.setValue(stockValue);
stockObject.setTime(stockTime);
stockObject.setDiff(stockDiff);
stockObject.setInfo(stockInfo);
```

To create an `ObjectMessage`, to pass the `StockObject` in the message, you would do the following:

```
/* Create an ObjectMessage */
ObjectMessage message;
message = session.createObjectMessage();

/* Set the body of the message to the StockObject */
message.setObject(stockObject);
```

9.4.10. *Unpacking an ObjectMessage*

To unpack an `ObjectMessage`, use the `ObjectMessage.getObject` method to get the object. Once the object is retrieved, the client program can use methods appropriate to that object type to retrieve data from the object.

```
StockObject stockObject;

/* Retrieve the StockObject from the message */
stockObject = (StockObject)message.getObject();

/* Extract data from the StockObject by using
   StockObject methods */
String stockName; /* Name of the stock quote */
double stockValue; /* Current value of the stock */
long stockTime; /* Time stock quote was updated */
double stockDiff; /* +/- change in the stock quote */
String stockInfo; /* Information on this stock */
stockName = stockObject.getName();
stockValue = stockObject.getValue();
stockTime = stockObject.getTime();
stockDiff = stockObject.getDiff();
```

```
stockInfo = stockObject.getInfo();
```

10. Use of JMS API in Java EE applications

10.1. Overview

The Java™ Platform, Enterprise Edition (Java EE) Specification, v7 requires support for the JMS API as part of the full Java EE platform.

The Java EE platform provides a number of additional features which are not available in the Java Platform Standard Edition (Java SE). These include the following:

- Support for distributed transactions which are demarcated either programmatically, using methods on `javax.transaction.UserTransaction`, or automatically by the container. These are referred to in this specification as JTA transactions to distinguish them from JMS local transactions.
- Support for JMS message-driven beans.

These features are defined in detail in other specifications including the Java EE 7 specification and the Enterprise JavaBeans 3.2 specification. However the use of the Java EE platform imposes restrictions on the way that the JMS API may be used by applications, and those restrictions are described here.

The JMS specification does not define how a Java EE container integrates with its JMS provider. Different Java EE containers may integrate with their JMS provider in different ways.

10.2. Restrictions on the use of JMS API in the Java EE web or EJB container

JMS applications which run in the Java EE web or EJB container are subject to a number of restrictions in the way the JMS API may be used. These restrictions are necessary for the following reasons:

- In a Java EE web or EJB container, a JMS provider operates as a transactional resource manager which must participate in JTA transactions as defined in the Java EE platform specification. This overrides the behaviour of JMS sessions as defined elsewhere in the JMS specification. For more details see section 10.3 "Behaviour of JMS sessions in the Java EE web or EJB container".
- The Java EE web or EJB containers need to be able to manage the threads used to run applications.
- The Java EE web and EJB containers perform connection management which may include the pooling of JMS connections.

The restrictions described in this section do not apply to the Java EE application client container.

Applications running in the Java EE web and EJB containers must not attempt to create more than one active (not closed) `Session` object per connection.

- If an application attempts to use the `Connection` object's `createSession` method when an active `Session` object exists for that connection then a `JMSEException` should be thrown.
- If an application attempts to use the `JMSContext` object's `createContext` method then a `JMSRuntimeException` should be thrown, since the first `JMSContext` already contains a connection and session and this method would create a second session on the same connection.

The following methods are intended for use by the application server and their use by applications running in the Java EE web or EJB container may interfere with the container's ability to properly manage the threads used in the runtime environment. They must therefore not be called by applications running in the Java EE web or EJB container:

- `javax.jms.Session` method `setMessageListener`
- `javax.jms.Session` method `getMessageListener`
- `javax.jms.Session` method `run`
- `javax.jms.Connection` method `createConnectionConsumer`
- `javax.jms.Connection` method `createDurableConnectionConsumer`

The following methods may interfere with the container's ability to properly manage the threads used in the runtime environment and must not be used by applications running in the Java EE web or EJB container:

- `javax.jms.MessageConsumer` method `setMessageListener`
- `javax.jms.MessageConsumer` method `getMessageListener`
- `javax.jms.JMSContext` method `setMessageListener`
- `javax.jms.JMSContext` method `getMessageListener`

This restriction means that applications running in the Java EE web or EJB container which need to receive messages asynchronously may only do so using message-driven beans.

The following methods may interfere with the container's management of connections and must not be used by applications running in the Java EE web or EJB container:

- `javax.jms.Connection` method `setClientID`
- `javax.jms.Connection` method `stop`
- `javax.jms.Connection` method `setExceptionListener`
- `javax.jms.JMSContext` method `setClientID`
- `javax.jms.JMSContext` method `stop`
- `javax.jms.JMSContext` method `setExceptionListener`

Applications which need to use a specific client identifier must set it on the connection factory, as described in section 4.3.2 "Client identifier"

All the methods listed in this section may throw a `javax.jms.JMSEException` (if allowed by the method) or a

`javax.jms.JMSRuntimeException` (if not) when called by an application running in the Java EE web or EJB container. This is recommended but not required.

10.3. Behaviour of JMS sessions in the Java EE web or EJB container

The behaviour of a JMS session in respect of transactions and message acknowledgement is different for applications which run in a Java EE web or EJB container than it is for applications which run in a normal Java SE environment or in the Java EE application client container.

These differences also apply to `JMSContext` objects, since these incorporate a JMS session.

When an application creates a `Session` or `JMSContext` in a Java EE web or EJB container, and there is an active JTA transaction in progress, then the session that is created will participate in the JTA transaction and will be committed or rolled back when the JTA transaction is committed or rolled back. Any session parameters that are specified when creating the `Session` or `JMSContext` are ignored. The use of local transactions or client acknowledgement is not permitted.

This applies irrespective of whether the JTA transaction is demarcated automatically by the container or programmatically using methods on `javax.transaction.UserTransaction`.

The term "session parameters" here refers to the arguments that may be passed into a call to the `createSession` or `createContext` methods to specify whether the session should use a local transaction and, if the session is non-transacted, what the acknowledgement mode should be.

When an application creates a `Session` or `JMSContext` in a Java EE web or EJB container, and there is no active JTA transaction in progress, then the session that is created will be non-transacted and will be automatically-acknowledged. The use of local transactions or client acknowledgement is still not permitted. Parameters may be specified when creating the `Session` or `JMSContext` to specify whether the acknowledgement mode should be `AUTO_ACKNOWLEDGE` or `DUPS_OK_ACKNOWLEDGE`. If any other session parameter values are specified they will be ignored and an acknowledgement mode of `AUTO_ACKNOWLEDGE` used.

The use of local transactions or client acknowledgement is not permitted in a Java EE web or EJB container even if there is no active JTA transaction because this would require applications to be written differently depending on whether there was a JTA transaction or not.

The JMS API provides the following methods to create a session which allow the session to be defined using either the two parameters `transacted` and `acknowledgeMode` or by the single parameter `sessionMode`. If these methods are called in a Java EE web or EJB container then these parameters will be overridden as described above.

- `javax.jms.Connection` method `createSession(boolean transacted, int acknowledgeMode)`
- `javax.jms.QueueConnection` method `createQueueSession(boolean transacted, int acknowledgeMode)`

- `javax.jms.TopicConnection` method
`createTopicSession(boolean transacted, int acknowledgeMode)`
- `javax.jms.Connection` method `createSession(int sessionMode)`

It is recommended that applications that run in the Java EE web or EJB container create a session using the following method which does not specify a parameter:

- `javax.jms.Connection` method `createSession()`

The JMS API provides the following methods to create a `JMSContext` which allow the session to be defined using the single parameter `sessionMode`. If these methods are called in a Java EE web or EJB container then this parameter will be overridden as described above.

- `javax.jms.ConnectionFactory` method `createContext(int sessionMode)`
- `javax.jms.ConnectionFactory` method
`createContext(String userName, String password, int sessionMode)`

The following method to create a `JMSContext` from an existing `JMSContext` is not permitted in a Java EE web or EJB container because it would create a second session on an existing connection, which is not permitted in a Java EE web or EJB container.]

- `javax.jms.JMSContext` method `createContext(int sessionMode)`

It is recommended that applications that run in the Java EE web or EJB container create a `JMSContext` using one of the following methods which do not specify a `sessionMode`:

- `javax.jms.ConnectionFactory` method `createContext()`
- `javax.jms.ConnectionFactory` method
`createContext(String username, String password)`

When programmatic transaction demarcation is being used, the session should be both created and used within an active JTA transaction.

If a `Session` or `JMSContext` is created when there is an active JTA transaction, then after that transaction is committed or rolled back the session remains available for use in any subsequent JTA transaction until the `Session` or `JMSContext` is closed.

However, if a `Session` or `JMSContext` is created when there is an active JTA transaction but is subsequently used to send or receive messages when there is no active JTA transaction then the behaviour is undefined.

Similarly, if a `Session` or `JMSContext` is created when there is no active JTA transaction but subsequently used to send or receive messages when there is an active JTA transaction then the behaviour is undefined.

The Bean Provider should not make use of the JMS request/reply paradigm (sending of a JMS message, followed by the synchronous receipt of a reply to that message) within a single transaction. Because a JMS message is typically not delivered to its final destination until the

transaction commits, the receipt of the reply within the same transaction will not take place.

11. Simplified JMS API

The simplified JMS API offers an alternative to the standard JMS API. It is designed to allow applications which use JMS to be simpler and less verbose than is possible when using the standard API. It was added to the JMS specification in version 2.0.

This section uses the term "standard API" to refer to the following JMS interfaces which have existing since JMS 1.1:

- `javax.jms.Connection` and its subtypes
`javax.jms.QueueConnection` and
`javax.jms.TopicConnection`.
- `javax.jms.Session` and its subtypes `javax.jms.QueueSession`
and `javax.jms.TopicSession`.
- `javax.jms.MessageProducer` and its subtypes
`javax.jms.QueueSender` and `javax.jms.TopicPublisher`.
- `javax.jms.MessageConsumer` and its subtypes
`javax.jms.QueueReceiver` and `javax.jms.TopicSubscriber`.

The term "simplified API" refers to the following JMS interfaces and classes which were added in JMS 2.0:

- `javax.jms.JMSContext`
- `javax.jms.JMSConsumer`
- `javax.jms.JMSProducer`
- `javax.jms.JMSRuntimeException` and its subtypes
`javax.jms.IllegalStateRuntimeException`,
`javax.jms.InvalidClientIDRuntimeException`,
`javax.jms.InvalidDestinationRuntimeException`,
`javax.jms.InvalidSelectorRuntimeException`,
`javax.jms.JMSSecurityRuntimeException`,
`javax.jms.MessageFormatRuntimeException` and
`javax.jms.TransactionRolledBackRuntimeException`.

All the other interfaces and classes in the JMS API can be considered as part of both APIs. This includes:

- `javax.jms.ConnectionFactory` and its subtypes
`javax.jms.QueueConnectionFactory` and
`javax.jms.TopicConnectionFactory`
- `javax.jms.Message` and its subtypes
`javax.jms.ObjectMessage`, `javax.jms.TextMessage`,
`javax.jms.MapMessage`, `javax.jms.StreamMessage`,
`javax.jms.BytesMessage`
- `javax.jms.JMSException` and its subtypes
`javax.jms.IllegalStateException`,
`javax.jms.InvalidClientIDException`,
`javax.jms.InvalidDestinationException`,
`javax.jms.InvalidSelectorException`,
`javax.jms.JMSSecurityException`,

`javax.jms.MessageFormatException` and
`javax.jms.TransactionRolledBackException`.

11.1. Goals of the simplified API

The simplified API has the following goals:

- To reduce the number of objects needed to send and receive messages, and in particular to combine the `JMS Connection`, `Session` and `MessageProducer` objects into a single object.
- To maintain a consistent style with the existing API where possible so that users of the old API feel it to be an evolution which that can learn quickly. In particular the simplified API will continue to use the concepts of connection and session even though it doesn't require the use of `Connection` or `Session` objects.
- To be capable of use in both Java EE and Java SE applications.
- To allow resource injection to be exploited in those environment which support it.
- To provide the option to send and receive message payloads directly without the need to use `javax.jms.Message` objects.
- To remove where possible the need to catch `JMSEException` on method calls
- To be functionally as complete as the standard API, so that users of the simplified API will not have the need to switch back to the standard API in order to perform an operation this is unavailable in the simplified API.
- To be an alternative to, but not a replacement for, the standard API. The standard API remains and is not deprecated. Developers who are familiar with the standard API, or who prefer it, may continue to use the standard API.

11.2. Key features of the simplified API

11.2.1. JMSContext

The main object in the simplified API is `javax.jms.JMSContext`. This combines in a single object the functionality of several separate objects from the standard API. In particular it combines the functionality of a `Connection` and a `Session` in a single object.

Although the `JMSContext` does not expose constituent `Connection` and `Session` objects to applications, the concepts of connection and session remain important. A `Connection` represents a physical link to the JMS server, a `Session` represents a single-threaded context for sending and receiving messages, and a `JMSContext` represents both.

Applications that send messages will use the `JMSContext` method `createProducer` to create a `javax.jms.JMSProducer` object. This provides API to send messages. Although it provides similar functionality to an anonymous `MessageProducer` (one with no destination specified) it provides a more convenient API for configuring delivery options, message properties and message headers. See section 11.2.3 "Sending messages" for more information.

Applications that consume messages will use one of several methods on `JMSContext` to create a `javax.jms.JMSConsumer` object. This provides similar API to a `MessageConsumer` for consuming messages from a particular queue or topic. Messages may be consumed either synchronously or asynchronously, except in a Java EE web or EJB container where messages may be consumed only synchronously. See section 11.2.5 "Consuming messages" for more information.

A `JMSContext` object may be created by calling one of four methods on a `ConnectionFactory`:

| ConnectionFactory methods to create a JMSContext | |
|---|--|
| <code>createContext()</code> | Creates a <code>JMSContext</code> with the default user identity and an unspecified <code>sessionMode</code> . |
| <code>createContext(int sessionMode)</code> | Creates a <code>JMSContext</code> with the default user identity and the specified session mode. |
| <code>createContext(String userName, String password)</code> | Creates a <code>JMSContext</code> with the specified user identity and an unspecified <code>sessionMode</code> . |
| <code>createContext(String userName, String password, int sessionMode)</code> | Creates a <code>JMSContext</code> with the specified user identity and the specified session mode. |

`sessionMode` here has the same meaning and values as for the `createSession(int sessionMode)` method on a `Connection`.

Applications running in the Java EE web and EJB containers are not permitted to create more than one active session on a connection (see Section 10.2 "Restrictions on the use of JMS API in the Java EE web or EJB container"). Since a `JMSContext` contains a single connection and a single session it is ideally suited for use by such applications.

Applications running in a Java SE environment or in the Java EE application client container are permitted to create multiple active sessions on the same connection. This allows the same physical connection to be used in multiple threads simultaneously. Such applications which require multiple sessions to be created on the same connection should use the factory methods on the `ConnectionFactory` interface to create the first `JMSContext` and then use the `createContext` method on `JMSContext` to create additional `JMSContext` objects that use the same connection:

| JMSContext methods to create a new JMSContext | |
|---|---|
| <code>createContext(int sessionMode)</code> | Creates a new <code>JMSContext</code> with the specified session mode using the same connection as this <code>JMSContext</code> and creating a new session. |

To simplify application code, methods on `JMSContext` throw unchecked exceptions rather than checked exceptions. See section 11.2.9 "Exceptions" for more information.

11.2.2. Static constants for session mode

New static integer constants have been defined for use with the simplified API.

```
JMSContext.AUTO_ACKNOWLEDGE,  
JMSContext.CLIENT_ACKNOWLEDGE,  
JMSContext.DUPS_OK_ACKNOWLEDGE and  
JMSContext.SESSION_TRANSACTED
```

These have the same values, and the same meaning, as the equivalent constants on `Session`. This avoids the need for applications that use the new API to use the `Session` interface.

11.2.3. Creating messages

An application using the standard API creates messages objects using methods on the `Session`.

An application using the simplified API may create messages using methods on the `JMSContext`. These methods are identical in behaviour to the corresponding methods on `Session`.

| JMSContext methods to create a message | |
|--|---|
| <code>createMessage()</code> | Creates a <code>Message</code> object. |
| <code>createBytesMessage()</code> | Creates a <code>BytesMessage</code> object. |
| <code>createMapMessage()</code> | Creates a <code>MapMessage</code> object. |
| <code>createObjectMessage()</code> | Creates an <code>ObjectMessage</code> object. |
| <code>createObjectMessage(Serializable object)</code> | Creates an initialized <code>ObjectMessage</code> object. |
| <code>createStreamMessage()</code> | Creates a <code>StreamMessage</code> object. |
| <code>createTextMessage()</code> | Creates a <code>TextMessage</code> object. |
| <code>createTextMessage(String text)</code> | Creates an initialized <code>TextMessage</code> object. |

11.2.4. Sending messages

An application using the standard API sends messages using methods on `MessageProducer`.

An application using the simplified API does not create a `MessageProducer`. Instead it uses the `JMSContext` method `createProducer` to create a `JMSProducer` object. This provides a method `send(Destination destination, Message message)` which will send the specified message to the specified destination.

| |
|--|
| JMSContext method to send a Message object |
|--|

| | |
|--|--|
| <pre>send(Destination destination, Message message)</pre> | Sends a message to the specified destination, using any send options, message properties and message headers that have been defined on this <code>JMSProducer</code> . |
|--|--|

A `JMSProducer` is similar to an anonymous `MessageProducer` in that it does not have a destination associated with it. The `Destination` object must therefore be supplied as the first argument of each send method.

Destination objects can be obtained either by JNDI lookup or by calling the `JMSContext` methods `createQueue(String queueName)` or `createTopic(String topicName)`.

A `JMSProducer` object provides four further send methods which allow the application to supply the message payload directly as a `String`, `Serializable`, `Map` or `byte[]`. The `JMSProducer` will automatically construct a `Message` object of the appropriate type to hold the specified payload:

| JMSContext methods to send a Message payload | |
|--|--|
| <pre>send(Destination destination, String payload)</pre> | Send a <code>TextMessage</code> with the specified payload to the specified destination, using any send options, message properties and message headers that have been defined on this <code>JMSProducer</code> . |
| <pre>send(Destination destination, Map<String, Object> payload)</pre> | Send a <code>MapMessage</code> with the specified payload to the specified destination, using any send options, message properties and message headers that have been defined on this <code>JMSProducer</code> . |
| <pre>send(Destination destination, byte[] payload)</pre> | Send a <code>BytesMessage</code> with the specified payload to the specified destination, using any send options, message properties and message headers that have been defined on this <code>JMSProducer</code> . |
| <pre>send(Destination destination, Serializable payload)</pre> | Send an <code>ObjectMessage</code> with the specified payload to the specified destination, using any send options, message properties and message headers that have been defined on this <code>JMSProducer</code> . |

A `JMSProducer` also provides methods to allow message send options, message properties and message headers to be specified prior to sending a message or set of messages.

Message send options may be specified using one or more of the following methods: `setDeliveryMode`, `setPriority`, `setTimeToLive`, `setDeliveryDelay`, `setDisableMessageTimestamp`, `setDisableMessageID` and `setAsync`.

By default messages are sent synchronously. The method `setAsync(CompletionListener cl)` may be used to specify that messages should be sent asynchronously.

Message properties may be specified using one or more of nine `setProperty` methods. Any message properties set using these methods will override any message properties that have been set directly on the message.

Message headers may be specified using one or more of the following methods: `setJMSCorrelationID`, `setJMSCorrelationIDAsBytes`, `setJMSType` or `setJMSReplyTo`. Any message headers set using these methods will override any message headers that have been set directly on the message.

All the above methods return the `JMSProducer` to allow method calls to be chained together, allowing a fluid programming style. For example:

```
context.createProducer().
    setProperty("foo", "bar").
    setTimeToLive(10000).
    setDeliveryMode(NON_PERSISTENT).
    setDisableMessageTimestamp(true).
    send(inboundQueue, payload);
```

Instances of `JMSProducer` are intended to be lightweight objects which can be created freely and which do not consume significant resources. `JMSProducer` therefore does not provide a close method.

To simplify application code, methods on `JMSProducer` throw unchecked exceptions rather than checked exceptions. See section 11.2.9 "Exceptions" for more information.

11.2.5. Consuming messages

An application using the standard API to consume messages needs to create a `MessageConsumer` on the specified destination. It then either calls `setMessageListener` to consume messages asynchronously or calls one of three receive methods to receive messages synchronously.

An application using the simplified API does not create a `MessageConsumer`. Instead it uses several methods on `JMSContext` to create a `JMSConsumer` on the specified destination. The application then either calls `setMessageListener` to consume messages asynchronously or calls any of six receive methods to consume messages synchronously.

The following methods on `JMSContext` are used to create a `JMSConsumer`:

| JMSContext methods to create a JMSConsumer | |
|--|---|
| <code>createConsumer(Destination destination)</code> | Creates a <code>JMSConsumer</code> for the specified destination. |
| <code>createConsumer(Destination destination, String messageSelector)</code> | Creates a <code>JMSConsumer</code> for the specified destination, using a message selector. |
| <code>createConsumer(Destination destination,</code> | Creates a <code>JMSConsumer</code> for the specified destination, using a |

| | |
|---|--|
| <code>String messageSelector, boolean noLocal)</code> | message selector and the <code>noLocal</code> parameter. |
| <code>createDurableConsumer(Topic topic, String name)</code> | Creates a durable subscription with the specified name on the specified topic, and creates a <code>JMSConsumer</code> on that durable subscription. |
| <code>createDurableConsumer(Topic topic, String name, String messageSelector, boolean noLocal)</code> | Creates a durable subscription with the specified name on the specified topic, and creates a <code>JMSConsumer</code> on that durable subscription, specifying a message selector and the <code>noLocal</code> parameter. |
| <code>createSharedConsumer(Topic topic, String sharedSubscriptionName)</code> | Creates a shared non-durable subscription with the specified name on the specified topic, and creates a <code>JMSConsumer</code> on that subscription. |
| <code>createSharedConsumer(Topic topic, String sharedSubscriptionName, String messageSelector)</code> | Creates a shared non-durable subscription with the specified name on the specified topic, specifying a message selector, and creates a <code>JMSConsumer</code> on that subscription |
| <code>createSharedConsumer(Topic topic, String sharedSubscriptionName, String messageSelector, boolean noLocal)</code> | Creates a shared non-durable subscription with the specified name on the specified topic, specifying a message selector and the <code>noLocal</code> parameter, and creates a <code>JMSConsumer</code> on that subscription. |

The following method on `JMSConsumer` may be used to set a message listener to asynchronously consume messages:

| JMSConsumer methods to set a message listener | |
|--|--|
| <code>setMessageListener(MessageListener listener)</code> | Sets the <code>JMSConsumer</code> 's listener to be the specified <code>MessageListener</code> . |

The following methods on `JMSConsumer` may be used to synchronously consume messages:

| JMSConsumer methods to synchronously consume messages | |
|---|--|
| <code>receive()</code> | Receives the next message produced for this <code>JMSConsumer</code> . |
| <code>receive(long timeout)</code> | Receives the next message produced for this <code>JMSConsumer</code> that arrives within the specified timeout interval. |
| <code>receiveNoWait()</code> | Receives the next message produced for this <code>JMSConsumer</code> if one is immediately available. |

In addition, the following methods on `JMSConsumer` may be used to receive a message payload directly:

| JMSConsumer methods to consume message payloads directly | |
|--|---|
| <code><T> T receivePayload(Class<T> c);</code> | Receives the next message produced for this <code>JMSConsumer</code> and returns its payload, which must be of the specified type |
| <code><T> T receivePayload(Class<T> c, long timeout);</code> | Receives the next message produced for this <code>JMSConsumer</code> and that arrives within the specified timeout period, and returns its payload, which must be of the specified type |
| <code><T> T receivePayloadNoWait(Class<T> c);</code> | Receives the next message produced for this <code>JMSConsumer</code> and returns its payload, which must be of the specified type |

These methods may be used when receiving messages of type `TextMessage`, `ObjectMessage`, `MapMessage` or `BytesMessage` and the application has no need to access message headers or properties.

If the next message is expected to be a `TextMessage` then this should be set to `String.class`. If the next message is expected to be a `ObjectMessage` then this should be set to `java.io.Serializable.class`. If the next message is expected to be a `MapMessage` then this should be set to `java.util.Map.class`. If the next message is expected to be a `BytesMessage` then this should be set to `byte[].class`. If the next message is not of the expected type a `ClassCastException` will be thrown and the message will not be delivered.

To simplify application code, methods on `JMSConsumer` throw unchecked exceptions rather than checked exceptions. See section 11.2.9 "Exceptions" for more information.

11.2.6. Closing the *JMSContext*

A `JMSContext` needs to be closed after use using the `close()` method.

This closes the underlying session and any underlying producers and consumers. If there are no other active (not closed) `JMSContext` objects

using the underlying connection then this method also closes the underlying connection.

The `JMSContext` interface extends the `java.lang.AutoCloseable` interface. This means that applications which create the `JMSContext` in a `try-with-resources` statement do not need to call the `close` method when the connection is no longer needed. Instead the session will be closed automatically at the end of the statement. The use of a `try-with-resources` statement also simplifies the handling of any exceptions thrown by the `close` method.

11.2.7. Automatic start of message delivery

An application using the standard API to consume messages needs to call the connection's `start` method to start delivery of incoming messages. It may temporarily suspend delivery by calling `stop`, after which a call to `start` will restart delivery. This is described in section 4.3.3 "Connection setup".

The simplified API provides corresponding `start` and `stop` methods on `JMSContext`. The `start` method will be called automatically when `createConsumer` or `createDurableConsumer` are called on the `MessageContext` object. This means there is no need for the application to call `start` when the consumer is first established. As with the standard API, an application may temporarily suspend delivery by calling `stop`, after which a call to `start` will restart delivery.

Sometimes an application will need the connection to remain in stopped mode until setup is complete and not commence message delivery until the `start` method is explicitly called, as with the standard API. This can be configured by calling `setAutoStart(false)` on the `JMSContext` prior to calling `createConsumer` or `createDurableConsumer`.

11.2.8. Threading restrictions on a JMSContext

Since a `JMSContext` incorporates a `Session` it is subject to the same threading restrictions as a `Session`. These are described in section 4.4.6 "Conventions for using a session" which explains how a session may only be used by one thread at a time.

The `JMSContext` method `createContext` does not use its underlying `Session` and so is not subject to this threading restriction.

This restriction also does not apply to the `JMSContext`'s `close` method (since closing the session from another thread is permitted),

By default, when `createConsumer` or `createDurableConsumer` is used to create a `JMSConsumer` the connection will automatically be started. This behaviour is described in section 11.2.7 "Automatic start of message delivery". It means that if `setMessageListener` is called to configure the asynchronous delivery of messages then the `JMSContext`'s session will immediately become dedicated to the thread of control that delivers messages to the listener and the application must not subsequently call methods on the `JMSContext` from another thread of control. However this restriction does not apply to applications which call `setMessageListener` to set a second or subsequent message listener. The JMS provider will be responsible for ensuring that a second message listener may be safely configured even if the underlying connection has been started.

11.2.9. Exceptions

Most methods in the standard API are declared as throwing a `javax.jms.JMSEException` or a subtype of it. This means that the calling method must either catch this exception or declare it in its own `throws` statement.

The simplified API does not throw checked exceptions. Instead, equivalent unchecked exceptions are thrown instead.

The new unchecked exceptions, and the checked exceptions to which they correspond are listed below:

| Old checked exception | Corresponding new unchecked exception |
|---|--|
| <code>JMSEException</code> | <code>JMSRuntimeException</code> |
| <code>TransactionRolledBackException</code> | <code>TransactionRolledBackRuntimeException</code> |
| <code>IllegalStateException</code> | <code>IllegalStateRuntimeException</code> |
| <code>InvalidDestinationException</code> | <code>InvalidDestinationRuntimeException</code> |
| <code>InvalidSelectorException</code> | <code>InvalidSelectorRuntimeException</code> |
| <code>MessageFormatException</code> | <code>MessageFormatRuntimeException</code> |
| <code>JMSSecurityException</code> | <code>JMSSecurityRuntimeException</code> |
| <code>InvalidClientIDException</code> | <code>InvalidClientIDRuntimeException</code> |

11.3. Injection of *JMSContext* objects

11.3.1. Support for injection

Injection of *JMSContext* objects is supported in those Java EE application classes which support dependency injection using CDI and for which CDI support has been enabled by means of a `META-INF/beans.xml` descriptor.

Section EE.5.20 of the Java EE specification lists the application classes that support dependency injection using CDI.

Section 12.1 of the CDI specification specifies how CDI support may be enabled for a particular application.

11.3.2. Container-managed and application-managed *JMSContexts*

A *JMSContext* object which has been injected is described as being *container-managed*, as it is created and closed by the container, not the application.

A *JMSContext* object which has been created by calling the `ConnectionFactory` method `createContext` is described as being *application-managed*. The application is responsible for calling `close` when the object is not longer needed.

11.3.3. Injection syntax

Applications may declare a field of type `javax.jms.JMSContext` and annotate it with the `javax.inject.Inject` annotation:

```
@Inject
private JMSContext context;
```

The container will inject a `JMSContext`. This object will have a scope as defined by section 11.3.3 "Scope of injected `JMSContext` objects".

The annotation `javax.jms.JMSConnectionFactory` may be used to specify the JNDI lookup name of the `ConnectionFactory` used to create the `JMSContext`. For example:

```
@Inject
@JMSConnectionFactory("jms/connectionFactory")
private JMSContext context;
```

If no lookup name is specified or the `JMSConnectionFactory` annotation is omitted then the platform default JMS connection factory will be used.

The annotation `javax.jms.JMSPasswordCredential` may be used to specify a user name and password which will be used when the `JMSContext` is created. For example:

```
@Inject
@JMSConnectionFactory("jms/connectionFactory")
@JMSPasswordCredential(username="admin",password="mypassword")
private JMSContext context;
```

Since it is undesirable to hardcode clear text passwords in an application, the password may be specified as an alias:

```
@Inject
@JMSPasswordCredential(
    username="admin", password="${ALIAS=myAdminPassword}")
private JMSContext context;
```

The use of a password alias allows the password to be defined in a secure manner separately from the application. See the Java EE 7 platform specification for more information on password aliases.

The annotation `javax.jms.JMSSessionMode` may be used to specify the session mode of the `JMSContext`. For example:

```
@Inject
@JMSConnectionFactory("jms/connectionFactory")
@JMSSessionMode(JMSContext.AUTO_ACKNOWLEDGE)
private JMSContext context;
```

The meaning and possible values of session mode are the same as for the `ConnectionFactory` method `createContext(int sessionMode)`:

- In the Java EE application client container, session mode may be set to any of `JMSContext.SESSION_TRANSACTED`, `JMSContext.CLIENT_ACKNOWLEDGE`, `JMSContext.AUTO_ACKNOWLEDGE` or

`JMSContext.DUPS_OK_ACKNOWLEDGE`. If no session mode is specified or the `JMSSessionMode` annotation is omitted a session mode of `JMSContext.AUTO_ACKNOWLEDGE` will be used.

- In a Java EE web or EJB container, when there is an active JTA transaction in progress, session mode is ignored and the `JMSSessionMode` annotation is unnecessary.
- In a Java EE web or EJB container, when there is no active JTA transaction in progress, session mode may be set to either of `JMSContext.AUTO_ACKNOWLEDGE` or `JMSContext.DUPS_OK_ACKNOWLEDGE`. If no session mode is specified or the `JMSSessionMode` annotation is omitted a session mode of `JMSContext.AUTO_ACKNOWLEDGE` will be used.

For more information about the use of session mode when creating a messaging context, see section 10.3 "Behaviour of JMS sessions in the Java EE web or EJB container" and the API documentation for the `ConnectionFactory` method `createContext(int sessionMode)`.

11.3.4. *Scope of injected JMSContext objects*

The scope of an injected `JMSContext` defines whether different injected `JMSContext` objects will actually refer to the same `JMSContext` object

It also defines when the injected `JMSContext` will be closed by the container. When the object falls out of scope, the container will automatically call `close()`.

The scope of an injected `JMSContext` object will depend on whether it is used in a transaction.

- If an injected `JMSContext` is used in a JTA transaction (both bean-managed and container-managed), its scope will be that of the transaction. This means that:
 - The `JMSContext` object will be automatically created the first time it is used within the transaction.
 - The `JMSContext` object will be automatically closed when the transaction is committed.
 - Within the same JTA transaction, different injected `JMSContext` objects which are injected using identical annotations will all refer to the same `JMSContext` object.
- If an injected `JMSContext` is used when there is no JTA transaction then its scope will be the existing CDI scope `@RequestScoped`. This means that:
 - The `JMSContext` object will be automatically created the first time it is used within a request.
 - The `JMSContext` object will be automatically closed when the request ends.
 - Within the same request, different injected `JMSContext` objects which are injected using identical annotations will all refer to the same `JMSContext` object.
- If an injected `JMSContext` is used both in a JTA transaction and outside a JTA transaction then separate `JMSContext` objects will be

used, with a separate `JMSContext` object being used for each JTA transaction as described above.

11.3.5. Restrictions on use of injected `JMSContext` objects

Within the same scope, different injected `JMSContext` objects which are injected using identical annotations will all refer to the same `JMSContext` object.

This means that they will all use the same connection. This will reduce the resource usage of the application and improve performance.

It also means that messages would be sent using the same session. Messages sent using different `JMSContext` objects in the same scope will be therefore received in order in which they were sent (see section 4.4.10.2 "Order of message sends" for a few qualifications).

However, to avoid the possibility of code in one bean having an unexpected effect on a different bean, the following methods which change the public state of a `JMSContext` will not be permitted if the `JMSContext` is injected.

- `setClientID`
- `setExceptionListener`
- `stop`
- `acknowledge`
- `commit`
- `rollback`
- `recover`
- `setAutoStart`
- `start`
- `close`

These methods must throw a `JMSRuntimeException` if the `JMSContext` is injected. These restrictions do not apply when the `JMSContext` is managed by the application; though note that several of these methods are in any case prohibited in a Java EE web or EJB container.

11.4. Examples using the simplified API

The examples in this section compare the use of the standard and simplified JMS APIs for some common JMS operations.

11.4.1. Sending a message (Java EE)

This example compares the use of the standard and simplified JMS APIs for sending a `TextMessage` in a Java EE web or EJB container.

11.4.1.1. Example using the standard API

Here's how you might do this using the standard API:

```

@Resource(lookup = "jms/connectionFactory ")
ConnectionFactory connectionFactory;

@Resource(lookup="jms/inboundQueue")
Queue inboundQueue;

public void sendMessageOld (String payload) throws JMSEException{
    try (Connection connection =
        connectionFactory.createConnection()) {
        Session session = connection.createSession();
        MessageProducer messageProducer =
            session.createProducer(inboundQueue);
        TextMessage textMessage =
            session.createTextMessage(payload);
        messageProducer.send(textMessage);
    }
}

```

11.4.1.2. Example using the simplified API

Here's how you might do this using the simplified API:

```

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

@Resource(lookup="jms/inboundQueue")
Queue inboundQueue;

public void sendMessageNew (String payload) {

    try (JMSContext context = connectionFactory.createContext()){
        context.createProducer().send(inboundQueue,payload);
    }
}

```

Note that sendMessageNew does not need to throw JMSEException.

11.4.1.3. Example using the simplified API and injection

Here's how you might do this using the simplified API with the JMSContext created by injection:

```

@Inject
@JMSConnectionFactory("jms/connectionFactory")
private JMSContext context;

@Resource(mappedName = "jms/inboundQueue")
private Queue inboundQueue;

public void sendMessageNew(String payload) {
    context.send(inboundQueue, payload);
}

```

11.4.2. Sending a message (Java SE)

This example compares the use of the standard and simplified JMS APIs for sending a TextMessage in a Java SE environment.

11.4.2.1. Example using the standard API

Here's how you might do this using the standard API:

```
public void sendMessageOld(String payload)
    throws JMSException, NamingException{

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");

    try (Connection connection =
        connectionFactory.createConnection()) {
        Session session = connection.createSession();
        MessageProducer messageProducer =
            session.createProducer(inboundQueue);
        TextMessage textMessage = session.createTextMessage(payload);
        messageProducer.send(textMessage);
    }
}
```

11.4.2.2. Example using the simplified API

Here's how you might do this using the simplified API:

```
public void sendMessageNew(String payload) throws NamingException{

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");

    try (JMSContext context = connectionFactory.createContext()){
        context.createProducer().send(inboundQueue, payload);
    }
}
```

Note that `receiveMessagesNew` does not need to throw `JMSException`.

11.4.3. Sending a message with properties (Java SE)

This example is similar to the previous example in that it compares the use of the standard and simplified JMS APIs for sending a `TextMessage` in a Java SE environment.

However this example also configures various attributes of the message that is sent:

- The message property "foo" is set to a value of "bar".
- The message is sent using a delivery mode of `NON_PERSISTENT`.
- The JMS provider is informed that message timestamps are not required.

11.4.3.1. Example using the standard API

Here's how you might do this using the standard API:


```

public void sendMessageOld(String payload)
    throws JMSEException, NamingException{

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");

    try (Connection connection =
        connectionFactory.createConnection()) {
        Session session = connection.createSession();
        MessageProducer messageProducer =
            session.createProducer(inboundQueue);
        TextMessage textMessage = session.createTextMessage(payload);
        textMessage.setStringProperty("foo", "bar");
        messageProducer.setDeliveryMode(NON_PERSISTENT);
        messageProducer.setDisableMessageTimestamp(true);
        messageProducer.send(textMessage);
    }
}

```

11.4.3.2. Example using the simplified API

Here's how you might do this using the simplified API:

```

public void sendMessageNew(String payload) throws NamingException{

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");

    try (JMSContext context = connectionFactory.createContext()){
        context.createProducer().
            setProperty("foo", "bar").
            setTimeToLive(10000).
            setDeliveryMode(NON_PERSISTENT).
            setDisableMessageTimestamp(true).
            send(inboundQueue, payload);
    }
}

```

Note that `receiveMessagesNew` does not need to throw `JMSEException`.

11.4.4. Receiving a message synchronously (Java EE)

This example compares the use of the standard and simplified JMS APIs for synchronously receiving a `TextMessage` in a Java EE web or EJB container.

11.4.4.1. Example using the standard API

Here's how you might do this using the standard API:

```

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

@Resource(lookup="jms/inboundQueue")
Queue inboundQueue;

public String receiveMessageOld() throws JMSEException {

    try (Connection connection =
        connectionFactory.createConnection()) {
        connection.start();
        Session session = connection.createSession();
        MessageConsumer messageConsumer =
            session.createConsumer(inboundQueue);
        TextMessage textMessage =
            (TextMessage)messageConsumer.receive();
        String payload = textMessage.getText();
        return payload;
    }
}

```

11.4.4.2. Example using the simplified API

Here's how you might do this using the simplified API.

```

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

@Resource(lookup="jms/inboundQueue")
Queue inboundQueue;

public String receiveMessageNew() {
    try (JMSContext context = connectionFactory.createContext()) {
        JMSConsumer consumer = context.createConsumer(inboundQueue);
        return consumer.receivePayload(String.class);
    }
}

```

Note that `receiveMessageNew` does not need to throw `JMSEException`.

11.4.4.3. Example using the simplified API and injection

Here's how you might do this using the simplified API with the `JMSContext` created by injection:

```

@Inject
@JMSConnectionFactory("jms/connectionFactory")
private JMSContext context;

@Resource(lookup="jms/inboundQueue")
Queue inboundQueue;

public String receiveMessageNew() {
    JMSConsumer consumer = context.createConsumer(inboundQueue);
    return consumer.receivePayload(String.class);
}

```

11.4.5. *Receiving a message synchronously (Java SE)*

This example compares the use of the standard and simplified JMS APIs for synchronously receiving a `TextMessage` in a Java SE environment.

11.4.5.1. *Example using the standard API*

Here's how you might do this using the standard API:

```

public String receiveMessageOld()
    throws JMSEException, NamingException {

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");

    try (Connection connection =
        connectionFactory.createConnection()); {
        Session session = connection.createSession(AUTO_ACKNOWLEDGE);
        MessageConsumer messageConsumer =
            session.createConsumer(inboundQueue);
        connection.start();
        TextMessage textMessage=
            (TextMessage) messageConsumer.receive();
        return textMessage.getText();
    }
}

```

11.4.5.2. *Example using the simplified API*

Here's how you might do this using the simplified API.

```

public String receiveMessageNew() throws NamingException {

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue)initialContext.lookup("jms/inboundQueue");

    try (JMSContext context =
        connectionFactory.createContext(AUTO_ACKNOWLEDGE);) {
        JMSConsumer consumer = context.createConsumer(inboundQueue);
        return consumer.receivePayload(String.class);
    }
}

```

Note that `receiveMessageNew` does not need to throw `JMSEException`.

11.4.6. *Receiving a message synchronously from a durable subscription (Java EE)*

This example compares the use of the standard and simplified JMS APIs for synchronously receiving a `TextMessage` from a durable topic subscription in a Java EE web or EJB container.

11.4.6.1. *Example using the standard API*

Here's how you might do this using the standard API.

```

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

@Resource(lookup = "jms/inboundTopic")
Topic inboundTopic;

public String receiveMessageOld() throws JMSEException {

    try (Connection connection =
        connectionFactory.createConnection()) {
        Session session = connection.createSession();
        MessageConsumer messageConsumer =
            session.createDurableConsumer(inboundTopic, "mysub");
        connection.start();
        TextMessage textMessage =
            (TextMessage) messageConsumer.receive();
        return textMessage.getText();
    }
}

```

11.4.6.2. *Example using the simplified API*

Here's how you might do this using the simplified API.

```

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

@Resource(lookup="jms/inboundTopic")
Topic inboundTopic;

public String receiveMessageNew() {

    try (JMSContext context = connectionFactory.createContext()) {
        JMSConsumer consumer =
            context.createDurableConsumer(inboundTopic, "mysub");
        return consumer.receivePayload(String.class);
    }
}

```

Note that `receiveMessageNew` does not need to throw an exception.

11.4.6.3. Example using the simplified API and injection

Here's how you might do this using the simplified API with the `JMSContext` created by injection:

```

@Inject
@JMSConnectionFactory("jms/connectionFactory")
private JMSContext context;

@Resource(lookup="jms/inboundTopic")
Topic inboundTopic;

public String receiveMessageNew() {
    JMSConsumer consumer =
        context.createDurableConsumer(inboundTopic, "mysub");
    return consumer.receivePayload(String.class);
}

```

11.4.7. Receiving messages asynchronously (Java SE)

This example compares the use of the standard and simplified JMS APIs for asynchronously receiving `TextMessage` objects in a Java SE environment.

11.4.7.1. Example using the standard API

Here's how you might do this using the standard API, using a message listener class `MyListener`:

```

public void receiveMessagesOld()
    throws JMSEException, NamingException{

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");

    try (Connection connection =
        connectionFactory.createConnection());{
        Session session = connection.createSession(AUTO_ACKNOWLEDGE);
        MessageConsumer consumer =
            session.createConsumer(inboundQueue);
        MessageListener messageListener = new MyListener();
        consumer.setMessageListener(messageListener);
        connection.start();

        // wait for messages to be received - details omitted
    }
}

```

11.4.7.2. Example using the simplified API

Here's how you might do this using the simplified API.

```

public void receiveMessagesNew() throws NamingException {

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue = (Queue)
        initialContext.lookup("jms/inboundQueue");

    try (JMSContext context =
        connectionFactory.createContext(AUTO_ACKNOWLEDGE));{
        JMSConsumer consumer = context.createConsumer(inboundQueue);
        MessageListener messageListener = new MyListener();
        consumer.setMessageListener(messageListener);

        // wait for messages to be received - details omitted
    }
}

```

Note that `receiveMessagesNew` does not need to throw `JMSEException`.

11.4.8. Receiving a message asynchronously from a durable subscription (Java SE)

This example compares the use of the standard and simplified JMS APIs for asynchronously receiving a `TextMessage` from a durable topic subscription in a Java SE environment.

11.4.8.1. Example using the standard API

Here's how you might do this using the standard API, using a message listener class `MyListener`:

```

public void receiveMessagesOld()
    throws JMSEException, NamingException{

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Topic inboundTopic =
        (Topic)initialContext.lookup("jms/inboundTopic");

    try (Connection connection =
        connectionFactory.createConnection();) {
        Session session =
            connection.createSession( AUTO_ACKNOWLEDGE);
        session.createDurableSubscriber(inboundTopic, "");
        TopicSubscriber topicSubscriber =
            session.createDurableSubscriber(inboundTopic, "mysub");
        MessageListener messageListener = new MyListener();
        topicSubscriber.setMessageListener(messageListener);

        connection.start();

        // wait for messages to be received - details omitted
    }
}

```

11.4.8.2. Example using the simplified API

Here's how you might do this using the simplified API:

```

public void receiveMessagesNew() throws NamingException {

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Topic inboundTopic =
        (Topic) initialContext.lookup("jms/inboundTopic");

    try (JMSContext context =
        connectionFactory.createContext(AUTO_ACKNOWLEDGE);){
        JMSConsumer consumer =
            context.createDurableConsumer(inboundTopic, "mysub");
        MessageListener messageListener = new MyListener();
        consumer.setMessageListener(messageListener);

        // wait for messages to be received - details omitted
    }
}

```

Note that `receiveMessagesNew` does not need to throw `JMSEException`.

11.4.9. Receiving messages in multiple threads (Java SE)

This example compares the use of the standard and simplified JMS APIs for asynchronously receiving `TextMessage` objects from a queue using multiple threads in a Java SE environment. In this example two threads are used, which means two sessions are needed. In this example, both sessions use the same connection.

11.4.9.1. Example using the standard API

Here's how you might do this using the standard API, using a message listener class `MyListener`:

```
public void receiveMessagesOld()
    throws JMSEException, NamingException {

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");

    try (Connection connection =
        connectionFactory.createConnection()); {
        Session s1 = connection.createSession(AUTO_ACKNOWLEDGE);
        MessageConsumer messageConsumer1 =
            s1.createConsumer(inboundQueue);
        MyListener messageListener1 = new MyListener("One");
        messageConsumer1.setMessageListener(messageListener1);

        Session s2 = connection.createSession(AUTO_ACKNOWLEDGE);
        MessageConsumer messageConsumer2 =
            s2.createConsumer(inboundQueue);
        MyListener messageListener2 = new MyListener("Two");
        messageConsumer2.setMessageListener(messageListener2);

        connection.start();

        // wait for messages to be received - details omitted
    }
}
```

11.4.9.2. Example using the simplified API

Here's how you might do this using the simplified API:


```

public void receiveMessagesNew() throws NamingException {

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");

    try (JMSContext context1 =
        connectionFactory.createContext(AUTO_ACKNOWLEDGE);
        JMSContext context2 =
            context1.createContext(AUTO_ACKNOWLEDGE);) {
        JMSConsumer consumer1 =
            context1.createConsumer(inboundQueue);
        MyListener messageListener1 = new MyListener("One");
        consumer1.setMessageListener(messageListener1);

        JMSConsumer consumer2 =
            context2.createConsumer(inboundQueue);
        MyListener messageListener2 = new MyListener("Two");
        consumer2.setMessageListener(messageListener2);

        // wait for messages to be received - details omitted
    }
}

```

11.4.10. Receiving synchronously and sending a message in the same local transaction (Java SE)

This example compares the use of the standard and simplified JMS APIs for the use case in which a Java SE application repeatedly consumes a message from one queue and forwards it to another queue in a Java SE environment. In this example each message is received and forwarded in the same local transaction. This means that the receiving and sending of the message must be done using the same transacted session which is then committed.

In this example the application consumes the incoming messages synchronously. However since this is a Java SE application the message could also be consumed asynchronously using a `MessageListener`.

11.4.10.1. Example using the standard API

Here's how you might do this using the standard API:

```

public void receiveAndSendMessageOld()
    throws JMSEException, NamingException {
    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");
    Queue outboundQueue =
        (Queue) initialContext.lookup("jms/outboundQueue");

    try (Connection connection =
        connectionFactory.createConnection());{
        Session session =
            connection.createSession(SESSION_TRANSACTED);
        MessageConsumer messageConsumer =
            session.createConsumer(inboundQueue);
        MessageProducer messageProducer =
            session.createProducer(outboundQueue);
        connection.start();

        TextMessage textMessage = null;
        do {
            textMessage = (TextMessage) messageConsumer.receive(1000);
            if (textMessage!=null){
                messageProducer.send(textMessage);
                session.commit();
            }
        } while (textMessage!=null);
    }
}

```

11.4.10.2. Example using the simplified API

Here's how you might do this using the simplified API:

```

public void receiveAndSendMessageNew() throws NamingException {

    InitialContext initialContext = getInitialContext();
    ConnectionFactory connectionFactory = (ConnectionFactory)
        initialContext.lookup("jms/connectionFactory");
    Queue inboundQueue =
        (Queue) initialContext.lookup("jms/inboundQueue");
    Queue outboundQueue =
        (Queue) initialContext.lookup("jms/outboundQueue");

    try (JMSContext context =
        connectionFactory.createContext(SESSION_TRANSACTED);) {
        JMSConsumer consumer = context.createConsumer(inboundQueue);
        TextMessage textMessage = null;
        do {
            textMessage = (TextMessage) consumer.receive(1000);
            if (textMessage != null) {
                context.createProducer().send(
                    outboundQueue, textMessage);
                context.commit();
            }
        } while (textMessage != null);
    }
}

```

Note that `receiveAndSendMessageNew` does not need to throw `JMSException`.

11.4.11. Request/reply pattern using a *TemporaryQueue* (Java EE)

This example compares the use of the standard and simplified JMS APIs for implementing a request/reply pattern in a Java EE EJB container.

In this example, a session bean (the requestor) sends a request message to some queue (the request queue). The `setJMSReplyTo` property of the request message is set to a `TemporaryQueue`, to which the reply should be set. After sending the request, the session bean listens on the temporary queue until it receives the reply.

Since the request message won't actually be sent until the transaction is committed, the request message is sent in a separate transaction from that used to receive the reply.

A message-driven bean (the responder) listens on the request queue for request messages. When it receives a message it creates a reply message and sends it to the reply queue specified in the `setJMSReplyTo` property of the incoming message.

When implementing this pattern, the following features of JMS must be borne in mind:

- The same `Connection` object that was used to create the `TemporaryQueue` must also be used to consume the response message from it. (This is a restriction of temporary queues).
- If the request message is sent in a transaction then the response message must be consumed in a separate transaction. That's why the message is sent in a separate business which has the transactional attribute `REQUIRES_NEW`.

11.4.11.1. Example using the standard API

Here's how you might implement the requestor this using the standard API:

There are two session beans involved in sending the request message. The first bean

The first session bean `RequestReplyOld` creates the temporary reply queue, calls a second bean `SenderBeanOld` to send the request in a separate transaction and then listens for the reply:

```
@Stateless
@LocalBean
public class RequestReplyOld {

    @Resource(lookup = "jms/connectionFactory")
    ConnectionFactory connectionFactory;

    @EJB private SenderBeanOld senderBean;

    @TransactionAttribute(TransactionAttributeType.REQUIRED)
    public String requestReplyOld(String request) throws JMSEException {

        try (Connection connection =
            connectionFactory.createConnection()) {
            Session session = connection.createSession();
            TemporaryQueue replyQueue = session.createTemporaryQueue();

            // call a second bean to
            // send the request message in a separate transaction
            senderBean.sendRequestOld(request, replyQueue);

            // now receive the reply, using the same connection
            // as was used to create the temporary reply queue
            MessageConsumer consumer = session.createConsumer(replyQueue);
            connection.start();
            TextMessage reply = (TextMessage) consumer.receive();
            return reply.getText();
        }
    }
}
```

The second session bean `SenderBeanOld` simply sends the request to the request queue in a separate transaction:

```

@Stateless
@LocalBean
public class SenderBeanOld {

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

@Resource(lookup="jms/requestQueue")
Queue requestQueue;

@TransactionAttribute(TransactionAttributeType.REQUIRES_NEW)
public void sendRequestOld(
    String requestString, TemporaryQueue replyQueue)
    throws JMSEException {
    try (Connection connection =
        connectionFactory.createConnection()) {
        Session session = connection.createSession();
        TextMessage requestMessage =
            session.createTextMessage(requestString);
        requestMessage.setJMSReplyTo(replyQueue);
        MessageProducer messageProducer =
            session.createProducer(requestQueue);
        messageProducer.send(requestMessage);
    }
}
}

```

Here is the message-driven bean RequestResponderOld which receives request messages and sends responses:

```

@MessageDriven(mappedName = "jms/requestQueue")
public class RequestResponderOld implements MessageListener {

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

public void onMessage(Message message) {

    try (Connection connection =
        connectionFactory.createConnection()){
        Session session = connection.createSession();

        // extract request from request message
        String request = ((TextMessage)message).getText();

        // extract temporary reply destination from request message
        Destination replyDestination = message.getJMSReplyTo();

        // prepare response
        TextMessage replyMessage =
            session.createTextMessage("Reply to: "+request);

        // send response
        MessageProducer messageProducer =
            session.createProducer(replyDestination);
        messageProducer.send(replyMessage);
    } catch (JMSException ex) {
        // log an error here
    }
}
}

```

11.4.11.2. Example using the simplified API

Here's how the same example might look when using the simplified API:

There are two session beans involved in sending the request message. The first bean

The first session bean `RequestReplyNew` creates the temporary reply queue, calls a second bean `SenderBeanNew` to send the request in a separate transaction and then listens for the reply:

```

@Stateless
@LocalBean
public class RequestReplyNew {

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

@EJB private SenderBeanNew senderBean;

@TransactionalAttribute(TransactionAttributeType.REQUIRED)
public String requestReplyNew(String request) throws JMSException {

    try (JMSContext context = connectionFactory.createContext()) {
        TemporaryQueue replyQueue = context.createTemporaryQueue();

        // send the request message in a separate transaction
        // so use a separate bean
        // this call may throw JMSException
        senderBean.sendRequestNew(request, replyQueue);

        // now receive the reply, using the same connection
        // as was used to create the temporary reply queue
        JMSConsumer consumer = context.createConsumer(replyQueue);
        return consumer.receivePayload(String.class);
    }
}
}

```

The second session bean `SenderBeanNew` simply sends the request to the request queue in a separate transaction:

```

@Stateless
@LocalBean
public class SenderBeanNew {

@Resource(lookup = "jms/connectionFactory")
ConnectionFactory connectionFactory;

@Resource(lookup="jms/requestQueue")
Queue requestQueue;

@TransactionalAttribute(TransactionAttributeType.REQUIRES_NEW)
public void sendRequestNew(
    String requestString, TemporaryQueue replyQueue)
    throws JMSException {
    try (JMSContext context = connectionFactory.createContext()) {
        TextMessage requestMessage =
            context.createTextMessage(requestString);
        // this call may throw JMSException
        requestMessage.setJMSReplyTo(replyQueue);
        context.createProducer().send(
            requestQueue, requestMessage);
    }
}
}

```

Here is the message-driven bean `RequestResponderNew` which receives request messages and sends responses:

```

@MessageDriven(mappedName = "jms/requestQueue")
public class RequestResponderNew implements MessageListener {

    @Resource(lookup = "jms/connectionFactory")
    ConnectionFactory connectionFactory;

    public void onMessage(Message message) {

        try (JMSContext context = connectionFactory.createContext()){

            // extract request from request message
            // this may throw a JMSEException
            String request = ((TextMessage)message).getText();

            // extract temporary reply destination from request message
            // this may throw a JMSEException
            Destination replyDestination = message.getJMSReplyTo();

            // prepare response
            TextMessage replyMessage =
                context.createTextMessage("Reply to: "+request);

            // send response
            context.createProducer().send(replyDestination,replyMessage);
        } catch (JMSEException ex) {
            // log an error here
        }
    }
}

```

Note that in this example it is not possible to eliminate the need to declare to catch `JMSEException` since it uses methods on `Message` and `TextMessage` which throw `JMSEException`.

11.4.11.3. Example using the simplified API and injection

Here's how the same example might look when using the simplified API with the `JMSContext` created by injection:

There are two session beans involved in sending the request message. The first bean

The first session bean `RequestReplyNew` creates the temporary reply queue, calls a second bean `SenderBeanNew` to send the request in a separate transaction and then listens for the reply:


```

@Stateless
@LocalBean
public class RequestReplyNew {

    @Inject
    @JMSConnectionFactory("jms/connectionFactory2")
    private JMSContext context;

    @EJB private SenderBeanNew senderBean;

    @TransactionAttribute(TransactionAttributeType.REQUIRED)
    public String requestReplyNew(String request) throws JMSEException {

        TemporaryQueue replyQueue = context.createTemporaryQueue();

        // send the request message in a separate transaction
        // so use a separate bean
        // this call may throw JMSEException
        senderBean.sendRequestNew(request, replyQueue);

        // now receive the reply, using the same connection
        // as was used to create the temporary reply queue
        JMSConsumer consumer = context.createConsumer(replyQueue);
        return consumer.receivePayload(String.class);
    }
}

```

The second session bean `SenderBeanNew` simply sends the request to the request queue in a separate transaction:

```

@Stateless
@LocalBean
public class SenderBeanNew {

    @Inject
    @JMSConnectionFactory("jms/connectionFactory")
    private JMSContext context;

    @Resource(lookup="jms/requestQueue")
    Queue requestQueue;

    @TransactionAttribute(TransactionAttributeType.REQUIRES_NEW)
    public void sendRequestNew(
        String requestString, TemporaryQueue replyQueue)
        throws JMSEException {

        TextMessage requestMessage =
            context.createTextMessage(requestString);
        // this call may throw JMSEException
        requestMessage.setJMSReplyTo(replyQueue);
        context.createProducer().send(requestQueue, requestMessage);
    }
}

```

Here is the message-driven bean `RequestResponderNew` which receives request messages and sends responses:

```

@MessageDriven(mappedName = "jms/requestQueue")
public class RequestResponderNew implements MessageListener {

@Inject
@JMSConnectionFactory("jms/connectionFactory")
private JMSContext context;

public void onMessage(Message message) {

    try {
        // extract request from request message
        // this may throw a JMSEException
        String request = ((TextMessage)message).getText();

        // extract temporary reply destination from request message
        // this may throw a JMSEException
        Destination replyDestination = message.getJMSReplyTo();

        // prepare response
        TextMessage replyMessage =
            context.createTextMessage("Reply to: "+request);

        // send response
        context.createProducer().send(replyDestination,replyMessage);
    } catch (JMSEException ex) {
        // log an error here
    }
}
}

```

Note that in this example it is not possible to eliminate the need to declare to catch `JMSEException` since it uses methods on `Message` and `TextMessage` which throw `JMSEException`.

12. Resource Adapter

The Java EE Connector Architecture (JCA) specification defines a standard architecture for connecting the Java EE platform to enterprise information systems (EISs).

A JMS provider is required to include a resource adapter which connects to that JMS provider and which conforms to the Java EE Connector Architecture specification and as further specified in this chapter. Such a resource adapter is referred a "JMS standard resource adapter".

The version of the Java EE Connector Architecture specification which should be used is 1.6.

This chapter is not intended to prevent the creation and use of additional resource adapters for connecting to a JMS provider which do not conform to the specifications in this chapter. However Java EE applications which use such resource adapters may be less portable.

12.1. ActivationSpec properties

A JMS standard resource adapter must support the ActivationSpec JavaBean properties defined in the following table. It may support additional properties in addition to those listed.

Table 12.1 ActivationSpec properties that a JMS standard resource adapter must support

| ActivationSpec property | Description |
|-------------------------|--|
| destinationLookup | This property may be used to specify the lookup name of an administratively-defined <code>javax.jms.Queue</code> or <code>javax.jms.Topic</code> object which defines the JMS queue or topic from which the endpoint (message-driven bean) is to receive messages. |
| connectionFactoryLookup | This property may be used to specify the lookup name of an administratively-defined <code>javax.jms.ConnectionFactory</code> , <code>javax.jms.QueueConnectionFactory</code> or <code>javax.jms.TopicConnectionFactory</code> object that will be used to connect to the JMS provider from which the endpoint (message-driven bean) is to receive messages. |
| acknowledgeMode | <p>If bean-managed transaction demarcation is used, this property may be used to indicate whether JMS <code>AUTO_ACKNOWLEDGE</code> semantics or <code>DUPS_OK_ACKNOWLEDGE</code> semantics should apply.</p> <p>This property may be set to either <code>Auto-acknowledge</code> or <code>Dups-ok-acknowledge</code>. If this property is not specified, a default of <code>Auto-acknowledge</code> will be used.</p> |
| messageSelector | This property may be used to specify a message selector. If this property is not specified then a message selector will not be used. |

| ActivationSpec property | Description |
|-------------------------|--|
| destinationType | This property may be used to specify whether the specified destination is a queue or topic. The valid values are <code>javax.jms.Queue</code> or <code>javax.jms.Topic</code> . |
| subscriptionDurability | <p>This property only applies to endpoints (message-driven beans) that receive messages published to a topic. It may be used to specify whether the subscription is durable or non-durable.</p> <p>This property may be set to either <code>Durable</code> or <code>NonDurable</code>. If this property is not specified, a default of <code>NonDurable</code> will be used.</p> |
| clientId | <p>This property may be used to specify the client identifier that will be used when connecting to the JMS provider from which the endpoint (message-driven bean) is to receive messages.</p> <p>If this property is not specified then the client identifier will be left unset.</p> |
| subscriptionName | <p>This property only applies to endpoints (message-driven beans) that receive messages published to a topic. If the <code>subscriptionDurability</code> property has been used to specify that the subscription is durable then the <code>subscriptionName</code> property may be used to specify the name of the durable subscription.</p> <p>If a durable subscription is specified but <code>subscriptionName</code> is not specified then the resource adapter will set the name of the durable subscription to be a name which is unique to the deployed MDB. If the message-driven bean is deployed into a clustered application server then the <code>shareSubscriptions</code> property will be used to determine whether the durable subscription name generated by the resource adapter will be the same or different for each instance in the cluster.</p> <p>The resource adapter may obtain the name unique to the deployed MDB by performing a JNDI lookup of the name <code>java:comp/UniqueMDBName</code>, as specified in the EJB 3.2 specification section 5.7.3 "Unique Identifier for JMS Message-Driven Bean". If a name different for each instance in the cluster is required the resource adapter may obtain a name that identifies the instance by performing a JNDI lookup of the name <code>java:comp/InstanceName</code> as specified in the Java EE 7 Platform Specification section 5.16 "Application Server Instance Name"</p> |

| ActivationSpec property | Description |
|-------------------------|--|
| shareSubscriptions | <p>This property only applies to message-driven beans that receive messages published to a topic and are deployed into a clustered application server.</p> <p>If a durable subscription is specified but <code>subscriptionName</code> is not specified then the <code>shareSubscription</code> property may be used to specify whether the durable subscription name generated by the resource adapter should be the same or different for each instance in the cluster.</p> <p>If a non-durable subscription is specified then the <code>shareSubscription</code> property may be used to specify whether each instance in the cluster should use the same shared non-durable subscription or whether each instance should use a separate non-shared subscription.</p> <p>This property may have the string values <code>true</code> or <code>false</code>.</p> <p>A value of <code>true</code> means that the same durable or non-durable subscription will be used for each instance in the cluster.</p> <p>A value of <code>false</code> means that a different durable or non-durable subscription will be used for each instance in the cluster.</p> <p>By default a value of <code>true</code> is assumed.</p> |

A.Issues

A.1. Resolved issues

A.1.1 JDK 1.1.x compatibility

JMS is compatible with JDK 1.1.x.

A.1.1 Distributed Java event model

JMS can be used, in general, as a notification service; however, it does not define a distributed version of Java Events.

One alternative for implementing distributed Java Events would be as JavaBeans that transparently, to the event producer and listener beans, distribute the events via JMS.

A.1.2 Should the two JMS domains, PTP and pub/sub, be merged?

Even though there are many similarities, providing separate domains still seem to be important.

It means that vendors aren't forced to support facilities out of their domain, and that client code can be a bit more portable because products more fully support a domain (as opposed to supporting less defined subsets of a merged domain).

A.1.3 Should JMS specify a set of JMS JavaBeans?

JMS is a low level API and like other Java low level API's it doesn't lend itself to direct representation as JavaBeans.

A.1.4 Alignment with the CORBA notification service

The Notification service adds filtering, delivery guarantee semantics, durable connections, and the assembly of event networks to the CORBA Event Service. It gets its delivery guarantee semantics from the CORBA Messaging Service (which defines asynchronous CORBA method invocation).

Java technology is well integrated with CORBA. It provides Java IDL and COS Naming. In addition, OMG has recently defined RMI over IIOP.

It is expected that most use of IIOP from Java will be via RMI. It is expected that most use of COS Naming from Java will be via JNDI (Java Naming and Directory Service). JMS is a Java specific API designed to be layered over a wide range of existing and future MOM systems (just like JNDI is layered over existing name and directory services).

A.1.5 Should JMS provide end-to-end synchronous message delivery and notification of delivery?

Some messaging systems provide synchronous delivery to destinations as a mechanism for implementing reliable applications. Some systems provide clients with various forms of delivery notification so that the clients can detect dropped or ignored messages. This is not the model defined by JMS.

JMS messaging provides guaranteed delivery via the once-and-only-once delivery semantics of `PERSISTENT` messages. In addition, message consumers can insure reliable processing of messages by using either `CLIENT_ACKNOWLEDGE` mode or transactional sessions.

This achieves reliable delivery with minimum synchronization and is the enterprise messaging model most vendors and developers prefer.

JMS does not define a schema of systems messages (such as delivery notifications). If an application requires acknowledgment of message receipt, it can define an application level acknowledgment message.

These issues are more clearly understood when they are examined in the context of pub/sub applications. In this context, synchronous delivery and/or system acknowledgment of receipt are not an effective mechanism for implementing reliable applications (because producers by definition are not, and don't want to be, responsible for end-to-end message delivery).

A.1.6 Should JMS provide a send-to-list mechanism?

Currently JMS provides a number of message send options; however, messages can only be sent to one destination at a time.

The benefit of send-to-list is slightly less work for the programmer and the potential for the JMS provider to optimize the fact that several destinations are being sent the same message.

The down side of a send-to-list mechanism is that the list is, in effect, a group that is implemented and maintained by the client. This would complicate the administration of JMS clients.

Instead of JMS providing a send-to-list mechanism, it is recommended that providers support configuring destinations that represent a group. This allows a client to reach all consumers with a single send, while insuring that groups are properly administrable.

A.1.7 Should JMS provide subscription notification?

If it were possible for a publisher to detect when subscribers for a topic existed, it could inhibit publication on unsubscribed topics.

Although there may be some benefit in providing publishers with a mechanism for inhibiting publication to unsubscribed topics, the complexity this would add to JMS and the additional provider overhead it would require is not justified by its potential benefits. Instead, JMS providers should insure that they minimize the overhead for handling messages published to an unsubscribed topic.

A.2. Unresolved issues in the JMS 2.0 Early Draft

This section has been added to assist discussion of the JMS 2.0 Early Draft and will be removed prior to final release.

A.2.1 Simplified API: Injecting a JMSContext

The JMS 2.0 Early Draft release proposes how in a Java EE application `JMSContext` objects can be injected. See section 11.3 "Injection of `JMSContext` objects" for details.

The container is responsible for creating `JMSContext` objects and in closing them after use.

How much does the specification need to say about how such objects are managed by the container? To some extent this can be considered an implementation detail which can be left to the container. However there are cases when the application needs to know whether two successive calls to methods on a `JMSContext` apply to the same or different sessions, since JMS only defines the relative order of messages produced using the same session.

A.3. Unresolved issues in the JMS 2.0 Public Draft

This section has been added to assist discussion of the JMS 2.0 Public Draft and may be removed prior to final release if the issue has been resolved.

A.3.1 Delivery delay

Delivery delay is a new feature added in JMS 2.0 and is described in section 4.12 "Delivery delay".

There is an unresolved issue regarding the delivery of messages to topics which have a delivery delay specified. This is whether the decision to add a message to a subscription (whether durable or non-durable) should be made (a) when the message reaches its delivery time or (b) when the message is sent.

Note that this is a question about deciding which subscriptions a message is added to, not about when the message would actually be delivered. In both cases the message wouldn't be delivered to a consumer until the delivery time has been reached.

If (a) were adopted it would require the JMS provider to keep all messages in the server until their delivery time is reached, even if there were no durable or non-durable subscriptions in existence. This might even be needed for non-persistent messages. Adopting (b) does not require this and by not requiring a message to be held separately from a subscription is closer to the way in which JMS providers work now. Forcing a JMS provider to implement (a) might potentially add a significant burden simply to cater for an unimportant edge case.

In this specification option (b) has been chosen, and section 4.12 "Delivery delay" states that if a message is published to a topic, it will only be added to a durable or non-durable subscription on that topic if the subscription exists at the time the message is sent and continues to exist at the time the specified message delivery time is reached.

However there were differing views on this within the JMS 2.0 expert group and further views are invited.

In addition there is an unresolved issue regarding the behaviour of a `QueueBrowser`. In this specification, section 5.9 "QueueBrowser" has been updated to state that "a message must not be returned by a `QueueBrowser` before its delivery time has been reached." However there were differing views on this within the JMS 2.0 expert group and further views are invited.

B. Change history

B.1. Version 1.0.1

B.1.1 JMS exceptions

A new JMS Exception chapter was added and it contains the following new information:

- Two fields were added to `JMSEException` - a vendor error code and an Exception reference.
- In version 1.0, `JMSEException` was the only JMS exception specified. Version 1.0.1 adds a list of standard exceptions derived from `JMSEException` and describes when each should be thrown by JMS providers.

B.2. Version 1.0.2

The objective of JMS 1.0.2 is to correct errata in the JMS 1.0.1 specification and code that have been uncovered by implementors and users. It also contains many clarifications that resolve ambiguities found in the previous versions.

B.2.1 The multiple topic subscriber special case

JMS 1.0.1 specified that in the special case of two topic subscribers on a session with overlapping subscriptions, a message that was selected by both would only be delivered to one. Implementation experience revealed that this case was better handled in the same way that overlapping subscriptions from different sessions are treated, so this special case has been removed.

B.2.2 Message selector comparison of exact and inexact numeric values

JMS 1.0.1 specified that message selectors did not support the comparison of exact and inexact numeric values. This conflicted with the requirement to support numeric promotion. This has been changed to support exact and inexact comparison.

B.2.3 Connection and session close

JMS 1.0.1 did not fully specify the sequence for closing a connection and its sessions. This sequence is now fully specified.

JMS 1.0.1 was ambiguous about whether or not calls to connection and session close returned immediately. Connection and session close now explicitly state that they block until message processing has been shutdown in an orderly fashion.

B.2.4 Creating a session on an active connection

When a session is created on an active (as opposed to stopped) connection it is only possible to create at most a single asynchronous consumer for it. A more detailed discussion of this case is provided.

B.2.5 Delivery mode and message retention

The effect that delivery mode has on message retention for a consumer has been clarified.

B.2.6 The ‘single thread’ use of sessions

Sessions are designed to minimize the need to write for multithreaded code in order to support the asynchronous consumption of messages. Clarification on the benefits and the programming model of this design have been added.

B.2.7 Clearing a message’s properties and body

A clarification has been added that notes that clearing a message’s properties and clearing its body are independent.

B.2.8 Message selector numeric literal syntax

A note has been added that states that the numeric literal syntax is that specified by the Java language.

B.2.9 Comparison of boolean values in message selectors

A note has been added that only equality and inequality comparisons are supported.

B.2.10 Order of messages read from a queue

A note has been added that explains that a client can read messages from a destination in an order different from the order they have been sent by using a selector that matches a later message and then using a selector that matches an earlier message.

B.2.11 Null values in messages

A note has been added that message values are allowed to be null.

B.2.12 Closing constituents of closed connections and sessions

There was some ambiguity about whether or not close needed to be called on all JMS objects. A note has been added that states that there is no need to close the sessions of a closed connection; and, there is no need to close the producers and consumers of a closed session.

B.2.13 The termination of a pending receive on close

JMS 1.0.1 did not describe how a pending message receive is terminated if its session or connection is closed. It is now specified that in this case receive returns a null message.

B.2.14 Incorrect entry in Stream and Map Message conversion table

This table erroneously included a required conversion between char and String. This has been removed.

B.2.15 Inactive durable subscription

A note explaining that an inactive durable subscription is one that exists but does not at the time have a TopicSubscriber created for it.

B.2.16 Read-only message body

The read-only semantics of received message bodies was documented in the `Message` javadoc but was not included in the spec. It has been added.

B.2.17 Changing header fields of a received message

When a message is received, its header field values may be changed; however, its property entries and its body are read-only. A note clarifying this has been added.

B.2.18 Null/missing message properties and message fields

The result of accessing a null/missing value as a Java primitive type was previously not fully specified. This has clarified.

B.2.19 JMS source errata

Two methods required by the spec were left out of the source, the `getJMSXPropertyNames` method of `ConnectionMetaData` and the `getExceptionListener` method of `Connection`. These have been added.

The type of the time-to-live parameter of `setTimeToLive` and `getTimeToLive` methods of `MessageProducer` and the type of the default time-to-live constant were `int` and have been changed to `long`.

The close sequence of `TopicRequestor` and `QueueRequestor` did not agree with the order specified in the specification and this has been corrected.

The type of the parameter of the `createTextMessage` method that takes an input value was changed from `StringBuffer` to `String`.

The subscription name parameter was missing from the `createDurableSubscription` method of `TopicConnection`. It has been added.

B.2.20 JMS source Java API documentation errata

The correct end-of-message indicator for the `readBytes` method of `BytesMessage` is a return value of `-1`.

The `setPriority` method of `MessageProducer` should have a parameter named `priority` not `deliveryMode`.

B.2.21 JMS source Java API documentation clarifications

Note that byte values are returned as `byte[]` not `Byte[]` by the `readObject` method of `StreamMessage` and the `getObject` method of `MapMessage`.

Note that the `acknowledge` method of `Message` acknowledges all messages received on that message's session.

Note that the `InvalidClientIDException` is used for any client id value that a JMS provider considers invalid. Since client id value is JMS provider specific the criteria for determining a valid value is provider specific.

A note has been added to the `readBytes` method of `StreamMessage` and `BytesMessage` to describe how values that overflow the size of the input buffer are handled.

A note has been added that clarifies when `setClientID` method of `Connection` should be used.

Note that calling the `setMessageListener` method of `MessageConsumer` with a null value is equivalent to unsetting the `MessageListener`.

Note that the `unsubscribe` method of `TopicSession` should not be called to delete a durable subscription if there is a `TopicConsumer` currently consuming it.

Note that result of calling the `setMessageListener` method of `MessageConsumer` while messages are being consumed by an existing listener or the consumer is being used to synchronously consume messages is undefined.

Note the `createTopic` method of `TopicSession` and the `createQueue` method of `QueueSession` are used for converting a JMS provider specific name into a `Topic` or `Queue` object that represents an existing topic or queue by that name. These methods are not for creating the physical topic or queue. The physical creation of topics and queues are administrative tasks and are not done by JMS. The one exception is the creation of temporary topics and queues which is done using the `createTemporaryTopic` and `createTemporaryQueue` methods.

Note that the `setObject` method of `ObjectMessage` places a copy of the input object in a message.

Note that a connection is created in stopped mode and, for incoming messages to be delivered to the message listeners of its sessions, its `start` method must be called.

Documentation of `Message` default constants has been added.

Note the result of `readBytes` method of `StreamMessage` when the caller's `byte[]` buffer is smaller than the `byte[]` field value being read.

The documentation of `QueueRequestor` and `TopicRequestor` has been improved.

The `IllegalStateException` has been noted as a required exception for several more error conditions. They are: acknowledging a message received from a closed session; attempting to call the `recover` method of a transacted session; attempting to call any method of a closed connection, session, consumer or producer (with the exception of the `close` method itself); attempting to set a connection's client identifier at the wrong time or when it has been administratively configured.

B.3. Version 1.0.2b

The objective of version 1.0.2b of the JMS API Specification and Java API documentation is to correct errata in the JMS 1.02 Specification and the JMS 1.0.2a Java API documentation that have been uncovered by implementors and users.

Version 1.0.2b incorporates two sets of errata, which are marked by change bars in the Specification:

- Major errata and clarifications approved by a Java Community ProcessSM program Maintenance Review that closed June 25, 2001.
- Minor errata formerly listed on the JMS documentation web page.

B.3.1 JMS API specification, version 1.0.2: errata and clarifications

The following errata and clarifications have been incorporated into the Specification. They are listed in the order in which they occur in the Specification.

- Section 3.4.7 "JMSRedelivered": Change first paragraph to clarify when a provider must set this header field.
- Section 3.5.9 "JMS defined properties": Correct return value of `ConnectionMetaData.getJMSXPropertyNames` method.
- Section 3.8.1.1 "Message selector syntax": After the first sentence, add sentence about the interpretation of a message selector whose value is an empty string. In the third sub-bullet item under "Identifiers," add `ESCAPE` to the list of prohibited identifiers. In the fourth sub-bullet item, add sentence about data types of property values, and move description of the value of nonexistent properties referenced in a selector from last bullet item to here. Add sub-bullet item clarifying that data type conversions do not apply to properties used in message selectors. In the first sub-bullet item under "Comparison Operators," clarify the result of comparing non-like type values. At end of section, correct quotation marks in example.
- Section 3.10 "Changing the value of a received message": Add paragraph clarifying the semantics of redelivering a message that was modified after being received.
- Section 3.12 "Provider implementations of JMS message interfaces": Insert paragraph clarifying the handling of destinations for foreign message implementations.
- Section 4.4.12 "Duplicate delivery of messages" (formerly misnumbered 4.4.14): Add sentence about `JMSRedelivered` message header field.
- Section 4.5.2 "Asynchronous delivery": Clarify explanation of redelivery for `AUTO_ACKNOWLEDGE` and `DUPS_OK_ACKNOWLEDGE` acknowledgment modes.
- Section 4.10 "Reliability": Clarify meaning of `PERSISTENT` and `NON_PERSISTENT` delivery modes throughout section.
- Section 6.9 "TopicSession": Clarify redelivery of messages for durable and nondurable subscriptions.

Rationale for this change: The scope of redelivery is the lifetime of a destination, not of the session that is consuming it. Each nondurable subscription is a different destination, and its lifetime is the session that creates it. Each temporary queue or topic is a different destination whose lifetime is the connection that creates it.

- Section 6.12 "Recovery and redelivery": Clarify recoverability of messages for nondurable subscriptions.

Rationale for this change: Update the Specification to meet the expectation that a nondurable subscriber performs the same as a

durable subscriber as long as the nondurable subscriber is in existence. The original statement in the specification could be interpreted to mean that message recovery was optional for a nondurable subscriber. It would be valuable to have a lower quality of service that did not require acknowledgement overhead, but a new mechanism should be provided to specify the lower quality of service option; the minimum quality of service required by the current specification should not be lowered.

- Section 7.3 "Standard exceptions": In description of `IllegalStateException`, change "should" to "must". In description of `MessageFormatException`, correct method names, and change "should" to "must" in last sentence.

B.3.2 JMS API Java API documentation, version 1.0.2a: major errata

The following items represent significant clarifications of the JMS API Java API documentation, version 1.0.2a. They are categorized as follows:

- Corrections of mistakes
- Reconciliations between the Specification and the Java API documentation

Less important clarifications to the Java API documentation are listed in Section B.3.3 "JMS API Java API documentation, version 1.0.2a: lesser errata".

B.3.2.1. Corrections of mistakes

In the following cases, the Java API documentation was in error and has been corrected:

- `BytesMessage` and `StreamMessage` interfaces: Correct discussion of modification of sent messages.
- `TemporaryQueue.delete` and `TemporaryTopic.delete` methods: Remove references to senders and publishers.

B.3.2.2. Reconciliations between the specification and the Java API documentation

The following items update the Java API documentation to match the correct language in the Specification:

- `Message` interface: Correct description of getting values for unset property names to match Section 3.5.4 "Property value conversion". Remove incorrect bullet items about `NULL` values in arithmetic operations and `BETWEEN` operations.
- `Message.acknowledge` method: Clarify that the method applies to all consumed messages of the session.

Rationale for this change: A possible misinterpretation of the existing Java API documentation for `Message.acknowledge` assumed that only messages received prior to "this" message should be acknowledged. The updated Java API documentation statement emphasizes that message acknowledgement is really a session-level activity and that this message is only being used to identify the session in order to acknowledge all messages consumed by the session. The `acknowledge` method was placed in the message object

only to enable easy access to acknowledgement capability within a message listener's `onMessage` method. This change aligns the specification and Java API documentation to define `Message.acknowledge` in the same manner.

- `Message.getJMSTimestamp` and `MessageProducer.setDisableMessageTimestamp` methods: Correct descriptions of effect of disabling timestamps.
- `TopicSession.createSubscriber` and `TopicSession.createDurableSubscriber` methods: Correct **Throws:** lists.

B.3.3 JMS API Java API documentation, version 1.0.2a: lesser errata

The Java API documentation corrections listed in this section concern the application of logic from the Specification or elsewhere in the Java API documentation:

- Corrections to the Specification listed in Section B.3.1 "JMS API specification, version 1.0.2: errata and clarifications".
 - Information in the Specification not previously reflected in the Java API documentation
 - Information provided in some parts of the Java API documentation, but not in others where it also belongs.
4. Message interface: Add the corrections to Section 3.8.1.1 "Message selector syntax" to the section on message selectors.

Also change the Java API documentation for the following methods to reflect these changes:

```
QueueConnection.createConnectionConsumer
QueueSession.createReceiver
QueueSession.createBrowser
TopicConnection.createConnectionConsumer
TopicConnection.createDurableConnectionConsumer
TopicSession.createSubscriber
TopicSession.createDurableSubscriber
QueueBrowser.getMessageSelector
MessageConsumer.getMessageSelector
```

5. Correct the Java API documentation for the following methods to add *InvalidDestinationException* to the **Throws:** list, in accordance with Section 7.3 "Standard exceptions":

```
QueueConnection.createConnectionConsumer
QueueRequestor.QueueRequestor
TopicConnection.createConnectionConsumer
TopicConnection.createDurableConnectionConsumer
TopicRequestor.TopicRequestor
```

6. `TopicSession.createDurableSubscriber` method: Change the description of the two-argument form to accord with the description of the one-argument form of the *TopicSession.createSubscriber* method.
7. `QueueSender` and `TopicPublisher` interfaces: Add clarifications from Section 3.9 "Access to sent messages" and Section 3.4.11 "How message header values are set". Add

UnsupportedOperationException to send and publish method
Throws: lists where relevant.

8. QueueReceiver interface: Add language from Section 5.8 "QueueReceiver".
9. IllegalStateException and MessageFormatException classes: Add corrections from Section 7.3 "Standard exceptions".

B.4. Version 1.1

This section describes the changes to the JMS specification for version 1.1. The changes include API unification of messaging domains, specification clarifications, and several additional methods.

B.4.1 Unification of messaging domains

This maintenance release addresses the unification of the programming interfaces for the point-to-point and pub/sub messaging domains in the Java Message Service (JMS) API. In the 1.0.2b version of the JMS specification, the client programming model made a strong distinction between these two domains. One consequence of domain separation is that actions from the point-to-point domain and the pub/sub domain could not be used in the same transaction.

In this version of the interfaces, methods have been added to support the ability to include PTP and pub/sub messaging in the same transaction. In addition, domain unification simplifies the client programming model, so that the client programmer can use a simplified set of APIs to create an application.

The scope of a transaction in JMS is on a per *Session* basis. To add the ability to work across both domains, a number of methods have been added to the `javax.jms.Session` interface. Adding these methods supports the creation of `javax.jms.MessageConsumer` and `javax.jms.MessageProducer` objects for either domain at the *Session* level, and supports sending and receiving message using either domain within the same *Session*.

For example, using these proposed methods, a JMS client can create a transacted session, and then receive messages from a queue and send messages to a topic within the same transaction. In JMS 1.0.2b, this was not possible.

At the same time, the semantic differences between the two domains are retained. While it is possible to support actions on PTP and pub/sub destinations within the same session, the semantic differences that cause different behaviors within those domains are retained.

B.4.2 JMS API specification, version 1.1: domain unification

The following is a list of changes that were added to the JMS specification to describe the requirements related to domain unification. They are listed in the order in which they appear in the specification.

- Section 1.2.3.3 "JMS domains" describes the backward compatibility relationship between earlier versions of the JMS specification and version 1.1 of the JMS specification.
- Section 2.4 "Two messaging styles" and Section 2.5 "JMS interfaces" add information about the two message domains, and a table that

describes the relationship between the JMS common interfaces and the domain-specific interfaces that are derived from the JMS common interfaces.

- Section 4.4 "Session" updates the list of the activities that can be performed in a `Session` to include that it is a factory for `MessageProducer` and `MessageConsumer` objects, and is a factory for `TemporaryTopic` and `TemporaryQueue` objects.
- Section 4.5 "MessageConsumer" adds that a `MessageConsumer` can be created from a `Session`.
- Section 4.11 "Method inheritance across messaging domains" is a new section that describes how to handle methods that are not appropriate to a specific messaging domain.
- Section 5.1 "Overview" adds a table that describes the relationship between the JMS common interfaces and the domain-specific interfaces that are derived from the JMS common interfaces.
- Section 5.4 "TemporaryQueue" adds that the lifespan of the `TemporaryQueue` is the life of the `Connection` or `QueueConnection` that creates it. Previously, only `QueueConnection` was mentioned, but `TemporaryQueues` can now be created from `Connections`.
- Section 5.9 "QueueBrowser" adds that a `QueueBrowser` can be created from `Session`, as well as from the `QueueSession`.
- Section 6.1 "Overview" adds a table that describes the relationship between the JMS common interfaces and the domain-specific interfaces that are derived from the JMS common interfaces.
- Section 6.6 "TemporaryTopic" adds that the lifespan of the `TemporaryTopic` is the life of the `Connection` or `TopicConnection` that creates it. Previously, only `TopicConnection` was mentioned, but a `TemporaryTopic` can now be created from a `Connection`.
- Section 6.10 "TopicPublisher" adds a comment that messages can be sent to a topic either using a `TopicPublisher` or a `MessageProducer`.
- Section 6.11.1 "Durable" adds that durable `TopicSubscribers` can be created either relative to a `TopicConnection` or a `Connection`. The `unsubscribe` method for the durable `Topic` subscription can also be used either at the `TopicConnection` or `Connection` level.
- Section 8.6 "JMS application server interfaces" adds a table that shows the relationships between the JMS common interfaces and the domain-specific interfaces that are derived from the JMS common interfaces.
- Chapter 9 "JMS example code" has been rewritten to reflect the use of the JMS common interfaces. It now uses the new methods associated with domain unification.

B.4.3 JMS API specification, version 1.1: updates and clarifications

The following are additional updates to the JMS specification. They include both updated material, and clarifications of existing material. They are listed in the order in which they appear in the specification.

B.4.3.1. Updates to introduction, added figures

These changes reflect new information about how the JMS API relates to other technologies, and what's new in this version of the specification. It also reflects the addition some diagrams to assist in the reading of the specification.

- Section 1.4 "Relationship to other Java APIs" is updated with the current status of the relationship of the JMS specification to the JDBC API, the EJB API, and the JTA API.
- Section 1.4 "Relationship to other Java APIs" has two new sections: Section 1.4.7 "Java Platform, Enterprise Edition (Java EE) " and section 1.4.8 "Integration of JMS with the EJB Components" [which has subsequently been deleted in JMS 2.0]. These new sections describe how JMS relates to the J2EE platform.
- Section 1.5 "What is new in JMS 1.1?" is a new section that summarizes the changes in this maintenance release.
- Section 2.3 "Administration" contains a new figure which illustrates the relationship between the Administered objects and other elements of the JMS system.
- Section 2.5 "JMS interfaces" adds a figure which illustrates the relationships among the basic JMS elements.

B.4.3.2. Clarifications

- Section 3.8.1.1 "Message selector syntax" clarifies when semantic checking may occur. At the end of that section, there is a requirement that JMS providers must check syntactic correctness at the time that a message selector is presented. This statement has been updated to note that JMS providers are also permitted to check semantic correctness at that time, although not all semantic correctness can be verified at that time.
- Section 4.3.8 "ExceptionListener" adds a clarification that if no `ExceptionListener` is registered, the `getExceptionListener` method should return `null`.
- Section 4.4.6 "Conventions for using a session" adds a clarification that use of the JTS aware interfaces described in Chapter 8 are not intended for use in the client JMS program. Use of these interfaces may create nonportable software, as the JTS aware interfaces described in Chapter 8 are optional.
- Section 4.4.9 "Multiple sessions" adds a further clarification that the JMS specification does not assign a semantic meaning to multiple `QueueReceivers` consuming from one `Queue`.
- Section 6.12 "Recovery and redelivery" adds an additional clarification that setting the delivery mode to `PERSISTENT` will not change the delivery model for messages sent to a non durable subscriber. This is already described in section 6.15 "Reliability".
- Section 8.1 "Overview" adds a clarification that JMS client program use of the JTS aware interfaces described in Chapter 8 may create non-portable code.

B.4.4 JMS API Java API documentation, version 1.1: domain unification

In order to support domain unification a number of existing interfaces were updated with additional methods. Table 11-1 lists the interfaces that were changed, and the new methods for those interfaces.

Table 11.2 New JMS API methods for domain unification

| Interface | New Methods |
|--------------------------|--|
| Connection | ConnectionConsumer createConnectionConsumer (Destination destination, String messageSelector, ServerSessionPool sessionPool, int maxMessages) throws JMSEException; |
| | ConnectionConsumer createDurableConnectionConsumer (Topic topic, String subscriptionName, String messageSelector, ServerSessionPool sessionPool, int maxMessages) throws JMSEException; |
| ConnectionFactory | Connection createConnection () throws JMSEException; |
| | Connection createConnection (String userName, String password) throws JMSEException; |
| MessageProducer | Destination getDestination () throws JMSEException; |
| | void send (Message message) throws JMSEException; |
| | void send (Message message, int deliveryMode, int priority, long timeToLive) throws JMSEException; |
| | void send (Destination destination, Message message) throws JMSEException; |
| Session | MessageProducer createProducer (Destination destination) throws JMSEException; |
| | MessageConsumer createConsumer (Destination destination) throws JMSEException; |
| | MessageConsumer createConsumer (Destination destination, java.lang.String messageSelector) throws JMSEException; |
| | MessageConsumer createConsumer (Destination destination, java.lang.String messageSelector, boolean NoLocal) throws JMSEException; |

| Interface | New Methods |
|----------------------------|--|
| | TopicSubscriber createDurableSubscriber (Topic topic, java.lang.String name) throws JMSEException; |
| Session | TopicSubscriber createDurableSubscriber (Topic topic, java.lang.String name, java.lang.String messageSelector, boolean noLocal) throws JMSEException; |
| | QueueBrowser createBrowser (Queue queue) throws JMSEException; |
| | QueueBrowser createBrowser (Queue queue, String messageSelector) throws JMSEException; |
| | Queue createQueue (String name) throws JMSEException; |
| | Topic createTopic (String name) throws JMSEException; |
| | TemporaryTopic createTemporaryTopic () throws JMSEException; |
| | TemporaryQueue createTemporaryQueue () throws JMSEException; |
| | void unsubscribe (String string name); |
| XAConnection | XASession createXASession () throws JMSEException; |
| XAConnectionFactory | XAConnection createXAConnection () throws JMSEException; |
| | XAConnection createXAConnection (String userName, String password) throws JMSEException; |
| XASession | Session getSession () throws JMSEException; |

In addition, explanatory material was added to describe the relationship between the new methods and existing interfaces and methods. The interfaces that have been changed to describe these relationships are:

Queue
QueueBrowser
QueueConnection
QueueConnectionFactory
QueueReceiver
QueueSender
QueueSession
Session
TemporaryQueue
TemporaryTopic
Topic
TopicConnection

TopicConnectionFactory
TopicPublisher
TopicSubscriber
TopicSession

B.4.5 JMS API documentation, version 1.1: changes

The Java API documentation also includes updates that reflect new features or additional clarifications.

B.4.5.1. New methods

1. BytesMessage.getBodyLength

`long getBodyLength()` throws `JMSEException`

This method permits the programmer to determine the size of the `BytesMessage` body and, if necessary, allocate a bytes array to copy the body.

2. Session.getAcknowledgeMode

`int getAcknowledgeMode()` throws `JMSEException`

This method returns the currently set value of how a `Session` acknowledges messages. This method is added for completeness, because in previous versions of the specification there was no way to get this value.

B.4.5.2. Clarifications

1. Connection.getExceptionListener

If `Connection.getExceptionListener` is called, and no `ExceptionListener` is registered, the JMS provider must return `null`. A client program may optionally associate an `ExceptionListener` with a `Connection`. If no `ExceptionListener` is associated with the `ConnectionListener`, `null` should be returned. Previously, the Java API documentation did not specify what the return value should be.

2. MapMessage

A clarification to the set methods of `MapMessage`, stating if the name parameter is `null` or an empty string, the method must throw the error `InvalidArgumentException`.

The rationale is that each of the named elements in the `MapMessage` should have names that are not `null` or blank.

Methods affected:

`MapMessage.setBoolean`
`MapMessage.setByte`
`MapMessage.setBytes`
`MapMessage.setChar`
`MapMessage.setDouble`
`MapMessage.setFloat`
`MapMessage.setInt`
`MapMessage.setLong`
`MapMessage.setObject`
`MapMessage.setShort`

MapMessage.setString

3. Message

A clarification to the set property methods of Message states if the property name parameter is null or empty string, the method must throw the error `IllegalArgumentException`.

The rationale is that each of the properties in the Message should have names that are not null or blank.

Methods affected:

```
Message.setBooleanProperty
Message.setByteProperty
Message.setDoubleProperty
Message.setFloatProperty
Message.setIntProperty
Message.setLongProperty
Message.setObjectProperty
Message.setShortProperty
Message.setStringProperty
```

4. TextMessage

A comment in the description for TextMessage that indicated that XML might become popular has been changed to state that TextMessage can be used to send XML messages.

5. XA interfaces

The descriptions of the XA interfaces now state that those interfaces are primarily used by JMS providers, and are optional; that is, the JMS provider is not required to support them. Use of the XA interfaces by a client program may lead to non-portable code.

Interfaces affected:

```
XAConnection
XAConnectionFactory
XAQueueConnection
XAQueueConnectionFactory
XAQueueSession
XASession
XATopicConnection
XATopicConnectionFactory
XATopicSession
```

6. The descriptions of QueueSession, TopicSession, and QueueConnection now list methods that must not be called through these interfaces. These methods are a result of inheritance, but are not appropriate to be called from domain-specific interfaces. These are also described in Section 4.11 "Method inheritance across messaging domains". If they are invoked, an `IllegalStateException` must be thrown.

Table 11.3 Domain dependent interfaces

| Interface | Method |
|-----------------|---------------------------------|
| QueueConnection | createDurableConnectionConsumer |
| QueueSession | createDurableSubscriber |

| Interface | Method |
|--------------|-----------------------------------|
| | <code>createTemporaryTopic</code> |
| | <code>createTopic</code> |
| | <code>unsubscribe</code> |
| TopicSession | <code>createQueueBrowser</code> |
| | <code>createQueue</code> |
| | <code>createTemporaryQueue</code> |

B.5. Version 2.0

All changes made for JMS 2.0 are represented by individual issues in the JMS specification issue tracker at http://java.net/jira/browse/JMS_SPEC. The appropriate issue number (e.g. JMS_SPEC-64) is given for each change below.

B.5.1 Re-ordering of chapters

Chapter 10 "Issues" and chapter 11 "Change history" have become appendices A and B and moved to the end of the specification.

New chapters 10 "Use of JMS API in Java EE applications" and 11 "Simplified JMS API" have been added.

B.5.2 JMS providers must implement both P2P and Pub-Sub (JMS_SPEC-50)

The specification has been amended to state that a JMS provider must implement both point-to-point messaging (queues) and publish-subscribe messaging (topics). This was already required by the Java EE 6 specification, section EE.2.7, but was not previously required by the JMS specification itself.

Section 1.3 "What is required by JMS" has therefore been updated to delete the sentence that states "Providers of JMS point-to-point functionality are not required to provide publish/subscribe functionality and vice versa".

B.5.3 Use of JMS API in Java EE applications (JMS_SPEC-45 and JMS_SPEC-27)

A new chapter 10 "Use of JMS API in Java EE applications" has been added. This chapter incorporates and clarifies various additional requirements which were previously only described in the Java EE and EJB specifications. Section 10.2 "Restrictions on the use of JMS API in the Java EE web or EJB container" includes a list of methods which may not be used in a Java EE web or EJB container and section 10.3 "Behaviour of JMS sessions in the Java EE web or EJB container" clarifies how the arguments to `createSession` are mostly ignored when used in a Java EE web or EJB container.

Section 1.4.7 "Java Platform, Enterprise Edition (Java EE)" has been updated to refer to Java EE 7 rather than J2EE 1.3. A reference has also been added to the new chapter 10 "Use of JMS API in Java EE applications".

Section 1.4.8 "Integration of JMS with the EJB components" has been deleted. It is superseded by the new chapter 10 "Use of JMS API in Java EE applications".

B.5.4 New methods to create a session (JMS_SPEC-45)

The Connection method `createSession(boolean transacted, int acknowledgeMode)` has sometimes been a cause of confusion because if the `transacted` argument is set to `true` then the `acknowledgeMode` argument is ignored but must still be given a value.

To simplify application code a new Connection method `createSession(int sessionMode)` has been added which provides the same functionality as the previous method but with a single argument.

Examples 9.1.4 "Creating a Session" and 9.3.3.1 "Creating a durable subscription" have been updated to use this new method.

In addition, a second new Connection method `createSession()` has been added. This has no arguments and is intended for use in a Java EE web or EJB container in the case when there is an active JTA transaction, when the `sessionMode` supplied to `createSession(int sessionMode)` is ignored.

B.5.5 Multiple consumers now allowed on the same topic subscription (JMS_SPEC-40)

In JMS 1.1, a durable or non-durable topic subscription was not permitted to have more than one consumer at a time. This meant that the work of processing messages on a subscription could not be shared amongst multiple threads, connections or JVMs, thereby limiting scalability. This restriction has therefore been removed in JMS 2.0.

For durable subscriptions, no changes have been made to the JMS API other than removing this restriction from the `createDurableSubscriber` methods on `Session` and the new `createDurableConsumer` methods on `Session` and `JMSContext`. Section 6.11.3 "Durable subscriptions" has been updated accordingly.

For non-durable subscriptions, a new distinction is introduced between an unshared and a shared non-durable subscription.

The existing `createConsumer` and `createSubscriber` methods on `Session` and the `createConsumer` methods on `JMSContext` remain unchanged and are used to create what is now called an unshared non-durable subscription. A new section 6.11.1 "Unshared non-durable subscriptions" has been added.

New `createSharedConsumer` methods have been added on `Session` and `JMSContext`. These create a shared non-durable subscription and allow a name to be specified to identify the subscription. A new section 6.11.2 "Shared non-durable subscriptions" has been added.

B.5.6 Delivery delay (JMS_SPEC-44)

A new feature "delivery delay" has been added which allows a producing client to specify the earliest time when a provider may make the message visible on the target destination and available for delivery to consumers.

A new section 4.13 "Delivery delay" and a corresponding new section 3.4.13 "JMSDeliveryTime" have been added to describe this new feature. Section 4.4.10.2 "Order of message sends" has been updated to state that messages with a later delivery time may be delivered after messages with an earlier delivery time.

Section 4.4.11 "Message acknowledgment" has been updated to state that when a session's `recover` method is called the messages it now delivers may be different from those that were originally delivered due to the delivery of messages which could not previously be delivered as they had not reached their specified delivery time.

Section 4.6 "MessageProducer" has been updated to mention that a client may now define a default delivery delay for messages sent by a producer.

B.5.7 Sending messages asynchronously (JMS_SPEC-43)

New `send` methods have been added to `MessageProducer` which allow messages to be sent asynchronously. These methods return immediately and perform the send in a separate thread without blocking the calling thread. When the send is complete, a callback method is invoked on an object supplied by the caller. Similar methods are available on the new `JMSContext` interface.

Section 4.6 "MessageProducer" has been extended to describe these additional `send` methods..

B.5.8 Use of `AutoCloseable` (JMS_SPEC-53)

The `Connection`, `Session`, `MessageProducer`, `MessageConsumer` and `QueueBrowser` interfaces have been modified to extend the `java.lang.AutoCloseable` interface. This means that applications can create these objects using a Java SE 7 try-with-resources statement which removes the need for applications to explicitly call `close()` when these objects are no longer required.

The new `JMSContext` and `JMSConsumer` interfaces also extend the `java.lang.AutoCloseable` interface.

Sections 4.3.5 "Closing a Connection" and 4.4.1 "Closing a Session" and the new section 11.2.6 "Closing the `JMSContext`" all explain that the use of a try-with-resources statement makes it easier to ensure that these objects are closed after use.

The example in section 9.1.3 "Creating a Connection" has been extended to add a second example which uses the try-with-resources statement.

B.5.9 `JMSXDeliveryCount` (JMS_SPEC-42)

The existing message property `JMSXDeliveryCount` has been made mandatory. It was previously optional. This means that JMS providers must set this property when a message is delivered to the number of times the message has been delivered.

A new section 3.5.11 "`JMSXDeliveryCount`" has been added which describes this property and explains how it is not required to be guaranteed in all possible cases, such as after a server failure.

Section 3.5.9 "JMS defined properties" has been updated accordingly. Some of the wording in this section has been rearranged to reflect the fact that some properties are optional but that one (`JMSXDeliveryCount`) is now mandatory. A clarification has been added to state that the effect of setting a message selector on a property (such as `JMSXDeliveryCount`) which is set by the provider on receive is undefined.

Section 3.4.7 "JMSRedelivered" has been amended to mention the `JMSXDeliveryCount` property as well.

Section 4.4.11 "Message acknowledgment": A sentence which mentions the `JMSRedelivered` flag has been amended to mention the `JMSXDeliveryCount` property as well.

4.4.12 "Duplicate delivery of messages": A sentence which mentions the `JMSRedelivered` flag has been amended to mention the `JMSXDeliveryCount` property as well..

4.5.2 "Asynchronous delivery": A sentence which mentions the `JMSRedelivered` flag has been amended to mention the `JMSXDeliveryCount` property as well.

4.10 "Reliability": A sentence which mentions the `JMSRedelivered` flag has been amended to mention the `JMSXDeliveryCount` property as well.

B.5.10 Client ID optional on Durable subscriptions (JMS_SPEC-39)

It is no longer mandatory for the client identifier to be set when creating or activating a durable subscription.

The javadocs for the various methods which create a durable subscription have updated to reflect this change and rewritten to improve clarify.

In addition the following sections have been updated:

Section 4.3.2 "Client identifier" has been changed to state that its use in identifying a durable subscription is optional.

Section 6.3 "Durable subscription" has been amended by adding a cross-reference to Section 6.11.1 "Durable " at the end.

Section 6.11.1 "Durable subscriptions" has been completely rewritten. This section was essentially a copy of the javadoc comment on the `createDurableSubscriber` methods and since those javadoc comments have been rewritten to make them clearer this section has been rewritten as well. The only substantive change is to state that the use of client identifier in identifying a durable subscription is optional. Cross-references to Section 6.3 "Durable subscription" and Section 4.3.2 "Client identifier" have been added at the end.

B.5.11 New createDurableConsumer methods (JMS_SPEC-51)

The Session interface has been extended to add two `createDurableConsumer` methods which return a `MessageConsumer`.

These are intended to replace the existing `createDurableSubscription` methods which return a `TopicSubscriber`. A `TopicSubscriber` is a domain-specific interface whose use has been discouraged since the domain-independent interfaces were introduced in JMS 1.1.

Section 6.11.1 "Durable " has been updated to reflect this.

B.5.12 Simplified API (JMS_SPEC-64)

Three new objects `JMSContext`, `JMSProducer` and `JMSConsumer` have been added which together combine the functionality of the existing `Connection`, `Session`, `MessageProducer` and `MessageConsumer` objects. This provides an alternative API for using JMS which is referred to in this specification as the "simplified API".

JMSContext objects may be created using new methods on ConnectionFactory. Java EE applications may alternatively create JMSContext objects using injection.

The goals of the simplified API are described in 11.1 "Goals of the simplified API" and a summary of the API is given in section 11.2 "Key features of the simplified API".

Developers now have a choice as to whether to use the "standard API" (the Connection, Session, MessageProducer and MessageConsumer objects) or the "simplified API" (the JMSContext, JMSProducer and JMSConsumer objects).

The two APIs are intended to offer identical functionality. The standard API is not deprecated and will remain part of JMS indefinitely.

Section 11.4 "Examples using the simplified API" contains a number of examples which compare the use of the simplified and standard APIs in a number of simple Java EE and Java SE use cases.

B.5.13 Clarification: message may be sent using any session (JMS_SPEC-52)

The specification and javadocs have been clarified to make it clear that a message may be sent using any session, not just the session used to create the message.

Section 4.4.5 "Optimized message implementations" has been updated accordingly.

B.5.14 Clarification: use of ExceptionListener (JMS_SPEC-49)

Section 4.3.8 "ExceptionListener" has been amended to clarify how an ExceptionListener is used:

- The existing text which states that a connection "serializes execution of its ExceptionListener" has been extended to explain what this means.
- A note has been added to state that there are no restrictions on the use of the JMS API by the listener's onException method.

In addition, the following changes to javadoc comments have been made:

- The javadoc comments for the stop and close methods on the Connection interface have been amended to clarify that, if an exception listener for the connection is running when stop or close are invoked, there is no requirement for the stop or close call to wait until the exception listener has returned before it may return.
- Similarly, the javadoc comment for the close method on the Session interface has been amended to clarify that, if an exception listener for the session's connection is running when close is invoked, there is no requirement for the close call to wait until the exception listener has returned before it may return.
- The javadoc comments for the stop and close methods on the JMSContext interface have been amended to clarify that, if an exception listener for the JMSContext's connection is running when stop or close are invoked, there is no requirement for the stop or

`close` call to wait until the exception listener has returned before it may return.

B.5.15 Clarification: use of `stop` or `close` from a message listener (JMS_SPEC-48)

The specification has been clarified to state that a message listener must not call its own connection's `stop` or `close` methods, or its own session's `stop` method. This is because the specification requires that these methods should not return until any message listeners have returned and so calling them from a message listener would lead to deadlock.

A new requirement has been added that the JMS provider throw a `javax.jms.IllegalStateException` in such cases.

The following sections have been updated accordingly:

- Section 4.3.4 "Pausing delivery of incoming messages"
- Section 4.3.5 "Closing a Connection"
- Section 4.4.1 "Closing a Session"

The following javadoc comments have been updated accordingly:

- The `Connection` method `stop`
- The `Connection` method `close`
- The `Session` method `close`
- The `JMSContext` method `stop`
- The `JMSContext` method `close`

B.5.16 Clarification: use of `noLocal` when creating a durable subscription (JMS_SPEC-65)

The specification has been amended to clarify the effect of setting the `noLocal` argument when creating a durable subscription. This was poorly defined in JMS 1.1.

In addition, the definition of `noLocal` has been extended to cover the case added in JMS 2.0 and described in section B.5.5 where a durable subscription has more than one active consumer

The new definition of `noLocal` is given in section 6.11.3 "Durable subscriptions". This states that when a durable subscription is created on a topic, the `noLocal` argument may be used to specify that messages published to the topic by its own connection or any other with the same client identifier will not be added to the durable subscription. It also states that if the client identifier is unset then setting `noLocal` to true, or changing it subsequently, has no effect.

B.5.17 Clarification: message headers that are intended to be set by the JMS provider (JMS_SPEC-34)

The specification has been clarified to state that the following methods on `Message` are not for use by client applications and setting them does not have any effect:

`setJMSDeliveryMode`, `setJMSExpiration`, `setJMSPriority`,
`setJMSMessageID`, `setJMSTimestamp`, `setJMSRedelivered`,
`setJMSDeliveryTime` (new header property: see section B.5.6).

Section 3.4.11 "How message header values are set" has been extended to explain this.

B.5.18 Clarification: Session methods `createQueue` and `createTopic` (JMS_SPEC-31)

The javadoc comments for the `createQueue` and `createTopic` methods on `Session` and `JMSContext` have been reworded to clarify that these methods simply create a `Queue` or `Topic` object which encapsulates the name of the queue or topic and do not create the physical queue or topic in the JMS provider.

In addition a note has been added to these javadoc comments to explain that although creating a physical queue or topic is provider-specific and is typically an administrative task performed by an administrator, some providers may create them automatically when needed.

B.5.19 Correction: Reconnecting to a durable subscription (JMS_SPEC-80)

In the JMS 1.1 specification, section 9.3.3.2 "Reconnect to a topic using a durable subscription" stated that "the client must be attached to the same Connection". This was incorrect and has now been corrected to state that the client must use a connection with the same client identifier.

In addition this section has been renamed 9.3.3.2 "Creating a consumer on an existing durable subscription" and rewritten to make it clearer.

B.5.20 Correction: `MapMessage` when name is null (JMS_SPEC-77)

In the JMS 1.1 API documentation for `javax.jms.MapMessage`, the method `setBytes(String name, byte[] value)` is defined as throwing a `NullPointerException` "if the name is null, or if the name is an empty string."

However there are eleven other methods on `MapMessage` of the form `setSomething(name, value)`. These all specify that a `IllegalArgumentException` is thrown "if the name is null or if the name is an empty string."

This appears to be an error in the API documentation. This is confirmed by the JMS compliance tests which already expect `setBytes` to throw a `IllegalArgumentException`.

The API documentation for `setBytes` has therefore been changed to match the other methods and specify that an `IllegalArgumentException` should be thrown in this case.