

Tuning false positives

Last Updated: 2025-06-11

You can tune false positive events and flows to prevent them from creating offenses.

Before you begin [↗](#)

To create a new rule, you must have the **Offenses > Maintain Custom Rules** permission for creating customized rules to tune false positives. For more information about roles and permissions, see the *IBM QRadar User Guide*.

Procedure [↗](#)

1. Click the **Log Activity** tab, or the **Network Activity** tab.
2. Select the event or flow that you want to tune.
3. Click **False Positive**.

Note: If you are viewing events or flows in streaming mode, you must pause streaming before you click **False Positive**.

4. Select one of the following **Event** or **Flow Property** options:
 - Event/Flow(s) with a specific QID of *<Event>*
 - Any Event/Flow(s) with a low-level category of *<Event>*
 - Any Event/Flow(s) with a high-level category of *<Event>*
5. Select one of the following **Traffic Direction** options:
 - *<Source IP Address>* to *<Destination IP Address>*
 - *<Source IP Address>* to Any Destination
 - Any Source to *<Destination IP Address>*
 - Any Source to any Destination
6. Click **Tune**.

QRadar prevents you from selecting **Any Events/Flow(s)** and **Any Source To Any Destination**. This change creates a custom rule and prevents QRadar from creating offenses.

For more information about tuning false positives, see the *IBM QRadar User Guide*.

Parent topic:

→ [Guidelines for tuning system performance](#)

