

Quotation/Proforma Invoice



To:
張景繁
百容電子股份有限公司
台中市40850工業區25路20號

Taiwan
TEL:04-23598668#1325
FAX:04-23593893

Date: 2017/9/13

NEOUSYS TECHNOLOGY INC
15F., No.868-3, Zhongzheng Rd.
Zhonghe Dist., New Taipei City 23586
TAIWAN, R.O.C
TEL: +886-2-22236182
FAX: +886-2-22236183

Customer PO No. :
Carrier/Forwarder : 新竹貨運
Expected Delivery Date : 2017/8/23
Estimated Delivery Date :

Order No.: OID201709131109_百容電子股份有限公司
OID201709131106_百容電子股份有限公司

CID: 12714 **Currency :** **NTD**

No.	Model Name	Description	Delivery	Price	Q'TY	Amount
1.1	Nuvo-6032	6th-Gen Intel® Core™ i7/i5/i3 Fanless Controller with 5x Expansion Slots, -25 °C to 60 °C fanless operation, One PCIe x16, one PCIe x8, 3x PCI slots, 2x GbE ports by Intel I210/I219 GbE controller, 3x SATA port for 2.5" HDD/SSD, 4x USB 3.0, 2x software programmable COM ports, 2x 3-wire RS-232 ports, 2x DVI-D video outputs. W/O power adapter and power cord are not included.		32000	4	128000
1.2	DDR4-8GB	8GB DDR4 Memory, 0 - 85 °C Operating Temperature			4	
1.3	i5-6500	Intel® Core™ i5-6500 Processor (6M Cache, up to 3.60 GHz), TDP:65W			4	
1.4	SSDMLC128G	2.5" 128GB MLC SSD, Operating temperature : 0 to 70 °C			4	
1.5	win 10 IoT-V-64	Operating system, Windows 10 IoT Enterprise LTSC Value, for system with Core i3/i5/Core M/Pentium/Celeron CPU 64bit OS, installation included			4	
1.6	PA-160W-OW	160W AC/DC power adapter 20V/8A;18AWGx4C/120cm, Cord end terminals for terminal block.			4	
1.7	Power cord	Power Cord for Taiwan			4	
1.8	cable-DVI-D-VGA	Cable, DVI-D to VGA, 10CM, for Nuvo-6000 series			4	
1.9	Opt SFAN-4000	Optional smart Fan for Nuvo-4000. The fan will turn on when the temperature in Cassette is > 55 °C and turn off < 45 °C.			4	
1.1	Nuvo-6032	6th-Gen Intel® Core™ i7/i5/i3 Fanless Controller with 5x Expansion Slots, -25 °C to 60 °C fanless operation, One PCIe x16, one PCIe x8, 3x PCI slots, 2x GbE ports by Intel I210/I219 GbE controller, 3x SATA port for 2.5" HDD/SSD, 4x USB 3.0, 2x software programmable COM ports, 2x 3-wire RS-232 ports, 2x DVI-D video outputs. W/O power adapter and power cord are not included.		31000	8	248000
1.2	DDR4-8GB	8GB DDR4 Memory, 0 - 85 °C Operating Temperature			8	
1.3	i5-6500	Intel® Core™ i5-6500 Processor (6M Cache, up to 3.60 GHz), TDP:65W			8	
1.4	SSDMLC128G	2.5" 128GB MLC SSD, Operating temperature : 0 to 70 °C			8	
1.5	win 10 IoT-V-64	Operating system, Windows 10 IoT Enterprise LTSC Value, for system with Core i3/i5/Core M/Pentium/Celeron CPU 64bit OS, installation included			8	
1.6	PA-160W-OW	160W AC/DC power adapter 20V/8A;18AWGx4C/120cm, Cord end terminals for terminal block.			8	
1.7	Power cord	Power Cord for Taiwan			8	
1.8	cable-DVI-D-VGA	Cable, DVI-D to VGA, 10CM, for Nuvo-6000 series			8	

1.9	Opt SFAN-4000	Optional smart Fan for Nuvo-4000. The fan will turn on when the temperature in Cassette is > 55 °C and turn off < 45 ° C.	8	
	5% VAT	Value Added Tax, 5%.		18800
		TOTAL		394800

Remark:

1. Payment Term : 現金交易

2. Warranty : 二年

3. Quotation Validity : 90 days

4. Bank information:

玉山銀行(808) 佳里分行

戶名: 宸曜科技股份有限公司

帳號: 0428-940-007592

Account Manager

Jack Liu

Neosys Technology Inc.