

---

## Table of Contents

MyMainScript2 .....	1
Value of M .....	1
Error between original and calculated image .....	2

## MyMainScript2

```
%This correspond to p1 - 3xn
img1 = importdata(' ../data/Features2D_dataset2.mat');
p1 = img1(1:2, :);

%This correspond to p - 4xn
img2 = importdata(' ../data/Features3D_dataset2.mat');
p = img2(1:3, :);

n = size(img1, 2);

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%Adding noise;this may be commented
%maxc = 0.05 * max(max(abs(img2)));
%p1 = p1 + (maxc .* randn([n 2]));
%p = p + (maxc .* randn([n 3]));
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

a = [p, ones(n, 1), zeros(n, 4)];
q = -1 * p .* (p1(:, 1)*ones(1,3)) ;
a = [a q (-1 * p1(:, 1))];

b = [zeros(n, 4), p, ones(n, 1)];
r = -1 * p .* ( p1(:, 2)*ones(1,3)) ;
b = [b r (-1 * p1(:, 2))];

A = [ a; b];

[U, D, V] = svd(A);

% Taking the last row of matrix V so
% that we have row of V corresponding
% to min eigen value
m = V(:, 12)';
M = reshape(m, 4, 3)';

plval = M * img2;
plval = plval ./ (ones(3,1)*plval(3,:));
```

## Value of M

M

---

$M =$

-0.0087	-0.0011	0.0039	-0.9986
-0.0001	-0.0092	-0.0005	0.0520
-0.0000	-0.0000	-0.0000	-0.0027

## Error between original and calculated image

```
error = norm(plval - img1)/sqrt(norm(plval) * norm(img1)) * 100;  
% value of error (in percentage)  
error
```

$error =$

0.1512

*Published with MATLAB® R2013a*