

---

## Table of Contents

MyMainScript1 .....	1
Value of M .....	1
Error between original and calculated image .....	2

## MyMainScript1

```
%This correspond to p1 - 3xn
img1 = importdata(' ../data/Features2D_dataset1.mat');
p1 = img1(1:2, :);

%This correspond to p - 4xn
img2 = importdata(' ../data/Features3D_dataset1.mat');
p = img2(1:3, :);

n = size(img1, 2);

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%Adding noise;this may be commented
%maxc = 0.05 * max(max(abs(img2)));
%p1 = p1 + (maxc .* randn([n 2]));
%p = p + (maxc .* randn([n 3]));
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

a = [p, ones(n, 1), zeros(n, 4)];
q = -1 * p .* (p1(:, 1)*ones(1,3)) ;
a = [a q (-1 * p1(:, 1))];

b = [zeros(n, 4), p, ones(n, 1)];
r = -1 * p .* ( p1(:, 2)*ones(1,3)) ;
b = [b r (-1 * p1(:, 2))];

A = [ a; b];

[U, D, V] = svd(A);

% Taking the last row of matrix V so
% that we have row of V corresponding
% to min eigen value
m = V(:, 12)';
M = reshape(m, 4, 3)';

plval = M * img2;
plval = plval ./ (ones(3,1)*plval(3,:));
```

## Value of M

M

---

$M =$

0.2905	0.0532	-0.1866	-0.6283
-0.0881	0.3264	-0.0881	-0.6010
0.0002	0.0002	0.0002	-0.0021

## Error between original and calculated image

```
error = norm(plval - img1)/sqrt(norm(plval) * norm(img1)) * 100;  
% value of e (in percentage)  
error
```

$error =$

$5.1422e-12$

*Published with MATLAB® R2013a*