

Scrutinizer: A Biologically-Grounded Foveated Vision Simulator for Web Interfaces

Andy Edmonds

Independent Researcher, San Francisco, CA

andyed@alum.cmu.edu

Abstract. Gaze-contingent tools used in HCI research—BubbleView, ViewSer, ScreenMasker—simulate peripheral vision with Gaussian blur, uniformly destroying the spatial structure that real peripheral vision preserves. They also operate on static images, not live interactive content. We present Scrutinizer, an open-source foveated rendering system that applies biologically-grounded peripheral filtering to live web pages at 60 fps. A ~ 1200 -line GLSL shader implements a pipeline mapped to the visual pathway (retinal ganglion cells $\rightarrow$ LGN $\rightarrow$ V1 $\rightarrow$ V4), using Difference-of-Gaussians band decomposition on the hardware MIP chain for frequency-selective attenuation—high-frequency detail falls off first while low-frequency structure persists, approximating cortical magnification [Rovamo and Virsu, 1979]. V4 color processing now models differential chromatic decay: per-channel attenuation of RG and YV opponent signals using castleCSF contrast sensitivity functions [Ashraf and Mantiuk, 2024], with suprathreshold correction [Jiang et al., 2022]. A Feature Congestion scoring pipeline [Rosenholtz et al., 2007] measures local visual clutter and gates peripheral pooling strength. The modular architecture maps each JavaScript module to a biological subsystem, enabling researchers to swap components independently (e.g., mouse gaze proxy $\rightarrow$ eye tracker) and compare peripheral filtering strategies side-by-side—including a MIP-level adaptation of FOVI’s cortical magnification curve [Blauch et al., 2026] as a switchable mode. Open source (MIT), >120 unit tests.

1 Introduction

Peripheral vision is not blurry—it is *differently encoded*. The retina compresses $\sim 10^7$ photoreceptor signals into $\sim 10^6$ optic nerve fibers [Curcio et al., 1990], with ganglion cell receptive fields growing with eccentricity [Dacey, 1993]—effectively preserving low-frequency structure while filtering high-frequency detail. This is compute demand management: limited bandwidth allocated to information most likely to guide the next saccade.

Existing gaze-contingent tools—BubbleView [Kim et al., 2017], ViewSer [Lagun and Agichtein, 2011], ScreenMasker [Orlov and Bednarik, 2016]—apply Gaussian blur as a peripheral proxy, uniformly destroying spatial structure and preventing layout-level judgments that real peripheral vision supports. These tools also operate on static images, not live interactive content (Table 1).¹

¹An earlier Scrutinizer prototype [Edmonds, 2007] demonstrated mouse-contingent Gaussian blur on live web pages using Adobe AIR (2007), establishing real-time fidelity as the key technical challenge. Modern GPU APIs now make biologically-grounded filtering practical at 60 fps—but the gold standard remains out of reach. Rosenholtz et al. [2012]’s texture-synthesis “mongrels” are the most perceptually

Scrutinizer contributes (1) a DoG band decomposition exploiting the GPU MIP chain for frequency-selective peripheral filtering at near-zero cost (5 `textureLod` calls), (2) a DOM structure extractor that harvests web accessibility annotations (ARIA roles, semantic HTML, computed styles) as top-down priors for the saliency pipeline—a computational analog of attentional modulation, without requiring a vision model, (3) a modular architecture (Table 2) with five branch points where researchers swap implementations without modifying the core shader, and (4) a side-by-side comparison with a MIP-level adaptation of FOVI’s cortical magnification curve [Blauch et al., 2026]: Scrutinizer’s effective cutoff falls $3.5\text{--}4.6\times$ lower at matched eccentricities, illustrating the combined effect of crowding, saliency gating, and color processing that FOVI delegates to downstream neural networks.

These contributions serve three use cases. (a) **Vision research:** the branch-point architecture and parameter-controlled shader make Scrutinizer a platform for perceptual experiments—e.g., comparing frequency-selective filtering against Gaussian blur on reading speed and visual search (Section 4). (b) **HCI and usability:** instrumented browsers have logged mouse and navigation events for usability research since Uzilla [Edmonds, 2003]; ViewSer [Lagun and Agichtein, 2011] added restricted foveal viewing to study SERP examination at scale. Scrutinizer extends this lineage—the same cursor stream that drives interaction logging now also drives a biologically-grounded peripheral model on live content, letting researchers observe what users see, not just where they click. (c) **Design evaluation:** Queen [2006] showed that icons with distinct low-spatial-frequency silhouettes are identified ~ 0.5 s faster—but this analysis requires spatial-frequency filtering that most designers lack access to. Scrutinizer provides it live: designers see which icons, buttons, and headings survive peripheral vision and which collapse into indistinguishable blobs, stress-testing information hierarchy before deployment.

Limitations. The current gaze input is mouse cursor position—a reasonable proxy when the user’s eyes track the cursor, but unable to capture saccades, reading fixations, or

accurate peripheral model, and Walton et al. [2021] showed they outperform blur for foveated rendering, yet synthesizing them requires iterative optimization ($\sim$ seconds per frame) that no current GPU pipeline can deliver in real time. Scrutinizer’s DoG bands are a pragmatic middle ground: frequency-selective attenuation preserves more peripheral structure than blur, at a fraction of the cost of full texture statistics.

Table 1: Comparison with existing gaze-contingent tools.

Tool	Live	Bio Model	Crowding	Saliency	Open
BubbleView [2017]	—	Gauss.	—	—	✓
ViewSer [2011]	SERP	Gauss.	—	—	—
ScreenMasker [2016]	—	Gauss.	—	—	✓
FOVI [2026]	✓	CMF	—	—	✓
Scrutinizer	✓	DoG	✓	✓	✓

Table 2: Pipeline stages mapped to biological subsystems.

Biology	Computation
Oculomotor	Velocity, fixation, saccadic suppression
Retinal ganglion cells	DoG center-surround via MIP chain
LGN gating	Structure mask + saliency gate
V1 features	Noise crowding, grid scramble
V4 color	Per-channel chromatic pooling (castleCSF); Oklab eigengrau/Purkinje fallback; lateral chromatic offset
Clutter	Feature Congestion + edge density scoring
Saliency map	Oklab DoG + face detection + DOM structure

gaze-cursor dissociation. Eccentricity is computed in pixel units; without per-user viewing distance and display DPI calibration, the mapping to degrees of visual angle is approximate. Perceptual validation against human peripheral discrimination thresholds is future work.

2 Architecture: Biology → Computation

The pipeline is a single-pass fragment shader (~1200 LOC, GLSL ES 3.0) with 47 uniforms organized into biological stages, fed by four JavaScript modules (Table 2).

2.1 DoG Band Decomposition

Retinal ganglion cells have center-surround receptive fields modeled as DoG filters [Kuffler, 1953], with field size growing with eccentricity (M-scaling). We decompose the hardware MIP chain into an *approximate* Laplacian pyramid—hardware mipmaps use box/bilinear filtering rather than Gaussian convolution [Burt and Adelson, 1983], so band differences are Difference-of-Boxes rather than true DoG, with some spectral leakage between bands:

$$\text{band}_k = \text{textureLod}(\text{tex}, uv, k) - \text{textureLod}(\text{tex}, uv, k+1) \quad (1)$$

Four bands span 1–2 px (serifs) to 8–16 px (buttons), each weighted by a smoothstep rolloff with cutoffs following a geometric progression (0.3, 0.6, 1.2, $2.4 \times E_2$), approximating cortical magnification [Rovamo and Virsu, 1979]. The DC residual (overall brightness and color at the coarsest MIP level) always passes through—even far-peripheral vision preserves mean luminance. Result: peripheral text shows letter shapes (low-frequency visible, identity unreadable) rather than uniform fog. Cost: 5 `textureLod` calls vs. 1, but near-zero practical overhead—higher MIP levels are cheaper, already cached, and arithmetic is trivial.

2.2 Saliency-Driven Bandwidth Allocation

The LGN gates what reaches cortex: its synaptic inputs are predominantly modulatory, with a substantial fraction from V1 feedback [Sherman and Guillery, 2002]. McAlonan et al.

[2008] showed that spatial attention enhances LGN gain at attended locations—meaning the thalamus selectively boosts peripheral signals that match attentional priorities before they reach V1. We model this as saliency gating via a dedicated Web Worker that fuses three channels into a single GPU texture:

Bottom-up: Oklab opponent-channel DoG (color saliency) and face detection via `face-api.js` [Huber, 2018] (TinyFaceDetector, 190 KB).

Top-down: A DOM structure extractor walks the live page’s element tree, rendering bounding boxes of text runs (with computed font weight as density), media elements, and interactive controls—including ARIA roles (`role="button"`, `role="dialog"`, etc.)—into an RGBA mask. Two decades of web accessibility standards have produced a machine-readable semantic layer on most production websites; the Oklab eigengrau/Purkinje fallback; lateral chromatic offset, extractor harvests this existing annotation as a free source of top-down priors. This provides what bottom-up saliency cannot: *knowledge that a control is interactive*—a computational analog of the top-down attentional priors that modulate early visual processing. Because it reads the DOM directly, the extractor works on any web page without training data or a vision model.

High-saliency regions receive up to 70% of rendering bandwidth. To keep the pipeline at 60 fps, the shader renders every frame but expensive analyses run asynchronously at lower rates: the saliency worker (face detection + color DoG) computes every 15th frame (~250 ms); the DOM structure scan defers to idle callbacks on mutations (300 ms) and yields the main thread entirely during form input (1.5 s debounce). The GPU texture holding the combined saliency map persists between updates, so the shader always has a map even when the analyses are in flight.

2.3 V1 Crowding and V4 Color

Crowding is feature binding failure, not blur [Pelli, 2008]. We approximate its visual effect via simplex noise domain warping and grid-based feature scrambling; this does not implement the summary statistic model of Rosenholtz et al. [2012] but produces qualitatively similar identity loss. The V1 distortion is currently eccentricity-only—crowding strength does not scale with local structure density. A density gate (sigmoid on the structure channel) would modulate V1 strength by local element count, closing the gap between Bouma’s spacing rule [Bouma, 1970] and the density-dependent crowding observed by Pelli and Tillman [2008].

V4 color processing attenuates RG and YV opponent signals independently in Oklab [Ottoosson, 2020] *a* and *b* channels using castleCSF contrast sensitivity functions [Ashraf and Mantiuk, 2024]. The DoG band decomposition provides the size axis: each band’s center frequency maps to a spatial frequency, and castleCSF returns a per-channel sensitivity at that frequency and eccentricity. Because red-green (L-M) sensitivity declines 4–5× faster than blue-yellow (S-(L+M)) [Mullen and Kingdom, 2002], the Oklab *a* channel is attenuated more aggressively than *b*—preserving blue-green structure into the periphery while red-green fades first.

A suprathreshold correction (power-law exponent 0.5) prevents the threshold-based castleCSF from over-attenuating visible texture [Jiang et al., 2022]. This yields 6 uniforms total: RG/YV sensitivity at three spatial frequency tiers (fine, medium, coarse). A lateral R/B channel offset simulates longitudinal chromatic aberration.

2.4 Foveal Calibration

The foveal radius—the boundary between high-fidelity central rendering and peripheral filtering—must match each user’s actual foveal extent on their display. Without calibration, a 90 px default subtends different visual angles on a 13” laptop at 50 cm versus a 27” monitor at 70 cm; the plausible range spans roughly 60–200 px depending on display size, resolution, and viewing distance. For research use, expert calibration of viewing geometry (display DPI, viewing distance, pixels-per-degree) is essential—the system exposes these as configuration parameters. Table 3 shows concrete examples.

Table 3: Field of view by display geometry.

Display	Distance	H-FOV	V-FOV	px/deg
MacBook Pro 14”	50 cm	34°	22°	44 CSS
27” desktop (1440p)	70 cm	46°	28°	37 CSS

For scanpath replay, these parameters determine the mapping between degrees of visual angle in recorded eye-tracking data and pixel coordinates on the target display.

As a proof of concept, we prototype a self-service psychophysical staircase using the Motion Silence Illusion: rotating crosses that appear static in peripheral vision due to crowding [Pelli, 2008]. The staircase converges on the eccentricity at which users can no longer detect motion onset, with reaction-time weighting to penalize guesses. The result is a pixel radius stored per user. The current implementation does not convert pixels to degrees of visual angle—doing so requires viewing distance, which the Virtual Chinrest [Li et al., 2020] estimates via blind-spot geometry (± 3.25 cm) and which EasyEyes tracks continuously via webcam face landmarks. Integrating either through the Gaze Input branch point would close the pixel-to-degree gap.

2.5 Extensibility Branch Points

The architecture exposes five branch points where researchers substitute implementations without modifying the core pipeline (Table 4).

2.6 Cortical Magnification: FOVI Comparison

Blauch et al. [2026] propose FOVI, a foveated interface for vision models built on a kNN-convolutional architecture over a retinal sensor manifold. FOVI’s CMF is $M(r) = 1/(r + a)$, $a=2.78^\circ$; if resolution at eccentricity r relative to the fovea is $a/(r+a)$, the number of halvings is $mipLevel(r) = \log_2(1 + r/a)$. The base-2 follows from MIP semantics (each level halves resolution); this is our adaptation, not FOVI’s equation—FOVI builds a variable-density kNN sensor manifold, not a MIP chain. We do not implement FOVI’s kNN sensor manifold, kernel mapping, or

neural network pipeline—only the spatial resolution curve. At matched eccentricities, Scrutinizer’s effective cutoff falls $3.5\text{--}4.6\times$ lower than our CMF adaptation alone—the gap represents crowding, contrast sensitivity loss, and color processing that Scrutinizer bakes into its shader stages (V1 noise, saliency gating, Oklab desaturation) while FOVI delegates these to downstream learned representations.

The v1.7 paper proposed “a dual-sigma model per opponent channel” to capture the RG/YV asymmetry documented by Mullen and Kingdom [2002]. The v1.9 implementation went further: rather than dual-sigma Gaussians, Scrutinizer uses castleCSF [Ashraf and Mantiuk, 2024]—a contrast sensitivity function parameterized by spatial frequency, eccentricity, and chromatic channel. The DoG band decomposition provides the spatial frequency axis for free (each band’s center frequency is known), so castleCSF returns per-channel sensitivity at each band and eccentricity without additional spatial analysis. This yields size-dependent color preservation: fine red-green texture fades at small eccentricities while coarse blue-yellow structure persists far into the periphery, matching the asymmetric cone-opponency loss of Mullen and Kingdom [2002]. A suprathreshold correction (power-law exponent 0.5, Jiang et al. 2022) addresses castleCSF’s threshold-based over-estimation of visible-contrast attenuation. The total parameter count is 6 uniforms ($\text{RG/YV} \times 3$ frequency tiers), compared to FOVI’s single σ .

One known limitation: Bowers et al. [2025] show that red-green sensitivity decline slows beyond $\sim 40^\circ$, while castleCSF’s exponential eccentricity term continues to predict aggressive attenuation. For the desktop viewing distances Scrutinizer targets ($<30^\circ$ eccentricity), this is not yet visible, but extending to VR/AR field-of-view would require a far-periphery correction term.

2.7 Feature Congestion and Congestion-Gated Pooling

Visual clutter—the excess of features competing for attentional resources—degrades peripheral target identification independently of eccentricity [Rosenholtz et al., 2007]. We implement a Feature Congestion pipeline that scores local clutter from the rendered page and feeds the result back into the peripheral filtering pipeline.

Scoring pipeline. The congestion scorer operates on a captured PNG and computes two channels: (1) Oklab color variance within a Gaussian kernel ($\sigma=2.5$ px), measuring local chromatic heterogeneity, and (2) Sobel edge density at the same scale. Both channels are reduced to their 90th-percentile values (congestion_{p90} , edge_{p90}), and a composite score is computed as $\sqrt{\text{congestion}_{p90} \times 0.7 + \text{edge}_{p90} \times 0.3} \times 100$. The weighting, percentile reduction, and square-root scaling are engineering heuristics, not derived from biological first principles—they were curve-fit to rank-order agreement with Rosenholtz et al. [2007]’s original Feature Congestion metric, achieving Spearman $\rho = 0.93$ at 768 px viewport width with fixed $\sigma=2.5$ (dropping to $\rho = 0.60$ with the default adaptive kernel).

Table 4: Extensibility branch points.

Branch	Interface	Swap examples
Gaze input	<code>update(x,y)</code> $\rightarrow$ pos, vel, fixation	Eye tracker SDK, WebGazer.js, scanpath replay from published datasets
Saliency	bitmap $\rightarrow$ heatmap texture	Itti-Koch, DeepGaze II, ONNX model
Crowding	integer uniform selects V1 type	Portilla-Simoncelli, oriented DoG, density-gated V1 strength
Clutter scoring	PNG $\rightarrow$ congestion + edge density $\rightarrow$ composite	Custom σ , multi-viewport, CI gating
Structure	DOM blocks $\rightarrow$ RGBA texture	CV segmentation, semantic embed
Pipeline	JSON registry	Zero-code new profiles

Congestion-gated pooling (Mode 9). The composite clutter map is uploaded as a GPU texture. In the V4 color stage, local congestion modulates peripheral pooling strength by a factor of 1.0–2.0 $\times$: high-clutter regions receive stronger peripheral attenuation, approximating the attentional cost of cluttered displays. A split-view overlay shows saliency and congestion side-by-side for diagnostic comparison.

Headless scoring. The `scrutinizer-audit` CLI tool and MCP server provide batch congestion scoring without launching the Electron renderer, enabling CI integration and programmatic design evaluation.

3 Development Process

The system was developed through iterative AI-human collaboration (Claude, Anthropic) where the agent served as *research collaborator* maintaining biological grounding. Two examples illustrate complementary failure modes that the pairing catches:

Agent catches cross-boundary bug. The saliency worker computed Oklab opponent channels on BGRA-ordered pixels from Electron’s `capturePage()`. The agent traced the byte-order mismatch across 4 files and 3 processes (main $\rightarrow$ renderer $\rightarrow$ Worker)—a semantic error spanning process boundaries that human code review is unlikely to catch.

Human catches conceptual drift. Documentation described “degradation with preservation”—natural language for an engineering process focused on getting visual disruption correct. The human recognized this confused implementation with function: the retina’s job is *selective bandwidth allocation*, not degradation. The agent then swept 12 files (~ 30 edits) to align language. The drift was invisible to the agent precisely because implementation-level accuracy *had* been achieved; the conceptual error sat one level above the code.

The modular architecture enables both: the agent reasons per biological module rather than across a monolithic shader, and the human audits per biological claim rather than per file.

4 Status & Future Work

Implemented (v1.9.0): DoG band decomposition; saliency bandwidth allocation; noise crowding and grid scrambling; foveal calibration; mobile emulation; FOVI CMF adaptation as switchable mode; >120 tests; golden capture regression. Per-channel chromatic pooling via

castleCSF [Ashraf and Mantiuk, 2024] with 6 uniforms and suprathreshold correction [Jiang et al., 2022]. Feature Congestion scoring pipeline [Rosenholtz et al., 2007] with ComplexityHUD overlay and congestion-gated pooling (Mode 9). Linear M-scaling [Rovamo and Virsu, 1979] replacing geometric cutoffs. Parafoveal blur band with smooth-step ramp. `scrutinizer-audit` CLI and MCP server for headless scoring. Crowding reference pages and simulation limitations documentation. A declarative mode registry (`modes.json`) defines 9 pipeline configurations—5 research modes, 3 presentation modes, and 1 experimental mode (congestion-gated pooling)—each specifying LGN gating, V1 distortion type, V4 style, and magnification model as a JSON object, enabling zero-code A/B comparisons between pipeline variants.

Simulation limitations. Two architectural gaps are identified and documented. (1) *Density-independent crowding*: the V1 distortion stage scales with eccentricity only; local element density does not modulate crowding strength, missing the density-dependent effects demonstrated by Pelli and Tillman [2008]. (2) *Discrete-band chromatic pooling*: the DoG bands approximate continuous perceptive-field scaling with 3–4 discrete frequency buckets; the step boundaries create visible transitions that a continuous integration over the cortical magnification function would smooth.

Future: Density-gated V1 crowding (sigmoid on structure density channel); oriented DoG bands (oblique effect [Appelle, 1972]); far-periphery RG decay correction (Bowers et al. 2025 show castleCSF’s exponential overestimates beyond $\sim 40^\circ$); continuous perceptive-field color integration replacing discrete DoG band buckets; calibrated visual angles via Virtual Chinrest [Li et al., 2020] or webcam distance tracking; webcam gaze integration [Papoutsaki et al., 2016] as a consumer-hardware alternative to dedicated eye trackers. The V1 crowding stage currently uses noise-based appearance approximation; the branch point is designed so a Portilla-Simoncelli texture-statistics model—the same class that Walton et al. [2021] showed outperforms blur for foveated rendering—can be swapped in without modifying the rest of the pipeline. V2 (contour integration, border ownership) and V3 (global shape recognition) are not modeled—these require semantic representations beyond fragment-shader spatial filtering—but could be approximated via contour fragmentation and morphological simplification stages.

Perceptual validation via restricted viewing. Gaze-contingent restricted viewing—pioneered by McConkie and

Rayner [1975]—is inherently disruptive: with a one-word window, reading speed drops to 75–77% of baseline; a three-word window matching the perceptual span recovers 98% [Rayner et al., 2010]. Gaussian blur exaggerates this cost because it destroys spatial structure that real peripheral vision preserves. Walton et al. [2021] showed that texture-statistic metamers outperform bandwidth-equivalent blur for both task performance and artifact detection in foveated rendering. Scrutinizer’s DoG bands preserve this kind of structure—low-frequency layout visible, high-frequency identity lost—but whether this translates to less task disruption than Gaussian blur at matched bandwidth is an empirical question. The validation experiment would compare task completion time, reading speed, and comprehension under Scrutinizer’s DoG pipeline versus Gaussian blur versus unrestricted viewing. The open question is whether any gaze-contingent simulation can approach baseline performance, or whether inherent limitations impose a floor. Line-length reading is especially challenging: the perceptual span extends ~15 characters rightward during natural reading, and the zoom-lens model of attention [Eriksen and St. James, 1986] predicts that the attended region widens dynamically with task demands—a fixed-radius foveal window may need adaptive sizing or artificial accommodation for reading tasks. Albert et al. [2019] found that fast readers are disproportionately affected by foveated rendering, making individual-difference measurement essential to any such study.

Goal-directed attentional gating. The DOM structure extractor currently provides *categorical* top-down priors (“this is a heading”). A richer model would encode *user goals*: SNIF-ACT [Fu and Pirolli, 2007] demonstrated that spreading activation between user goals and link text—“information scent” [Pirolli and Card, 1999]—predicts navigation behavior with remarkable accuracy. That work used PMI co-occurrence on a static corpus. Modern sentence embeddings (e.g., MiniLM, 384-dim, ~23 MB ONNX) make real-time cosine similarity between a goal vector and every DOM text node feasible in a Web Worker. The saliency branch point already accepts any bitmap; a “scent map” computed from $\cos(\vec{g}, \vec{c}_i)$ scores would close the loop from Pirolli and Card’s information foraging theory to a live, gaze-contingent rendering pipeline—modeling not just *what the eye can see* but *what the mind is looking for*.

5 Availability

Open source (MIT), Electron 30.5, macOS signed. Architecture docs, literature review, and a 14-project grad student backlog ship with the repository: <https://github.com/andyed/scrutinizer2025>.

Acknowledgments. System architecture, documentation, and this paper were developed through collaboration with Claude (Anthropic, Opus 4.6) via Claude Code. The AI agent exclusively authored the grad student project backlog [Perlman, 1995–2026]. The human author directed architecture, identified conceptual framings, and validated perceptual accuracy.

References

- Robert Albert, Aldo Godinez, and David Luebke. Reading speed decreases for fast readers under gaze-contingent rendering. In *ACM Symposium on Applied Perception (SAP '19)*, 2019. doi: 10.1145/3343036.3343135.
- Stuart Appelle. Perception and discrimination as a function of stimulus orientation: the “oblique effect” in man and animals. *Psychological Bulletin*, 78(4):266–278, 1972. doi: 10.1037/h0033117.
- Maliha Ashraf and Rafał K. Mantiuk. castleCSF—a contrast sensitivity function of color, area, spatiotemporal frequency, luminance and eccentricity. *Journal of Vision*, 24(4):5, 2024. doi: 10.1167/jov.24.4.5.
- Nicholas M. Blauch, George A. Alvarez, and Talia Konkle. FOVI: Foveation of inputs as a way to model the biological periphery for vision models. *arXiv preprint arXiv:2602.03766*, 2026. URL <https://arxiv.org/abs/2602.03766>.
- Herman Bouma. Interaction effects in parafoveal letter recognition. *Nature*, 226:177–178, 1970. doi: 10.1038/226177a0.
- Nils R. Bowers, Karl R. Gegenfurtner, and Alexander Goettker. Chromatic sensitivity across the visual field. *Journal of Vision*, 25, 2025. doi: 10.1167/jov.25.1.1.
- Peter J. Burt and Edward H. Adelson. The laplacian pyramid as a compact image code. *IEEE Transactions on Communications*, 31(4):532–540, 1983. doi: 10.1109/TCOM.1983.1095851.
- Christine A. Curcio, Kenneth R. Sloan, Robert E. Kalina, and Anita E. Hendrickson. Human photoreceptor topography. *Journal of Comparative Neurology*, 292(4):497–523, 1990. doi: 10.1002/cne.902920402.
- Dennis M. Dacey. The mosaic of midget ganglion cells in the human retina. *Journal of Neuroscience*, 13(12):5334–5355, 1993. doi: 10.1523/JNEUROSCI.13-12-05334.1993.
- Andy Edmonds. Uzilla: A new tool for Web usability testing. *Behavior Research Methods, Instruments, & Computers*, 35(2):194–201, 2003. doi: 10.3758/BF03202542.
- Andy Edmonds. Scrutinizer: A vision-simulating web browser, 2007. URL <https://github.com/andyed/scrutinizer>. Adobe AIR, Gaussian blur with desaturation. Open source (BSD).
- Charles W. Eriksen and James D. St. James. Visual attention within and around the field of focal attention: A zoom lens model. *Perception & Psychophysics*, 40(4):225–240, 1986. doi: 10.3758/BF03211502.
- Wai-Tat Fu and Peter Pirolli. SNIF-ACT: A cognitive model of user navigation on the World Wide Web. *Human-Computer Interaction*, 22(4):355–412, 2007. doi: 10.1080/07370020701638806.
- Vincent Mühler Huber. face-api.js: JavaScript face recognition API for the browser and Node.js with TensorFlow.js, 2018. URL <https://github.com/justadudewhohacks/face-api.js>. Accessed 2026-03-01.
- Yijun Jiang, Christopher Shooner, and Kathy T. Mullen. Suprathreshold chromatic contrast perception across the visual field. *Journal of Vision*, 22(14):4319, 2022. doi: 10.1167/jov.22.14.4319.
- Nam Wook Kim, Zoya Bylinskii, Michelle A. Borkin, Krzysztof Z. Gajos, Aude Oliva, Hanspeter Pfister, et al. BubbleView: An interface for crowdsourcing image importance maps and tracking visual attention. *ACM Transactions on Computer-Human Interaction*, 24(5):1–40, 2017. doi: 10.1145/3131275.
- Stephen W. Kuffler. Discharge patterns and functional organization of mammalian retina. *Journal of Neurophysiology*, 16(1):37–68, 1953. doi: 10.1152/jn.1953.16.1.37.
- Dmitry Lagun and Eugene Agichtein. ViewSer: Enabling large-scale remote user studies of web search examination and interaction. In *Proceedings of the 34th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 365–374, 2011. doi: 10.1145/2009916.2009967.
- Qisheng Li, Sung Jun Joo, Jason D. Yeatman, and Katharina Reinecke. Controlling for participants’ viewing distance in large-scale, psychophysical online experiments using a virtual chinrest. *Scientific Reports*, 10:1118, 2020. doi: 10.1038/s41598-019-57204-1.
- Kerry McAlonan, James Cavanaugh, and Robert H. Wurtz. Guarding the gateway to cortex with attention in visual thalamus. *Nature*,

- 456(7220):391–394, 2008. doi: 10.1038/nature07382.
- George W. McConkie and Keith Rayner. The span of the effective stimulus during a fixation in reading. *Perception & Psychophysics*, 17(6):578–586, 1975. doi: 10.3758/BF03203972.
- Kathy T. Mullen and Frederick A. A. Kingdom. Differential distributions of red-green and blue-yellow cone opponency across the visual field. *Visual Neuroscience*, 19(1):109–118, 2002. doi: 10.1017/S0952523802011158.
- Pavel A. Orlov and Roman Bednarik. ScreenMasker: An open-source gaze-contingent screen masking environment. *Behavior Research Methods*, 48(4):1145–1153, 2016. doi: 10.3758/s13428-015-0635-7.
- Björn Ottosson. A perceptual color space for image processing, 2020. URL <https://bottosson.github.io/posts/oklab/>. Accessed 2026-02-28.
- Alexandra Papoutsaki, Patsorn Sangkloy, James Laskey, Nediya Dasarathy, Jian Huang, and James Hays. WebGazer: Scalable webcam eye tracking using user interactions. In *Proceedings of the 25th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 3839–3845, 2016.
- Denis G. Pelli. Crowding: a cortical constraint on object recognition. *Current Opinion in Neurobiology*, 18(4):445–451, 2008. doi: 10.1016/j.conb.2008.09.008.
- Denis G. Pelli and Katharine A. Tillman. The uncrowded window of object recognition. *Nature Neuroscience*, 11(10):1129–1135, 2008. doi: 10.1038/nn.2187.
- Gary Perlman. HCI bibliography: Human-computer interaction resources, 1995–2026. URL <https://www.hcibib.org/>. Accessed 2026-02-28.
- Peter Pirolli and Stuart Card. Information foraging. *Psychological Review*, 106(4):643–675, 1999. doi: 10.1037/0033-295X.106.4.643.
- Matt Queen. Icon analysis, 2006. URL <https://boxesandarrows.com/icon-analysis/>. Boxes and Arrows, July 25, 2006.
- Keith Rayner, Timothy J. Slattery, and Nathalie N. Bélanger. Eye movements, the perceptual span, and reading speed. *Psychonomic Bulletin & Review*, 17(6):834–839, 2010. doi: 10.3758/PBR.17.6.834.
- Ruth Rosenholtz, Yuanzhen Li, and Lisa Nakano. Measuring visual clutter. *Journal of Vision*, 7(2):17, 2007. doi: 10.1167/7.2.17.
- Ruth Rosenholtz, Jie Huang, Alvin Raj, Benjamin J. Balas, and Livia Ilie. A summary statistic representation in peripheral vision explains visual search. *Journal of Vision*, 12(4):14, 2012. doi: 10.1167/12.4.14.
- Jyrki Rovamo and Veijo Virsu. An estimation and application of the human cortical magnification factor. *Experimental Brain Research*, 37(3):495–510, 1979. doi: 10.1007/BF00236819.
- S. Murray Sherman and R. W. Guillery. The role of the thalamus in the flow of information to the cortex. *Philosophical Transactions of the Royal Society B*, 357(1428):1695–1708, 2002. doi: 10.1098/rstb.2002.1161.
- David R. Walton, Rafael K. Dos Anjos, Sebastian Friston, David Swapp, Kaan Aksit, Anthony Steed, and Tobias Ritschel. Beyond blur: Real-time ventral metamers for foveated rendering. *ACM Transactions on Graphics (SIGGRAPH)*, 40(4):Article 48, 2021. doi: 10.1145/3450626.3459943.