

Scrutinizer: A Biologically-Motivated Foveated Vision Simulator for Web Interfaces, Built Through AI-Human Collaboration

Andy Edmonds

Independent Researcher, San Francisco, CA
andyed@alum.cmu.edu

Table 1: Comparison with existing gaze-contingent tools.

Tool	Live	Bio Model	Crowding	Saliency	Open
BubbleView [2017]	–	Gauss.	–	–	✓
ViewSer [2011]	SERP	Gauss.	–	–	–
ScreenMasker	–	Gauss.	–	–	✓
Scrutinizer	✓	DoG	✓	✓	✓

Abstract. We present Scrutinizer, an open-source, real-time gaze-contingent foveated rendering system for live web content. An 888-line GLSL shader implements a pipeline mapped to the visual pathway (retinal ganglion cells → LGN → V1 → V4), with four swappable JavaScript modules aligned to biological subsystems. The key technical contribution is a Difference-of-Gaussians (DoG) band decomposition exploiting the hardware MIP chain for frequency-selective peripheral filtering—high-frequency detail attenuates first while low-frequency structure persists, mirroring M-scaling. The system was developed through iterative AI-human collaboration where an AI agent (Claude, Anthropic) cross-referenced neuroscience literature against shader code, caught coordinate-space bugs empirically, and maintained biological grounding across 27 uniforms. Open source (MIT), 60 fps, 138 unit tests.

1 Introduction

Peripheral vision is not blurry—it is *differently encoded*. The retina compresses $\sim 10^7$ photoreceptor signals into $\sim 10^6$ optic nerve fibers, selectively preserving low-frequency structure while filtering high-frequency detail [Curcio et al., 1990, Dacey, 1993]. This is compute demand management: limited bandwidth allocated to information most likely to guide the next saccade.

Existing gaze-contingent tools—BubbleView [Kim et al., 2017], ViewSer [Lagun and Agichtein, 2011], ScreenMasker—apply Gaussian blur as a peripheral proxy, uniformly destroying spatial structure and preventing layout-level judgments that real peripheral vision supports. These tools also operate on static images, not live interactive content.

Scrutinizer contributes (1) a modular architecture where each module maps to a biological subsystem (Table 2), enabling independent swapping—replace the mouse-based gaze proxy with an eye tracker by changing one module—and (2) an AI-assisted development process where biological grounding is maintained by an agent cross-referencing neuroscience

Table 2: Module architecture mapped to biological subsystems.

Biology	Module (LOC)	Function
Oculomotor	GazeModel (166)	Velocity, fixation, saccadic suppression
Retinal	ContentAnalysis (361)	DoG center-surround via MIP chain
LGN gating	ContentAnalysis	Structure mask + saliency gate
V1 features	Orchestrator (536)	Noise crowding, grid scramble
V4 color	Renderer (526)	Oklab desat., chrom. aberration
Saliency	Worker (489)	Oklab DoG + face det. + structure

literature against rendering code.

2 Architecture: Biology → Computation

The pipeline is a single-pass fragment shader (888 LOC, GLSL ES 3.0) with 27 uniforms organized into biological stages, fed by four JavaScript modules (Table 2).

2.1 DoG Band Decomposition

Retinal ganglion cells have center-surround receptive fields modeled as DoG filters [Kuffler, 1953], with field size growing with eccentricity (M-scaling). We decompose the hardware MIP chain into a Laplacian pyramid:

$$\text{band}_k = \text{textureLod}(\text{tex}, uv, k) - \text{textureLod}(\text{tex}, uv, k+1) \quad (1)$$

Four bands span 1–2 px (serifs) to 8–16 px (buttons), each weighted by a smoothstep rolloff with cutoffs following a geometric progression $(0.3, 0.6, 1.2, 2.4 \times E_2)$, approximating M-scaling [Curcio et al., 1990]. The DC residual always passes through. Result: peripheral text shows letter shapes (low-frequency visible, identity unreadable) rather than uniform fog. Cost: 5 `textureLod` calls vs. 1, but near-zero practical overhead—higher MIP levels are cheaper, already cached, and arithmetic is trivial.

2.2 Saliency-Driven Bandwidth Allocation

The LGN’s synaptic inputs are $\sim 90\%$ modulatory, with $\sim 30\%$ from V1 feedback [Sherman and Guillery, 2002]; spatial attention enhances LGN gain [McAlonan et al., 2008]. We model this as saliency gating: a Web Worker computes a saliency map (Oklab opponent-channel DoG + face de-

tection + Gestalt structure masks), uploaded as a GPU texture. High-saliency regions receive up to 70% of rendering bandwidth.

2.3 V1 Crowding and V4 Color

Crowding is feature binding failure, not blur [Pelli, 2008]. We model it via simplex noise domain warping and grid-based feature scrambling [Rosenholtz et al., 2012]. V4 applies Oklab desaturation [Ottooson, 2020] for rod dominance and chromatic aberration for M/P asynchrony [Livingstone and Hubel, 1988].

2.4 Extensibility Branch Points

The architecture exposes five branch points where researchers substitute implementations without modifying the core pipeline (Table 3).

Table 3: Extensibility branch points.

Branch	Interface	Swap examples
Gaze input	<code>update(x,y)</code> → pos, vel, fixation	Tobii SDK, WebGazer.js, scanpath replay
Saliency	bitmap → heatmap texture	Itti-Koch, DeepGaze II, ONNX model
Crowding	integer uniform selects V1 type	Portilla-Simoncelli, oriented DoG
Structure	DOM blocks → RGBA texture	CV segmentation, semantic embed
Pipeline	JSON registry	Zero-code new profiles

3 AI-Assisted Development Process

This documents AI as *research collaborator* maintaining biological grounding—not a report on code generation.

Cross-process bug detection. The saliency worker computed Oklab opponent channels on BGRA-ordered pixels from Electron’s `capturePage()`. The agent traced the byte-order mismatch across 4 files and 3 processes (main → renderer → Worker).

AI checking AI. A separate AI session removed DPR scaling from structure masks, reasoning `toBitmap()` returns logical pixels. The primary agent disproved this empirically: `getSize()`=3252×1690 (physical) on a 1626-logical display, DPR = 2.

Conceptual reframing. Documentation described “degradation with preservation.” The human identified the biological analog is *selective bandwidth allocation*. The agent then swept 12 files (~30 edits) to align language.

Literature—shader validation. Shader comments cite Kuffler [1953], Pelli [2008], McAlonan et al. [2008]. The agent validated these against the scientific literature review, ensuring shader claims matched cited mechanisms.

The modular architecture *enables* this workflow: the agent reasons per biological module, not across an 888-line monolith.

4 Status & Future Work

Implemented (v1.6.0): DoG band decomposition; saliency bandwidth allocation; noise crowding and grid scrambling; Oklab desaturation and chromatic aberration;

foveal calibration; mobile emulation; 138 tests; golden capture regression.

Future: Oriented DoG bands (oblique effect [Appelle, 1972]); calibrated visual angles; eye tracker integration (GazeModel branch point); Portilla-Simoncelli mongrel synthesis (V1 branch point).

5 Availability

Open source (MIT), Electron 30.5, macOS signed. Architecture docs, literature review, and a 14-project grad student backlog ship with the repository.

Acknowledgments. System architecture, documentation, and this paper were developed through collaboration with Claude (Anthropic, Opus 4.6) via Claude Code. The AI agent exclusively authored the grad student project backlog [Perlman, 1995–2026]. AE directed architecture, identified conceptual framings, and validated perceptual accuracy.

References

- Stuart Appelle. Perception and discrimination as a function of stimulus orientation: the “oblique effect” in man and animals. *Psychological Bulletin*, 78(4):266–278, 1972. doi: 10.1037/h0033117.
- Christine A. Curcio, Kenneth R. Sloan, Robert E. Kalina, and Anita E. Hendrickson. Human photoreceptor topography. *Journal of Comparative Neurology*, 292(4):497–523, 1990. doi: 10.1002/cne.902920402.
- Dennis M. Dacey. The mosaic of midget ganglion cells in the human retina. *Journal of Neuroscience*, 13(12):5334–5355, 1993. doi: 10.1523/JNEUROSCI.13-12-05334.1993.
- Nam Wook Kim, Zoya Bylinskii, Michelle A. Borkin, Krzysztof Z. Gajos, Aude Oliva, Hanspeter Pfister, et al. BubbleView: An interface for crowdsourcing image importance maps and tracking visual attention. *ACM Transactions on Computer-Human Interaction*, 24(5):1–40, 2017. doi: 10.1145/3131275.
- Stephen W. Kuffler. Discharge patterns and functional organization of mammalian retina. *Journal of Neurophysiology*, 16(1):37–68, 1953. doi: 10.1152/jn.1953.16.1.37.
- Dmitry Lagun and Eugene Agichtein. ViewSer: Enabling large-scale remote user studies of web search examination and interaction. In *Proceedings of the 34th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 365–374, 2011. doi: 10.1145/2009916.2009967.
- Margaret Livingstone and David Hubel. Segregation of form, color, movement, and depth: anatomy, physiology, and perception. *Science*, 240(4853):740–749, 1988. doi: 10.1126/science.3283936.
- Kerry McAlonan, James Cavanaugh, and Robert H. Wurtz. Guarding the gateway to cortex with attention in visual thalamus. *Nature*, 456(7220):391–394, 2008. doi: 10.1038/nature07382.
- Björn Ottooson. A perceptual color space for image processing, 2020. URL <https://bottosson.github.io/posts/oklab/>. Accessed 2026-02-28.
- Denis G. Pelli. Crowding: a cortical constraint on object recognition. *Current Opinion in Neurobiology*, 18(4):445–451, 2008. doi: 10.1016/j.conb.2008.09.008.
- Gary Perlman. HCI bibliography: Human-computer interaction resources, 1995–2026. URL <https://www.hcibib.org/>. Accessed 2026-02-28.
- Ruth Rosenholtz, Jie Huang, Alvin Raj, Benjamin J. Balas, and Livia Ilie. A summary statistic representation in peripheral vision explains visual search. *Journal of Vision*, 12(4):14, 2012. doi: 10.1167/12.4.14.
- S. Murray Sherman and R. W. Guillery. The role of the thalamus in the flow of information to the cortex. *Philosophical Transactions of the Royal Society B*, 357(1428):1695–1708, 2002. doi: 10.1098/rstb.2002.1161.