

Scrutinizer: A Biologically-Grounded Foveated Vision Simulator for Web Interfaces

Andy Edmonds

Independent Researcher, San Francisco, CA

andyed@alum.cmu.edu

Table 1: Comparison with existing gaze-contingent tools.

Tool	Live	Bio Model	Crowding	Saliency	Open
BubbleView [2017]	–	Gauss.	–	–	✓
ViewSer [2011]	SERP	Gauss.	–	–	–
ScreenMasker	–	Gauss.	–	–	✓
FOVI [2026]	✓	CMF	–	–	✓
Scrutinizer	✓	DoG	✓	✓	✓

Abstract. We present Scrutinizer, an open-source, real-time gaze-contingent foveated rendering system for live web content. A 1157-line GLSL shader implements a pipeline mapped to the visual pathway (retinal ganglion cells → LGN → V1 → V4), with four swappable JavaScript modules aligned to biological subsystems. The key technical contribution is a Difference-of-Gaussians (DoG) band decomposition exploiting the hardware MIP chain for frequency-selective peripheral filtering—high-frequency detail attenuates first while low-frequency structure persists, mirroring cortical magnification [Rovamo and Virsu, 1979]. A reference implementation of FOVI [Blauch et al., 2026] enables direct comparison of cortical magnification strategies within the same framework. Open source (MIT), 60 fps, 138 unit tests.

1 Introduction

Peripheral vision is not blurry—it is *differently encoded*. The retina compresses $\sim 10^7$ photoreceptor signals into $\sim 10^6$ optic nerve fibers, selectively preserving low-frequency structure while filtering high-frequency detail [Curcio et al., 1990, Dacey, 1993]. This is compute demand management: limited bandwidth allocated to information most likely to guide the next saccade.

Existing gaze-contingent tools—BubbleView [Kim et al., 2017], ViewSer [Lagun and Agichtein, 2011], ScreenMasker—apply Gaussian blur as a peripheral proxy, uniformly destroying spatial structure and preventing layout-level judgments that real peripheral vision supports. These tools also operate on static images, not live interactive content.

Scrutinizer contributes (1) a modular architecture where each module maps to a biological subsystem (Table 2), enabling independent swapping—replace the mouse-based gaze proxy with an eye tracker by changing one module—and (2) a swappable pipeline enabling side-by-side comparison of peripheral filtering strategies, including a reference implementation of FOVI cortical magnification [Blauch et al., 2026].

Table 2: Module architecture mapped to biological subsystems.

Biology	Module (LOC)	Function
Oculomotor	GazeModel (166)	Velocity, fixation, saccadic suppression
Retinal GC	ContentAnalysis (361)	DoG center-surround via MIP chain
LGN gating	ContentAnalysis	Structure mask + saliency gate
V1 features	Orchestrator (536)	Noise crowding, grid scramble
V4 color	Renderer (548)	Oklab desat., chrom. aberration
Saliency	Worker (489)	Oklab DoG + face det. + structure

2 Architecture: Biology → Computation

The pipeline is a single-pass fragment shader (1157 LOC, GLSL ES 3.0) with 27 uniforms organized into biological stages, fed by four JavaScript modules (Table 2).

2.1 DoG Band Decomposition

Retinal ganglion cells have center-surround receptive fields modeled as DoG filters [Kuffler, 1953], with field size growing with eccentricity (M-scaling). We decompose the hardware MIP chain into a Laplacian pyramid:

$$\text{band}_k = \text{textureLod}(\text{tex}, uv, k) - \text{textureLod}(\text{tex}, uv, k+1) \quad (1)$$

Four bands span 1–2 px (serifs) to 8–16 px (buttons), each weighted by a smoothstep rolloff with cutoffs following a geometric progression (0.3, 0.6, 1.2, $2.4 \times E_2$), approximating cortical magnification [Rovamo and Virsu, 1979]. The DC residual always passes through. Result: peripheral text shows letter shapes (low-frequency visible, identity unreadable) rather than uniform fog. Cost: 5 `textureLod` calls vs. 1, but near-zero practical overhead—higher MIP levels are cheaper, already cached, and arithmetic is trivial.

2.2 Saliency-Driven Bandwidth Allocation

The LGN’s synaptic inputs are $\sim 90\%$ modulatory, with $\sim 30\%$ from V1 feedback [Sherman and Guillery, 2002]; spatial attention enhances LGN gain [McAlonan et al., 2008]. We model this as saliency gating: a Web Worker computes a saliency map (Oklab opponent-channel DoG + face detection + Gestalt structure masks), uploaded as a GPU texture. High-saliency regions receive up to 70% of rendering bandwidth.

2.3 V1 Crowding and V4 Color

Crowding is feature binding failure, not blur [Pelli, 2008]. We model it via simplex noise domain warping and grid-based feature scrambling [Rosenholtz et al., 2012]. V4 applies Oklab desaturation [Ottoosson, 2020] for rod dominance and chromatic aberration for M/P asynchrony [Livingstone and Hubel, 1988].

2.4 Extensibility Branch Points

The architecture exposes five branch points where researchers substitute implementations without modifying the core pipeline (Table 3).

Table 3: Extensibility branch points.

Branch	Interface	Swap examples
Gaze input	<code>update(x,y)</code> → pos, vel, fixation	Tobii SDK, WebGazer.js, scanpath replay
Saliency	bitmap → heatmap texture	Itti-Koch, DeepGaze II, ONNX model
Crowding	integer uniform selects V1 type	Portilla-Simoncelli, oriented DoG
Structure	DOM blocks → RGBA texture	CV segmentation, semantic embed
Pipeline	JSON registry	Zero-code new profiles

2.5 Cortical Magnification: FOVI Comparison

Blauch et al. [2026] propose FOVI, a cortical magnification transform for vision models: $mipLevel(e) = \log_2(1 + e/a)$, $a=2.78^\circ$. We implemented FOVI alongside Scrutinizer’s DoG pipeline, enabling direct comparison. At matched eccentricities, Scrutinizer’s effective cutoff falls $3.5\text{--}4.6\times$ lower than FOVI’s—the gap represents crowding, receptive-field growth, and contrast sensitivity loss that Scrutinizer bakes into its shader stages (V1 noise, saliency gating, Oklab desaturation) while FOVI leaves to the downstream neural network.

Both systems share an open question: the desaturation transfer function. Scrutinizer uses smoothstep in Oklab space; FOVI applies exponential decay in RGB. Neither approach is definitively grounded—Mullen and Kingdom [2002] show red-green sensitivity declining faster than blue-yellow with eccentricity, suggesting a dual-sigma model per opponent channel rather than a uniform curve.

3 Development Process

The system was developed through iterative AI-human collaboration (Claude, Anthropic) where the agent served as *research collaborator* maintaining biological grounding.

Cross-process bug detection. The saliency worker computed Oklab opponent channels on BGRA-ordered pixels from Electron’s `capturePage()`. The agent traced the byte-order mismatch across 4 files and 3 processes (main → renderer → Worker)—a class of bug where human code review is unlikely to catch the cross-boundary semantic error.

Conceptual reframing. Documentation described “degradation with preservation.” The human identified the

biological analog is *selective bandwidth allocation*; the agent then swept 12 files (~ 30 edits) to align language, illustrating the agent as conceptual partner rather than code generator.

The modular architecture *enables* this workflow: the agent reasons per biological module, not across a monolithic shader.

4 Status & Future Work

Implemented: DoG band decomposition; saliency bandwidth allocation; noise crowding and grid scrambling; Oklab desaturation and chromatic aberration; foveal calibration; mobile emulation; FOVI cortical magnification reference implementation; hot-switchable pipeline profiles; 138 tests; golden capture regression.

Future: Dual-sigma color decay per opponent channel [Mullen and Kingdom, 2002]; oriented DoG bands (oblique effect [Appelle, 1972]); calibrated visual angles; eye tracker integration (GazeModel branch point); Portilla-Simoncelli mongrel synthesis (V1 branch point).

5 Availability

Open source (MIT), Electron 30.5, macOS signed. Architecture docs, literature review, and a 14-project grad student backlog ship with the repository.

Acknowledgments. System architecture, documentation, and this paper were developed through collaboration with Claude (Anthropic, Opus 4.6) via Claude Code. The AI agent exclusively authored the grad student project backlog [Perlman, 1995–2026]. AE directed architecture, identified conceptual framings, and validated perceptual accuracy.

References

- Stuart Appelle. Perception and discrimination as a function of stimulus orientation: the “oblique effect” in man and animals. *Psychological Bulletin*, 78(4):266–278, 1972. doi: 10.1037/h0033117.
- Nicholas M. Blauch, George A. Alvarez, and Talia Konkle. FOVI: Foveation of inputs as a way to model the biological periphery for vision models. *arXiv preprint arXiv:2602.03766*, 2026. URL <https://arxiv.org/abs/2602.03766>.
- Christine A. Curcio, Kenneth R. Sloan, Robert E. Kalina, and Anita E. Hendrickson. Human photoreceptor topography. *Journal of Comparative Neurology*, 292(4):497–523, 1990. doi: 10.1002/cne.902920402.
- Dennis M. Dacey. The mosaic of midget ganglion cells in the human retina. *Journal of Neuroscience*, 13(12):5334–5355, 1993. doi: 10.1523/JNEUROSCI.13-12-05334.1993.
- Nam Wook Kim, Zoya Bylinskii, Michelle A. Borkin, Krzysztof Z. Gajos, Aude Oliva, Hanspeter Pfister, et al. BubbleView: An interface for crowdsourcing image importance maps and tracking visual attention. *ACM Transactions on Computer-Human Interaction*, 24(5):1–40, 2017. doi: 10.1145/3131275.
- Stephen W. Kuffler. Discharge patterns and functional organization of mammalian retina. *Journal of Neurophysiology*, 16(1):37–68, 1953. doi: 10.1152/jn.1953.16.1.37.
- Dmitry Lagun and Eugene Agichtein. ViewSer: Enabling large-scale remote user studies of web search examination and interaction. In *Proceedings of the 34th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 365–374, 2011. doi: 10.1145/2009916.2009967.
- Margaret Livingstone and David Hubel. Segregation of form, color, movement, and depth: anatomy, physiology, and perception. *Science*, 240(4853):740–749, 1988. doi: 10.1126/science.3283936.
- Kerry McAlonan, James Cavanaugh, and Robert H. Wurtz. Guarding

- the gateway to cortex with attention in visual thalamus. *Nature*, 456(7220):391–394, 2008. doi: 10.1038/nature07382.
- Kathy T. Mullen and Frederick A. A. Kingdom. Differential distributions of red-green and blue-yellow cone opponency across the visual field. *Visual Neuroscience*, 19(1):109–118, 2002. doi: 10.1017/S0952523802011158.
- Björn Ottosson. A perceptual color space for image processing, 2020. URL <https://bottosson.github.io/posts/oklab/>. Accessed 2026-02-28.
- Denis G. Pelli. Crowding: a cortical constraint on object recognition. *Current Opinion in Neurobiology*, 18(4):445–451, 2008. doi: 10.1016/j.conb.2008.09.008.
- Gary Perlman. HCI bibliography: Human-computer interaction resources, 1995–2026. URL <https://www.hcibib.org/>. Accessed 2026-02-28.
- Ruth Rosenholtz, Jie Huang, Alvin Raj, Benjamin J. Balas, and Livia Ilie. A summary statistic representation in peripheral vision explains visual search. *Journal of Vision*, 12(4):14, 2012. doi: 10.1167/12.4.14.
- Jyrki Rovamo and Veijo Virsu. An estimation and application of the human cortical magnification factor. *Experimental Brain Research*, 37(3):495–510, 1979. doi: 10.1007/BF00236819.
- S. Murray Sherman and R. W. Guillery. The role of the thalamus in the flow of information to the cortex. *Philosophical Transactions of the Royal Society B*, 357(1428):1695–1708, 2002. doi: 10.1098/rstb.2002.1161.