

# PLT 4115 LRM: **JaTesté**

Andrew Grant  
amg2215@columbia.edu

Jemma Losh  
jal2285@columbia.edu

Jared Weiss  
jbw2140@columbia.edu

Jake Weissman  
jdw2159@columbia.edu

March 3, 2016

## 1 Introduction

The goal of JaTesté is to design a language that promotes good coding practices - mainly as it relates to testing. JaTesté will require the user to explicitly define test cases for any function that is written in order to compile and execute code. This will ensure that no code goes untested and will increase the overall quality of programmer code written in our language. The user will be required to provide some test cases for their code, and the language will also generate some important test cases for their code as well. JaTesté is mostly a functional language with a syntax quite similar to C. The details of our language usage is provided in the rest of the document.

## 2 Lexical Conventions

This chapter will describe how input code will be processed and how tokens will be generated.

### 2.1 Identifiers

Identifiers are used to name a variable, a function, or other types of data. An identifier can include all letters, digits, and the underscore character. An identifier must start with either a letter or an underscore - it cannot start with a digit. Capital letters will be treated differently from lower case letters.

### 2.2 Keywords

Keywords are a set of words that serve a specific purpose in our language and may not be used by the programmer for any other reason. The list of keywords the language recognizes and reserves is as follows:

```
int char float struct if else for while break continue with test using func return string
print
```

### 2.3 Constants

Our language includes integer, character, real number, and string constants. They're defined in the following sections.

#### 2.3.1 Integer Constants

Integer constants are a sequence of digits. An integer is taken to be decimal. Here are some examples:

```
13
1357
23
987
```

### 2.3.2 Character Constants

Character constants hold a single character and are enclosed in single quotes. They are stored in a variable of type `char`. Character constants that are preceded with a backslash have special meaning. Here are some examples:

```
'a'  
'\n' newline  
'\t' tab
```

### 2.3.3 Real Number Constants

Real number constants represent a floating point number. They are composed of a sequence of digits, representing the whole number portion, followed by a decimal and another sequence of digits, representing the fractional part. Here are some examples. The whole part or the fractional part may be omitted, but not both.

```
3.14  
0.4  
.7  
8
```

### 2.3.4 String Constants

Strings are a sequence of characters enclosed by double quotes. A String is treated like a character array. Here are some examples:

```
"Hello, world!"  
"JaTeste"
```

## 2.4 Operators

Operators are special tokens such as multiply, equals, etc. that are applied to one or two operands. Their use will be explained further in chapter 4.

## 2.5 White Space

Whitespace is considered to be a space, tab, or newline. It is used for token delimitation, but has no meaning otherwise.

## 2.6 Comments

A comment is a sequence of characters beginning with a forward slash followed by an asterisk. It continues until it is ended with an asterisk followed by a forward slash. Comments are treated as whitespace.

# 3 Data Types

The data types in JaTeste can be classified into three categories: primitive types, structures, and arrays.

## 3.1 Primitives

### 3.1.1 Integer Types

The integer data type is a 32 bit value that can hold whole numbers ranging from  $-2,147,483,648$  to  $2,147,483,647$ . Keyword `'int'` is required to declare a variable with this type.

```
1 int a = 10;  
2 int b = a + 10;
```

### 3.1.2 Character Type

The character type is an 8 bit value that is used to hold a single character. The keyword “char” is used to declare a variable with this type.

```
1 char c = 'h';
2 char b = 'e';
3 char d = 'l';
```

## 3.2 Structures

The structure data type is a collection of primitive types and other structures. The keyword “struct” followed by the name of the struct is used to define structures. Curly braces are then used to define what the structure is made of. As an example, consider the following:

### 3.2.1 Defining Structures

```
1
2 struct person = {
3     string name;
4     int age;
5     int height;
6 };
7
8
9 struct manager = {
10     struct person name;
11     int salary;
12 };
```

This syntax is very similar to C.

### 3.2.2 Initializing Structures

To create instances of structs:

```
1 struct manager yahoo_manager;
2 struct person sam;
```

Here, we create two variables yahoo\_manager and sam. The former is of type “struct manager”, and the latter is of type “struct person”.

### 3.2.3 Accessing Structure Members

To access structs and modify its variables, a period following by the variable name is used:

```
1 yahoo_manager.name = sam;
2 yahoo_manager.age = 45;
3 yahoo_manager = 65000;
```

Ultimately, all structures are backed by some collection of primitives. For example, the first struct, manager, is made up of another struct and an int. Since the struct person is made up of two ints, manager is really just made up of three ints.

## 3.3 Arrays

### 3.3.1 Defining Arrays

### 3.3.2 Initializing Arrays

### 3.3.3 Accessing Array Elements

### 3.3.4 Multidimensional Arrays

### 3.3.5 Arrays of Structures

Text

## 4 Expressions and Operators

### 4.1 Expressions

An expression is a collection of one or more operands and zero or more operators that can be evaluated to produce a value. A function that returns a value can be an operand as part of an expression. Additionally, parenthesis can be used to group smaller expressions together as part of a larger expression. A semicolon terminates an expression. Some examples of expressions include:

```
1 35 - 6;  
2 foo(42) * 10;  
3 8 - (9 / (2 + 1) );
```

### 4.2 Assignment Operators

Assignment can be used to assign the value of an expression on the right side to a named variable on the left hand side of the equals operator. The left hand side can either be a named variable that has already been declared or a named variable that is being declared and initialized in this assignment. Examples include:

```
1 int x = 5;  
2 float y;  
3 y = 9.9;
```

Additionally, the following operators can also be used for variations of assignment:

- += increments the left hand side by the result of the right hand side
- -= decrements the left hand side by the result of the right hand side

### 4.3 Incrementing and Decrementing

This can be done using the ++ operator to increment and the -- operator to decrement a value. If the operator is placed before a value it will be incremented / decremented first, then it will be evaluated. If the operator is placed following a value, it will be evaluated with its original value and then incremented / decremented.

### 4.4 Arithmetic Operators

- + can be used for addition
- - can be used for subtraction (on two operands) and negation (on one operand)
- \* can be used for multiplication
- / can be used for division

- $\wedge$  can be used for exponents
- $\%$  can be used for modular division

## 4.5 Comparison Operators

- `==` can be used to evaluate equality
- `!=` can be used to evaluate inequality
- `>` can be used to evaluate is the left greater than the right
- `>=` can be used to evaluate is the left greater than or equal to the right
- `<` can be used to evaluate is the left less than the right
- `<=` can be used to evaluate is the left less than or equal to the right

## 4.6 Logical Operators

- `!` can be used to evaluate the negation of one expression
- `&&` can be used to evaluate logical and
- `||` can be used to evaluate logical or

## 4.7 Operator Precedence

## 4.8 Order of Evaluation

# 5 Statements

Statements include: `if`, `while`, `for`, `return` as explained in the following sections

## 5.1 If Statement

The `if`, `else if`, `else` construct will work as expected in other languages.

```

1  if (x == 42) {
2      print("Gotcha");
3  }
4  else if (x > 42) {
5      print("Sorry, too big");
6  }
7  else {
8      print("I'll allow it");
9  }

```

## 5.2 While Statement

The `while` statement will evaluate in a loop as long as the specified condition in the `while` statement is true.

```

1  /* Below code prints "Hey there" 10 times */
2  int x = 0;
3  while (x < 10) {
4      print("Hey there");
5      x++;
6  }

```

## 5.3 For Statement

The for condition will also run in a loop so long as the condition specified in the for statement is true. The expectation for a for statement is as follows:

for ( <initial state>; <test condition>; <step forward> )

Examples are as follows:

```
1  /* This will run as long as i is less than 100
2     i will be incremented on each iteration of the loop */
3  for (int i = 0; i < 100; i++) {
4     /* do something */
5  }
6
7  /* i can also be declared or initialized outside of the for loop */
8  int i;
9  for (i = 0; i < 100; i += 2) {
10     /* code block */
11 }
```

## 5.4 Code Blocks

Blocks are code that is contained within a pair of brackets, { code }, that gets executed within a statement. For example, any code blocks that follow an if statement will get executed if the if condition is evaluated as true:

```
1  int x = 42;
2  if (x == 42) {
3     /* the following three lines are executed */
4     print("Hey");
5     x++;
6     print("Bye");
7 }
```

## 5.5 Return Statement

The return statement is used to exit out of a function and return a value. The return value must be the same type that is specified by the function declaration. Return can be used as follows:

```
1  /* The function trivially returns the input int value */
2  func int someValue(int x) {
3     return x;
4 }
```

## **6 Functions**

### **6.1 Function Declarations**

### **6.2 Calling Functions**

### **6.3 Function Parameters**

### **6.4 Main Function**

### **6.5 Recursive Functions**

## **7 Program Structure and Scope**

### **7.1 Program Structure**

### **7.2 Scope**

## **8 A Sample Program**