

Announcements:

Midterm 2: Wed. 10/18 7:00-8:30, Noyes 217
(same time/place as Midterm 1)

Quiz 2: Fri 10/13 (in class)

Optimization: want to minimize or maximize some quantity

Algorithms:

Kruskal's algorithm: find a minimal-weight spanning tree

Dijkstra's algorithm: find a shortest path from u to v

Both are "greedy" algorithms: charge ahead, and don't look back

Let G be a weighted graph w/ nonneg. wts.

If $H \subseteq G$, let $wt(H) = \sum_{e \in E(H)} wt(e)$

The weight of the path/spanning tree/etc. is the sum of the weights of its edges

[Different convention than what we used in the weighted matrix tree thm. related by \log]

Kruskal's Algorithm (2.3.1) (for convenience, assume distinct wts)

Input: A weighted conn. graph G

Start: Let $T \subseteq G$ be the subgraph $V(T) = V(G)$, $E(T) = \emptyset$

While T is disconnected:


Let e be the least weight of an edge not yet considered

If the endpoints of e are in diff. components of T :
(i.e. if $T \cup e$ is acyclic)

Add e to T

Output: A minimal-weight spanning tree T

Class activity: Kruskal!



Thm 2.2.3: The output of Kruskal's Algorithm is always a minimum-weight spanning tree

Pf:

Dijkstra's Algorithm (2.3.5)

Input: A weighted graph G and a vertex $u \in V(G)$

Start: $S = \{u\}$, $t(u) = 0$,

$$t(z) = \min_{\substack{e \\ u \text{ --- } z}} wt(e) \quad \text{if } z \neq u$$

While $\exists z \notin S$, $t(z) < \infty$:

Choose $v \notin S$ s.t. $t(v) = \min_{z \notin S} t(z)$



Add v to S

For all edges $\substack{e \\ v \text{ --- } z}$, $z \notin S$:

Replace $t(z)$ w/ $\min(t(z), t(v) + wt(e))$

Output: $t(v) = d(u, v)$ for all $v \in V(G)$

Class activity: Dijkstra!



$$t(u) =$$

$$t(a) =$$

$$t(b) =$$

$$t(c) =$$

$$t(d) =$$

$$t(e) =$$

$$t(f) =$$

Thm 2.3.7: The output of Dijkstra's Algorithm is always the distance function $d(u, v)$.

Pf: