

Computer Programming 2

2024/04/10 Andy Hung

Outline

- HW04 solution
- Midterm Review
 - `malloc`
 - Linked List
 - Function Pointer

HW04

```
1  #include <stdio.h>
2  #include <stdlib.h>
3
4  struct Program{
5      int start;
6      int end;
7  };
8  typedef struct Program Program;
9
10 int cmp(const void* a, const void* b) {
11     Program* programA = (Program*)a;
12     Program* programB = (Program*)b;
13     return programA->end - programB->end;
14 }
15
16 int main() {
17     int N;
18     scanf("%d", &N);
```

Midterm Review

malloc

```
1  // ptr = (cast-type*) malloc(byte-size)
2
3  // Create an int array of size 10
4  int* ptr = malloc(sizeof(int) * 10)
```

- Allocate memory in **heap**.
- Remember to free if you don't need it anymore.

Midterm Review

Linked List

```
1  typedef struct node Node;
2
3  struct node {
4      int value;
5      Node* nextPtr;
6  }
```

Midterm Review


Linked List

```
1  typedef struct node Node;
2
3  struct node {
4      int value;
5      Node* nextPtr;
6  }
```

- Other Concept
- Insert
- Delete
- Remove

Midterm Review

Linked List - Other Concept



Use a dummy header to avoid strange pointer problem

Midterm Review

Linked List - Insert



```
1 Node* newPtr = malloc(sizeof(Node));  
2 newPtr -> value = 0;  
3 newPtr -> nextPtr = currPtr -> nextPtr;  
4 currPtr -> nextPtr = newPtr;
```


Midterm Review

Linked List - Insert



```
1 Node* newPtr = malloc(sizeof(Node));  
2 newPtr -> value = 0;  
3 newPtr -> nextPtr = currPtr -> nextPtr;  
4 currPtr -> nextPtr = newPtr;
```

Midterm Review


Linked List - Insert



```
1 Node* newPtr = malloc(sizeof(Node));
2 newPtr -> value = 0;
3 newPtr -> nextPtr = currPtr -> nextPtr;
4 currPtr -> nextPtr = newPtr;
```


Midterm Review

Linked List - Delete



Midterm Review

Linked List - Delete



```
1 Node* tmpPtr = currPtr -> nextPtr;  
2 currPtr -> nextPtr = tmpPtr -> nextPtr;  
3 free(tmpPtr);
```

Midterm Review

Linked List - Remove

```
1  while(ptr != NULL) {  
2      Node* nextPtr = ptr -> nextPtr;  
3      free(ptr);  
4      ptr = nextPtr;  
5  }
```

When using `malloc`, use `free` when not used.

Midterm Review

Function Pointer

```
1  struct test {  
2      void (*test_function)();  
3  };  
4  
5  void this_is_test() {  
6      printf("Hello world");  
7  }  
8  
9  // ...  
10 test->test_function = this_is_test;
```

An alternative solution of oop in C (very basic version)

Midterm Review

What else

- CP1 and CP2
- Slides
- Labs

Midterm Review

What else

- CP1 and CP2
- Slides
- Labs

Thanks for listening