

Sparse Array Toolbox

Andrew J. Milne*

*The MARCS Institute for Brain, Behaviour and Development, Western Sydney University,
NSW 2751, Australia*

1. Sparse Array Toolbox

For sparse data, sparse formats can significantly increase speed and reduce memory requirements. However, MATLAB's built-in sparse format represents only vectors and matrices. This toolbox contains a new *sparse array structure* and associated operations – outer, entrywise, and inner products, addition, summation, convolution, permutation, (circular) shifts, and distance measures – that can be applied to sparse representations of N -dimensional arrays.

A sparse array structure has the following fields: **Ind**, which is a column vector of linear indices of nonzero values in the full array that they represent; **Val**, which is a column vector of the values at those indices; **Size**, which is a row vector of the sizes of each dimension of the full array – for example, a column vector with N entries has a size of N ; a row vector with N entries has a size of $(1, N)$; a matrix with N entries has a size (J, K) , where $JK = N$; a three-way array with N entries has a size (J, K, L) , where $JKL = N$.

1.1. *array2spArray*

`spA = array2spArray(A)`: Convert a full array into a sparse array structure.

1.2. *spArray2Array*

`A = spArray2Array(spA)`: Convert a sparse array structure into a full array.

1.3. *spInd2spSub*

`subsA = spInd2spSub(spA)`: Convert a sparse array's linear index into a matrix of subscripts.

*Corresponding author. Email: a.milne@westernsydney.edu.au

1.4. *spSub2spInd*

`indC = spSub2spInd(siz,subsA)`: Convert a matrix of subscripts into a vector of the linear indices for an array of size `siz`.

1.5. *spOuter*

`spC = spOuter(varargin)`: The outer (tensor) product of full arrays, each represented as a sparse array structure (`spA`). The sparse array structures can entered as a comma separated list or as a members of a cell. The output is a sparse array structure. Calculations are performed from left to right in the list; that is, `spOuter(spA, spB, spC, spD)` corresponds to $((A \otimes B) \otimes C) \otimes D$. All singleton dimensions are collapsed: if A is a row vector of size $(1, M)$ and B is a matrix of size (N, P) , the resulting tensor has size (M, N, P) , not size $(1, M, N, P)$. The output is a sparse array structure.

1.6. *spTimes*

`spC = spTimes(varargin)`: Entrywise (Hadamard) product of full arrays and/or scalars, the former represented as sparse array structures. The arrays and scalars can be entered as a comma separated list or as a members of a cell. The output is a sparse array structure.

1.7. *spInner*

`c = spInner(varargin)`: Inner (scalar) product of two full arrays represented by sparse array structures. There are alternative definitions of ‘inner product’ for tensors/arrays. Here, it is their scalar product – the sum of entries resulting from their entrywise (Hadamard) product. The sparse arrays can entered as a comma separated list or as a members of a cell.

1.8. *spPlus*

`spC = spPlus(varargin)`: The sum of identically sized full arrays, each represented as a sparse array structure. The sparse arrays can entered as a comma separated list or as a members of a cell. The output is a sparse array structure.

1.9. *spSum*

`spC = spSum(spA,dim)`: Sum a full array, represented as a sparse array structure, over the dimension specified as a scalar in ‘dim’. The output is a sparse array structure.

1.10. *spConv*

`spC = spConv(spA,spB,shape)`: The N -dimensional convolution of two N -dimensional arrays represented as sparse array structures. The output is a sparse array structure.

`shape == ‘full’`: full convolution (default). Its size is the sum of the sizes of its arguments.

`shape == ‘same’`: central part of the convolution, same size as `spA`.

`shape == ‘circ’`: circular convolution over the size of `spA`.

1.11. *spPerm*

`spC = spPerm(spA,order)`: Permute the dimensions of the full array represented as a sparse array structure. The second argument is the vector of permutations. The output is a sparse array structure.

1.12. *spShift*

`spC = spShift(spA,shifts,isPer,isProg,collapse)`: Shift each dimension of the full array represented as a sparse array structure by the amounts specified in the integer vector `shifts`. The output is a sparse array structure.

`isPer == 1`: the shifts are circular .

`isProg == 1`: the shift for all dimensions except the last are multiplied by the index of the last dimension. For example, if the shift value for the first dimension is m , the shift of that dimension when the final dimension's index is n is mn .

`collapse == 1`: the array is summed over this last dimension.

Setting `isProg=1` and `collapse=1` is useful for converting absolute r -ad expectation tensors into relative r -ad expectation tensors.

1.13. *spCosSim*

`s = spCosSim(spA,spB)`: Cosine similarity of two vectorized full arrays, represented as sparse array structures, with same numbers of entries (`spInner`).

1.14. *spPDist*

`d = spPDist(spA,spB,p)`: The p -norm distance between two vectorized full arrays, represented as sparse array structures, with same numbers of entries.

Acknowledgements

Dr Andrew Milne is the recipient of an Australian Research Council Discovery Early Career Award (project number DE170100353) funded by the Australian Government.