

Università degli
Studi di Milano-Bicocca


PCA & Dashboards

Prof. Flavio Piccoli - Dr. Mirko Paolo Barbato

Principal Component Analysis (PCA)

- Mathematical procedure to **reduce the dimensionality** of a dataset (e.g. from 4200 variables to 5)
- dataset contains many variables correlated with each other
- PCA retains the variation present in the dataset, up to the maximum extent

Principal Component Analysis (PCA) algorithm




- Transforms the variables to a new set of variables, which are known as the **principal components** (PCs)
- PCs are orthogonal (uncorrelated) to each other
- PC ordered such that the retention of variation present in the original variables decreases as we move down in the order

Terms

- **Dimensionality**
 - is the number of random variables (features) in a dataset
- **Correlation**
 - it shows how strongly two variables are related to each other
 - it is a value in the interval $[-1, 1]$
 - high positive correlation \rightarrow variables are directly proportional
 - high negative correlation \rightarrow variables are inversely proportional

N.B.: Correlation does not imply causation!

- two variables can be highly correlated but have no relationship
- <https://www.tylervigen.com/spurious-correlations>



- **Orthogonal variables**
 - uncorrelated to each other
 - correlation between any pair of variables is 0

Eigenvectors and eigenvalues

- **Eigenvectors**

- Consider a non-zero vector v
- v is an eigenvector of a square matrix A , if Av is a scalar multiple of v , i.e:

$$Av = \lambda v$$

A diagram showing the equation $Av = \lambda v$. Arrows point from the labels to the corresponding parts of the equation: 'Matrix' points to A , 'Eigenvector' points to v (under the first v), and 'Eigenvalue' points to λ .

- where v is the eigenvector and λ is the eigenvalue associated to it.

Example:

For this matrix, $\begin{bmatrix} -6 & 3 \\ 4 & 5 \end{bmatrix}$, an eigenvector is $\begin{bmatrix} 1 \\ 4 \end{bmatrix}$ with a matching eigenvalue of 6. Let's check if it is true.

The calculation is shown as follows: $\begin{bmatrix} -6 & 3 \\ 4 & 5 \end{bmatrix} \begin{bmatrix} 1 \\ 4 \end{bmatrix} = \begin{bmatrix} -6 \times 1 + 3 \times 4 \\ 4 \times 1 + 5 \times 4 \end{bmatrix} = \begin{bmatrix} 6 \\ 24 \end{bmatrix} = 6 \begin{bmatrix} 1 \\ 4 \end{bmatrix}$. The matrix is enclosed in a green box and labeled 'matrix' with a green arrow. The eigenvector $\begin{bmatrix} 1 \\ 4 \end{bmatrix}$ is enclosed in a red box and labeled 'eigenvector' with a red arrow. The scalar 6 is enclosed in a purple box and labeled 'eigenvalue' with a purple arrow. A red arrow also points from the 'eigenvector' label to the final $\begin{bmatrix} 1 \\ 4 \end{bmatrix}$ in the result.

How do we find eigenvectors and eigenvalues?

- We start by finding the eigenvalue. Remember that:

$$Av = \lambda v$$

- We can put an identity matrix in the right part:

$$Av = \lambda Iv$$

- Bring everything in the left side:

$$Av - \lambda Iv = 0$$

- If v is hopefully non-zero, we can solve for λ using the determinant:

$$|A - \lambda I| = 0$$

Finding the eigenvalues

- If v is hopefully non-zero, we can solve for λ using the determinant:

$$|A - \lambda I| = 0$$

- Let's try with previous matrix:

$$\left| \begin{bmatrix} -6 & 3 \\ 4 & 5 \end{bmatrix} - \lambda \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \right| = 0$$

- Computing products and subtractions we obtain:

$$\begin{vmatrix} -6 - \lambda & 3 \\ 4 & 5 - \lambda \end{vmatrix} = 0$$

- Finally, we compute the determinant

$$(-6 - \lambda)(5 - \lambda) - 3 \times 4 = 0$$

Finding the eigenvalues

- Simplifies to:

$$\lambda^2 + \lambda - 42 = 0$$

- Solving, we obtain:

$$\lambda = -7 \text{ or } 6$$

- These are two possible eigenvalues!
- Now, let's find the associated eigenvectors

Finding the eigenvectors

- Let's start by finding the eigenvector associated to the eigenvalue $\lambda = 6$
- We insert the eigenvector as unknown and solve the system to determine its values

$$\begin{bmatrix} -6 & 3 \\ 4 & 5 \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} = 6 \begin{bmatrix} x \\ y \end{bmatrix}$$

- Solving, we obtain:

$$-6x + 3y = 6x$$

$$4x + 5y = 6y$$

- Taking everything on the left side:

$$-12x + 3y = 0$$

$$4x + 5y = 0$$

- Both equations show that:

$$y = 4x$$

Finding the eigenvectors

- So, for the eigenvalue $\lambda = 6$ there are many eigenvectors associated that respect the eq. $y = 4x$, e.g.:

$$\begin{bmatrix} 1 \\ 4 \end{bmatrix}, \begin{bmatrix} 2 \\ 8 \end{bmatrix} \text{ and } \begin{bmatrix} 3 \\ 12 \end{bmatrix}$$

- Find the eigenvectors associated with the eigenvalue $\lambda = -7$

Finding the eigenvectors

- So, for the eigenvalue $\lambda = 6$ there are many eigenvectors associated that respect the eq. $y = 4x$, e.g.:

$$\begin{bmatrix} 1 \\ 4 \end{bmatrix}, \begin{bmatrix} 2 \\ 8 \end{bmatrix} \text{ and } \begin{bmatrix} 3 \\ 12 \end{bmatrix}$$

- Find the eigenvectors associated with the eigenvalue $\lambda = -7$

$$x = -3y$$

$$\begin{bmatrix} -3 \\ 1 \end{bmatrix}, \begin{bmatrix} -6 \\ 2 \end{bmatrix}, \begin{bmatrix} -9 \\ 3 \end{bmatrix}, \dots$$

PCA

1. Normalize the data (standardization)
2. Calculate the covariance matrix (suppose only two variables x_1 and x_2)

$$\text{Matrix}(\text{Cov}) = \begin{bmatrix} \text{Var}[X_1] & \text{Cov}[X_1, X_2] \\ \text{Cov}[X_2, X_1] & \text{Var}[X_2] \end{bmatrix}$$

3. Calculate eigenvalues and eigenvectors of the covariance matrix
4. Order eigenvalues from largest to smallest (so that it gives the components in order of significance).
 - a. dataset with n variables \rightarrow n eigenvalues, n eigenvectors
 - b. **We can reduce the number of variables by keeping only the most important**
5. Create a matrix composed by the corresponding eigenvectors


$$\text{FeatureVector} = \begin{bmatrix} eig_1 \\ eig_2 \end{bmatrix}$$

PCA

6. Get principal components of data




$$NewData = FeatureVector^T \times ScaledData^T$$

FeatureVector is also called **rotation matrix** as it changes the axis:




PCA

FeatureVector is also called **rotation matrix** as it changes the axis:



PCA for feature reduction

It is possible to use PCA to get rid of useless features



PCA in Python

- Sklearn package offer convenient function to compute PCA

```
sklearn.decomposition.PCA( n_components = ... )
```


- **n_components** can be:
 - **a float**: specifies the retained variance to keep
 - **an integer**: specifies the number of principal components to keep
- It follows the schema of all sklearn objects
 - **fit**: train the object on the specified data
 - **transform**: use the fitted object on new data
 - **fit_transform**: performs both the operations together

Exercise 1 - Mastering PCA

1. Download the validation set of the Lucas dataset (file `lucas_dataset_val.csv`)
2. Compute the PCA of this set
 - Use a retained variance of 0.9.
 - Print the number of principal components survived.
3. Invert the PCA transformation (*`pca.inverse_transform`*)
4. Plot the first original sample together with the same sample inverted (*with `Matplotlib`*)
5. Repeat the process with a retained variance of 0.99, then with 0.9999. Finally, try with only one component.


Exercise 1 - Mastering PCA

1. Download the validation set of the Lucas dataset (file `lucas_dataset_val.csv`)
2. Compute the PCA of this set
 - Use a retained variance of 0.9.
 - Print the number of principal components survived.
3. Invert the PCA transformation
4. Plot the first original sample together with the same sample inverted
5. Repeat the process with a retained variance of 0.99, then with 0.9999. Finally, try with only one component.



Dashboarding

R&D process



Deployment

How to provide the service?

Three strategies:

- **As-a-Service:** your forecasting model will be provided as a remote service
- **Product Integration:** your model will be integrated inside a product
- **Standalone product:** your method will be a product itself dispensed through a dashboard

Streamlit

- It offers a powerful set of layouts and widgets
- useful for creating a highly-interactive GUI
- To install streamlit:

```
pip install streamlit
```


- You can search streamlit components on Streamlit itself! ***inception***



Streamlit Components Hub




Newcomers



<https://components.streamlit.app/>

Layouts

Sidebar



Lorem ipsum dolor sit amet

Consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Diam quis enim lobortis scelerisque fermentum dui faucibus in. Pharetra magna ac placerat vestibulum lectus mauris ultrices.

Adipiscing elit dui tristique sollicitudin. Velit aliquet sagittis id consectetur purus ut faucibus pulvinar.

Tincidunt lobortis

Feugiat vivamus ut augue eget arcu dictum. Sed risus pretium quam vulputate. Cursum in hac habitasse platea dictumst. Aliquam ultrices sagittis orci a.

Non diam phasellus vestibulum

Vel quam elementum pulvinar etiam. Blandit volutpat maecenas volutpat blandit aliquam. Est sit amet facilis magna etiam tempor orci eu lobortis.

- Ut pharetra sit amet aliquam id.
- Etiam tempor orci eu lobortis elementum nibh tellus molestie nunc.
- Sed enim ut sem viverra aliquet eget sit.
- Duis at consectetur lorem donec massa sapien faucibus et molestie.

Sem integer vitae justo eget. In egestas erat imperdiet sed euismod nisi porta lorem mollis. Eu feugiat pretium nibh ipsum consequat nisi vel pretium. Elit ut aliquam purus sit amet. Aliquet nibh praesent tristique magna sit. Dapibus ultrices in iaculis nunc.

Enim eu turpis egestas pretium aenean pharetra. Nunc sed blandit libero volutpat sed cras ornare arcu. Etiam erat velit scelerisque in. Purus semper eget dui at tellus at urna condimentum mattis. Sapien

Columns

Lorem ipsum dolor sit amet

Consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Diam quis enim lobortis scelerisque fermentum dui faucibus in. Pharetra magna ac placerat vestibulum lectus mauris ultrices.




Sem integer vitae justo eget. In egestas erat imperdiet sed euismod nisi porta lorem mollis. Eu feugiat pretium nibh ipsum consequat nisi vel pretium. Elit ut aliquam purus sit amet. Aliquet nibh praesent tristique magna sit. Dapibus ultrices in iaculis nunc.

Enim eu turpis egestas pretium aenean pharetra. Nunc sed blandit libero volutpat sed cras ornare arcu. Etiam erat velit scelerisque in. Purus semper eget dui at tellus at urna condimentum mattis. Sapien

Tabs

Lorem ipsum dolor sit amet

Consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Diam quis enim lobortis scelerisque fermentum dui faucibus in. Pharetra magna ac placerat vestibulum lectus mauris ultrices.



Sem integer vitae justo eget. In egestas erat imperdiet sed euismod nisi porta lorem mollis. Eu feugiat pretium nibh ipsum consequat nisi vel pretium. Elit ut aliquam purus sit amet. Aliquet nibh praesent tristique magna sit. Dapibus ultrices in iaculis nunc.

Enim eu turpis egestas pretium aenean pharetra. Nunc sed blandit libero volutpat sed cras ornare arcu. Etiam erat velit scelerisque in. Purus semper eget dui at tellus at urna condimentum mattis. Sapien

```
import streamlit as st
```

```
with st.sidebar:
```

```
    add_radio = st.radio(
        "Choose a shipping method",
        ("Standard", "Express")
    )
```

```
import streamlit as st
```

```
col1, col2 = st.columns(2)
```

```
with col1:
    st.header("A cat")
    st.image("https://static.streamlit.io/cat.jpg")
```

```
with col2:
    st.header("A dog")
    st.image("https://static.streamlit.io/dog.jpg")
```

```
import streamlit as st
```

```
tab1, tab2 = st.tabs(["Cat", "Dog"])
```

```
with tab1:
    st.header("A cat")
    st.image("./cat.jpg", width=200)
```


```
with tab2:
    st.header("A dog")
    st.image("./dog.jpg", width=200)
```

Layouts

Expander

Lorem ipsum dolor sit amet

Consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Diam quis enim lobortis scelerisque fermentum dui [faucibus in](#). Pharetra magna ac placerat vestibulum lectus mauris ultrices.



Sem integer vitae justo eget. In egestas erat imperdiet sed euismod nisi porta lorem mollis. Eu feugiat pretium nibh ipsum consequat nisl vel pretium. Eit ut aliquam purus sit amet. Aliquet nibh praesent tristique magna sit. Dapibus ultrices in iaculis nunc.

Enim eu turpis egestas pretium aenean pharetra. Nunc sed blandit libero volutpat sed cras ornare arcu. Etiam erat velit scelerisque in. Purus semper eget dui at tellus at urna condimentum mattis. Sapien

Quibus in convallis in dui et tempus. Quibus in convallis in dui et tempus. Quibus in convallis in dui et tempus.


```
import streamlit as st
```

```
with st.expander("See explanation"):  
    st.write("Here it is")
```

Container

Lorem ipsum dolor sit amet

Consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Diam quis enim lobortis scelerisque fermentum dui [faucibus in](#). Pharetra magna ac placerat vestibulum lectus mauris ultrices.



Sem integer vitae justo eget. In egestas erat imperdiet sed euismod nisi porta lorem mollis. Eu feugiat pretium nibh ipsum consequat nisl vel pretium. Eit ut aliquam purus sit amet. Aliquet nibh praesent tristique magna sit. Dapibus ultrices in iaculis nunc.

Enim eu turpis egestas pretium aenean pharetra. Nunc sed blandit libero volutpat sed cras ornare arcu. Etiam erat velit scelerisque in. Purus semper eget dui at tellus at urna condimentum mattis. Sapien

Quibus in convallis in dui et tempus. Quibus in convallis in dui et tempus. Quibus in convallis in dui et tempus.

```
import streamlit as st
```

```
with st.container():  
    st.write("This is inside the container")
```

Prints

In streamlit it is very easy to print everything, especially Pandas dataframes

```
import streamlit as st
```

```
# print a number or a string  
st.write(1234)
```

```
# print a Pandas dataframe  
st.write(pd.DataFrame({  
    'first column': [1, 2, 3, 4],  
    'second column': [10, 20, 30, 40],  
}))  
# you can also use st.dataframe
```

```
# print latex equation  
st.latex(r'\mu = \frac{1}{N} \sum_{n=1}^N e_n')
```

1234

	first column	second column
0	1	10
1	2	20
2	3	30
3	4	40

$$\mu = \frac{1}{N} \sum_{n=1}^N e_n$$

Prints

It's also possible to print json files

```
import streamlit as st
```

```
st.json({  
    'foo': 'bar',  
    'baz': 'boz',  
    'stuff': [  
        'stuff 1',  
        'stuff 2',  
        'stuff 3',  
        'stuff 5',  
    ],  
})
```

```
{  
  "foo" : "bar"  
  "baz" : "boz"  
  "stuff" : [  
    0 : "stuff 1"  
    1 : "stuff 2"  
    2 : "stuff 3"  
    3 : "stuff 5"  
  ]  
}
```

metrics

```
import streamlit as st
```

```
st.metric( label="Temperature",  
           value="70 °F",  
           delta="1.2 °F")
```

Temperature

70 °F

↑ 1.2 °F

Plotting

Plotting is extremely easy as well

```
import streamlit as st
import pandas as pd
import numpy as np
```

```
chart_data = pd.DataFrame(
    np.random.randn(20, 3),
    columns=['a', 'b', 'c'])
```

```
st.line_chart(chart_data)
```




Plotting geographical data





```
import streamlit as st
import pandas as pd
import numpy as np
```

```
df = pd.DataFrame(
    np.random.randn(1000, 2) / [50, 50] + [37.76, -122.4],
    columns=['lat', 'lon'])
```

```
st.map(df)
```



Inputs


 <p>A time input widget with a label "Set an alarm for" and a text field containing "08:45". A mouse cursor is pointing at the text field.</p>	 <p>A file uploader widget with the label "Choose a CSV file". It features a cloud icon, the text "Drag and drop file here", a subtext "Limit 200MB per file", and a "Browse files" button. A mouse cursor is pointing at the drop area.</p>	 <p>A camera input widget showing a live video feed of a person's face. Above the feed is the text "Take picture or upload an image". Below the feed is a "Take photos" button. A mouse cursor is pointing at the video feed.</p>	 <p>A color picker widget showing a color selection interface with a gradient bar, a selected color swatch, and a text field displaying the hex code "#4F7942". A mouse cursor is pointing at the color bar. Below the text field is the label "HEX".</p>
Time input Display a time input widget.	File Uploader Display a file uploader widget.	Camera input Display a widget that allows users to upload images directly from a camera.	Color picker Display a color picker widget.
<pre>time = st.time_input("Meeting</pre>	<pre>data = st.file_uploader("Uploa</pre>	<pre>image = st.camera_input("Take</pre>	<pre>color = st.color_picker("Pick</pre>

Caching

- Data and objects that do not need to be updated can be loaded in a function with
 - `@st.cache_data` or
 - `@st.cache_resource` decorator


`st.cache_data`

anything you *CAN* store in a database



`st.cache_resource`

anything you *CAN'T* store in a database



Example:

```
@st.cache_data
def load_data(fn):
    # read csv
    df = pd.read_csv(fn)
    # return
    return df
```

Maintaining the state

- Variables (except the ones associated to widgets) are reset at each interaction.
- This does not include dataframes and variables loaded from cache
- To make the system stateful
 - you can use the dictionary **st.session_state**

without state, it does not update the value up to 1

```
import streamlit as st
```

```
# define variable
```

```
my_var = 0
```

```
# if button is clicked, increment variable
```

```
if st.button('Increment the variable'):  
    my_var += 1
```

```
# display variable
```

```
st.text(f'Variable value: {my_var}')
```

Increment the variable

Variable value: 1

with state, it works as expected

```
import streamlit as st
```

```
# if variable is not in session state, initialize it
```

```
if 'my_var' not in st.session_state:  
    st.session_state['my_var'] = 0
```

```
# if button is clicked, increment variable
```

```
if st.button('Increment the variable'):  
    # increment variable  
    st.session_state['my_var'] += 1
```

```
# display variable
```

```
st.text(f'Variable value: {st.session_state["my_var"]}')
```

Increment the variable

Variable value: 20

First example - simple calculator

Let's create a simple app that reads two numeric values, an operation and prints the output

```
import streamlit as st

# define the first operand
first_number = st.number_input('First operand', value=50, step=10)

# define operation selector
operation = st.radio(
    "Choose the operation",
    ['sum', 'subtraction']
)

# define the second operand
second_number = st.number_input('Second operand', value=10, step=10)

# compute operation
if operation == 'sum':
    res = first_number + second_number
else:
    res = first_number - second_number

# print output
st.text(f'The result of the {operation} is {res}')
```

- Start it with `streamlit run calculator.py`

First example - simple calculator

Let's create a simple app that reads two numeric values, an operation and prints the output

```
import streamlit as st
```

```
# define the first operand  
first_number = st.number_input('First operand', value=50, step=10)
```

```
# define operation selector  
operation = st.radio(  
    "Choose the operation",  
    ['sum', 'subtraction']  
)
```

```
# define the second operand  
second_number = st.number_input('Second operand', value=10, step=10)
```

```
# compute operation  
if operation == 'sum':  
    res = first_number + second_number  
else:  
    res = first_number - second_number
```

```
# print output  
st.text(f'The result of the {operation} is {res}')
```

First operand

50 - +

Choose the operation

☒ sum

☐ subtraction

Second operand

10 - +

The result of the sum is 60

First operand

50 - +

Choose the operation

☐ sum

☒ subtraction

Second operand


10 - +

The result of the subtraction is 40

- Start it with `streamlit run calculator.py`

Exercise 2 - data visualization

- For this example, you will need to use UNIMIB's virtual machine
- Goal: create a dashboard for visualizing the LUCAS dataset
- Layout: two columns, as shown in picture
- On left column:
 - a file uploader where the user will drop a CSV file containing part of the LUCAS dataset
 - a selectbox where the user will choose the soil variable that will be displayed on the map
- On the right column:
 - the map (use the function inside the file on eLearning)



Exercise 3 - PCA manipulation

- Goal: create a dashboard for visualizing the principal components of the LUCAS dataset
- Download the partial file and follow the instructions (#todo: lines)

PCA hyperspectral

