Real-time Entropic Event Detection.

Andrew James Reagan,[1,*] Suma Desu,[1,†] and Jake Williams[1,‡]

[1] *Department of Mathematics and Statistics, Center for Complex Systems, Computational Story Lab, & the Vermont Advanced Computing Core, University of Vermont, Burlington, VT, 05401*

(Dated: May 30, 2013)

Reporting of events through aggregate social media has become increasingly important. Recent crises have highlighted this trend, with the extensive use of Twitter and Reddit for news and crowdsourcing in the Boston Marathon bombings of April 2013. Building on the text partitioner of Williams et. al. [**?**], we develop a method of findi ng and classifying stories in real time text. This "storyfinder" computes entropy and ambient valence of phrases, then shifts these measures on individual phrases over time to detect which stories are driving significant changes in langauge use [**?**] . An attempt to implement this method on Twitter during the week of the 2013 Boston Marathon serves as a case st udy on the effectiveness of this method. With access to the real-time Twitter feed, this measure can hopefully be fully tested and built into a useful distributed news finder.

PACS numbers:

The advent of the internet brought forth the ability to share information with others in unprecedented time, and advancements in technology, like external storage, have revolutionized our access to knowledge. This nexus of limitless storage and real time capabilities has created a wealth of non-traditional forms of data that are decentralized, social, and crowd sourced. This presents a new challenge of how to store, quantify, and make sense of these new data sources. The democratization of information has culminated today in a dynamic crowd sourced encyclopeida vaster than anything before (Wikipeida.org), and in the social realm, social media sites Twitter and Facebook have created a wealth of social interaction data. Since sharing in these mediums, is not subject to linguistic of grammatical framework, it reveals organic interactions and highlights topics which matter to individuals. On Twitter, in particular, more voices are being heard than ever before with more than 500 million people generating over 340 million messages per day [citation needed - pew state of the twitter study?]. This data has been leveraged in the past to crush hard problems (FoldIt) [PNAS or science reference] and digitize all books (ReCaptcha) [citation needed] .

Alongside these efforts, we seek to use text shared on Twitter to detect any collapse in language, or convergence on some particular topic, thereby computationally detecting the stories and topics that are being reported by individual users and shared across the network. Unlike traditionally news websites which fact check, write, rewrite, edit and then report, our news is reported by the people as soon as it is detected. We call this distributed news, and the aggregate tool the 'storyfinder.' After outlining the methods, which include partitioning texts into meaningful units developed by Williams et all [citation], and define our measures of conditional entropy [citation needed] and ambient valence [citation needed], we present the results of the storyfinder for one week of Twitter data surrounding the 2013 Boston Marathon bombings.

Partitioning Text:

Before we can analyze the patterns in information being shared, we need to break down large texts into their meaningful units. We rely on a method developed by Williams et al.[citation needed]. First we create a probability distribution of all possible phrases in a text based on frequency of appearance in that text. We then go back and partition the same text using that probability distribution to find the optimal partition of phrases. It is important to note that the probability distribution represents the same text, such that all necessary phrases are included. It is also important to note, that the partitions are completely disjoint and span the entire text.

Are equations/ diagrams needed here?!

Computing Entropy of Phrases

Once we have a partition of meaningful units of language, we can look at the context in which these units appear. We focus on the entropy of a phrase, which is computed within its local context (or clauses) using Shannon's entropy. A plunge in entropy indicates a collapse of language around central topics, indicating a possible story.

For a phrase p, let N_p be the count of p, let $\{c_p\}$ be all of the neighborhoods of p, let N_{c_p} be the count of neighborhood c_p and then we define the entropy E_p as

$$E_p = -\sum_{c_p} N_{c_p} \log_2 \left(N_p / N_{c_p} \right) .$$

It is then necessary to normalize this over the sum of the neighborhoods so that we are getting at the probability of each neighborhood, so we set

$$E_p = E_p / \sum_{c_p} N_{c_p} .$$

Typeset by REVTEX



FIG. 1: The valence and ambient valence of words in the LabMT set.



FIG. 2: An example entropy shift shows each of the ways that a phrase can contribute to a changing entropy.

For a phrase, the value of entropy is limited by the frequency of appearance of the phrase. Furthermore, since this measure of entropy is conditioned on a reference text, its entropy of a particular phrase is further limited the by length of the reference text. In our case, we compare the current fifteen minutes of tweets to the past fifteen minutes of tweets. By only using the fifteen minutes prior, we can pick up a diurnal cycle as well as find the shapes of stories.

note: do we need to perform experiments to validate the choice of a 15 minute window?

Computing Ambient Valence of Phrases

The LabMT dataset provided by Dodds et. al. [**?**] contains 10222 words with happiness scores on a 1 to 9 scale, averaged over 50 independent ratings through Mechanical Turk. To extend the valence scores on words into scores on phrases, we compute the ambient valence of a phrase p be averaging the scores of all the words surrounding this phrase for which we have scores. The correlation between valence and ambient valence of words in the LabMT set in Figure 1 provides some evidence for the validity of this scoring, showing a positive trend with correlation $\rho = .51$.

We next will perform a validation of the choice for $\Delta h = 0$ for this application via a timeseries correlation, in addition to the LabMT word correlations presented as in Figure 1, which we include in the supplementary for more choices of Δh.

Shifting Phrases Measures Against a Reference

When a significant change in the entropy or valence of langauge occurs, we desire to find the phrases most responsible for this change to indicate the event. The difficulty here is that specific phrases can contribute to changes in entropy and valence in many ways, since the entropy and valence of that phrase can change. For valence, this shift is written as

$$h_{\text{avg}}^{(\text{comp})} - h_{\text{avg}}^{(ref)} \tag{1}$$

where $h_{\text{avg}}^{(\text{comp})}$ is the valence of the text in question and $h_{\text{avg}}^{(\text{ref})}$ is the valence of the reference text.

There are many ways to break down equation **??**, and what we find to give the most insightful breakdown of contributions is analogous to the 2-dimensional derivative. This is writing Eq 1 as, for each word w with happiness h_w and probability of appearance $P(w)$,

$$\sum_w \left(h_w^{(\text{comp})} - h_w^{(\text{ref})}\right)\left(P(w)^{(\text{comp})} - P(w)^{(\text{ref})}\right). \tag{2}$$

This is represented by Figure 2 for the top bar for each word, as the total contribution to the change in valence by that word. The two bars below represent the two ways in which a word shifted the signal: from a change in valence in the text, and from a change in frequency. The dashed bars represent the change in frequency, and the solid bars represent the change in frequency. Color indicated whether, relative to the comparison text, the phrase is above the average (whether it is happy). We are able to show the two bars by rewriting the sum above

into two terms in the following equation:

$$\sum_w h_w^{(\mathrm{comp})} \left(P(w)^{(\mathrm{comp})} - P(w)^{(\mathrm{ref})} \right) + \sum_w \left(h_w^{(\mathrm{comp})} - h_w^{(\mathrm{ref})} \right) P(w)^{(\mathrm{comp})}.$$

Preliminary Results with Twitter Data

Applying the above methodology to data from Twitter's Streaming API during the week of the Boston Marathon we hope to be able to see the events that took place through this lens. An example timeseries in Figure 3 for the six days ranging from April 18 through April 26 provides a picture of what we measure for entropy and valence over the week. The entropy and valence shifts below correspond to shifting the most recent 15 minutes of Twitter data against the 15 minutes prior. Choosing the window with which to bin tweets, and the reference text are important future considerations. Our current setup is shifting the current 15 minutes against the previous day, and future experiments will attempt to optimally combine reference texts for the option of attempting to remove the daily cycles that do not represent large events. Note the inaccuracies in the data of Figure 3 in the caption, but notice that we do see two significant downward spikes in entropy on April 19. We'll zoom in on those.

* Electronic address: `andrew.reagan@uvm.edu`
† Electronic address: `Suma.Desu@uvm.edu`
‡ Electronic address: `jakerylandwilliams@gmail.com`



FIG. 3: April 18 through April 26 on Twitter, with shifts plotted for the most recent 15 minutes against the 15 minutes prior. Some of the variations are artifacts of this being a work in progress, and halting our current experiment for hedonometer.org (check it out!): namely the downward spike in the middle of April 25th, and the upward valence bubble near the end are not accurate.



FIG. 4: Looking at the length two shifts when we see the first downward spike on Apr 19. The words make the story clear, and we recognize that this is the time at which the first bomber was caught.



FIG. 5: The same time as 5, looking at length 4 sequences.



FIG. 6: The all valence shift for the second dip in entropy, later on the 19th, about 10PM. The word shifts show us that this is when the final suspect is caught.



FIG. 7: The same time as 6, looking at the 2-grams. The cool thing here is, as I mentioned during my presentation, we pick up "franklin street", the location of the shootout, which was at the time classified information.