<!-- BEGIN_TF_DOCS -->

Terraform Reference

This file is generated from the root Terraform module by `terraform-docs`. Update the Terraform files, then regenerate this document instead of editing it by hand.

Requirements

Name	Version
terraform	>= 1.9, < 2.0
azapi	~> 2.0
azuread	~> 3.0
azurerm	~> 4.0
random	~>3.0

Providers

Name	Version
azapi	2.12.0
azurerm	4.81.0

Modules

Name	Source	Version
acr	git::https://github.com/andyxuan2010/azure-template.git//modules/acr	2e0d476c1e80c327162ff59147bff16454e4af3d
adf_basic	git::https://github.com/andyxuan2010/azure-template.git//modules/adf	2e0d476c1e80c327162ff59147bff16454e4af3d
aks	git::https://github.com/andyxuan2010/azure-template.git//modules/aks	2e0d476c1e80c327162ff59147bff16454e4af3d
app_registration_appservice	git::https://github.com/andyxuan2010/azure-template.git//modules/appregistration	2e0d476c1e80c327162ff59147bff16454e4af3d
app_service	git::https://github.com/andyxuan2010/azure-template.git//modules/appservice	2e0d476c1e80c327162ff59147bff16454e4af3d
app_service_plan	git::https://github.com/andyxuan2010/azure-template.git//modules/appserviceplan	2e0d476c1e80c327162ff59147bff16454e4af3d
automation_account	git::https://github.com/andyxuan2010/azure-template.git//modules/automationaccount	2e0d476c1e80c327162ff59147bff16454e4af3d
azure_ai_search	git::https://github.com/andyxuan2010/azure-template.git//modules/azure_ai_search	2e0d476c1e80c327162ff59147bff16454e4af3d
azure_ai_service	git::https://github.com/andyxuan2010/azure-template.git//modules/azure_ai_service	2e0d476c1e80c327162ff59147bff16454e4af3d
databricks	git::https://github.com/andyxuan2010/azure-template.git//modules/databricks	2e0d476c1e80c327162ff59147bff16454e4af3d
fortigate	git::https://github.com/andyxuan2010/azure-template.git//modules/fortigate	2e0d476c1e80c327162ff59147bff16454e4af3d
hub_virtual_network	git::https://github.com/andyxuan2010/azure-template.git//modules/vnet	2e0d476c1e80c327162ff59147bff16454e4af3d
keyvault	git::https://github.com/andyxuan2010/azure-template.git//modules/keyvault	2e0d476c1e80c327162ff59147bff16454e4af3d
linux_vm_basic	git::https://github.com/andyxuan2010/azure-template.git//modules/linuxvm	2e0d476c1e80c327162ff59147bff16454e4af3d
log_analytics	git::https://github.com/andyxuan2010/azure-template.git//modules/loganalytics	2e0d476c1e80c327162ff59147bff16454e4af3d
mg_landingzone	git::https://github.com/andyxuan2010/azure-template.git//modules/managementgroups	2e0d476c1e80c327162ff59147bff16454e4af3d

Name	Source	Version
mg_landingzone_children	git::https://github.com/andyxuan2010/azure-template.git//modules/managementgroups	2e0d476c1e80c327162ff59147bff16454e4af3d
mg_platform	git::https://github.com/andyxuan2010/azure-template.git//modules/managementgroups	2e0d476c1e80c327162ff59147bff16454e4af3d
mg_platform_children	git::https://github.com/andyxuan2010/azure-template.git//modules/managementgroups	2e0d476c1e80c327162ff59147bff16454e4af3d
mg_sandboxes	git::https://github.com/andyxuan2010/azure-template.git//modules/managementgroups	2e0d476c1e80c327162ff59147bff16454e4af3d
network_security_group	git::https://github.com/andyxuan2010/azure-template.git//modules/nsg	2e0d476c1e80c327162ff59147bff16454e4af3d
openai	git::https://github.com/andyxuan2010/azure-template.git//modules/openai	2e0d476c1e80c327162ff59147bff16454e4af3d
private_dns	git::https://github.com/andyxuan2010/azure-template.git//modules/private_dns	2e0d476c1e80c327162ff59147bff16454e4af3d
resource_group	git::https://github.com/andyxuan2010/azure-template.git//modules/rg	2e0d476c1e80c327162ff59147bff16454e4af3d
spoke_virtual_network	git::https://github.com/andyxuan2010/azure-template.git//modules/vnet	2e0d476c1e80c327162ff59147bff16454e4af3d
sqldb	git::https://github.com/andyxuan2010/azure-template.git//modules/sqldb	2e0d476c1e80c327162ff59147bff16454e4af3d
static_web_app	git::https://github.com/andyxuan2010/azure-template.git//modules/staticwebapp	2e0d476c1e80c327162ff59147bff16454e4af3d
storage_account	git::https://github.com/andyxuan2010/azure-template.git//modules/storageaccount	2e0d476c1e80c327162ff59147bff16454e4af3d
subscription_vending	git::https://github.com/andyxuan2010/azure-template.git//modules/subscription_vending	2e0d476c1e80c327162ff59147bff16454e4af3d
winvm_basic	git::https://github.com/andyxuan2010/azure-template.git//modules/winvm	2e0d476c1e80c327162ff59147bff16454e4af3d

Resources

Name	Type
azapi_resource.automation_ari_runtime_package (https://registry.terraform.io/providers/Azure/azapi/latest/docs/resources/resource)	resource
azapi_resource.shared_storage_container (https://registry.terraform.io/providers/Azure/azapi/latest/docs/resources/resource)	resource
azapi_resource.shared_storage_container_immutability_policy (https://registry.terraform.io/providers/Azure/azapi/latest/docs/resources/resource)	resource
azapi_update_resource.storage_account_blob_service (https://registry.terraform.io/providers/Azure/azapi/latest/docs/resources/update_resource)	resource
azurerm_automation_job_schedule.automation_ari (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/automation_job_schedule)	resource
azurerm_automation_runbook.automation_ari (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/automation_runbook)	resource
azurerm_automation_runtime_environment.automation_ari (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/automation_runtime_environment)	resource
azurerm_automation_schedule.automation_ari (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/automation_schedule)	resource
azurerm_key_vault_secret.linux_vm_admin_override (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/key_vault_secret)	resource
azurerm_role_assignment.automation_account_key_vault_secrets_officer (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/role_assignment)	resource
azurerm_role_assignment.automation_account_storage_blob_data_contributor (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/role_assignment)	resource
azurerm_role_assignment.linux_vm_app_service_website_contributor (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/role_assignment)	resource
azurerm_storage_container.automation_ari (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/storage_container)	resource
azurerm_subnet_network_security_group_association.spoke_network_security_group (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/subnet_network_security_group_association)	resource

Name	Type
azurerm_virtual_network_peering.hub_to_spoke (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/virtual_network_peering)	resource
azurerm_virtual_network_peering.spoke_to_hub (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/resources/virtual_network_peering)	resource
azurerm_client_config.current (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/data-sources/client_config)	data source
azurerm_key_vault.sql_iac (https://registry.terraform.io/providers/hashicorp/azurerm/latest/docs/data-sources/key_vault)	data source

Inputs

Name	Description	Type	Default	Required
acr_admin_enabled	Whether the ACR admin user is enabled.	`bool`	`false`	no
acr_anonymous_pull_enabled	Whether anonymous pull access is enabled for ACR.	`bool`	`false`	no
acr_customer_managed_key_id	Optional Key Vault key ID used to encrypt ACR.	`string`	`null`	no
acr_customer_managed_key_identity_client_id	Optional user-assigned identity client ID used with the ACR customer-managed key.	`string`	`null`	no
acr_data_endpoint_enabled	Whether dedicated ACR data endpoints are enabled.	`bool`	`false`	no
acr_diagnostic_log_categories	Diagnostic log categories to enable for ACR.	`list(string)`	["ContainerRegistryRepositoryEvents", "ContainerRegistryLoginEvents"]	no
acr_diagnostic_metric_categories	Diagnostic metric categories to enable for ACR.	`list(string)`	["AllMetrics"]	no
acr_enable_diagnostics	Whether to send ACR diagnostics to the shared Log Analytics workspace.	`bool`	`false`	no
acr_enable_network_rule_set	Whether to configure ACR network rules.	`bool`	`false`	no
acr_enable_private_endpoint	Whether to create a private endpoint for ACR.	`bool`	`false`	no
acr_export_policy_enabled	Whether the ACR export policy is enabled.	`bool`	`true`	no
acr_georeplications	Optional ACR georeplication locations.	list(object({ location = string regional_endpoint_enabled = optional(bool, true) zone_redundancy_enabled = optional(bool, false) tags = optional(map(string), {}) }))	`[]`	no
acr_identity_ids	User-assigned managed identity IDs for ACR when acr_identity_type includes UserAssigned.	`list(string)`	`[]`	no

Name	Description	Type	Default	Required
acr_identity_type	Managed identity type for ACR.	`string`	`"None"`	no
acr_managed_identity_role_assignments	Role assignments to apply to the ACR system-assigned managed identity.	map(object({ scope = string role_definition_name = optional(string) role_definition_id = optional(string) }))	`{}`	no
acr_name	Optional base name override for the Azure Container Registry. The ACR module adds the acr prefix, region, environment, and numeric suffix.	`string`	`""`	no
acr_network_rule_bypass_option	Bypass option for the ACR network rule set.	`string`	`"AzureServices"`	no
acr_network_rule_default_action	Default action for the ACR network rule set.	`string`	`"Deny"`	no
acr_network_rule_ip_rules	Optional public IP CIDR ranges allowed by ACR network rules.	`list(string)`	`[]`	no
acr_private_dns_zone_id	Optional private DNS zone ID for the ACR private endpoint. Leave empty to use privatelink.azurecr.io from the landing zone private DNS module when present.	`string`	`""`	no
acr_private_dns_zone_name	Optional existing private DNS zone name used for ACR private endpoint lookup when acr_private_dns_zone_id is not set.	`string`	`""`	no
acr_private_dns_zone_resource_group_name	Optional resource group containing acr_private_dns_zone_name.	`string`	`""`	no
acr_public_network_access_enabled	Whether public network access is enabled for ACR.	`bool`	`false`	no
acr_quarantine_policy_enabled	Whether the ACR quarantine policy is enabled.	`bool`	`false`	no
acr_retention_policy_in_days	Days to retain untagged manifests before purge. Supported only on Premium SKU.	`number`	`null`	no
acr_sku	SKU for the Azure Container Registry.	`string`	`"Premium"`	no
acr_trust_policy_enabled	Whether the ACR trust policy is enabled.	`bool`	`false`	no
acr_zone_redundancy_enabled	Whether zone redundancy is enabled for the primary ACR registry.	`bool`	`false`	no
adf_analytics_destination_type	Log Analytics destination type for ADF diagnostic settings.	`string`	`"Dedicated"`	no
adf_cleanup_enabled	Whether ADF data flow clusters are cleaned up after runs.	`bool`	`true`	no
adf_compute_type	Compute type for the default Azure Integration Runtime data flow cluster.	`string`	`"General"`	no

Name	Description	Type	Default	Required
adf_core_count	Core count for the default Azure Integration Runtime data flow cluster.	`number`	`8`	no
adf_default_integration_runtime_name	Optional override for the default Azure Integration Runtime name inside Data Factory.	`string`	`null`	no
adf_diagnostics_name	Optional override for the Azure Monitor diagnostic settings name used by the ADF module.	`string`	`null`	no
adf_enable_diagnostics	Whether to send Azure Data Factory diagnostics to the shared Log Analytics workspace.	`bool`	`false`	no
adf_enable_private_endpoint	Whether to create the Azure Data Factory control-plane private endpoint.	`bool`	`false`	no
adf_global_parameters	Optional Data Factory global parameters.	list(object({ name = string type = optional(string, "String") value = string }))	`[]`	no
adf_managed_private_endpoints	Optional managed private endpoints created from Azure Data Factory.	set(object({ name = string target_resource_id = string subresource_name = string }))	`[]`	no
adf_managed_virtual_network_enabled	Whether to enable the managed virtual network for Azure Data Factory.	`bool`	`true`	no
adf_name	Optional override for the Azure Data Factory name.	`string`	`""`	no
adf_permissions	Optional Azure Data Factory resource-level permissions in the module's expected object_id/role shape.	`list(map(string))`	`[]`	no
adf_private_dns_zone_id	Optional existing private DNS zone ID for privatelink.datafactory.azure.net.	`string`	`""`	no
adf_private_dns_zone_name	Private DNS zone name used for Azure Data Factory control-plane private endpoint resolution.	`string`	`"privatelink.datafactory.azure.net"`	no
adf_private_dns_zone_resource_group_name	Resource group containing the existing Azure Data Factory private DNS zone when an explicit zone ID is not provided.	`string`	`""`	no
adf_public_network_enabled	Whether the Azure Data Factory control plane is exposed to the public network.	`bool`	`false`	no

Name	Description	Type	Default	Required
adf_self_hosted_integration_runtime_enabled	Whether to enable the self-hosted integration runtime path for the ADF module.	`bool`	`false`	no
adf_shir_name	Optional override for the SHIR name when self-hosted integration runtime is enabled.	`string`	`null`	no
adf_time_to_live_min	Time-to-live for the default Azure Integration Runtime data flow cluster.	`number`	`15`	no
adf_virtual_network_enabled	Whether the default Azure Integration Runtime uses managed virtual network execution.	`bool`	`true`	no

adf_vsts_configuration	Azure DevOps repository configuration for Data Factory source control integration.	object({
		account_name = string
		project_name = string
		repository_name = string
		branch_name = string
		root_folder = string
		tenant_id = string
		collaboration_branch = optional(string)
		})
			{
			"account_name": "
			CCOE-Azure",
			"branch_name": "adf_publish",
			"collaboration_branch": "main",
			"project_name": "
			CCoE-Infra-IaC",
			"repository_name": "",
			"root_folder": "/",
			"tenant_id": "b0f3630d-e5de-4
			172-b492-0cf5cd387a41"
			}
				no

aks_app_admin_group	List of Microsoft Entra group display names or object IDs that should receive AKS admin access.	`list(string)`	`[]`	no
aks_app_user_group	List of Microsoft Entra group display names or object IDs that should receive Reader access on the AKS cluster resource.	`list(string)`	`[]`	no
aks_automatic_upgrade_channel	AKS automatic upgrade channel.	`string`	`"patch"`	no
aks_azure_rbac_enabled	Whether Azure RBAC for Kubernetes Authorization is enabled.	`bool`	`true`	no

Name	Description	Type	Default	Required
aks_default_node_pool	AKS default node pool configuration.	object({ name = optional(string, "system") vm_size = optional(string, " Standard_D4s_v5") node_count = optional(number, 1) enable_auto_scaling = optional(bool, false) min_count = optional(number)	{}	no

Name	Description	Type	Default	Required
		max_count = optional(number) zones = optional(list(string), []) os_disk_size_gb = optional(number, 128) max_pods = optional(number) vnet_subnet_id = optional(string) only_critical_addons_enabled = optional(bool, false) orchestrator_version = optional(string) os_sku = optional(string, "Ubuntu") type = optional(string, "VirtualMachineScaleSets") upgrade_settings = optional(object({ max_surge = optional(string) drain_timeout_in_minutes = optional(number) node_soak_duration_in_minutes = optional(number) })) })		
aks_diagnostic_log_categories	AKS diagnostic log categories to enable.	`list(string)`	`[]`	no
aks_diagnostic_metric_categories	AKS diagnostic metric categories to enable.	`list(string)`	["AllMetrics"]	no
aks_dns_prefix	Optional override for the AKS DNS prefix.	`string`	`""`	no
aks_enable_diagnostics	Whether to enable diagnostics for AKS.	`bool`	`false`	no
aks_kubernetes_version	Optional Kubernetes version for AKS.	`string`	`null`	no
aks_local_account_disabled	Whether local AKS admin accounts are disabled.	`bool`	`true`	no
aks_log_analytics_workspace_id	Optional override for the Log Analytics workspace resource ID used by AKS diagnostics.	`string`	`""`	no
aks_name	Optional override for the AKS cluster name.	`string`	`""`	no
Name	Description	Type	Default	Required
aks_network_profile	AKS network profile configuration.	object({ network_plugin = optional(string, "azure") network_plugin_mode = optional(string)	`{}`	no

Name	Description	Type	Default	Required
		network_policy = optional(string) service_cidr = optional(string) dns_service_ip = optional(string) load_balancer_sku = optional(string, "standard") outbound_type = optional(string, "loadBalancer") })		
aks_oidc_issuer_enabled	Whether the AKS OIDC issuer is enabled.	`bool`	`true`	no
aks_private_cluster_enabled	Whether the AKS API server is private.	`bool`	`true`	no
aks_private_dns_zone_id	Optional private DNS zone resource ID for AKS.	`string`	`""`	no
aks_private_dns_zone_name	Optional private DNS zone name for AKS lookup.	`string`	`""`	no
aks_private_dns_zone_resource_group_name	Optional resource group containing aks_private_dns_zone_name.	`string`	`""`	no
aks_role_based_access_control_enabled	Whether Kubernetes RBAC is enabled.	`bool`	`true`	no
aks_sku_tier	AKS SKU tier.	`string`	`"Free"`	no
aks_subnet_prefixes	Address prefixes for the AKS subnet in the spoke VNet.	`list(string)`	["10.167.74.0/24"]	no
aks_tags	A mapping of tags to assign to the AKS cluster.	`map(string)`	`{}`	no
aks_terraform_execution_aks_role	Optional AKS Kubernetes RBAC role to assign to the current Terraform execution identity.	`string`	`"Azure Kubernetes Service RBAC Cluster Admin"`	no
aks_workload_identity_enabled	Whether AKS Workload Identity is enabled.	`bool`	`true`	no
allowed_policy_locations	Allowed Azure regions used by the sample allowed locations policy.	`list(string)`	["eastus", "canadaeast"]	no
app_admin_group	Optional Entra groups or object IDs with Contributor-style access on landing zone resources.	`list(string)`	`[]`	no

Name	Description	Type	Default	Required
app_registration_create_client_secret	Whether to create and store an app registration client secret for the App Service.	`bool`	`true`	no
app_registration_display_name	Optional display name override for the App Service app registration.	`string`	`null`	no
app_registration_web_redirect_uris	Optional explicit redirect URIs for the App Service app registration.	`list(string)`	`[]`	no
app_service_allow_anonymous	Whether Easy Auth should allow anonymous requests.	`bool`	`true`	no
app_service_app_secret_key	Application secret key setting for the sample app. Replace before production use.	`string`	`"replace-with-a-random-secret-32-long"`	no
app_service_app_settings	Additional App Service app settings merged with the module defaults.	`map(string)`	`{}`	no
app_service_auth_mode	Authentication mode for the App Service: none, easy_auth, msal, or both.	`string`	`"both"`	no
app_service_dotnet_version	The .NET runtime version configured on the Windows App Service.	`string`	`"v8.0"`	no
app_service_enable_private_endpoint	n/a	`bool`	`false`	no
app_service_ip_restriction_default_action	Default action for App Service site access traffic that does not match an IP restriction rule.	`string`	`"Deny"`	no

app_service_ip_restrictions	Site access restrictions for the App Service public endpoint.	list(object({
		action = optional(string, "Allow")
		ip_address = optional(string)
		name = string
		priority = number
		service_tag = optional(string)
		
		headers = optional(object({
		x_forwarded_for = optional(list(string))
		x_forwarded_host = optional(list(string))
		x_azure_fdid = optional(list(string))
		x_fd_health_probe = optional(list(string))
		}))
		}))
			`[]`	no

app_service_kind	The App Service operating system kind.	`string`	`"Windows"`	no
app_service_node_version	The Node.js runtime version configured on the App Service when appservice_stack is node.	`string`	`"24-lts"`	no

Name	Description	Type	Default	Required
app_service_plan_autoscale_cpu_threshold_scale_down	CPU threshold percentage that triggers App Service Plan scale in.	`number`	`25`	no
app_service_plan_autoscale_cpu_threshold_scale_up	CPU threshold percentage that triggers App Service Plan scale out.	`number`	`75`	no
app_service_plan_autoscale_default_capacity	Default App Service Plan autoscale instance count.	`number`	`1`	no
app_service_plan_autoscale_max_capacity	Maximum App Service Plan autoscale instance count.	`number`	`3`	no
app_service_plan_autoscale_min_capacity	Minimum App Service Plan autoscale instance count.	`number`	`1`	no
app_service_plan_autoscale_scale_down_increment	Number of App Service Plan instances to remove when scaling in.	`number`	`1`	no
app_service_plan_autoscale_scale_up_increment	Number of App Service Plan instances to add when scaling out.	`number`	`1`	no
app_service_plan_enable_autoscale	Whether to enable autoscale for the App Service Plan.	`bool`	`false`	no
app_service_plan_enable_diagnostics	Whether to send App Service Plan diagnostics to Log Analytics.	`bool`	`true`	no
app_service_plan_os_type	Operating system type for the App Service Plan.	`string`	`"Windows"`	no
app_service_plan_sku_name	SKU name for the App Service Plan.	`string`	`"S1"`	no
app_service_public_network_access_enabled	Whether public network access is enabled for the App Service.	`bool`	`true`	no
app_service_python_version	The Python runtime version configured on the App Service when appservice_stack is python.	`string`	`"3.14"`	no
app_service_scmIpSecurityRestrictionsUseMain	Optional App Service property override for scmIpSecurityRestrictionsUseMain. When null, app_service_scm_use_main_ip_restriction is used.	`bool`	`null`	no
app_service_scm_basic_auth_publishing_credentials_enabled	Whether SCM basic authentication publishing credentials are enabled.	`bool`	`true`	no
app_service_scm_ip_restriction_default_action	Default action for Kudu/SCM endpoint traffic that does not match an IP restriction rule.	`string`	`"Deny"`	no

Name	Description	Type	Default	Required

app_service_scm_ip_restrictions	Kudu/SCM endpoint access restrictions for the App Service.	list(object({
		action = optional(string, "Allow")
		description = optional(string)
		ip_address = optional(string)
		name = string
		priority = number
		service_tag = optional(string)
		virtual_network_subnet_id = optional(string)
		
		headers = optional(object({
		x_forwarded_for = optional(list(string))
		x_forwarded_host = optional(list(string))
		x_azure_fdid = optional(list(string))
		x_fd_health_probe = optional(list(string))
		}))
		}))
			`[]`	no

app_service_scm_use_main_ip_restriction	Whether the Kudu/SCM endpoint should reuse the main App Service IP restrictions.	`bool`	`false`	no
app_service_unauthenticated_action	Optional Easy Auth unauthenticated action override.	`string`	`"AllowAnonymous"`	no
app_service_vnet_integration_enabled	Whether to integrate the App Service with the spoke application subnet.	`bool`	`false`	no
app_service_vnet_route_all_enabled	Whether App Service VNet integration routes all outbound traffic through the VNet.	`bool`	`false`	no
app_service_webdeploy_publish_basic_authentication_enabled	Whether WebDeploy basic publishing authentication is enabled.	`bool`	`true`	no

Name	Description	Type	Default	Required

app_services	App Service instances to provision. Toggle each stack with enabled.	map(object({
		enabled = bool
		stack = string
		kind = string
		plan_os_type = string
		sku_name = string
		deployment_method = optional(string, "run_from_package")
		use_32_bit_worker = optional(bool)
		startup_command = optional(string)
		dotnet_version = optional(string)
			{
			"dotnet": {
			"deployment_center_azure_repos_branch": "main",
			"deployment_center_use_manual_integration": true,
			"deployment_method": "run_from_package",
			"dotnet_version": "v8.0",
			"enabled": true,
			"kind": "Windows",
				no

Name	Description	Type	Default	Required

		node_version = optional(string)
		python_version = optional(string)
		app_settings = optional(map(string), {})
		enable_diagnostics = optional(bool, true)
		health_check_path = optional(string)
		health_check_eviction_time_in_min = optional(number)
		custom_hostname_bindings = optional(map(object({
		hostname = string
		ssl_state = optional(string, "SniEnabled")
		})), {})
		# Deprecated: prefer deployment_method. Retained only for backward compatibility
		# when older callers omit deployment_method.
		deployment_center_enabled = optional(bool, false)
		deployment_center_repo_url = optional(string)
		deployment_center_azure_repos_organization = optional(string)
		deployment_center_azure_repos_project = optional(string)
		deployment_center_azure_repos_repository = optional(string)
		deployment_center_azure_repos_branch = optional(string, "main")
		deployment_center_use_manual_integration = optional(bool, true)
		}))
			"plan_os_type": "Windows",
			"sku_name": "S1",
			"stack": "dotnet",
			"startup_command": null,
			"use_32_bit_worker": null
			},
			"node": {
			"app_settings": {
			"WEBSITE_NODE_DEFAULT_VERSION": "~24"
			},
			"deployment_center_azure_repos_branch": "main",
			"deployment_center_use_manual_integration": true,
			"deployment_method": "run_from_package",
			"enabled": true,
			"kind": "Linux",
			"node_version": "24-lts",
			"plan_os_type": "Linux",
			"sku_name": "S1",
			"stack": "node",
			"startup_command": null,
			"use_32_bit_worker": null
			},
			"python": {
			"deployment_center_azure_repos_branch": "main",
			"deployment_center_use_manual_integration": true,
			"deployment_method": "run_from_package",
			"enabled": false,
			"kind": "Linux",
			"plan_os_type": "Linux",
			"python_version": "3.14",
			"sku_name": "S1",
			"stack": "python",
			"startup_command": null,
			"use_32_bit_worker": null
			}
			}	

Name	Description	Type	Default	Required
app_subnet_prefixes	Address prefixes for the application subnet in the spoke VNet.	`list(string)`	["10.167.70.0/24"]	no
app_user_group	Optional Entra groups or object IDs with Reader-style access on landing zone resources.	`list(string)`	`[]`	no
appservice_stack	Application runtime stack used by the App Service module.	`string`	`"dotnet"`	no

Name	Description	Type	Default	Required

automation_accounts	Automation Account instances to provision. Toggle each account with enabled.	map(object({
		enabled = bool
		name = optional(string)
		sku_name = optional(string, "Basic")
		local_auth_enabled = optional(bool, false)
		public_access_enabled = optional(bool, true)
		system_managed_identity_enabled = optional(bool, true)
		app_admin_group = optional(list(string), [])
		app_user_group = optional(list(string), [])
		managed_identity_role_assignments = optional(map(object({
		scope = string
		role_definition_name = optional(string)
		role_definition_id = optional(string)
		})), {})
		private_endpoint_enabled = optional(bool, false)
		private_endpoint_subresource_name = optional(string, "Webhook")
		enable_webhook_private_endpoint = optional(bool)
		enable_hrw_private_endpoint = optional(bool)
		private_endpoint_subnet_id = optional(string, "")
		private_endpoint_subnet_name = optional(string)
		private_endpoint_vnet_name = optional(string)
		private_endpoint_network_resource_group_name = optional(string)
			{
			"default": {
			"app_admin_group": [],
			"app_user_group": [],
			"diagnostic_log_categories": [
			"JobLogs",
			"JobStreams",
			"AuditEvent",
			"DscNodeStatus"
			],
			"diagnostic_metric_categories": [
			"AllMetrics"
			],
			"enable_diagnostics": true,
			"enable_hrw_private_endpoint": null,
			"enable_webhook_private_endpoint": null,
			"enabled": false,
			"local_auth_enabled": false,
			"managed_identity_role_assignments": {},
			"name": null,
			"private_dns_zone_id": "",
			"private_endpoint_enabled": false,
			"private_endpoint_network_resource_group_name": null,
			"private_endpoint_subnet_id": "",
			"private_endpoint_subnet_name": null,
				no

Name	Description	Type	Default	Required
		private_dns_zone_id = optional(string, "") enable_diagnostics = optional(bool, true) diagnostic_log_categories = optional(list(string), ["JobLogs", "JobStreams", "AuditEvent", "DscNodeStatus"]) diagnostic_metric_categories = optional(list(string), ["AllMetrics"]) tags = optional(map(string), {}) }))	"private_endpoint_subresource_name": "Webhook", "private_endpoint_vnet_name": null, "public_access_enabled": true, "sku_name": "Basic", "system_managed_identity_enabled": true, "tags": {} } }	

Name	Description	Type	Default	Required

automation_ari_workloads	Azure Resource Inventory (ARI) workloads to attach to provisioned Automation Accounts.	map(object({
		enabled = bool
		automation_account_key = string
		storage_container_name = optional(string, "ari")
		report_name = optional(string, "AZURE")
		report_dir = optional(string, "C:\\AzureResourceInventory")
		ari_lite_mode = optional(bool, false)
		ari_diagram_full_environment_enabled = optional(bool, true)
		ari_security_center_enabled = optional(bool, true)
		runbook_name = optional(string, "ARI_Runbook")
		runtime_environment_name = optional(string, "PowerShell-7.4-Env")
		runbook_template_path = optional(string, "runbooks/ari.ps1.tftpl")
		runtime_packages = optional(map(string), {})
		schedule_enabled = optional(bool, true)
		schedule_name = optional(string, "Azure Inventory Collection - daily")
		schedule_description = optional(string, "Daily schedule for the ARI runbook.")
		schedule_frequency = optional(string, "Day")
		schedule_interval = optional(number, 1)
		schedule_timezone = optional(string, "
			{
			"default": {
			"alert_evaluation_frequency": "PT15M",
			"alert_window_duration": "PT15M",
			"ari_diagram_full_environment_enabled": true,
			"ari_lite_mode": false,
			"ari_security_center_enabled": true,
			"automation_account_key": "default",
			"enable_job_failure_alert": true,
			"enable_long_running_alert": true,
			"enabled": false,
			"job_failure_alert_name": null,
			"job_failure_severity": 2,
			"long_running_alert_name": null,
			"long_running_severity": 3,
			"long_running_threshold_minutes": 90,
			"monitor_action_group_ids": [],
			"report_dir": "C:\\AzureResourceInventory",
			"report_name": "AZURE",
			"runbook_log_progress": true,
				no

Name	Description	Type	Default	Required
		America/Toronto") schedule_start_time = optional(string) runbook_log_verbose = optional(bool, true) runbook_log_progress = optional(bool, true) enable_job_failure_alert = optional(bool, true) job_failure_alert_name = optional(string) job_failure_severity = optional(number, 2) enable_long_running_alert = optional(bool, true) long_running_alert_name = optional(string) long_running_severity = optional(number, 3) long_running_threshold_minutes = optional(number, 90) alert_evaluation_frequency = optional(string, "PT15M") alert_window_duration = optional(string, "PT15M") monitor_action_group_ids = optional(list(string), []) tags = optional(map(string), {}) }))	"runbook_log_verbose": true, "runbook_name": "ARI_Runbook", "runbook_template_path": "runbooks/ari.ps1.tftpl", "runtime_environment_name": "PowerShell-7.4-Env", "runtime_packages": {}, "schedule_description": "Daily schedule for the ARI runbook.", "schedule_enabled": true, "schedule_frequency": "Day", "schedule_interval": 1, "schedule_name": "Azure Inventory Collection - daily", "schedule_start_time": null, "schedule_timezone": "America/Toronto", "storage_container_name": "ari", "tags": {} } }	
azure_ai_search_allowed_ips	Optional list of public IP ranges allowed to access the Azure AI Search service.	`list(string)`	`[]`	no
azure_ai_search_authentication_failure_mode	Optional authentication failure mode for the Azure AI Search service.	`string`	`""`	no
azure_ai_search_customer_managed_key_enforcement_enabled	Whether customer-managed key enforcement is enabled on the Azure AI Search service.	`bool`	`false`	no
azure_ai_search_diagnostic_log_categories	Diagnostic log categories to enable for Azure AI Search.	`list(string)`	`[]`	no
azure_ai_search_diagnostic_metric_categories	Diagnostic metric categories to enable for Azure AI Search.	`list(string)`	["AllMetrics"]	no
azure_ai_search_enable_diagnostics	Whether to send Azure AI Search diagnostics to the shared Log Analytics workspace.	`bool`	`false`	no

Name	Description	Type	Default	Required
azure_ai_search_hosting_mode	Hosting mode for the Azure AI Search service.	`string`	`"default"`	no
azure_ai_search_identity	Optional managed identity configuration for the Azure AI Search service.	object({ type = string identity_ids = optional(set(string)) })	`null`	no
azure_ai_search_local_authentication_enabled	Whether API-key based local authentication is enabled on the Azure AI Search service.	`bool`	`true`	no
azure_ai_search_name	Optional override for the Azure AI Search service name.	`string`	`""`	no
azure_ai_search_network_rule_bypass_option	Optional network rule bypass option for the Azure AI Search service.	`string`	`"None"`	no
azure_ai_search_partition_count	Partition count for the Azure AI Search service.	`number`	`1`	no
azure_ai_search_private_dns_zone_id	Optional override private DNS zone ID for the Azure AI Search private endpoint. Leave empty to use the landing zone private DNS module when privatelink.search.windows.net is present.	`string`	`""`	no
azure_ai_search_public_network_access_enabled	Whether public network access is enabled on the Azure AI Search service.	`bool`	`true`	no
azure_ai_search_replica_count	Replica count for the Azure AI Search service.	`number`	`1`	no
azure_ai_search_semantic_search_sku	Optional semantic ranker SKU for the Azure AI Search service.	`string`	`""`	no
azure_ai_search_sku	SKU for the Azure AI Search service.	`string`	`"standard"`	no
azure_ai_service_custom_subdomain_name	Optional custom subdomain name for the Azure AI Services account.	`string`	`""`	no
azure_ai_service_customer_managed_key	Optional customer-managed key configuration for the Azure AI Services account.	object({ key_vault_key_id = string identity_client_id = optional(string) })	`null`	no
azure_ai_service_diagnostic_log_categories	Diagnostic log categories to enable for Azure AI Services.	`list(string)`	`[]`	no
azure_ai_service_diagnostic_metric_categories	Diagnostic metric categories to enable for Azure AI Services.	`list(string)`	["AllMetrics"]	no
azure_ai_service_dynamic_throttling_enabled	Whether dynamic throttling is enabled for the Azure AI Services account.	`bool`	`false`	no

Name	Description	Type	Default	Required
azure_ai_service_enable_diagnostics	Whether to send Azure AI Services diagnostics to the shared Log Analytics workspace.	`bool`	`false`	no
azure_ai_service_fqdns	Optional list of outbound FQDNs for the Azure AI Services account.	`list(string)`	`[]`	no
azure_ai_service_identity	Optional managed identity configuration for the Azure AI Services account.	object({ type = string identity_ids = optional(set(string)) })	`null`	no
azure_ai_service_local_auth_enabled	Whether local auth keys are enabled on the Azure AI Services account.	`bool`	`true`	no
azure_ai_service_name	Optional override for the Azure AI Services account name.	`string`	`""`	no

azure_ai_service_network_acls	Optional network ACL configuration for the Azure AI Services account.	object({
		default_action = string
		bypass = optional(string)
		ip_rules = optional(set(string))
		virtual_network_rules = optional(set(object({
		subnet_id = string
		ignore_missing_vnet_service_endpoint = optional(bool)
		})))
		})
			`null`	no

azure_ai_service_outbound_network_access_restricted	Whether outbound network access is restricted on the Azure AI Services account.	`bool`	`false`	no
azure_ai_service_private_dns_zone_id	Optional override private DNS zone ID for the Azure AI Services private endpoint. Leave empty to use the landing zone private DNS module when privatelink.cognitiveservices.azure.com is present.	`string`	`""`	no
azure_ai_service_project_management_enabled	Whether project management is enabled for the Azure AI Services account.	`bool`	`false`	no
azure_ai_service_public_network_access_enabled	Whether public network access is enabled on the Azure AI Services account.	`bool`	`true`	no
azure_ai_service_sku_name	SKU name for the Azure AI Services account.	`string`	`"S0"`	no

Name	Description	Type	Default	Required
azure_ai_service_storage	Optional storage account attachments for the Azure AI Services account.	list(object({ storage_account_id = string identity_client_id = optional(string) }))	`[]`	no
bastion_resource_group_name	Resource group containing bastion_resource_name.	`string`	`""`	no
bastion_resource_name	Optional Bastion host name that receives Network Contributor RBAC for linux_vm_app_admin_group and linux_vm_app_user_group.	`string`	`""`	no
billing_scope_id	Billing scope ID when creating a new subscription alias.	`string`	`""`	no

common_tags	n/a	`map(any)`	{
			"AppSupport Team": "CCOE",
			"Application Name": "CCOE INFRA IAC",
			"Application Owner": "CCOE",
			"Approval Group": "CCOE",
			"Business Owner": "CCOE",
			"Infra Availability Classification": "Bronze",
			"InfraSupport Team": "CCOE",
			"Maintenance Window": "CCOE",
			"Project Name": "CCOE INFRA IAC",
			"Project Number": "N/A",
			"RPO-RTO": "48H/24H",
			"Run Cost(Approved Run Budget)-USD": "100"
			}
				no

connectivity_subscription_id	Azure subscription ID used by the aliased azurerm.connectivity provider.	`string`	`"d3927a5b-0ea7-40e1-bbb5-d3ba34515fb0"`	no
connectivity_tenant_id	Azure tenant ID used by the aliased azurerm.connectivity provider.	`string`	`"d5b038fb-4b39-41cc-8a10-fba75212180b"`	no
databricks_access_connector_id	Optional existing Databricks access connector resource ID.	`string`	`""`	no
databricks_access_connector_identity_ids	User-assigned identity IDs for the Databricks access connector.	`list(string)`	`[]`	no
databricks_access_connector_name	Optional Databricks access connector name.	`string`	`""`	no

Name	Description	Type	Default	Required
databricks_access_connector_role_assignments	Role assignments for the Databricks access connector identity.	`any`	`{}`	no
databricks_access_connector_system_assigned_identity_enabled	Whether the Databricks access connector uses a system-assigned identity.	`bool`	`true`	no
databricks_create_access_connector	Whether to create a Databricks access connector.	`bool`	`false`	no
databricks_custom_parameters	Optional Databricks custom parameters for VNet injection, no-public-IP, storage, and ML linkage.	`any`	`null`	no
databricks_customer_managed_key_enabled	Whether customer-managed keys are enabled for Databricks.	`bool`	`false`	no
databricks_default_storage_firewall_enabled	Whether the Databricks default storage firewall is enabled.	`bool`	`false`	no
databricks_diagnostic_eventhub_authorization_rule_id	Optional Event Hub authorization rule ID for Databricks diagnostics.	`string`	`null`	no
databricks_diagnostic_eventhub_name	Optional Event Hub name for Databricks diagnostics.	`string`	`null`	no
databricks_diagnostic_setting_name	Optional Databricks diagnostic setting name.	`string`	`""`	no
databricks_diagnostic_storage_account_id	Optional Storage Account ID for Databricks diagnostic archive.	`string`	`null`	no
databricks_enable_diagnostics	Whether Databricks diagnostic settings are enabled.	`bool`	`false`	no
databricks_enhanced_security_compliance	Optional enhanced security and compliance settings for Databricks.	`any`	`null`	no
databricks_infrastructure_encryption_enabled	Whether infrastructure encryption is enabled for Databricks.	`bool`	`false`	no
databricks_inherit_resource_group_tags	Whether the Databricks module should merge tags from the target resource group.	`bool`	`false`	no
databricks_log_analytics_workspace_id	Optional Log Analytics workspace ID for Databricks diagnostics.	`string`	`""`	no
databricks_managed_disk_cmk_key_vault_id	Optional Key Vault ID for Databricks managed disk CMK.	`string`	`""`	no
databricks_managed_disk_cmk_key_vault_key_id	Optional Key Vault key ID for Databricks managed disk CMK.	`string`	`""`	no
databricks_managed_disk_cmk_rotation_to_latest_version_enabled	Whether Databricks managed disk CMK rotates to the latest key version.	`bool`	`false`	no
databricks_managed_resource_group_name	Optional managed resource group name for the Databricks workspace.	`string`	`""`	no

Name	Description	Type	Default	Required
databricks_managed_services_cmk_key_vault_id	Optional Key Vault ID for Databricks managed services CMK.	`string`	`""`	no
databricks_managed_services_cmk_key_vault_key_id	Optional Key Vault key ID for Databricks managed services CMK.	`string`	`""`	no
databricks_name	Optional Databricks workspace name override.	`string`	`""`	no
databricks_network_security_group_rules_required	Network security group rules mode for Databricks VNet injection.	`string`	`"NoAzureDatabricksRules"`	no
databricks_private_dns_zone_ids	Private DNS zone IDs attached to Databricks private endpoints.	`list(string)`	`[]`	no
databricks_private_dns_zone_names	Private DNS zone names resolved for Databricks private endpoints.	`list(string)`	`[]`	no
databricks_private_dns_zone_resource_group_name	Resource group containing Databricks private DNS zones.	`string`	`null`	no
databricks_private_endpoint_manual_connection_enabled	Whether Databricks private endpoints use manual private service connection approval.	`bool`	`false`	no
databricks_private_endpoint_network_interface_name	Optional base network interface name for Databricks private endpoints.	`string`	`""`	no
databricks_private_endpoint_network_resource_group_name	Network resource group used for Databricks private endpoint lookup when subnet ID is not set.	`string`	`""`	no
databricks_private_endpoint_request_message	Manual private endpoint connection request message for Databricks.	`string`	`""`	no
databricks_private_endpoint_subnet_id	Optional subnet ID for Databricks private endpoints. Defaults to the landing zone private endpoint subnet.	`string`	`""`	no
databricks_private_endpoint_subnet_name	Subnet name used for Databricks private endpoint lookup when subnet ID is not set.	`string`	`""`	no
databricks_private_endpoint_subresource_names	Databricks private endpoint subresources, for example databricks_ui_api or browser_authentication.	`list(string)`	`[]`	no
databricks_private_endpoint_vnet_name	VNet name used for Databricks private endpoint lookup when subnet ID is not set.	`string`	`""`	no

databricks_private_subnet_prefixes	Address prefixes for the Databricks private subnet in the spoke VNet.	`list(string)`	`[`
			`"10.167.73.0/24"`
			`]`
				no

Name	Description	Type	Default	Required
databricks_public_network_access_enabled	Whether public network access is enabled for the Databricks workspace.	`bool`	`false`	no
databricks_public_subnet_prefixes	Address prefixes for the Databricks public subnet in the spoke VNet.	`list(string)`	["10.167.72.0/24"]	no
databricks_role_assignments	Additional Databricks workspace role assignments.	`any`	`{}`	no
databricks_root_dbfs_customer_managed_key	Optional customer-managed key configuration for Databricks root DBFS.	`any`	`null`	no
databricks_sku	Databricks workspace SKU.	`string`	`"premium"`	no
enable_acr	Enable the Azure Container Registry module in the landing zone.	`bool`	`false`	no
enable_adf	Enable the Azure Data Factory module in the landing zone.	`bool`	`false`	no
enable_aks	Whether to deploy the AKS module.	`bool`	`false`	no
enable_app_registration_for_appservice	Whether to create an Entra app registration for the App Service.	`bool`	`true`	no
enable_azure_ai_search	Enable the Azure AI Search module in the landing zone.	`bool`	`false`	no
enable_azure_ai_search_private_endpoint	Whether to create a private endpoint for the Azure AI Search service.	`bool`	`false`	no
enable_azure_ai_service	Enable the Azure AI Services module in the landing zone.	`bool`	`false`	no
enable_azure_ai_service_private_endpoint	Whether to create a private endpoint for the Azure AI Services account.	`bool`	`false`	no
enable_databricks	Enable the Azure Databricks workspace module in the landing zone.	`bool`	`false`	no
enable_linux_vm	Whether to provision the Linux VM jumpbox module and its related root role assignments.	`bool`	`true`	no
enable_management_group	Whether to create a management group in the example.	`bool`	`false`	no
enable_openai	Enable the Azure OpenAI module in the landing zone.	`bool`	`false`	no
enable_openai_private_endpoint	Whether to create a private endpoint for the Azure OpenAI account.	`bool`	`false`	no
enable_sqldb	Whether to deploy the Azure SQL Database module.	`bool`	`false`	no
enable_static_web_apps	Whether the Static Web App demo instances are enabled when the feature map does not override this setting.	`bool`	`false`	no

Name	Description	Type	Default	Required
enable_subscription_bootstrap	Whether to use subscription_vending in the example.	`bool`	`false`	no
enable_winvm	Whether to provision the Windows VM jumpbox module.	`bool`	`false`	no
environment	Environment suffix used in generated names.	`string`	`"sbx"`	no
existing_subscription_id	Existing subscription resource ID used when bootstrapping an existing subscription.	`string`	`""`	no
features	Optional high-level feature switches. Known keys include enable_management_group, enable_subscription_bootstrap, enable_private_dns, enable_adf, enable_azure_ai_search, enable_azure_ai_service, enable_openai, enable_acr, enable_app_services, enable_static_web_apps, enable_app_registration_for_appservice, enable_automation_accounts, enable_automation_ari_workloads, enable_winvm, enable_linux_vm, enable_aks, enable_sqldb, and enable_fortigate. Unspecified keys fall back to the existing individual variables.	`map(bool)`	`{}`	no
firewall_name	Optional override for the Azure Firewall name.	`string`	`""`	no
firewall_sku_tier	Azure Firewall SKU tier.	`string`	`"Standard"`	no
firewall_subnet_prefixes	Address prefixes for AzureFirewallSubnet in the hub VNet.	`list(string)`	["10.167.33.64/26"]	no
fortigate_admin_password	Optional FortiGate administrator password. Supply through a secret variable.	`string`	`""`	no
fortigate_admin_ssh_public_key	Optional SSH public key for FortiGate administration. When empty, linux_vm_admin_ssh_key is used.	`string`	`""`	no
fortigate_admin_ssh_source_address_prefixes	Trusted IPv4 addresses or CIDR prefixes allowed to administer FortiGate over TCP/22.	`list(string)`	`[]`	no
fortigate_admin_username	FortiGate VM administrator username.	`string`	`"azureadmin"`	no
fortigate_create_dedicated_vnet	Whether the FortiGate module creates a dedicated VNet. When false, it creates the FortiGate subnets in the shared hub VNet.	`bool`	`false`	no
fortigate_custom_data	Optional FortiOS bootstrap configuration.	`string`	`""`	no

Name	Description	Type	Default	Required
fortigate_dedicated_external_subnet_prefixes	Address prefixes for the external subnet when FortiGate uses a dedicated VNet.	`list(string)`	["10.168.32.0/24"]	no
fortigate_dedicated_internal_subnet_prefixes	Address prefixes for the internal subnet when FortiGate uses a dedicated VNet.	`list(string)`	["10.168.33.0/24"]	no
fortigate_deployment_mode	FortiGate deployment mode. single creates one VM; ha creates two VMs.	`string`	`"single"`	no
fortigate_external_subnet_name	Optional name for the FortiGate external subnet in the hub VNet.	`string`	`""`	no
fortigate_external_subnet_prefixes	Address prefixes for the FortiGate external subnet in the hub VNet.	`list(string)`	["10.167.34.0/24"]	no

fortigate_image	Marketplace image reference for FortiGate.	object({
		publisher = string
		offer = string
		sku = string
		version = string
		})
			{
			"offer": "fortinet_fortigate-vm_v5",
			"publisher": "fortinet",
			"sku": "fortinet_fg-vm",
			"version": "latest"
			}
				no

fortigate_internal_subnet_name	Optional name for the FortiGate internal subnet in the hub VNet.	`string`	`""`	no
fortigate_internal_subnet_prefixes	Address prefixes for the FortiGate internal subnet in the hub VNet.	`list(string)`	["10.167.35.0/24"]	no
fortigate_license_type	FortiGate licensing model marker. The Marketplace image and plan must match this value.	`string`	`"byol"`	no
fortigate_management_access_model	Private management access model recorded on FortiGate resources.	`string`	`"private"`	no

fortigate_marketplace_plan	Marketplace plan for the selected FortiGate image.	object({
		name = string
		product = string
		publisher = string
		})
			{
			"name": "fortinet_fg-vm",
			"product": "fortinet_fortigate-vm_v5",
			"publisher": "fortinet"
			}
				no

fortigate_name_prefix	Optional name prefix for FortiGate VM and NIC resources.	`string`	`""`	no

Name	Description	Type	Default	Required
fortigate_network_interfaces	Optional FortiGate NIC definitions. Empty uses external and internal NICs with static .4 addresses.	list(object({ name = string role = string subnet_name = string address_prefixes = optional(list(string), []) primary = optional(bool, false) enabled_in_modes = optional(set(string), ["single", "ha"]) private_ip_address_allocation = optional(string, "Dynamic") private_ip_addresses_by_suffix = optional(map(string), {}) enable_ip_forwarding = optional(bool, true) accelerated_networking_enabled = optional(bool, false) }))	[]	no
fortigate_network_security_group_name	Optional name for the NSG associated with FortiGate subnets.	`string`	""	no
fortigate_network_security_rules	NSG rules applied to the FortiGate subnets.	map(object({ priority = number direction = string access = string protocol = string source_port_range = optional(string) source_port_ranges = optional(list(string)) destination_port_range = optional(string) destination_port_ranges = optional(list(string)) source_address_prefix = optional(string) source_address_prefixes = optional(list(string)) destination_address_prefix = optional(string) destination_address_prefixes = optional(list(string)) description = optional(string) }))	{}	no

Name	Description	Type	Default	Required
fortigate_os_disk	OS disk settings for FortiGate VMs.	object({ caching = optional(string, "ReadWrite")	{}	no

Name	Description	Type	Default	Required
		storage_account_type = optional(string, "Premium_LRS") disk_size_gb = optional(number) })		
fortigate_resource_group_name	Optional existing resource group for FortiGate compute resources. Defaults to the landing zone resource group.	`string`	`""`	no
fortigate_virtual_network_address_space	Address space for a dedicated FortiGate VNet. The FortiGate subnet prefixes must fall within this space.	`list(string)`	["10.168.32.0/22"]	no
fortigate_virtual_network_name	Optional dedicated FortiGate VNet name. Used only when fortigate_create_dedicated_vnet is true.	`string`	`""`	no
fortigate_vm_size	Azure VM size for FortiGate instances.	`string`	`"Standard_F4s_v2"`	no
fortigate_zone	Optional availability zone for a single FortiGate VM.	`string`	`""`	no

hierarchy_subscriptions	Optional subscription hierarchy entries. By default the map key is the target management group key; set management_group_key to place multiple subscriptions in the same management group.	map(object({
		subscription_name = string
		existing_subscription_id = string
		management_group_key = optional(string, "")
		subscription_alias_enabled = optional(bool, false)
		subscription_alias_name = optional(string, "")
		billing_scope_id = optional(string, "")
		}))
			{
			"landingzone": {
			"existing_subscription_id": "/subscriptions/00000000-0000-0000-0000-000000000013",
			"management_group_key": "landingzone",
			"subscription_name": "landingzone-dev"
			}
			}
				no

hub_address_space	Address space for the hub virtual network.	`list(string)`	["10.167.32.0/20"]	no
hub_vnet_name	Optional override for the hub virtual network name.	`string`	`""`	no
identity_subscription_id	Azure subscription ID used by the aliased azurerm.identity provider.	`string`	`"74c3c03d-217f-4138-b9a6-79145d37781a"`	no
identity_tenant_id	Azure tenant ID used by the aliased azurerm.identity provider.	`string`	`"d5b038fb-4b39-41cc-8a10-fba75212180b"`	no
jumpbox_public_network_enabled	Whether the example jumpbox VMs receive public IPs.	`bool`	`true`	no

Name	Description	Type	Default	Required
jumpbox_subnet_prefixes	Address prefixes for the jumpbox subnet in the spoke VNet.	`list(string)`	["10.167.75.0/24"]	no
jumpbox_windows_image_offer	Marketplace image offer passed to the winvm module for the example jumpbox.	`string`	`"WindowsServer"`	no
jumpbox_windows_image_publisher	Marketplace image publisher passed to the winvm module for the example jumpbox.	`string`	`"MicrosoftWindowsServer"`	no
jumpbox_windows_image_sku	Marketplace image SKU passed to the winvm module for the example jumpbox.	`string`	`"2022-Datacenter"`	no
jumpbox_windows_image_version	Marketplace image version passed to the winvm module for the example jumpbox.	`string`	`"latest"`	no
key_vault_name	Optional override for the landing zone Key Vault name.	`string`	`""`	no
landingzone_mg_display	Optional override for the management group display name.	`string`	`"Landingzone Dev"`	no
landingzone_mg_name	Optional override for the management group ID.	`string`	`"mg-landingzone-dev"`	no
linux_vm_admin_credentials_key_vault_id	Optional Key Vault resource ID to use specifically for Linux VM admin credential secrets. When set, this takes precedence over linux_vm_iac_kv_id for resolving azure-user, azure-password, and azureadmin-pubkey.	`string`	`""`	no
linux_vm_admin_password	Optional root-level admin password override for the Linux VM module. Leave empty to use the admin_password secret from linux_vm_iac_kv.	`string`	`""`	no
linux_vm_admin_password_secret_name	Optional Key Vault secret name containing the Linux VM admin password.	`string`	`""`	no
linux_vm_admin_ssh_key	Optional administrator SSH public key override passed to the Linux VM module. Leave empty to use the azureadmin-pubkey secret from linux_vm_iac_kv.	`string`	`""`	no
linux_vm_admin_ssh_key_secret_name	Optional Key Vault secret name containing the Linux VM admin SSH public key.	`string`	`""`	no
linux_vm_admin_username	Optional administrator username override passed to the Linux VM module. Leave empty to use the admin_username secret from linux_vm_iac_kv.	`string`	`""`	no
linux_vm_admin_username_secret_name	Optional Key Vault secret name containing the Linux VM admin username.	`string`	`""`	no

Name	Description	Type	Default	Required
linux_vm_ado_runner_count	Number of Azure DevOps agents to register on each Linux runner VM.	`number`	`1`	no
linux_vm_app_admin_group	AD groups granted Contributor on the VM resource and sudo/admin access inside the Linux guest OS.	`list(string)`	`[ "" ]`	no
linux_vm_app_env	Environment, such as prod, qa, dev, poc, test, or sbx.	`string`	`"prod"`	no
linux_vm_app_user_group	AD groups granted Reader on the VM resource and standard SSH access inside the Linux guest OS.	`list(string)`	`[ "" ]`	no
linux_vm_data_disk_size_gb	Optional additional data disk size in GB. Set to 0 to skip the extra disk.	`number`	`0`	no
linux_vm_disable_password_authentication	Whether to disable password authentication for the Linux VM module.	`bool`	`true`	no
linux_vm_domain	AD domain used by the Linux VM bootstrap script when linux_vm_enable_domain_join = true.	`string`	`""`	no
linux_vm_domain_join_ou	Legacy domain join OU value retained for Linux VM module compatibility. Only relevant when linux_vm_enable_domain_join = true.	`string`	`"azure"`	no
linux_vm_domain_join_user	Domain join user in domain\username format, used only when linux_vm_enable_domain_join = true.	`string`	`""`	no
linux_vm_enable_domain_join	Whether the Linux VM module should attempt domain join during bootstrap. Default is false, which skips the domain-join secret lookup and keeps the VM off domain.	`bool`	`false`	no
linux_vm_enable_entra_ssh_login	Whether to enable Microsoft Entra ID SSH login on the Linux VMs.	`bool`	`false`	no
linux_vm_enable_linux_vm_extension	Whether to enable the optional storage-backed localization CustomScript VM extension for Linux VMs.	`bool`	`false`	no
linux_vm_enable_system_assigned_identity	Whether to enable a system-assigned managed identity on the Linux VMs. Required when linux_vm_enable_linux_vm_extension = true.	`bool`	`true`	no
linux_vm_iac_kv	Shared Key Vault name containing Linux VM secrets.	`string`	`""`	no
linux_vm_iac_kv_id	Shared Key Vault resource ID containing Linux VM secrets.	`string`	`""`	no
linux_vm_iac_rg	Resource group containing the shared IaC storage account and Key Vault.	`string`	`""`	no
linux_vm_iac_st	Shared storage account name containing bootstrap scripts.	`string`	`""`	no

Name	Description	Type	Default	Required
linux_vm_iac_st_id	Shared storage account resource ID containing bootstrap scripts.	`string`	`""`	no
linux_vm_iac_st_primary_blob_endpoint	Primary blob endpoint for the shared storage account containing bootstrap scripts.	`string`	`""`	no
linux_vm_image_offer	Offer of the Linux VM image.	`string`	`"ubuntu-24_04-lts"`	no
linux_vm_image_publisher	Publisher of the Linux VM image.	`string`	`"Canonical"`	no
linux_vm_image_sku	SKU of the Linux VM image.	`string`	`"server"`	no
linux_vm_image_version	Version of the Linux VM image.	`string`	`"latest"`	no
linux_vm_localization_container_name	Blob container name in the shared IaC storage account that holds Linux VM localization scripts.	`string`	`"localization"`	no
linux_vm_localization_os_script_name	OS-level localization script blob name to download first when the optional Linux VM extension is enabled.	`string`	`"ubuntu.sh"`	no
linux_vm_location	The Azure region in which the Linux VM resources will be created.	`string`	`"canadacentral"`	no
linux_vm_public_network_enabled	Whether to create public IPs and NSGs for Linux VM SSH access.	`bool`	`false`	no
linux_vm_resource_group_name	Target resource group name for the Linux VM resources.	`string`	`""`	no
linux_vm_rg_tags	Module-specific tags merged with the effective root rg_tags and applied to Linux VM module resources.	`map(any)`	`{}`	no
linux_vm_subnet_id	Optional subnet resource ID override for the Linux VM NICs.	`string`	`""`	no
linux_vm_subnet_name	Existing subnet name used for the Linux VM NICs.	`string`	`""`	no
linux_vm_upload_shared_localization_scripts	Whether to also upload shared OS localization scripts such as ubuntu.sh and redhat.sh to the localization container in addition to any per-VM scripts.	`bool`	`false`	no
linux_vm_vm_count	Number of Linux VMs to create.	`number`	`1`	no
linux_vm_vm_name	Base Linux VM name. Environment suffixes are appended by the module.	`string`	`""`	no
linux_vm_vm_size	Azure VM size for each Linux VM.	`string`	`"Standard_D4s_v3"`	no
linux_vm_vnet_id	Optional virtual network resource ID override for the Linux VM NICs.	`string`	`""`	no
linux_vm_vnet_name	Existing virtual network name used for the Linux VM NICs.	`string`	`""`	no

Name	Description	Type	Default	Required
linux_vm_vnet_resource_group_name	Resource group containing the target virtual network.	`string`	`""`	no
linux_vm_workload	Workload identifier used in Linux VM naming and tagging.	`string`	`"iactest"`	no
location	Azure region for the landing zone.	`string`	`"canadacentral"`	no
log_analytics_internet_ingestion_enabled	Whether public ingestion is enabled for the Log Analytics workspace.	`bool`	`true`	no
log_analytics_internet_query_enabled	Whether public query is enabled for the Log Analytics workspace.	`bool`	`true`	no
log_analytics_local_authentication_disabled	Whether local authentication is disabled for the Log Analytics workspace.	`bool`	`false`	no
log_analytics_name	Optional override for the Log Analytics workspace name.	`string`	`""`	no
log_analytics_reservation_capacity_in_gb_per_day	Optional commitment tier in GB/day for the Log Analytics workspace.	`number`	`null`	no
log_analytics_retention_in_days	Retention period in days for the Log Analytics workspace.	`number`	`30`	no
managed_identity_name	Optional override for the landing zone user-assigned managed identity name.	`string`	`""`	no
management_group_parent_management_group_id	Optional parent management group resource ID.	`string`	`""`	no
management_subscription_id	Azure subscription ID used by the aliased azurerm.management provider.	`string`	`"624ce74e-cf6e-4eed-afba-352bcf08bca0"`	no
management_tenant_id	Azure tenant ID used by the aliased azurerm.management provider.	`string`	`"d5b038fb-4b39-41cc-8a10-fba75212180b"`	no
mg_landingzone_children	Child management groups created under the landing zone management group.	map(object({ display_name = string }))	{}	no
Name	Description	Type	Default	Required

mg_platform_children	Child management groups created under the platform management group.	map(object({
		display_name = string
		}))
			{
			"connectivity": {
			"display_name": "Connectivity"
			},
			"identity": {
			"display_name": "Identity"
			},
				no

Name	Description	Type	Default	Required

			"management": {
			"display_name": "
			Management"
			},
			"security": {
			"display_name": "Security"
			}
			}	

nsg_name	Optional override for the landing zone NSG name.	`string`	`""`	no
openai_custom_subdomain_name	Optional custom subdomain name for the Azure OpenAI account.	`string`	`""`	no
openai_deployments	Azure OpenAI model deployments keyed by deployment name.	map(object({ model_format = string model_name = string model_version = optional(string) sku_name = string sku_capacity = optional(number) sku_family = optional(string) sku_size = optional(string) sku_tier = optional(string) dynamic_throttling_enabled = optional(bool) rai_policy_name = optional(string) version_upgrade_option = optional(string) }))	{}	no
openai_diagnostic_log_categories	Diagnostic log categories to enable for Azure OpenAI.	`list(string)`	`[]`	no
openai_diagnostic_metric_categories	Diagnostic metric categories to enable for Azure OpenAI.	`list(string)`	["AllMetrics"]	no
openai_dynamic_throttling_enabled	Whether dynamic throttling is enabled for the Azure OpenAI account.	`bool`	`false`	no
openai_enable_diagnostics	Whether to send Azure OpenAI diagnostics to the shared Log Analytics workspace.	`bool`	`false`	no
openai_local_auth_enabled	Whether local auth keys are enabled on the Azure OpenAI account.	`bool`	`true`	no
openai_name	Optional override for the Azure OpenAI account name.	`string`	`""`	no

Name	Description	Type	Default	Required

openai_network_acls	Optional network ACL configuration for the Azure OpenAI account.	object({
		default_action = string
		bypass = optional(string)
		ip_rules = optional(set(string))
		virtual_network_rules =
		optional(set(object({
		subnet_id = string
		ignore_missing_vnet_service_endpoint =
		optional(bool)
		})))
		})
			`null`	no

openai_outbound_network_access_restricted	Whether outbound network access is restricted on the Azure OpenAI account.	`bool`	`false`	no
openai_private_dns_zone_id	Optional override private DNS zone ID for the Azure OpenAI private endpoint. Leave empty to use the landing zone private DNS module when privatelink.openai.azure.com is present.	`string`	`""`	no
openai_public_network_access_enabled	Whether public network access is enabled on the Azure OpenAI account.	`bool`	`true`	no
openai_sku_name	SKU name for the Azure OpenAI account.	`string`	`"S0"`	no
platform_mg_display	Optional override for the management group display name.	`string`	`"Platform Dev"`	no
platform_mg_name	Optional override for the management group ID.	`string`	`"mg-platform-dev"`	no
platform_role_assignments	Optional platform RBAC assignments for the landing zone.	map(object({ scope = string role_definition_name = optional(string) role_definition_id = optional(string) principal_id = optional(string) principal_name = optional(string) principal_type = optional(string) condition = optional(string) condition_version = optional(string) }))	`{}`	no
private_dns_zone_names	Private DNS zones created and linked to both hub and spoke VNets.	`list(string)`	["privatelink.azurewebsites.net"]	no

Name	Description	Type	Default	Required
private_endpoint_subnet_prefixes	Address prefixes for the private endpoint subnet in the spoke VNet.	`list(string)`	["10.167.71.0/24"]	no
prod_subscription_id	Azure subscription ID used by the aliased azurerm.prod provider.	`string`	`"1ec5edd4-5654-4246-8027-b29ef63b3393"`	no
prod_tenant_id	Azure tenant ID used by the aliased azurerm.prod provider.	`string`	`"d5b038fb-4b39-41cc-8a10-fba75212180b"`	no
resource_group_name	Optional override for the landing zone resource group name.	`string`	`""`	no

rg_tags	13 default tags. The Environment tag is updated dynamically from the environment variable, and the remaining tags can be overridden with rg_tags.	`map(string)`	{
			"AppSupport Team": "CCOE",
			"Application Name": "CCOE INFRA IAC",
			"Application Owner": "CCOE",
			"Approval Group": "CCOE",
			"Business Owner": "CCOE",
			"Environment": "Sandbox",
			"Infra Availability Classification": "Bronze",
			"InfraSupport Team": "CCOE",
			"Maintenance Window": "CCOE",
			"Project Name": "CCOE INFRA IAC",
			"Project Number": "N/A",
			"RPO-RTO": "48H/24H",
			"Run Cost(Approved Run Budget)-USD": "100"
			}
				no

route_table_name	Optional override for the route table name.	`string`	`""`	no
sandbox_mg_display	Optional override for the sandbox management group display name.	`string`	`"Sandboxes"`	no
sandbox_mg_name	Optional override for the sandbox management group ID.	`string`	`"mg-sandboxes"`	no
security_subscription_id	Azure subscription ID used by the aliased azurerm.security provider.	`string`	`"903e61ee-68d8-4fee-aefd-5e207a6b0892"`	no
security_tenant_id	Azure tenant ID used by the aliased azurerm.security provider.	`string`	`"d5b038fb-4b39-41cc-8a10-fba75212180b"`	no

Name	Description	Type	Default	Required
shared_data_allowed_ipv4_cidrs	Approved public IPv4 addresses or CIDRs for shared storage and Key Vault. Empty allows no explicit public clients.	`list(string)`	`[]`	no
shared_data_public_network_access_enabled	Enable the shared storage and Key Vault public endpoints, restricted by deny-by-default ACLs. Requires approved IP access or private connectivity for data-plane operations.	`bool`	`false`	no
spoke_address_space	Address space for the spoke virtual network.	`list(string)`	["10.167.64.0/20"]	no
spoke_vnet_name	Optional override for the spoke virtual network name.	`string`	`""`	no
sql_ad_admin_login	Microsoft Entra administrator name used by the Azure SQL Database example.	`string`	`"sql-admin-group"`	no
sql_ad_admin_object_id	Microsoft Entra administrator object ID used by the Azure SQL Database example.	`string`	`"00000000-0000-0000-0000-000000000000"`	no
sql_admin_credentials_key_vault_id	Optional Key Vault resource ID containing the SQL admin username and password secrets. When set, this takes precedence for SQL admin secret lookup when inline values are empty.	`string`	`""`	no
sql_admin_password	Administrator password used by the Azure SQL Database example.	`string`	`"ChangeMeSql12345!"`	no
sql_admin_password_secret_name	Optional Key Vault secret name for the SQL admin password fallback.	`string`	`""`	no
sql_admin_username	Administrator login used by the Azure SQL Database example.	`string`	`"sqladminuser"`	no
sql_admin_username_secret_name	Optional Key Vault secret name for the SQL admin username fallback.	`string`	`""`	no
sql_auto_pause_delay_in_minutes	Serverless auto-pause delay in minutes. Set null for non-serverless SQL SKUs.	`number`	`null`	no
sql_backup_storage_redundancy	Backup storage redundancy for the Azure SQL Database example. Valid values are Local, Zone, or Geo.	`string`	`"Local"`	no
sql_enable_private_endpoint	Whether to create a private endpoint for the Azure SQL Server.	`bool`	`true`	no
sql_firewall_rules	Optional SQL Server firewall rules keyed by rule name.	map(object({ start_ip_address = string end_ip_address = string }))	{}	no

Name	Description	Type	Default	Required
sql_free_limit_exhaustion_behavior	Behavior when the Azure SQL free monthly limits are exhausted. Use AutoPause to pause for the rest of the month or BillOverUsage to allow billable overage.	`string`	`"AutoPause"`	no
sql_geo_backup_enabled	Whether geo backups are enabled for the SQL Database.	`bool`	`true`	no
sql_iac_kv	Optional shared Key Vault name containing SQL admin secrets. Used with sql_iac_rg when sql_admin_credentials_key_vault_id is empty.	`string`	`""`	no
sql_iac_rg	Optional resource group name for the shared Key Vault containing SQL admin secrets. Used when sql_admin_credentials_key_vault_id is empty.	`string`	`""`	no
sql_max_size_gb	The maximum size of the SQL Database in gigabytes.	`number`	`32`	no
sql_min_capacity	Minimum vCore capacity for Azure SQL serverless databases. Set null for non-serverless SQL SKUs.	`number`	`null`	no
sql_public_network_access_enabled	Whether to enable public network access on the Azure SQL Server.	`bool`	`false`	no
sql_sku_name	The SKU Name for the SQL Database.	`string`	`"S0"`	no
sql_use_free_limit	Whether the Azure SQL Database should use the Azure SQL free monthly limits.	`bool`	`false`	no
sqlmi_admin_password	Administrator password used by the SQL Managed Instance example.	`string`	`"ChangeMeSqlMi12345!"`	no
sqlmi_admin_username	Administrator login used by the SQL Managed Instance example.	`string`	`"sqlmiadminuser"`	no
sqlmi_subnet_prefixes	Address prefixes for the SQL Managed Instance subnet in the spoke VNet.	`list(string)`	["10.167.76.0/24"]	no
static_web_app_location	Azure region for Static Web Apps. This can differ from the resource group region because Static Web Apps has a limited regional footprint.	`string`	`"eastus2"`	no
Name	Description	Type	Default	Required
static_web_apps	Static Web App demo instances to provision. Each enabled instance uses the upstream module's Free SKU.	map(object({ name = string enabled = optional(bool, true) app_settings = optional(map(string), {}) configuration_file_changes_enabled = optional(bool, true) preview_environments_enabled =	`{}`	no

Name	Description	Type	Default	Required
		optional(bool, true) public_network_access_enabled = optional(bool, true) }))		
storage_account_allow_state_container_immutability	Whether to allow applying an immutability policy to the terraform state container.	`bool`	`false`	no
storage_account_blob_restore_policy_days	Retention in days for point-in-time blob restore on the landing zone storage account.	`number`	`13`	no
storage_account_blob_restore_policy_enabled	Whether point-in-time blob restore is enabled on the landing zone storage account.	`bool`	`true`	no
storage_account_blob_soft_delete_enabled	Whether blob soft delete is enabled on the landing zone storage account.	`bool`	`true`	no
storage_account_blob_soft_delete_retention_days	Retention in days for blob soft delete on the landing zone storage account.	`number`	`14`	no
storage_account_blob_versioning_enabled	Whether blob versioning is enabled on the landing zone storage account.	`bool`	`true`	no
storage_account_change_feed_enabled	Whether blob change feed is enabled on the landing zone storage account.	`bool`	`true`	no
storage_account_change_feed_retention_in_days	Optional retention in days for blob change feed. Set to null for the platform default.	`number`	`null`	no
storage_account_container_immutability_policies	Optional container-level immutability policies keyed by container name.	map(object({ immutability_period_since_creation_in_days = number allow_protected_append_writes = optional(bool, false) allow_protected_append_writes_all = optional(bool, false) }))	`{}`	no
storage_account_container_soft_delete_enabled	Whether container soft delete is enabled on the landing zone storage account.	`bool`	`true`	no
storage_account_container_soft_delete_retention_days	Retention in days for container soft delete on the landing zone storage account.	`number`	`14`	no
storage_account_name	Optional override for the landing zone storage account name.	`string`	`""`	no
subscription_alias_enabled	Whether the landing zone should create a new subscription alias.	`bool`	`false`	no

Name	Description	Type	Default	Required
subscription_alias_name	Subscription alias name when subscription_alias_enabled is true.	`string`	`""`	no
subscription_id	Default Azure subscription ID used by the root azurerm provider.	`string`	`"1ec5edd4-5654-4246-8027-b29ef63b3393"`	no
subscription_management_group_id	Existing management group resource ID to use when enable_management_group is false.	`string`	`""`	no
subscription_name	Display name for the subscription bootstrap example.	`string`	`"platform-landingzone-dev"`	no
subscription_resource_provider_registrations	Resource providers to register when subscription bootstrap is enabled.	`list(string)`	`[]`	no
tags	Tags applied to all landing zone resources.	`map(string)`	`{}`	no
tenant_id	Azure tenant ID used by the root azurerm provider.	`string`	`"d5b038fb-4b39-41cc-8a10-fba75212180b"`	no
trusted_ingress_ipv4_cidrs	Trusted IPv4 CIDRs allowed to reach workload HTTPS and SSH ports. Empty disables these explicit NSG allow rules.	`list(string)`	`[]`	no
vnet_integration_prefixes	Address prefixes for the vnet integration subnet in the spoke VNet.	`list(string)`	`[ "10.167.77.0/24" ]`	no
winvm_admin_credentials_key_vault_id	Optional Key Vault resource ID to use specifically for Windows VM admin credential secrets. When set, this takes precedence over the shared winvm_iac_kv value.	`string`	`""`	no
winvm_admin_password	Optional local administrator password override passed to the Windows VM module. Leave empty to use the configured Key Vault secret.	`string`	`""`	no
winvm_admin_password_secret_name	Optional Key Vault secret name containing the Windows VM admin password.	`string`	`""`	no
winvm_admin_username	Optional local administrator username override passed to the Windows VM module. Leave empty to use the configured Key Vault secret.	`string`	`""`	no
winvm_admin_username_secret_name	Optional Key Vault secret name containing the Windows VM admin username.	`string`	`""`	no
winvm_app_admin_group	AD groups granted Contributor on VM/NIC resources and elevated Windows VM login access.	`list(string)`	`[]`	no

Name	Description	Type	Default	Required
winvm_app_env	Environment passed to the Windows VM module. Leave empty to use the landing zone environment.	`string`	`""`	no
winvm_app_user_group	AD groups granted Reader on the VM resource and standard Windows VM login access.	`list(string)`	`[]`	no
winvm_availability_zones	Availability zones used for Windows VM round-robin placement when zone spread is enabled.	`list(string)`	`[ "1", "2", "3" ]`	no
winvm_data_disk_size_gb	Optional additional data disk size in GB. Set to 0 to skip the extra disk.	`number`	`0`	no
winvm_domain	AD domain used by the Windows VM module when domain join is enabled.	`string`	`""`	no
winvm_domain_join_user	Domain join user used by the Windows VM module when domain join is enabled.	`string`	`""`	no
winvm_enable_custom_script_extension	Whether to attach the Windows CustomScriptExtension bootstrap.	`bool`	`false`	no
winvm_enable_defender_performance_mode	Whether the Windows bootstrap may temporarily adjust Microsoft Defender settings during heavy software installation steps.	`bool`	`false`	no
winvm_enable_diagnostics	Whether to enable Windows VM diagnostics to Log Analytics.	`bool`	`false`	no
winvm_enable_domain_join	Whether the Windows VM module should attempt domain join. Sandbox skips domain join inside the module.	`bool`	`false`	no
winvm_enable_entra_login	Whether to enable Microsoft Entra login for Windows.	`bool`	`true`	no
winvm_enable_shir	Whether to enable Self-Hosted Integration Runtime bootstrap and Data Factory RBAC wiring.	`bool`	`false`	no
winvm_enable_zone_spread	Whether to spread multi-VM Windows deployments across availability zones.	`bool`	`true`	no
winvm_iac_kv	Shared Key Vault name containing Windows VM secrets.	`string`	`""`	no
winvm_iac_rg	Resource group containing the shared IaC storage account and Key Vault.	`string`	`""`	no
winvm_iac_st	Shared storage account name containing Windows VM bootstrap scripts.	`string`	`""`	no

Name	Description	Type	Default	Required
winvm_location	The Azure region in which the Windows VM resources will be created. Leave empty to use the landing zone location.	`string`	`""`	no
winvm_patch_mode	Windows VM guest patching mode.	`string`	`"AutomaticByPlatform"`	no
winvm_public_network_enabled	Whether to create public IPs and NSGs for Windows VM access.	`bool`	`false`	no
winvm_resource_group_name	Target resource group name for the Windows VM resources.	`string`	`""`	no
winvm_subnet_name	Existing subnet name used for the Windows VM NICs.	`string`	`""`	no
winvm_tags	Additional tags applied to Windows VM module resources.	`map(string)`	`{}`	no
winvm_vm_count	Number of Windows VMs to create.	`number`	`1`	no
winvm_vm_name	Base Windows VM name. The winvm module appends a two-digit instance suffix, so keep this short enough for the 15-character Windows computer-name limit.	`string`	`""`	no
winvm_vm_size	Azure VM size for each Windows VM.	`string`	`"Standard_D2s_v3"`	no
winvm_vnet_name	Existing virtual network name used for the Windows VM NICs.	`string`	`""`	no
winvm_vnet_resource_group_name	Resource group containing the target virtual network.	`string`	`""`	no
workload	Short workload or platform identifier used in generated names.	`string`	`"lzdemo"`	no

Outputs

Name	Description
features	Feature enablement and compact connection details for enabled resources. Resource IDs, tags, firewalls, and empty values are intentionally omitted.

<!-- END_TF_DOCS -->