

Terraform Reference

This file is generated from the root Terraform module by [terraform-docs](#). Update the Terraform files, then regenerate this document instead of editing it by hand.

Requirements

Name	Version
terraform	>= 1.0
azurerm	>= 4.0
random	~>3.0

Providers

Name	Version
azapi	2.9.0
azurerm	4.74.0

Modules

Name	Source	Version
acr	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/acr	main
adf_basic	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/adf	main
aks	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/aks	main
app_registration_appservice	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/appregistration	main
app_service	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/appservice	main
app_service_plan	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/appserviceplan	main
automation_account	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/automationaccount	main
azure_ai_search	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/azure_ai_search	main
azure_ai_service	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/azure_ai_service	main
hub_virtual_network	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/vnet	main
keyvault	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/keyvault	main
linux_vm_basic	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/linuxvm	main
log_analytics	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/loganalytics	main
mg_landingzone	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/managementgroups	main
mg_landingzone_children	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/managementgroups	main
mg_platform	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/managementgroups	main
mg_platform_children	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/managementgroups	main
mg_sandboxes	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/managementgroups	main
network_security_group	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/nsg	main
openai	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/openai	main
private_dns	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/private_dns	main
resource_group	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/rg	main
spoke_virtual_network	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/vnet	main
sqldb	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/sqldb	main
storage_account	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/storageaccount	main
subscription_vending	git::https://dev.azure.com/CCOE-Azure/laC/_git/template//modules/subscription_vending	main

Resources

Name	Type
azapi_resource.automation_ari_runtime_package	resource
azapi_resource.shared_storage_container	resource
azapi_resource.shared_storage_container_immutability_policy	resource
azapi_update_resource.storage_account_blob_service	resource
azurerm_automation_job_schedule.automation_ari	resource
azurerm_automation_runbook.automation_ari	resource
azurerm_automation_runtime_environment.automation_ari	resource
azurerm_automation_schedule.automation_ari	resource
azurerm_key_vault_secret.linux_vm_admin_override	resource
azurerm_role_assignment.automation_account_key_vault_secrets_officer	resource
azurerm_role_assignment.automation_account_storage_blob_data_contributor	resource
azurerm_role_assignment.linux_vm_app_service_website_contributor	resource
azurerm_storage_container.automation_ari	resource
azurerm_subnet_network_security_group_association.spoke_network_security_group	resource
azurerm_virtual_network_peering.hub_to_spoke	resource
azurerm_virtual_network_peering.spoke_to_hub	resource
azurerm_client_config.current	data source
azurerm_cognitive_account.azure_ai_service	data source
azurerm_cognitive_account.openai	data source
azurerm_data_factory.adf	data source
azurerm_key_vault.landingzone	data source
azurerm_key_vault.sql_iac	data source
azurerm_kubernetes_cluster.aks	data source
azurerm_linux_web_app.app_service_linux	data source
azurerm_mssql_database.sqlldb	data source
azurerm_mssql_server.sqlldb	data source
azurerm_resource_group.landingzone	data source
azurerm_search_service.azure_ai_search	data source
azurerm_storage_account.landingzone	data source
azurerm_windows_web_app.app_service_windows	data source

Inputs

Name	Description	Type
acr_admin_enabled	Whether the ACR admin user is enabled.	bool
acr_anonymous_pull_enabled	Whether anonymous pull access is enabled for ACR.	bool
acr_customer_managed_key_id	Optional Key Vault key ID used to encrypt ACR.	string
acr_customer_managed_key_identity_client_id	Optional user-assigned identity client ID used with the ACR customer-managed key.	string
acr_data_endpoint_enabled	Whether dedicated ACR data endpoints are enabled.	bool

Name	Description	Type
acr_diagnostic_log_categories	Diagnostic log categories to enable for ACR.	<code>list(string)</code>
acr_diagnostic_metric_categories	Diagnostic metric categories to enable for ACR.	<code>list(string)</code>
acr_enable_diagnostics	Whether to send ACR diagnostics to the shared Log Analytics workspace.	<code>bool</code>
acr_enable_network_rule_set	Whether to configure ACR network rules.	<code>bool</code>
acr_enable_private_endpoint	Whether to create a private endpoint for ACR.	<code>bool</code>
acr_export_policy_enabled	Whether the ACR export policy is enabled.	<code>bool</code>
acr_georeplications	Optional ACR georeplication locations.	<pre>list(object({ location = string regional_endpoint_enabled = optional(bool, true) zone_redundancy_enabled = optional(bool, false) tags = optional(map(string), {}) }))</pre>
acr_identity_ids	User-assigned managed identity IDs for ACR when <code>acr_identity_type</code> includes <code>UserAssigned</code> .	<code>list(string)</code>
acr_identity_type	Managed identity type for ACR.	<code>string</code>
acr_managed_identity_role_assignments	Role assignments to apply to the ACR system-assigned managed identity.	<pre>map(object({ scope = string role_definition_name = optional(string) role_definition_id = optional(string) }))</pre>
acr_name	Optional base name override for the Azure Container Registry. The ACR module adds the <code>acr</code> prefix, region, environment, and numeric suffix.	<code>string</code>
acr_network_rule_bypass_option	Bypass option for the ACR network rule set.	<code>string</code>
acr_network_rule_default_action	Default action for the ACR network rule set.	<code>string</code>
acr_network_rule_ip_rules	Optional public IP CIDR ranges allowed by ACR network rules.	<code>list(string)</code>
acr_private_dns_zone_id	Optional private DNS zone ID for the ACR private endpoint. Leave empty to	<code>string</code>

Name	Description	Type
	use privatelink.azurecr.io from the landing zone private DNS module when present.	
acr_private_dns_zone_name	Optional existing private DNS zone name used for ACR private endpoint lookup when acr_private_dns_zone_id is not set.	string
acr_private_dns_zone_resource_group_name	Optional resource group containing acr_private_dns_zone_name.	string
acr_public_network_access_enabled	Whether public network access is enabled for ACR.	bool
acr_quarantine_policy_enabled	Whether the ACR quarantine policy is enabled.	bool
acr_retention_policy_in_days	Days to retain untagged manifests before purge. Supported only on Premium SKU.	number
acr_sku	SKU for the Azure Container Registry.	string
acr_trust_policy_enabled	Whether the ACR trust policy is enabled.	bool
acr_zone_redundancy_enabled	Whether zone redundancy is enabled for the primary ACR registry.	bool
adf_analytics_destination_type	Log Analytics destination type for ADF diagnostic settings.	string
adf_cleanup_enabled	Whether ADF data flow clusters are cleaned up after runs.	bool
adf_compute_type	Compute type for the default Azure Integration Runtime data flow cluster.	string
adf_core_count	Core count for the default Azure Integration Runtime data flow cluster.	number
adf_default_integration_runtime_name	Optional override for the default Azure Integration Runtime name inside Data Factory.	string
adf_diagnostics_name	Optional override for the Azure Monitor diagnostic settings name used by the ADF module.	string
adf_enable_diagnostics	Whether to send Azure Data Factory diagnostics to the shared Log Analytics workspace.	bool
adf_enable_private_endpoint	Whether to create the Azure Data Factory control-plane private endpoint.	bool
adf_global_parameters	Optional Data Factory global parameters.	<pre>list(object({ name = string type = optional(string, "String") value = string }))</pre>
adf_managed_private_endpoints	Optional managed private endpoints created from Azure Data Factory.	<pre>set(object({ name = string target_resource_id = string subresource_name = string }))</pre>

Name	Description	Type
adf_managed_virtual_network_enabled	Whether to enable the managed virtual network for Azure Data Factory.	bool
adf_name	Optional override for the Azure Data Factory name.	string
adf_permissions	Optional Azure Data Factory resource-level permissions in the module's expected object_id/role shape.	list(map(string))
adf_private_dns_zone_id	Optional existing private DNS zone ID for privatelink.datafactory.azure.net.	string
adf_private_dns_zone_name	Private DNS zone name used for Azure Data Factory control-plane private endpoint resolution.	string
adf_private_dns_zone_resource_group_name	Resource group containing the existing Azure Data Factory private DNS zone when an explicit zone ID is not provided.	string
adf_public_network_enabled	Whether the Azure Data Factory control plane is exposed to the public network.	bool
adf_self_hosted_integration_runtime_enabled	Whether to enable the self-hosted integration runtime path for the ADF module.	bool
adf_shir_name	Optional override for the SHIR name when self-hosted integration runtime is enabled.	string
adf_time_to_live_min	Time-to-live for the default Azure Integration Runtime data flow cluster.	number
adf_virtual_network_enabled	Whether the default Azure Integration Runtime uses managed virtual network execution.	bool
adf_vsts_configuration	Azure DevOps repository configuration for Data Factory source control integration.	<pre>object({ account_name = string project_name = string repository_name = string branch_name = string root_folder = string tenant_id = string collaboration_branch = optional(string) })</pre>
aks_app_admin_group	List of Microsoft Entra group display names or object IDs that should receive AKS admin access.	list(string)
aks_app_user_group	List of Microsoft Entra group display names or object IDs that should receive Reader access on the AKS cluster resource.	list(string)
aks_automatic_upgrade_channel	AKS automatic upgrade channel.	string
aks_azure_rbac_enabled	Whether Azure RBAC for Kubernetes Authorization is enabled.	bool
aks_default_node_pool	AKS default node pool configuration.	<pre>object({ name = optional(string, "system")</pre>

Name	Description	Type
		<pre> vm_size = optional(string, "Standard_D4s_v5") node_count = optional(number, 1) enable_auto_scaling = optional(bool, false) min_count = optional(number) max_count = optional(number) zones = optional(list(string), []) os_disk_size_gb = optional(number, 128) max_pods = optional(number) vnet_subnet_id = optional(string) only_critical_addons_enabled = optional(bool, false) orchestrator_version = optional(string) os_sku = optional(string, "Ubuntu") type = optional(string, "VirtualMachineScaleSets") upgrade_settings = optional(object({ max_surge = optional(string) drain_timeout_in_minutes = optional(number) node_soak_duration_in_minutes = optional(number) }))) }) </pre>
aks_diagnostic_log_categories	AKS diagnostic log categories to enable.	<code>list(string)</code>
aks_diagnostic_metric_categories	AKS diagnostic metric categories to enable.	<code>list(string)</code>
aks_dns_prefix	Optional override for the AKS DNS prefix.	<code>string</code>
aks_enable_diagnostics	Whether to enable diagnostics for AKS.	<code>bool</code>
aks_kubernetes_version	Optional Kubernetes version for AKS.	<code>string</code>
aks_local_account_disabled	Whether local AKS admin accounts are disabled.	<code>bool</code>
aks_log_analytics_workspace_id	Optional override for the Log Analytics workspace resource ID used by AKS diagnostics.	<code>string</code>
aks_name	Optional override for the AKS cluster name.	<code>string</code>
aks_network_profile	AKS network profile configuration.	<pre> object({ network_plugin = optional(string, "azure") network_plugin_mode = optional(string) network_policy = optional(string) service_cidr = optional(string) dns_service_ip = optional(string) load_balancer_sku = optional(string, "standard") </pre>

Name	Description	Type
		<pre> outbound_type = optional(string, "loadBalancer") }) </pre>
aks_oidc_issuer_enabled	Whether the AKS OIDC issuer is enabled.	bool
aks_private_cluster_enabled	Whether the AKS API server is private.	bool
aks_private_dns_zone_id	Optional private DNS zone resource ID for AKS.	string
aks_private_dns_zone_name	Optional private DNS zone name for AKS lookup.	string
aks_private_dns_zone_resource_group_name	Optional resource group containing aks_private_dns_zone_name.	string
aks_role_based_access_control_enabled	Whether Kubernetes RBAC is enabled.	bool
aks_sku_tier	AKS SKU tier.	string
aks_subnet_prefixes	Address prefixes for the AKS subnet in the spoke VNet.	list(string)
aks_tags	A mapping of tags to assign to the AKS cluster.	map(string)
aks_terraform_execution_aks_role	Optional AKS Kubernetes RBAC role to assign to the current Terraform execution identity.	string
aks_workload_identity_enabled	Whether AKS Workload Identity is enabled.	bool
allowed_policy_locations	Allowed Azure regions used by the sample allowed locations policy.	list(string)
app_admin_group	Optional Entra groups or object IDs with Contributor-style access on landing zone resources.	list(string)
app_registration_create_client_secret	Whether to create and store an app registration client secret for the App Service.	bool
app_registration_display_name	Optional display name override for the App Service app registration.	string
app_registration_web_redirect_uris	Optional explicit redirect URIs for the App Service app registration.	list(string)
app_service_allow_anonymous	Whether Easy Auth should allow anonymous requests.	bool
app_service_app_secret_key	Application secret key setting for the sample app. Replace before production use.	string
app_service_app_settings	Additional App Service app settings merged with the module defaults.	map(string)

Name	Description	Type
app_service_auth_mode	Authentication mode for the App Service: none, easy_auth, msal, or both.	string
app_service_dotnet_version	The .NET runtime version configured on the Windows App Service.	string
app_service_enable_private_endpoint	n/a	bool
app_service_ip_restriction_default_action	Default action for App Service site access traffic that does not match an IP restriction rule.	string
app_service_ip_restrictions	Site access restrictions for the App Service public endpoint.	<pre>list(object({ action = optional(string, "Allow") ip_address = optional(string) name = string priority = number service_tag = optional(string) headers = optional(object({ x_forwarded_for = optional(list(string)) x_forwarded_host = optional(list(string)) x_azure_fdid = optional(list(string)) x_fd_health_probe = optional(list(string)) }))) }))</pre>
app_service_kind	The App Service operating system kind.	string
app_service_node_version	The Node.js runtime version configured on the App Service when appservice_stack is node.	string
app_service_plan_autoscale_cpu_threshold_scale_down	CPU threshold percentage that triggers App Service Plan scale in.	number
app_service_plan_autoscale_cpu_threshold_scale_up	CPU threshold percentage that triggers App Service Plan scale out.	number
app_service_plan_autoscale_default_capacity	Default App Service Plan autoscale instance count.	number
app_service_plan_autoscale_max_capacity	Maximum App Service Plan autoscale instance count.	number
app_service_plan_autoscale_min_capacity	Minimum App Service Plan autoscale instance count.	number
app_service_plan_autoscale_scale_down_increment	Number of App Service Plan instances to remove when scaling in.	number
app_service_plan_autoscale_scale_up_increment	Number of App Service Plan instances to add when scaling out.	number
app_service_plan_enable_autoscale	Whether to enable autoscale for the App Service Plan.	bool
app_service_plan_enable_diagnostics	Whether to send App Service Plan diagnostics to Log Analytics.	bool
app_service_plan_os_type	Operating system type for the App Service Plan.	string
app_service_plan_sku_name	SKU name for the App Service Plan.	string
app_service_public_network_access_enabled	Whether public network access is enabled for the App Service.	bool

Name	Description	Type
app_service_python_version	The Python runtime version configured on the App Service when appservice_stack is python.	string
app_service_scmlpSecurityRestrictionsUseMain	Optional App Service property override for scmlpSecurityRestrictionsUseMain. When null, app_service_scm_use_main_ip_restriction is used.	bool
app_service_scm_basic_auth_publishing_credentials_enabled	Whether SCM basic authentication publishing credentials are enabled.	bool
app_service_scm_ip_restriction_default_action	Default action for Kudu/SCM endpoint traffic that does not match an IP restriction rule.	string
app_service_scm_ip_restrictions	Kudu/SCM endpoint access restrictions for the App Service.	<pre>list(object({ action = optional(string, "Allow") description = optional(string) ip_address = optional(string) name = string priority = number service_tag = optional(string) virtual_network_subnet_id = optional(string) headers = optional(object({ x_forwarded_for = optional(list(string)) x_forwarded_host = optional(list(string)) x_azure_fdid = optional(list(string)) x_fd_health_probe = optional(list(string)) }))) }))</pre>
app_service_scm_use_main_ip_restriction	Whether the Kudu/SCM endpoint should reuse the main App Service IP restrictions.	bool
app_service_unauthenticated_action	Optional Easy Auth unauthenticated action override.	string
app_service_vnet_integration_enabled	Whether to integrate the App Service with the spoke application subnet.	bool
app_service_vnet_route_all_enabled	Whether App Service VNet integration routes all outbound traffic through the VNet.	bool
app_service_webdeploy_publish_basic_authentication_enabled	Whether WebDeploy basic publishing authentication is enabled.	bool
app_services	App Service instances to provision. Toggle each stack with enabled.	<pre>map(object({ enabled = bool stack = string kind = string plan_os_type = string sku_name = string deployment_method = optional(string, "run_from_package") }))</pre>

Name	Description	Type
		<pre> use_32_bit_worker = optional(bool) startup_command = optional(string) dotnet_version = optional(string) node_version = optional(string) python_version = optional(string) app_settings = optional(map(string), {}) # Deprecated: prefer deployment_method. Retained only for backward compatibility # when older callers omit deployment_method. deployment_center_enabled = optional(bool, false) deployment_center_azure_repos_organization = optional(string) deployment_center_azure_repos_project = optional(string) deployment_center_azure_repos_repository = optional(string) deployment_center_azure_repos_branch = optional(string, "main") deployment_center_use_manual_integration = optional(bool, true)))) </pre>
app_subnet_prefixes	Address prefixes for the application subnet in the spoke VNet.	<code>list(string)</code>
app_user_group	Optional Entra groups or object IDs with Reader-style access on landing zone resources.	<code>list(string)</code>
appservice_stack	Application runtime stack used by the App Service module.	<code>string</code>
automation_accounts	Automation Account instances to provision. Toggle each account with enabled.	<pre> map(object({ enabled = bool name = optional(string) sku_name = optional(string, "Basic") local_auth_enabled = optional(bool, false) public_access_enabled = optional(bool, true) system_managed_identity_enabled = optional(bool, true) app_admin_group = </pre>

Name	Description	Type
		<pre> optional(list(string), []) app_user_group = optional(list(string), []) managed_identity_role_assignments = optional(map(object({ scope = string role_definition_name = optional(string) role_definition_id = optional(string) })), {}) private_endpoint_enabled = optional(bool, false) private_endpoint_subresource_name = optional(string, "Webhook") enable_webhook_private_endpoint = optional(bool) enable_hrprivate_endpoint = optional(bool) private_endpoint_subnet_id = optional(string, "") private_endpoint_subnet_name = optional(string) private_endpoint_vnet_name = optional(string) private_endpoint_network_resource_group_name = optional(string) private_dns_zone_id = optional(string, "") enable_diagnostics = optional(bool, true) diagnostic_log_categories = optional(list(string), ["JobLogs", "JobStreams", "AuditEvent", "DscNodeStatus"]) diagnostic_metric_categories = optional(list(string), ["AllMetrics"]) tags = optional(map(string), {}) })) </pre>
automation_ari_workloads	Azure Resource Inventory (ARI) workloads to attach to provisioned Automation Accounts.	<pre> map(object({ enabled = bool automation_account_key = string storage_container_name = optional(string, "ari") report_name = optional(string, "AZURE") report_dir = optional(string, "C:\AzureResourceInventory") ari_lite_mode = optional(bool, false) ari_diagram_full_environment_enabled = optional(bool, true) ari_security_center_enabled = optional(bool, true) runbook_name = optional(string, "ARI_Runbook") runtime_environment_name = optional(string, "PowerShell-7.4-Env") runbook_template_path = optional(string, "runbooks/ari.ps1.tftpl") runtime_packages = optional(map(string), {}) schedule_enabled = optional(bool, true) </pre>

Name	Description	Type
		<pre> schedule_name = optional(string, "Azure Inventory Collection - daily") schedule_description = optional(string, "Daily schedule for the ARI runbook.") schedule_frequency = optional(string, "Day") schedule_interval = optional(number, 1) schedule_timezone = optional(string, "America/Toronto") schedule_start_time = optional(string) runbook_log_verbose = optional(bool, true) runbook_log_progress = optional(bool, true) enable_job_failure_alert = optional(bool, true) job_failure_alert_name = optional(string) job_failure_severity = optional(number, 2) enable_long_running_alert = optional(bool, true) long_running_alert_name = optional(string) long_running_severity = optional(number, 3) long_running_threshold_minutes = optional(number, 90) alert_evaluation_frequency = optional(string, "PT15M") alert_window_duration = optional(string, "PT15M") monitor_action_group_ids = optional(list(string), []) tags = optional(map(string), {})))) </pre>
azure_ai_search_allowed_ips	Optional list of public IP ranges allowed to access the Azure AI Search service.	<code>list(string)</code>
azure_ai_search_authentication_failure_mode	Optional authentication failure mode for the Azure AI Search service.	<code>string</code>
azure_ai_search_customer_managed_key_enforcement_enabled	Whether customer-managed key enforcement is enabled on the Azure AI Search service.	<code>bool</code>
azure_ai_search_diagnostic_log_categories	Diagnostic log categories to enable for Azure AI Search.	<code>list(string)</code>
azure_ai_search_diagnostic_metric_categories	Diagnostic metric categories to enable for Azure AI Search.	<code>list(string)</code>
azure_ai_search_enable_diagnostics	Whether to send Azure AI Search diagnostics to the shared Log Analytics workspace.	<code>bool</code>
azure_ai_search_hosting_mode	Hosting mode for the Azure AI Search service.	<code>string</code>

Name	Description	Type
azure_ai_search_identity	Optional managed identity configuration for the Azure AI Search service.	<pre>object({ type = string identity_ids = optional(set(string)) })</pre>
azure_ai_search_local_authentication_enabled	Whether API-key based local authentication is enabled on the Azure AI Search service.	bool
azure_ai_search_name	Optional override for the Azure AI Search service name.	string
azure_ai_search_network_rule_bypass_option	Optional network rule bypass option for the Azure AI Search service.	string
azure_ai_search_partition_count	Partition count for the Azure AI Search service.	number
azure_ai_search_private_dns_zone_id	Optional override private DNS zone ID for the Azure AI Search private endpoint. Leave empty to use the landing zone private DNS module when privatelink.search.windows.net is present.	string
azure_ai_search_public_network_access_enabled	Whether public network access is enabled on the Azure AI Search service.	bool
azure_ai_search_replica_count	Replica count for the Azure AI Search service.	number
azure_ai_search_semantic_search_sku	Optional semantic ranker SKU for the Azure AI Search service.	string
azure_ai_search_sku	SKU for the Azure AI Search service.	string
azure_ai_service_custom_subdomain_name	Optional custom subdomain name for the Azure AI Services account.	string
azure_ai_service_customer_managed_key	Optional customer-managed key configuration for the Azure AI Services account.	<pre>object({ key_vault_key_id = string identity_client_id = optional(string) })</pre>
azure_ai_service_diagnostic_log_categories	Diagnostic log categories to enable for Azure AI Services.	list(string)
azure_ai_service_diagnostic_metric_categories	Diagnostic metric categories to enable for Azure AI Services.	list(string)
azure_ai_service_dynamic_throttling_enabled	Whether dynamic throttling is enabled for the Azure AI Services account.	bool
azure_ai_service_enable_diagnostics	Whether to send Azure AI Services diagnostics to the shared Log Analytics workspace.	bool
azure_ai_service_fqdns	Optional list of outbound FQDNs for the Azure AI Services account.	list(string)

Name	Description	Type
azure_ai_service_identity	Optional managed identity configuration for the Azure AI Services account.	<pre>object({ type = string identity_ids = optional(set(string)) })</pre>
azure_ai_service_local_auth_enabled	Whether local auth keys are enabled on the Azure AI Services account.	bool
azure_ai_service_name	Optional override for the Azure AI Services account name.	string
azure_ai_service_network_acls	Optional network ACL configuration for the Azure AI Services account.	<pre>object({ default_action = string bypass = optional(string) ip_rules = optional(set(string)) virtual_network_rules = optional(set(object({ subnet_id string ignore_missing_vnet_service_endpoint = optional(bool) }))) })</pre>
azure_ai_service_outbound_network_access_restricted	Whether outbound network access is restricted on the Azure AI Services account.	bool
azure_ai_service_private_dns_zone_id	Optional override private DNS zone ID for the Azure AI Services private endpoint. Leave empty to use the landing zone private DNS module when privatelink.cognitiveservices.azure.com is present.	string
azure_ai_service_project_management_enabled	Whether project management is enabled for the Azure AI Services account.	bool
azure_ai_service_public_network_access_enabled	Whether public network access is enabled on the Azure AI Services account.	bool
azure_ai_service_sku_name	SKU name for the Azure AI Services account.	string
azure_ai_service_storage	Optional storage account attachments for the Azure AI Services account.	<pre>list(object({ storage_account_id = string identity_client_id = optional(string) }))</pre>
bastion_resource_group_name	Resource group containing bastion_resource_name.	string
bastion_resource_name	Optional Bastion host name that receives Network Contributor RBAC for linux_vm_app_admin_group and linux_vm_app_user_group.	string
billing_scope_id	Billing scope ID when creating a new subscription alias.	string

Name	Description	Type
common_tags	n/a	map(any)
connectivity_subscription_id	Azure subscription ID used by the aliased azure_rm_connectivity provider.	string
databricks_private_subnet_prefixes	Address prefixes for the Databricks private subnet in the spoke VNet.	list(string)
databricks_public_subnet_prefixes	Address prefixes for the Databricks public subnet in the spoke VNet.	list(string)
enable_acr	Enable the Azure Container Registry module in the landing zone.	bool
enable_adf	Enable the Azure Data Factory module in the landing zone.	bool
enable_aks	Whether to deploy the AKS module.	bool
enable_app_registration_for_appservice	Whether to create an Entra app registration for the App Service.	bool
enable_azure_ai_search	Enable the Azure AI Search module in the landing zone.	bool
enable_azure_ai_search_private_endpoint	Whether to create a private endpoint for the Azure AI Search service.	bool
enable_azure_ai_service	Enable the Azure AI Services module in the landing zone.	bool
enable_azure_ai_service_private_endpoint	Whether to create a private endpoint for the Azure AI Services account.	bool
enable_linux_vm	Whether to provision the Linux VM jumpbox module and its related root role assignments.	bool
enable_management_group	Whether to create a management group in the example.	bool
enable_openai	Enable the Azure OpenAI module in the landing zone.	bool
enable_openai_private_endpoint	Whether to create a private endpoint for the Azure OpenAI account.	bool

Name	Description	Type
enable_sqldb	Whether to deploy the Azure SQL Database module.	bool
enable_subscription_bootstrap	Whether to use subscription_vending in the example.	bool
environment	Environment suffix used in generated names.	string
existing_subscription_id	Existing subscription resource ID used when bootstrapping an existing subscription.	string
features	Optional high-level feature switches. Known keys include enable_management_group, enable_subscription_bootstrap, enable_private_dns, enable_adf, enable_azure_ai_search, enable_azure_ai_service, enable_openai, enable_acr, enable_app_services, enable_app_registration_for_appservice, enable_automation_accounts, enable_automation_ari_workloads, enable_linux_vm, enable_aks, and enable_sqldb. Unspecified keys fall back to the existing individual variables.	map(bool)
firewall_name	Optional override for the Azure Firewall name.	string
firewall_sku_tier	Azure Firewall SKU tier.	string
firewall_subnet_prefixes	Address prefixes for AzureFirewallSubnet in the hub VNet.	list(string)
hierarchy_subscriptions	Optional subscription hierarchy entries. By default the map key is the target management group key; set management_group_key to place multiple subscriptions in the same management group.	<pre>map(object({ subscription_name = string existing_subscription_id = string management_group_key = optional(string, "") subscription_alias_enabled = optional(bool, false) subscription_alias_name = optional(string, "") billing_scope_id = optional(string, "") }))</pre>
hub_address_space	Address space for the hub virtual network.	list(string)
hub_vnet_name	Optional override for the hub virtual network name.	string
identity_subscription_id	Azure subscription ID used by the aliased azurerm.identity provider.	string

Name	Description	Type
jumpbox_public_network_enabled	Whether the example jumpbox VMs receive public IPs.	bool
jumpbox_subnet_prefixes	Address prefixes for the jumpbox subnet in the spoke VNet.	list(string)
jumpbox_windows_image_offer	Marketplace image offer passed to the winvm module for the example jumpbox.	string
jumpbox_windows_image_publisher	Marketplace image publisher passed to the winvm module for the example jumpbox.	string
jumpbox_windows_image_sku	Marketplace image SKU passed to the winvm module for the example jumpbox.	string
jumpbox_windows_image_version	Marketplace image version passed to the winvm module for the example jumpbox.	string
key_vault_name	Optional override for the landing zone Key Vault name.	string
landingzone_mg_display	Optional override for the management group display name.	string
landingzone_mg_name	Optional override for the management group ID.	string
linux_vm_admin_credentials_key_vault_id	Optional Key Vault resource ID to use specifically for Linux VM admin credential secrets. When set, this takes precedence over linux_vm_iac_kv_id for resolving azure-user, azure-password, and azureadmin-pubkey.	string
linux_vm_admin_password	Optional root-level admin password override for the Linux VM module. Leave empty to use the admin_password secret from linux_vm_iac_kv.	string
linux_vm_admin_password_secret_name	Optional Key Vault secret name containing the Linux VM admin password.	string
linux_vm_admin_ssh_key	Optional administrator SSH public key override passed to the Linux VM module. Leave empty to use the azureadmin-pubkey secret from linux_vm_iac_kv.	string
linux_vm_admin_ssh_key_secret_name	Optional Key Vault secret name containing the Linux VM admin SSH public key.	string
linux_vm_admin_username	Optional administrator username override passed to the Linux VM module. Leave empty to use the admin_username secret from linux_vm_iac_kv.	string
linux_vm_admin_username_secret_name	Optional Key Vault secret name containing the Linux VM admin username.	string

Name	Description	Type
linux_vm_ado_runner_count	Number of Azure DevOps agents to register on each Linux runner VM.	number
linux_vm_app_admin_group	AD groups granted Contributor on the VM resource and sudo/admin access inside the Linux guest OS.	list(string)
linux_vm_app_env	Environment, such as prod, qa, dev, poc, test, or sbx.	string
linux_vm_app_user_group	AD groups granted Reader on the VM resource and standard SSH access inside the Linux guest OS.	list(string)
linux_vm_common_tags	Common tags merged into all Linux VM module resources.	map(any)
linux_vm_data_disk_size_gb	Optional additional data disk size in GB. Set to 0 to skip the extra disk.	number
linux_vm_datadog_api_key	Legacy Datadog API key retained for Linux VM module compatibility.	string
linux_vm_disable_password_authentication	Whether to disable password authentication for the Linux VM module.	bool
linux_vm_domain	AD domain used by the Linux VM bootstrap script when linux_vm_enable_domain_join = true.	string
linux_vm_domain_join_ou	Legacy domain join OU value retained for Linux VM module compatibility. Only relevant when linux_vm_enable_domain_join = true.	string
linux_vm_domain_join_user	Domain join user in domain\username format, used only when linux_vm_enable_domain_join = true.	string
linux_vm_enable_domain_join	Whether the Linux VM module should attempt domain join during bootstrap. Default is false, which skips the domain-join secret lookup and keeps the VM off domain.	bool
linux_vm_enable_entra_ssh_login	Whether to enable Microsoft Entra ID SSH login on the Linux VMs.	bool
linux_vm_enable_linux_vm_extension	Whether to enable the optional storage-backed localization CustomScript VM extension for Linux VMs.	bool
linux_vm_enable_system_assigned_identity	Whether to enable a system-assigned managed identity on the Linux VMs. Required when linux_vm_enable_linux_vm_extension = true.	bool
linux_vm_iac_kv	Shared Key Vault name containing Linux VM secrets.	string
linux_vm_iac_kv_id	Shared Key Vault resource ID containing Linux VM secrets.	string
linux_vm_iac_rg	Resource group containing the shared IaC storage account and Key Vault.	string

Name	Description	Type
linux_vm_iac_st	Shared storage account name containing bootstrap scripts.	string
linux_vm_iac_st_id	Shared storage account resource ID containing bootstrap scripts.	string
linux_vm_iac_st_primary_blob_endpoint	Primary blob endpoint for the shared storage account containing bootstrap scripts.	string
linux_vm_image_offer	Offer of the Linux VM image.	string
linux_vm_image_publisher	Publisher of the Linux VM image.	string
linux_vm_image_sku	SKU of the Linux VM image.	string
linux_vm_image_version	Version of the Linux VM image.	string
linux_vm_localization_container_name	Blob container name in the shared IaC storage account that holds Linux VM localization scripts.	string
linux_vm_localization_os_script_name	OS-level localization script blob name to download first when the optional Linux VM extension is enabled.	string
linux_vm_location	The Azure region in which the Linux VM resources will be created.	string
linux_vm_public_network_enabled	Whether to create public IPs and NSGs for Linux VM SSH access.	bool
linux_vm_resource_group_name	Target resource group name for the Linux VM resources.	string
linux_vm_rg_tags	Module-specific tags merged with linux_vm_common_tags and applied to Linux VM module resources.	map(any)
linux_vm_subnet_id	Optional subnet resource ID override for the Linux VM NICs.	string
linux_vm_subnet_name	Existing subnet name used for the Linux VM NICs.	string
linux_vm_upload_shared_localization_scripts	Whether to also upload shared OS localization scripts such as ubuntu.sh and redhat.sh to the localization container in addition to any per-VM scripts.	bool
linux_vm_vm_count	Number of Linux VMs to create.	number
linux_vm_vm_name	Base Linux VM name. Environment suffixes are appended by the module.	string
linux_vm_vm_size	Azure VM size for each Linux VM.	string
linux_vm_vnet_id	Optional virtual network resource ID override for the Linux VM NICs.	string
linux_vm_vnet_name	Existing virtual network name used for the Linux VM NICs.	string
linux_vm_vnet_resource_group_name	Resource group containing the target virtual network.	string
linux_vm_workload	Workload identifier used in Linux VM naming and tagging.	string
location	Azure region for the landing zone.	string
log_analytics_internet_ingestion_enabled	Whether public ingestion is enabled for the Log Analytics workspace.	bool

Name	Description	Type
log_analytics_internet_query_enabled	Whether public query is enabled for the Log Analytics workspace.	bool
log_analytics_local_authentication_disabled	Whether local authentication is disabled for the Log Analytics workspace.	bool
log_analytics_name	Optional override for the Log Analytics workspace name.	string
log_analytics_reservation_capacity_in_gb_per_day	Optional commitment tier in GB/day for the Log Analytics workspace.	number
log_analytics_retention_in_days	Retention period in days for the Log Analytics workspace.	number
managed_identity_name	Optional override for the landing zone user-assigned managed identity name.	string
management_group_parent_management_group_id	Optional parent management group resource ID.	string
management_subscription_id	Azure subscription ID used by the aliased azurerm.management provider.	string
mg_landingzone_children	Child management groups created under the landing zone management group.	<pre>map(object({ display_name = string }))</pre>
mg_platform_children	Child management groups created under the platform management group.	<pre>map(object({ display_name = string }))</pre>
nsg_name	Optional override for the landing zone NSG name.	string
openai_custom_subdomain_name	Optional custom subdomain name for the Azure OpenAI account.	string
openai_deployments	Azure OpenAI model deployments keyed by deployment name.	<pre>map(object({ model_format = string model_name = string model_version = optional(string) sku_name = string sku_capacity = optional(number) sku_family = optional(string) sku_size = optional(string) sku_tier = optional(string) dynamic_throttling_enabled = optional(bool)</pre>

Name	Description	Type
		<pre> rai_policy_name = optional(string) version_upgrade_option = optional(string)))) </pre>
openai_diagnostic_log_categories	Diagnostic log categories to enable for Azure OpenAI.	<code>list(string)</code>
openai_diagnostic_metric_categories	Diagnostic metric categories to enable for Azure OpenAI.	<code>list(string)</code>
openai_dynamic_throttling_enabled	Whether dynamic throttling is enabled for the Azure OpenAI account.	<code>bool</code>
openai_enable_diagnostics	Whether to send Azure OpenAI diagnostics to the shared Log Analytics workspace.	<code>bool</code>
openai_local_auth_enabled	Whether local auth keys are enabled on the Azure OpenAI account.	<code>bool</code>
openai_name	Optional override for the Azure OpenAI account name.	<code>string</code>
openai_network_acls	Optional network ACL configuration for the Azure OpenAI account.	<pre> object({ default_action = string bypass = optional(string) ip_rules = optional(set(string)) virtual_network_rules = optional(set(object({ subnet_id = string ignore_missing_vnet_service_endpoint = optional(bool) }))) })) </pre>
openai_outbound_network_access_restricted	Whether outbound network access is restricted on the Azure OpenAI account.	<code>bool</code>
openai_private_dns_zone_id	Optional override private DNS zone ID for the Azure OpenAI private endpoint. Leave empty to use the landing zone private DNS module when privatelink.openai.azure.com is present.	<code>string</code>
openai_public_network_access_enabled	Whether public network access is enabled on the Azure OpenAI account.	<code>bool</code>
openai_sku_name	SKU name for the Azure OpenAI account.	<code>string</code>
platform_mg_display	Optional override for the management group display name.	<code>string</code>
platform_mg_name	Optional override for the management group ID.	<code>string</code>
platform_role_assignments	Optional platform RBAC assignments for the landing zone.	<pre> map(object({ scope = string role_definition_name = optional(string) role_definition_id = optional(string) </pre>

Name	Description	Type
		<pre> principal_id = optional(string) principal_name = optional(string) principal_type = optional(string) condition = optional(string) condition_version = optional(string)))) </pre>
private_dns_zone_names	Private DNS zones created and linked to both hub and spoke VNets.	<code>list(string)</code>
private_endpoint_subnet_prefixes	Address prefixes for the private endpoint subnet in the spoke VNet.	<code>list(string)</code>
prod_subscription_id	Azure subscription ID used by the aliased azurearm.prod provider.	<code>string</code>
resource_group_name	Optional override for the landing zone resource group name.	<code>string</code>
rg_tags	n/a	<code>map(any)</code>
route_table_name	Optional override for the route table name.	<code>string</code>
sandbox_mg_display	Optional override for the sandbox management group display name.	<code>string</code>
sandbox_mg_name	Optional override for the sandbox management group ID.	<code>string</code>
security_subscription_id	Azure subscription ID used by the aliased azurearm.security provider.	<code>string</code>
spoke_address_space	Address space for the spoke virtual network.	<code>list(string)</code>
spoke_vnet_name	Optional override for the spoke virtual network name.	<code>string</code>

Name	Description	Type
sql_ad_admin_login	Microsoft Entra administrator name used by the Azure SQL Database example.	string
sql_ad_admin_object_id	Microsoft Entra administrator object ID used by the Azure SQL Database example.	string
sql_admin_credentials_key_vault_id	Optional Key Vault resource ID containing the SQL admin username and password secrets. When set, this takes precedence for SQL admin secret lookup when inline values are empty.	string
sql_admin_password	Administrator password used by the Azure SQL Database example.	string
sql_admin_password_secret_name	Optional Key Vault secret name for the SQL admin password fallback.	string
sql_admin_username	Administrator login used by the Azure SQL Database example.	string
sql_admin_username_secret_name	Optional Key Vault secret name for the SQL admin username fallback.	string
sql_auto_pause_delay_in_minutes	Serverless auto-pause delay in minutes. Set null for non-serverless SQL SKUs.	number
sql_backup_storage_redundancy	Backup storage redundancy for the Azure SQL Database example. Valid values are Local, Zone, or Geo.	string
sql_enable_private_endpoint	Whether to create a private endpoint for the Azure SQL Server.	bool
sql_firewall_rules	Optional SQL Server firewall rules keyed by rule name.	<pre>map(object({ start_ip_address = string end_ip_address = string }))</pre>
sql_free_limit_exhaustion_behavior	Behavior when the Azure SQL free monthly limits are exhausted. Use AutoPause to pause for the rest of the month or BillOverUsage to allow billable overage.	string
sql_geo_backup_enabled	Whether geo backups are enabled for the SQL Database.	bool
sql_iac_kv	Optional shared Key Vault name containing SQL admin secrets. Used with sql_iac_rg when sql_admin_credentials_key_vault_id is empty.	string
sql_iac_rg	Optional resource group name for the shared Key Vault containing SQL admin secrets. Used when sql_admin_credentials_key_vault_id is empty.	string
sql_max_size_gb	The maximum size of the SQL Database in gigabytes.	number
sql_min_capacity	Minimum vCore capacity for Azure SQL serverless databases. Set null for non-serverless SQL SKUs.	number

Name	Description	Type
sql_public_network_access_enabled	Whether to enable public network access on the Azure SQL Server.	bool
sql_sku_name	The SKU Name for the SQL Database.	string
sql_use_free_limit	Whether the Azure SQL Database should use the Azure SQL free monthly limits.	bool
sqlmi_admin_password	Administrator password used by the SQL Managed Instance example.	string
sqlmi_admin_username	Administrator login used by the SQL Managed Instance example.	string
sqlmi_subnet_prefixes	Address prefixes for the SQL Managed Instance subnet in the spoke VNet.	list(string)
storage_account_allow_state_container_immutability	Whether to allow applying an immutability policy to the terraform state container.	bool
storage_account_blob_restore_policy_days	Retention in days for point-in-time blob restore on the landing zone storage account.	number
storage_account_blob_restore_policy_enabled	Whether point-in-time blob restore is enabled on the landing zone storage account.	bool
storage_account_blob_soft_delete_enabled	Whether blob soft delete is enabled on the landing zone storage account.	bool
storage_account_blob_soft_delete_retention_days	Retention in days for blob soft delete on the landing zone storage account.	number
storage_account_blob_versioning_enabled	Whether blob versioning is enabled on the landing zone storage account.	bool
storage_account_change_feed_enabled	Whether blob change feed is enabled on the landing zone storage account.	bool
storage_account_change_feed_retention_in_days	Optional retention in days for blob change feed. Set to null for the platform default.	number
storage_account_container_immutability_policies	Optional container-level immutability policies keyed by container name.	<pre>map(object({ immutability_period_since_creation_in_days = number allow_protected_append_writes = optional(bool, false) allow_protected_append_writes_all = optional(bool, false) }))</pre>
storage_account_container_soft_delete_enabled	Whether container soft delete is enabled on the landing zone storage account.	bool
storage_account_container_soft_delete_retention_days	Retention in days for container soft delete on the landing zone storage account.	number

Name	Description	Type
storage_account_name	Optional override for the landing zone storage account name.	string
subscription_alias_enabled	Whether the landing zone should create a new subscription alias.	bool
subscription_alias_name	Subscription alias name when subscription_alias_enabled is true.	string
subscription_id	Default Azure subscription ID used by the root azurem provider.	string
subscription_management_group_id	Existing management group resource ID to use when enable_management_group is false.	string
subscription_name	Display name for the subscription bootstrap example.	string
subscription_resource_provider_registrations	Resource providers to register when subscription bootstrap is enabled.	list(string)
tags	Tags applied to all landing zone resources.	map(string)
vnet_integration_prefixes	Address prefixes for the vnet integration subnet in the spoke VNet.	list(string)
workload	Short workload or platform identifier used in generated names.	string

Outputs

Name	Description
acr_id	Azure Container Registry resource ID when the ACR module is enabled.
acr_login_server	Azure Container Registry login server when the ACR module is enabled.
acr_name	Azure Container Registry name when the ACR module is enabled.
acr_private_endpoint_id	Azure Container Registry private endpoint resource ID when private endpoint support is enabled.
adf_id	Azure Data Factory resource ID when the ADF module is enabled.
adf_name	Azure Data Factory name when the ADF module is enabled.
azure_ai_search_endpoint	Azure AI Search endpoint when the Azure AI Search module is enabled.
azure_ai_search_id	Azure AI Search service resource ID when the Azure AI Search module is enabled.
azure_ai_search_name	Azure AI Search service name when the Azure AI Search module is enabled.
azure_ai_search_private_endpoint_id	Azure AI Search private endpoint resource ID when private endpoint support is enabled.
azure_ai_service_endpoint	Azure AI Services endpoint when the Azure AI Services module is enabled.
azure_ai_service_id	Azure AI Services account resource ID when the Azure AI Services module is enabled.
azure_ai_service_name	Azure AI Services account name when the Azure AI Services module is enabled.
azure_ai_service_private_endpoint_id	Azure AI Services private endpoint resource ID when private endpoint support is enabled.
linux_vm_public_ip	Linux VM public IP addresses when the Linux VM module is enabled and public networking is turned on.
openai_deployment_ids	Azure OpenAI deployment resource IDs keyed by deployment name when the OpenAI module is enabled.
openai_endpoint	Azure OpenAI endpoint when the OpenAI module is enabled.
openai_id	Azure OpenAI account resource ID when the OpenAI module is enabled.
openai_name	Azure OpenAI account name when the OpenAI module is enabled.
openai_private_endpoint_id	Azure OpenAI private endpoint resource ID when private endpoint support is enabled.

Name	Description
sqldb_fqdn	FQDN of the Azure SQL Server when the SQL DB module is enabled.
sqldb_public_endpoint	Public SQL endpoint details when the SQL DB module is enabled and public access is configured. public_ip remains null because Azure SQL exposes a public FQDN rather than a dedicated static IP.