

```
In [1]: #meta 1/25/2021 Poker Example 1
#src https://medium.com/@virgoady7/poker-hand-prediction-7a801e254acd
#Claim: Keras nn models predicts much higher than LogR, CART or SVM

#history
#1/25/202 ORIGINAL EXAMPLE + MY CODE DELTA
#    Original code errored out in Keras NN section: problem is with your Lab
el-data shape
#    Fixed with $mycodedelta

#here 1/25/202 MANAGE DATA DOWNLOAD
#    Check if data already exists and downloaded if it doesn't
```

```
In [2]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import os
from os import path
import warnings
warnings.filterwarnings('ignore')

#modeling
from sklearn.linear_model import LogisticRegression
from sklearn.tree import DecisionTreeClassifier
from sklearn import svm
from sklearn.metrics import accuracy_score
from sklearn.metrics import confusion_matrix

#from joblib import load, dump
```

## Poker Example with Keras

### 0. Load Data

```
In [3]: #mycodedelta #was
#!wget http://archive.ics.uci.edu/ml/machine-Learning-databases/poker/poker-ha
nd-testing.data
#!wget http://archive.ics.uci.edu/ml/machine-Learning-databases/poker/poker-ha
nd-training-true.data
#!wget http://archive.ics.uci.edu/ml/machine-Learning-databases/poker/poker-ha
nd.names
```

```
In [4]: #$mycodedelta
#check if data already downloaded
if path.exists('data/poker-hand.names'):
    print('Poker data already exists')
else:
    !wget http://archive.ics.uci.edu/ml/machine-learning-databases/poker/poker-hand-testing.data -O 'data/poker-hand-testing.data'
    !wget http://archive.ics.uci.edu/ml/machine-learning-databases/poker/poker-hand-training-true.data -O 'data/poker-hand-training-true.data'
    !wget http://archive.ics.uci.edu/ml/machine-learning-databases/poker/poker-hand.names -O 'data/poker-hand.names'
```

Poker data already exists

## 1. Prep Data

note: When switch between train and test. SVM runs way longer. NN results are slightly better.

In reality need train , valid and test datasets.

```
In [5]: data_train=pd.read_csv("data/poker-hand-training-true.data",header=None)
data_test = pd.read_csv("data/poker-hand-testing.data",header=None)
#data_test=pd.read_csv("data/poker-hand-training-true.data",header=None)
#data_train = pd.read_csv("data/poker-hand-testing.data",header=None)
col=['Suit of card #1','Rank of card #1','Suit of card #2','Rank of card #2',
'Suit of card #3','Rank of card #3','Suit of card #4','Rank of card #4','Suit of card #5','Rank of card 5','Poker Hand']
col
```

```
Out[5]: ['Suit of card #1',
'Rank of card #1',
'Suit of card #2',
'Rank of card #2',
'Suit of card #3',
'Rank of card #3',
'Suit of card #4',
'Rank of card #4',
'Suit of card #5',
'Rank of card 5',
'Poker Hand']
```

```
In [6]: data_train.columns=col
data_test.columns=col
```

```
In [7]: y_train=data_train['Poker Hand']
y_test=data_test['Poker Hand']
y_train=pd.get_dummies(y_train)
y_test=pd.get_dummies(y_test)
```

```
In [8]: x_train=data_train.drop('Poker Hand',axis=1)
x_test=data_test.drop('Poker Hand',axis=1)
```

```
In [9]: print('Shape of Training Set:',x_train.shape)
        print('Shape of Testing Set:',x_test.shape)
```

Shape of Training Set: (25010, 10)  
Shape of Testing Set: (1000000, 10)

```
In [10]: x_train.head()
```

Out[10]:

	Suit of card #1	Rank of card #1	Suit of card #2	Rank of card #2	Suit of card #3	Rank of card #3	Suit of card #4	Rank of card #4	Suit of card #5	Rank of card #5
0	1	10	1	11	1	13	1	12	1	1
1	2	11	2	13	2	10	2	12	2	1
2	3	12	3	11	3	13	3	10	3	1
3	4	10	4	11	4	1	4	13	4	12
4	4	1	4	13	4	12	4	11	4	10

```
In [11]: from sklearn import preprocessing
        le = preprocessing.LabelEncoder()
        y_train=le.fit_transform(data_train['Poker Hand'])
        y_test=le.transform(data_test['Poker Hand'])
```

```
In [12]: y_train.shape, y_test.shape
```

Out[12]: ((25010,), (1000000,))

## 2. Model

### Logistic Regression

```
In [13]: clf = LogisticRegression(random_state=0, solver='lbfgs',max_iter=100,multi_class='ovr').fit(x_train, y_train)

        #predict
        y_hat=clf.predict(x_test)
        accuracy_score(y_hat,y_test)
```

Out[13]: 0.501209

```
In [14]: unique, counts = np.unique(y_hat, return_counts=True)
        print (np.asarray((unique, counts)).T)
```

```
[[      0 1000000]]
```

```
In [15]: cm = confusion_matrix(y_test, y_hat)
print("Confusion matrix:\n{}".format(cm))
```

Confusion matrix:

```
[[501209      0      0      0      0      0      0      0      0      0]
 [422498      0      0      0      0      0      0      0      0      0]
 [ 47622      0      0      0      0      0      0      0      0      0]
 [ 21121      0      0      0      0      0      0      0      0      0]
 [  3885      0      0      0      0      0      0      0      0      0]
 [  1996      0      0      0      0      0      0      0      0      0]
 [  1424      0      0      0      0      0      0      0      0      0]
 [   230      0      0      0      0      0      0      0      0      0]
 [    12      0      0      0      0      0      0      0      0      0]
 [     3      0      0      0      0      0      0      0      0      0]]
```

## CART

Classification and Regression Trees or CART for short

```
In [16]: decision_tree = DecisionTreeClassifier(random_state=0,max_depth = 3) #max_dept
h =2
decision_tree = decision_tree.fit(x_train,y_train)

#predict
y_hat = decision_tree.predict(x_test)
accuracy_score(y_hat,y_test)
```

Out[16]: 0.501209

```
In [17]: unique, counts = np.unique(y_hat, return_counts=True)
print (np.asarray((unique, counts)).T)

[[      0 1000000]]
```

```
In [18]: cm = confusion_matrix(y_test, y_hat)
print("Confusion matrix:\n{}".format(cm))
```

Confusion matrix:

```
[[501209      0      0      0      0      0      0      0      0      0]
 [422498      0      0      0      0      0      0      0      0      0]
 [ 47622      0      0      0      0      0      0      0      0      0]
 [ 21121      0      0      0      0      0      0      0      0      0]
 [  3885      0      0      0      0      0      0      0      0      0]
 [  1996      0      0      0      0      0      0      0      0      0]
 [  1424      0      0      0      0      0      0      0      0      0]
 [   230      0      0      0      0      0      0      0      0      0]
 [    12      0      0      0      0      0      0      0      0      0]
 [     3      0      0      0      0      0      0      0      0      0]]
```

## SVM

We plot each data item as a point in n-dimensional space (where n is number of features you have) with the value of each feature being the value of a particular coordinate

```
In [19]: clf = svm.LinearSVC()
         clf.fit(x_train,y_train)

         #predict
         y_hat = clf.predict(x_test)
         accuracy_score(y_hat,y_test)
```

Out[19]: 0.43198

```
In [20]: unique, counts = np.unique(y_hat, return_counts=True)
         print (np.asarray((unique, counts)).T)

[[ 0 703526]
 [ 1 169147]
 [ 2 127327]]
```

```
In [21]: cm = confusion_matrix(y_test, y_hat)
         print("Confusion matrix:\n{}".format(cm))
```

Confusion matrix:

```
[[355655  90209  55345      0      0      0      0      0      0      0]
 [295348  68529  58621      0      0      0      0      0      0      0]
 [ 32960   6866   7796      0      0      0      0      0      0      0]
 [ 14304   2838   3979      0      0      0      0      0      0      0]
 [  2752    158    975      0      0      0      0      0      0      0]
 [  1408    365    223      0      0      0      0      0      0      0]
 [   935    154    335      0      0      0      0      0      0      0]
 [   155     28     47      0      0      0      0      0      0      0]
 [     8      0      4      0      0      0      0      0      0      0]
 [     1      0      2      0      0      0      0      0      0      0]]
```

## Neural Net with Keras

A neural network is a progression of algorithms that attempts to perceive fundamental connections in a lot of information through a procedure that copies the manner in which the human brain works. Neural network can adjust to changing input; so the network produces the most ideal outcome without expecting to redesign the output criteria. To create NN we used Keras library which is a high-level API wrapper for the low-level API, capable of running on top of TensorFlow, CNTK, or Theano. My neural network architecture comprised of 3 dense layers with respectively 15,10 and 10 nodes in each layer.

```
In [22]: #$mycodedelta  
#code below errors out: ValueError: Error when checking target: expected dense  
_3 to have shape (10,) but got array with shape (1,)  
#src https://stackoverflow.com/questions/49392972/error-when-checking-target-e  
xpected-dense-3-to-have-shape-3-but-got-array-wi/55992428  
#issue: problem is with label-data shape  
# Keras expects y-data in (N, 10) shape, not (N,)  
# was: y_train.shape, y_test.shape  
# was: ((25010,), (1000000,))  
#fix: Recode labels using to_categorical to get the correct shape of inputs  
from keras.utils import to_categorical  
y_train_nn = to_categorical(y_train)  
y_test_nn = to_categorical(y_test)  
  
y_train_nn.shape, y_test_nn.shape
```

Using TensorFlow backend.

```
Out[22]: ((25010, 10), (1000000, 10))
```

```
In [35]: import keras
from keras.models import Sequential
from keras.layers import Dense, Dropout, Activation
from keras.optimizers import SGD
from keras import regularizers

model = Sequential()
model.add(Dense(15, activation='relu', input_dim=10))
model.add(Dense(10, activation='relu'))
model.add(Dense(10, activation='softmax'))
model.compile(loss='binary_crossentropy',
              optimizer='adam',
              metrics=['accuracy'])

history = model.fit(x_train, y_train_nn, epochs = 10, batch_size = 256, verbose=1, validation_data=(x_test, y_test_nn), shuffle=True) #mycodedelta

score = model.evaluate(x_test, y_test_nn, batch_size=256) #mycodedelta
```

Train on 25010 samples, validate on 1000000 samples

Epoch 1/10

25010/25010 [=====] - 4s 140us/step - loss: 0.3658 - accuracy: 0.8956 - val\_loss: 0.2173 - val\_accuracy: 0.8969

Epoch 2/10

25010/25010 [=====] - 3s 132us/step - loss: 0.1875 - accuracy: 0.8956 - val\_loss: 0.1786 - val\_accuracy: 0.8990

Epoch 3/10

25010/25010 [=====] - 3s 131us/step - loss: 0.1770 - accuracy: 0.8994 - val\_loss: 0.1757 - val\_accuracy: 0.8987

Epoch 4/10

25010/25010 [=====] - 3s 132us/step - loss: 0.1751 - accuracy: 0.9015 - val\_loss: 0.1741 - val\_accuracy: 0.9014

Epoch 5/10

25010/25010 [=====] - 3s 132us/step - loss: 0.1740 - accuracy: 0.9031 - val\_loss: 0.1731 - val\_accuracy: 0.9034

Epoch 6/10

25010/25010 [=====] - 3s 133us/step - loss: 0.1732 - accuracy: 0.9043 - val\_loss: 0.1725 - val\_accuracy: 0.9046

Epoch 7/10

25010/25010 [=====] - 3s 133us/step - loss: 0.1727 - accuracy: 0.9045 - val\_loss: 0.1722 - val\_accuracy: 0.9044

Epoch 8/10

25010/25010 [=====] - 3s 133us/step - loss: 0.1722 - accuracy: 0.9055 - val\_loss: 0.1717 - val\_accuracy: 0.9055

Epoch 9/10

25010/25010 [=====] - 3s 133us/step - loss: 0.1719 - accuracy: 0.9055 - val\_loss: 0.1715 - val\_accuracy: 0.9063


Epoch 10/10

25010/25010 [=====] - 3s 131us/step - loss: 0.1715 - accuracy: 0.9061 - val\_loss: 0.1713 - val\_accuracy: 0.9051

1000000/1000000 [=====] - 2s 2us/step

```
In [36]: plt.figure(figsize=(15, 5))
plt.subplot(1,2,1)
plt.plot(history.history['accuracy']) #mycodedelta
plt.plot(history.history['val_accuracy'])#mycodedelta
plt.title('Model accuracy')
plt.ylabel('Accuracy')
plt.xlabel('Epoch')
plt.legend(['Train', 'Test'], loc='upper left')
plt.subplot(1,2,2)
plt.plot(history.history['loss'])
plt.plot(history.history['val_loss'])
plt.title('Model loss')
plt.ylabel('Loss')
plt.xlabel('Epoch')
plt.legend(['Train', 'Test'], loc='lower left')
```

Out[36]: <matplotlib.legend.Legend at 0x25a62b27d88>



## Evaluate NN model

by predicting on the given test set (which unfortunately has been used for validation, too).

```
In [37]: #predict
y_hat = model.predict(x_test) #numpy.ndarray
y_hat_class = y_hat.argmax(axis=1)
print(y_hat.shape, y_hat_class.shape)
accuracy_score(y_hat_class, y_test)

(1000000, 10) (1000000,)
```

Out[37]: 0.520584

```
In [38]: unique, counts = np.unique(y_hat_class, return_counts=True)
print (np.asarray((unique, counts)).T)

[[ 0 660649]
 [ 1 339332]
 [ 2    19]]
```



```
In [39]: cm = confusion_matrix(y_test, y_hat_class)
print("Confusion matrix:\n{}".format(cm))
```

Confusion matrix:

```
[[360781 140428      0      0      0      0      0      0      0]
 [262701 159796      1      0      0      0      0      0      0]
 [ 24701  22914      7      0      0      0      0      0      0]
 [  9714  11398      9      0      0      0      0      0      0]
 [   700   3185      0      0      0      0      0      0      0]
 [  1500    496      0      0      0      0      0      0      0]
 [   502    922      0      0      0      0      0      0      0]
 [    48    180      2      0      0      0      0      0      0]
 [     0     12      0      0      0      0      0      0      0]
 [     2      1      0      0      0      0      0      0      0]]
```

## Summary

The author claims that the Neural Network using Keras Library enables us to produce the most accurate results above all. I further evaluated the model results by predicting on the test ds and found that NN predictions didn't perform anywhere close to 90% and more like other models ~ 50%.

In ML, using the same test ds for validation and testing is not a valid technique. Next step should be to truly have train, validation and test sets and see how all the models fair with a holdout dataset.

Src: [https://keras.io/guides/training\\_with\\_built\\_in\\_methods/](https://keras.io/guides/training_with_built_in_methods/)

([https://keras.io/guides/training\\_with\\_built\\_in\\_methods/](https://keras.io/guides/training_with_built_in_methods/)). Here's what the typical end-to-end workflow looks like, consisting of:

- Training
- Validation on a holdout set generated from the original training data
- Evaluation on the test data

```
In [40]: mystop
```

```
-----
NameError                                Traceback (most recent call last)
<ipython-input-40-255d8eb4da7e> in <module>
----> 1 mystop

NameError: name 'mystop' is not defined
```

## Xtra

```
In [ ]: ##$extra my export data for reuse
dump(data_train, 'data/poker_ex1_data_train.pkl')
dump(data_test, 'data/poker_ex1_data_test.pkl')
```