Operation microscope

OMS-800 series

OFFISS / Pro / Standard





SEEING EYE HEALTH DIFFERENTLY



Bright Wide Field

Topcon's pursuit for perfection is reflected in its continuing development of the OMS-800 range of operating microscopes, adapting them to meet the needs of modern ophthalmic procedures while maintaining the high quality and durablity that made Topcon the World Leader in Ophthalmic Equipment.

OFFISS Lenses (OFFISS: Optical Fiber Free Intravitreal Surgery System)

TOPCON has developed a state-of-art observation system for vitrectomy procedures that do not require the use of fiberoptic illumination. The TOPCON OFFISS lenses avoid complicated focusing by allowing the microscope head and indirect lens to move independently of each other, facilitating a clearly focused image at all times. The image inverter activates automatically whenever the OFFISS is in use. The indirect lens can quickly and simply be exchanged for another, saving time and increasing efficiency.



(Outer Diameter \$423) (Outer Dia











TOPCON OFFISS LENSES


Small 40D Lens

The small 40D lens can assist with membrane peeling in the macular region and is beneficial for highly myopic eyes by avoiding contact between the surgical tools and lens. It provides a crisp, wide angle view with remarkable stereopsis, giving a clear view of the posterior pole, an area that is inaccessible with contact lens observation.

surgical tools than the conventional 40D lens.


40D Lens

A bright, stereoscopic view is a particular feature of the 40D lens, making it ideal for posterior segment procedures. Combined with the microscope illumination, the characteristics of the lens make the use of additional fiber optic illumination unnecessary, enabling bimanual procedures and hence saving time.



80D Lens


The 80D lens allows observation from the posterior segment out to the intermediate peripheral zone of the retina. It can be used in combination with fiber optic illumination.



Small 120D Lens


This compact lens takes up minimal space in the operating field and does not interfere with the use of surgical instruments. The wide angle view of 100 degrees can expand up to approximately 130 degrees with the use of air substitution.





120D Lens

Useful for vitreous surgery and photocoagulation of the central and peripheral areas up to the Ora Serrata, the 120D lens provides a field of view of 130 degrees with good stereopsis. This lens can be used under air substitution in combination with a wide angle fiber optic endo illuminator.






Superb image quality for cataract and vitreous surgery

With the advancement of cataract surgery and phacoemulsification techniques, an increasing number of surgeons are performing simultaneous cataract and vitreous surgeries. By using a three mode illumination system, the OMS-800 provides an improved red reflex with better shadow and contrast, even under conditions of low illumination.









Hydrodissection

Easy switch among illumination modes


Three different illumination modes are available to meet all surgical lighting needs. Different modes are easily selected using the footswitch.



In this mode, the illumination, brightness, stereoscopic view and shadow contrast are perfectly balanced for superior observation clarity. The illumination is always optimum regardless of the position of the patient's eye.



This illumination mode generates a particularly good red-reflex and is very useful during anterior capsulotomies.



procedures to prevent

phototoxicity.

enables clear observation while preventing light damage

Low intensity illumination

Superbly designed optics provide optimum illumination, eliminating harmful wavelengths and unnecessary brightness. Low light intensity also helps to prevent light-related damage to the retinal tissues. The integral IR filter further reduces the risk of phototoxicity.

Coarse focusing*

The Coarse focusing mechanism allows the optical head to be quickly elevated during surgery and then brought back to the desired working position. This feature is particularly useful during IOL insertion and other procedures that momentarily require more space between the patient and the microscope.

 * Refer to the component list for further detail.

Apochromatic optics

The optics of the system are designed to greatly limit the effect of chromatic aberration.

Anti stain coating

The OMS-800 employs an anti-stain coating - the optical components remain clear and maintain their quality for a longer period.

Multifunction footswitch enhanced operating efficency

The multi-function footswitch permits surgeons to control virtually all of the OMS-800 functions without removing their hands from the operative field. Without any hand movement, the surgeon can adjust the illumination, zoom magnification, focus, illumination angle and X-Y positioning.

The control layout on the footswitch is conveniently arranged in the most accepted configuration.

Comfortable operating posture

The ergonomically designed optical head with a built-in beam splitter and adjustable eye pieces allows the surgeon to maintain a comfortable posture throughout the surgery. A key component to this comfort is the variable angle binocular tubes that allow for the setting of a personal viewing position from 45 to 90 degrees. This flexibility ensures a comfortable operating stance even when using OFFISS.

Increased working distance

The OFFISS system provides an extremely comfortable working distance between the OFFISS lenses and the patient's eye.


Easy bulb exchange

The illumination bulb can be simply replaced, by accessing the lamp housing using a rotating lever.

A warning lamp indicates when the spare lamp is burned out to ensure there is always an operational bulb available.

Electromagnetic locking system


The optical head can be quickly and accurately positioned for surgery and held in place by the fast acting electromagnetic locking system. (OFFISS/Pro)



Footswitch layout with well accepted control configuration.

OFFISS lens set

Standard components include; front lens holder, anterior segment observation lenses, 40D, small 40D, 80D, 120D, and small 120D. The boxes and lenses are easily maintained using an autoclave.



Assistant microscopes

The assistant microscope provides an additional viewer with bright, crisp images on the same visual axis as those seen by the main surgeon.

Coaxial binocular tube

It allows observation with the same field of view and magnification as the main surgeon. The angle of the binocular eyepieces is adjustable from 30 to 110 degrees, offering the assisting surgeon a comfortable viewing angle.



The angle of the binocular eyepieces is adjustable from 45 to 90 degrees, offering the assisting surgeon a comfortable viewing angle. In addition, a separate focus adjustment is available for the assistant surgeon.



Coaxial binocular tube



O degree assistant microscope

TV relay lens

The compact TV relay lens permits the attachment of a CCD camera useful for documentation and teaching. The relay lens accepts the most popular 1/2" and 1/3" CCD cameras with C mount or bayonet mount and is easily connected to the OMS-800.



OMS-800 OFFISS

OFFISS offers a new scope of possibilities for vitreoretinal surgery. Equipped with the OFFISS lenses mechanism, electromagnetic brakes and sophisticated electronics, this model is the highest specification for intravitreal surgery, as well as other ophthalmic procedures.



Electromagnetic brakes and sophisticated electronics confer the OMS-800 Pro the flexibility to facilitate virtually any type of ophthalmic surgical procedure.



Equipped with most of the state-of-the-art features of the OMS-800 range, the OMS-800 Standard answers the need for a simpler, easy to use operation microscope. Manual brakes and ease of mobility make the OMS-800 an affordable yet advanced unit for all ophthalmic procedures.





Component

	OFFISS	Pro	Standard
OFFISS	√	-	-
Electromagnetic locking	√	√	-
Coarse focusing	√	√	=
Inverter	√	-	=
Apochromatic optics	√	√	V
Beam spliter	V	√	√

Specifications

Microscope type	Galileo type	
Magnification change type	Electric zoom continous change	
Eyepiece(Eyepiece magnification)	12.5X	
Objective Lens	f=200mm	
Display magnification(X)	4.2/5/6/7/8/9/10/11/13/15/17/19/21	
Total magnification	4.2X - 21x	
1st arm length(Distance between shafts)	375mm	
1st arm rotation ragne	300°	
2nd arm length(Distance between shafts)	OFFISS, Pro : 990mm Standard : 875mm	
2nd arm rotation ragne	300°	
2nd arm vertical movement range	600mm	
2nd arm mounting weight	OFFISS, Pro : 6kg - 18kg Standard : 9kg - 21kg	
Power supply	AC 100-240V, 50-60Hz 280VA	
Dimensions		
Base (Base unit)	720mm(W) x 720mm(D)	
Base (Base total height)	1,865mm	
Weight	OFFISS : 250kg Pro : 247kg Standard : 244kg	
Permitted weight for accessories	OFFISS : 4.8kg Pro : 6.8kg Standard : 7.3kg	

Photos Courtesy of: Professor Masayuki Horiguchi, MD Ophthalmology Department Fujita Health University Associated Professor Kiyoshi Suzuma, MD Department of Ophthalmology and Visual Science Graduate School Biomedical Science, Nagasaki University







■ TOPCON CORPORATION

75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, JAPAN. Phone: +81-(0)3-3558-2522/2502 Fax: +81-(0)3-3965-6898 www.topconhealthcare.jp

TOPCON MEDICAL SYSTEMS, INC.
111 Bauer Drive, Oakland, NJ 07436,
U.S.A.

TOPCON CANADA INC. J7G 1N1 CANADA Phone: +1-450-430-7771 Fax: +1-450-430-6457

www.topcon.ca
TOPCON HEALTHCARE SOLUTIONS, INC.
III Bauer Drive, Oakland, NJ 07436,
U.S.A.
Phone: 1-201-599-5100
Fax: 1-201-599-5250 www.topconhealthcare.com

TOPCON HEALTHCARE SOLUTIONS

ASIA PACIFIC PTE. LTD.

1 Jalan Kilang Timor, #09-01
Pacific Tech Centre, SINGAPORE 159303
Phone: +65-68720606
E-mail: medical_sales@topcon.com.sg
www.topconhealthcare.sg

TOPCON HEALTHCARE SOLUTIONS

HQ & Product Development

TOPCON HEALTHCARE SOLUTIONS

AUSTRALIA PTY LTD 14 Park Way, Mawson Lakes, South Australia, 5095, Australia Phone: +61-8-8203-33306 Email: au.info@topcon.com www.topconhealth.com.au

EC REP TOPCON EUROPE MEDICAL B.V.

TOPCON EUROPE MEDICAL B.V. Essebaan II, 2908 LU Capelle a/d IJssel, P.O. Box 145, 2900 AC Capelle a/d IJssel, THE NETHERLANDS
Phone: +31-(0)10-4585077
Fax: +31-(0)10-4585045
E-mall: medical@topcon.com
www.topconhealthcare.eu

TOPCON ITALY

OPCON ITALY
Viale dell' Industria 60, 20037 Paderno
Dugnano, (Milano), ITALY
Phone: +39-02-9186671
Fax: +39-02-91081091
E-mail: info@topcon.it
www.topcon-medical.it

TOPCON DANMARK

Praestemarksvej 25, 400 DANMARK Phone: +45-46-327500 Fax: +45-46-327555 E-mail: info@topcon.dk www.topcon-medical.dk arksvei 25. 4000 Roskilde.

TOPCON IRELAND MEDICAL

OPCON IRELAND MEDICAL
Unit 292, Block G, Blanchardstown,
Corporate Park 2 Ballycoolin
Dublin 15, D15 DX58, IRELAND
Phone: +353-12233280
E-mail: medical.ie@topcon.com
www.topcon-medical.ie

TOPCON DEUTSCHLAND MEDICAL G.M.B.H.

Willich, GERMANY
Phone: +49-(0)2154-8850
Fax: +49-(0)2154-885177
E-mail: info@topcon-medical.de
www.topcon-medical.de

TOPCON SCANDINAVIA A.B.

UPCON SCANDINAVIA A.B.
Neongatan 2, P.O.Box 25; 43151 Mölndal,
SWEDEN
Phone: +46-(0)31-7109200
Fax: +46-(0)31-7109249
E-mail: medical@topcon.se
www.topcon-medical.se

TOPCON ESPAÑA S.A.
Frederic Mompou, 4, 08960 Sant Just
Desvern Barcelona, SPAIN
Phone: 434-93-4734057
Fax: 434-93-4733932
Espain en de la Politica de la Control de la Con -mail: medica@topcon.es vww.topcon-medical.es

TOPCON (GREAT BRITAIN) MEDICAL LTD.

OPCON (GREAT BRITAIN) MEDICAL Topcon House, Kennet Side, Bone L Newbury, Berkshire, RG14 5PX, UK Phone: +44-1635-551120 Fax: +44-1635-551170 E-mail: medical@topcon.co.uk www.topcon-medical.co.uk

TOPCON FRANCE MEDICAL S.A.S.

OPCON FRANCE MEDICAL S.A.S.
1 rue des Vergers, Parc Swen,
Bâtiment 2, 69760 Limonest, FRANCE
Phone: +33-4-37581940
Fax: +33-4-72238660
Email: topconfrance@topcon.com
www.topcon-medical.fr

TOPCON POLSKA SP. Z. O. O.

ul. Warszawska 28, 2. 0. 0. ul. Warszawska 23, 42-470 Siewierz, POLAND Phone: +48-(0)32-6705045 Fax: +48-(0)32-6713405 Email: info@topcon-polska.pl www.topcon-medical.pl

TOPCON SINGAPORE MEDICAL PTE. LTD.

OPCON SINGAPORE MEDICAL PTE. LT 100G Pasir Panjang Road, #05-05, Interlocal Centre, SINGAPORE 118523 Phone: #65-68720606 Fax: #65-67736150 E-mail: med.sales.sg@topcon.com www.topconhealthcare.sg

TOPCON INSTRUMENTS (MALAYSIA) SDN.

BHD.

No.6, Jalan Pensyarah UI/28, Hicom
Glenmarie Industrial Park, 40150 Shah Alam,
Selangor, MALAYSIA
Phone: +603 5022 3688
Fax: +603 5031 3968
Email: mys_medical_sales@topcon.com

TOPCON INSTRUMENTS (THAILAND) CO., LTD. 77/162 Sinsathorn Tower, 37th Floor, Krungthonburi Rd., Klongtonsai, Klongsarn, Bangkok 10600, THAILAND Phone: 662-4401158 Email: tha_medical@topcon.com

MEHRA EYETECH PRIVATE LIMITED

801 B Wing, Lotus Corporate Park, Grah Firth Steel Compound Goregaon (East) Mumbai 400063 Maharashtra, INDIA Phone: +91-22-61285455 www.topconhealthcare.in

TOPCON (BEIJING) MEDICAL TECHNOLOGY

TOPCON (BEJJINO), FILENCIA, CO., LTD.
Room 2808, Tower C., JinChangAn Building, No. 82, Middle Section of East 4th Ring Road, Chaoyang District, Beijing 100124, P.R. CHINA Phone: +86-10-8794-5176

IMPORTANT In order to obtain the best results with this instrument, please be sure to review all user instructions prior to operation. Not available for sale in all countries. Please check with your local distributor for availability in your country.

