

Minutes Class for Wits School of Electrical and Information Engineering

Alan Robert Clark/ Initial versions: Dean Redelinghuys

January 28, 2002

Abstract

This class allows users to prepare minutes using L^AT_EX 2_ε. Standard commands are used to define actions or notes, as well as header information.

1 Quick Start - Using ArcMinutes.cls

To use, make ArcMinutes your class (`\documentclass{ArcMinutes}`)

2 Example

This example is minutes from a Network committee.

```
\documentclass[widetext]{ArcMinutes}
\usepackage{graphicx}
\meeting{School Network Committee}
\date{31 October 1996}
\time{10h30}
\place{Conference Room}
\minuteref{NC96/10}
\begin{document}
\begin{present}
\item[BD]{Barry Dwolatzky}
\item[DR]{Dean Redelinghuys (in the chair)}
\end{present}

\section*{Welcome and Leave of Absence}
The chairman welcomed everyone.

\section*{New Network Rules}
\action[BD]{Schedule upgrade}
\action{After some discussion of the new network rules,
the committee was asked to propose new rules for use of the
network} % lack of [name] => [All]
\note{there is a need to upgrade} % 'that' is auto-inserted.
\end{document}
```

3 The Documentation Driver

The following code will generate the documentation for this file. Since it is the first piece of code, and it is separated by a special option, this file can be used to produce the documen-

tation but this code will *not* appear in the class.

```

\driver
\documentclass[a4paper]{article}
\usepackage{A4ee}
\usepackage{doc}
\begin{document} \DocInput{ArcMinutes.dtx} \end{document}
\driver

```

4 The Code

For starters, declare the package and version:

```
\ProvidesClass{ArcMinutes}[2002/01/22 Wits Elec\&Info Eng Minutes Class]
```

There are no options for this class, so pass anything onto the article class for handling there (forcing it into a4paper mode):

```

\DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
\ProcessOptions
\LoadClass{article}
\RequirePackage{xspace,A4ee}

```

4.1 Minute Defining Commands

Define `\meeting` similar to `\title`, in fact exactly like `\title`!

```
\newcommand{\meeting}[1]{\title{#1}}
```

Also define `\place` for those who like this, but make it graceful.

```

\newcommand{\EEplace}{.}
\newcommand{\place}[1]{\renewcommand{\EEplace}{\xspace in the #1.}}

```

We make `\time` set the time of the meeting, but use some smart defaults so that our construction makes sense without this definition:

```

\newcommand{\EEtime}{}
\newcommand{\EEdate}{\@date}
\renewcommand{\time}[1]{\renewcommand{\EEtime}{\xspace at #1}%
\renewcommand{\EEdate}{\@date\EEtime}}

```

We make `\minuteref` set the reference for the meeting. This is not currently used, but will eventually define the action number.

```

\newcommand{\EEminref}{}
\newcommand{\minuteref}[1]{\renewcommand{\EEminref}{#1}}

```

4.2 Header on first page

Define the header for the first page. This means people don't need to type `\maketitle` in every minute document.

```

\AtBeginDocument{%
  {\Large
    \begin{tabular}{p{7mm}l}
      \setlength{\unitlength}{1mm}
      \begin{picture}(0,0)(15,20)
        \includegraphics[width=25mm]{schllogo.eps}%

```

```

\end{picture}%
&\textsf{UNIVERSITY OF THE WITWATERSRAND, JOHANNESBURG}\\
&\textsl{School of Electrical and Information Engineering}\\
&\{\large\bfseries Minutes of the \@title{} meeting held on}\\
&\{\large\bfseries \EEdate \EEplace}\\ccline{2-2}
\end{tabular}
}
}

```

4.3 Commands for use in the body

The `\action[person]{action to be done}` command is used to typeset an action, and place the action person in special formatting in the right margin. The default for **person** is ALL. The `note` environment does something similar for notes, but leaves out the person.

```

\newcounter{EEaction}\setcounter{EEaction}{0}
\newcommand{\action}[2][ALL]{\stepcounter{EEaction}\par%
{\slshape\bfseries Action \arabic{EEaction}}: %
\marginpar{\textbf{#1}}#2\par}}
\newcommand{\note}[1]{\textbf{NOTED:} that #1}%

```

The `present` list environment allows us to define people present at the meeting. It works like this:

```

\begin{present}
\item[DR] - Dean Redelinghuys (in the chair)
\item[BD] - Barry Dwolatzky
\item[AL] - Ariel Levien
\end{present}

```

This works simply by starting a `\section*` with the heading `Present`, and using the `description` environment.

```

\newenvironment{present}{\section*{Present}}%
{\begin{description}\setlength{\itemsep}{-\parsep}}
{\end{description}}

```