

OBJECT:

- Simple data types, variables and constants,
- Arithmetic operators, arithmetic assignment operators, increment and decrement operators
- Escape sequences.

RULES FOR NAMING VARIABLES:

- Variable names must begin with a letter or names can also begin with \$ and _
- Variable names can contain letters, numbers, the underscore (_) and the dollar (\$) sign.
- Variable names cannot contain spaces.
- Variable name cannot be a keyword or a reserved word.
- Variable names cannot contain special characters such as all operators, #, <, +, etc.
- C++ is a case-sensitive language. Variable names written in capital letters differ from variable names with the same name but written in small letters. For example, the variable name EXFORSYS differs from the variable name exforsys.

DATA TYPES

You may like to store information of various data types like character, wide character, integer, floating point, double floating point, boolean etc. Based on the data type of a variable, the operating system allocates memory and decides what can be stored in the reserved memory.

Data Type	Range	No. of Bits in Memory
Integers: Used to store whole numbers. C++ supports several integer types, having different sizes for storing signed (both negative and positive) and unsigned numbers		
short	-32768 → 32767	16 bit
unsigned short	0 → 65535	16 bit
Int	-32768 → 32767 -2147483648 → 2147483647	16 bit or 32 bit
unsigned int	0 → 65535 0 → 4294967295	16 bit or 32 bit
Long	-2147483648 → 2147483647	32 bit
unsigned long	0 → 4294967295	32 bit
long long	-9223372036854775808 → 9223372036854775807	64 bit
unsigned long long	0 → 18446744073709551615	64 bit
Floating point: Floating point types are used to store numbers that contain decimal point (real numbers). C++ supports several floating point types, having different sizes.		
float	$10^{-38} \rightarrow 10^{38}$	32 bit
double	$10^{-308} \rightarrow 10^{308}$	64 bit
long double	$10^{-308} \rightarrow 10^{308}$	64 bit
Character: Used to hold single character can also store number (ASCII Code of a character)		
Char	Can also store integers (-128 → 127)	8 bit
unsigned char	Can also store integers (0 → 255)	8 bit
Boolean: Used to store only two types of values TRUE or FALSE. Can be used in decision making statements.		
bool	True / False	8 bit

DECLARING VARIABLES

Declaring means giving a name and a data type to a variable before it can be used. Syntax:

```
datatype variable_name;  
datatype variable_name1, variable_name2, ...;
```

THE ASSIGNMENT OPERATOR AND INITIAL VALUES

When you declare a variable, you can also assign first value to the variable using the assignment operator (=)

```
datatype variableName = initialValue;  
datatype var1=initialValue1, var2=initialValue2 ;
```

Notice that assignment is right to left. The initial value is assigned to the variable.

INTEGER VALUES

Can be expressed in decimal(base 10)

Hexadecimal(base 16) : Prefix 0x is used to indicate octal

Octal(base 8) : prefix 0o indicates hexadecimal

Examples:

```
short decimal = 100;    OR    int decimal = -230;  
int octal = 0144;       OR    long octal = -0234;  
int hexa = 0x4F;        OR    int hexa = -0x2A;
```

```
unsigned short decimal = 100;  
unsigned int octal = 0144;  
unsigned long hexa = 0x4F;
```

FLOATING-POINT VALUES

The floating point types (float and double) can also be expressed using E or e (for scientific notation),

Examples:

```
double d1 = 123.4;  
same value as d1, but in scientific notation  
double d2 = 1.234e2;          ←    1.234x102  
float f1 = -123.4;  
float f1 = 1.7E-3;           ←    1.7x10-3
```

CHAR VALUES

Character values can be given by using single quote :

```
char ch = 'N';
```

Character can also have integral values: Unicode value in Decimal, Octal and Hexadecimal.

Examples:

```
char ch = 78;                //range is 0 to 255  
char ch = 0116;              //range 000 to 377  
char ch = '\u4E';            // range \u00 to \uFF
```

Character values can also be escape sequence be given by using single quote :

```
char ch = '\n';
```

PROGRAM 1:

```
#include <iostream>
using namespace std;

int main()  {

    short s = 1234;           //Short Integer type variable
    unsigned short us = 41234; //unsigned Short

    int i = 3212;             //Integer type variable
    unsigned int ui = 54321;   //unsigned int

    long l = 123345435;       //Long Integer type variable
    unsigned long ul = 4111117295; //unsigned Long

    long long ll = -7612334543534454; //Long Long
    unsigned long long ull = 9451111172955545; //Unsigned Long Long

    float f = 123.432;        //Floating point type variable
    double d = 4.12e223;      //Double precision float type

    char ch1 = 'N';           //Character type variable
    unsigned char ch2 = 203;   //unsigned character

    bool q = true;            //Boolean Type Variable

    //Printing all variable values on screen

    cout << "short variable= " << s << endl;
    cout << "unsigned short variable= " << us << endl;
    cout << "int variable= " << i << endl;
    cout << "unsigned int variable= " << ui << endl;
    cout << "long variable= " << l << endl;
    cout << "unsigned long variable= " << ul << endl;
    cout << "long long variable= " << ll << endl;
    cout << "unsigned long long variable= " << ull << endl;
    cout << "float variable= " << f << endl;
    cout << "double variable= " << d << endl;
    cout << "char variable= " << ch1 << endl;
    cout << "unsigned char variable= " << ch2 << endl;
    cout << "bool variable= " << q << endl;

    return 0;
}
```

ESCAPE SEQUENCES SUMMARY:

Escape Sequence	Description
\'	Single quote
\"	Double quote
\\	Backslash
\nnn	Octal number (nnn)
\0	Null character (really just the octal number zero)
\a	Audible bell
\b	Backspace
\f	Formfeed
\n	Newline
\r	Carriage return
\t	Horizontal tab
\xnnn	Hexadecimal number (nnn)

PROGRAM 2:

```
#include <iostream>
using namespace std;
int main() {

    char ch1 = 'A';    //define char variable as character
    char ch2 = '\t';    //define char variable as tab

    cout << ch1 << ch2;    //display characters

    ch1 = 'B';    //set char variable to char constant

    cout << ch1;    //display character
    cout << '\n';    //display newline character

    return 0;
}
```

CONSTANTS:

Constants, like variables, contain data type but constants have fixed value and that value cannot be changed in the program. There are 2 ways to declare a constant

- `const data_type const_name = value;` (Example: `const int PI = 3.14;)`
- `#define const_name value` (Example: `#define PI 3.14)`

PROGRAM 3:

```
#include <iostream>
using namespace std;
int main(){
    float rad;                                //variable of type float
    const float PI = 3.14159;                //type const float
    cout << "Enter radius of circle: ";      //prompt
    cin >> rad;                               //get radius
    float area = PI * rad * rad;             //find area
    cout << "Area is " << area << endl;      //display answer
    return 0;
}
```

REMAINDER (MODULUS) OPERATOR

Take a simple arithmetic problem: what's left over when you divide 11 by 3? The answer is easy to compute: divide 11 by 3 and take the remainder: 2. The modulus operator ('%'), that computes the remainder that results from performing **integer** division.

PROGRAM 4:

```
#include <iostream>
using namespace std;
int main() {
    cout << 6 % 8 << endl    // 6
         << 8 % 8 << endl    // 0
         << 9 % 8 << endl    // 1
         << 10 % 8 << endl;   // 2
    return 0;
}
```

INCREMENT AND DECREMENT OPERATORS

The increment operator ++ adds 1 to its operand, and the decrement operator -- subtracts 1 from its operand.

x = x+1; is the same as **x++;**

And

x = x-1; is the same as **x--;**

Both the increment and decrement operators can either precede (prefix) or follow (postfix) the operand.

For example:

x = x+1; can be written as

++x; // prefix form

or as

x++; // postfix form

When an increment or decrement is used as part of an expression, there is an important difference in prefix and postfix forms. If you are using prefix form then increment or decrement will be done before rest of the expression, and if you are using postfix form, then increment or decrement will be done after the complete expression is evaluated.

PROGRAM 5:

```
#include <iostream>
using namespace std;
int main() {
    int c = 10;
    cout << "c =" << c << endl;    //displays 10
    cout << "++c =" << ++c << endl;  //displays 11 (prefix)
    cout << "c =" << c << endl;    //displays 11
    cout << "c++ =" << c++ << endl;  //displays 11 (postfix)
    cout << "c =" << c << endl;    //displays 12
    cout << "--c =" << --c << endl;  //displays 11 (prefix)
    cout << "c =" << c << endl;    //displays 11
    cout << "c-- =" << c-- << endl;  //displays 11 (postfix)
    cout << "c =" << c << endl;    //displays 10
    return 0;
}
```

ARITHMETIC ASSIGNMENT OPERATORS:

+=	Add AND assignment operator, It adds right operand to the left operand and assign the result to left operand.	C += A is equivalent to C = C + A
-=	Subtract AND assignment operator, It subtracts right operand from the left operand and assign the result to left operand.	C -= A is equivalent to C = C - A
*=	Multiply AND assignment operator, It multiplies right operand with the left operand and assign the result to left operand.	C *= A is equivalent to C = C * A
/=	Divide AND assignment operator, It divides left operand with the right operand and assign the result to left operand.	C /= A is equivalent to C = C / A
%=	Modulus AND assignment operator, It takes modulus using two operands and assign the result to left operand.	C %= A is equivalent to C = C % A

PROGRAM 6:

```
#include <iostream>
using namespace std;
int main() {
    int ans = 27;
    ans += 10;           //same as: ans = ans + 10;
    cout << ans << ", ";
    ans -= 7;            //same as: ans = ans - 7;
    cout << ans << ", ";
    ans *= 2;            //same as: ans = ans * 2;
    cout << ans << ", ";
    ans /= 3;            //same as: ans = ans / 3;
    cout << ans << ", ";
    ans %= 3;            //same as: ans = ans % 3;
    cout << ans;
    return 0;
}
```

EXERCISE 1:

Write a program which generate the following output on the screen you have to use scape sequences and you cannot use endl. Use one or more than one cout statements to generate output.

```
"Welcome All" is a string constant
'A' is a character constant
\t is for tab
\n for new line
```

EXERCISE 2:

Write a program which takes 2 **int** values from user and then perform all five arithmetic operations on them. The output should be like:

```
Enter First Number: 12
Enter Second Number: 32
12 + 32 = 44
12 - 32 = -20
12 x 32 = 384
12 / 32 = 0.375
12 % 32 = 11
```

User can give different values and output will be different every time. You will observe that the division operator is not giving the correct answer with 'int' data type.

Change the variable data type from **int** to **float** then observe if there is any other problem or error.

We will correct it in week 4. Also, you will notice if you take float variable than remainder operator will not work.

EXERCISE 1:

Write a program in C++ to calculate the volume of a sphere. Use the formula:

$$V = \frac{4}{3} \pi r^3$$

The Volume and Radius variables should be of **float** datatypes.

Create a constant **PI** for the value of PI and use it.

Your output should be:

```
Input the radius of a sphere : 6
The volume of a sphere is : 904.32
```

Observe the output is correct or not than to correct it use 4.0/3 instead of 4/3. The reason will be discussed in next week.

Course Instructor: **Nazish Basir** Page: **8**
Faculty of Engineering and Technology, University of Sindh.