

On Commonsense Domains within the Winograd Schema Challenge

Aneta Koleva

Supervisor: Emmanuelle-Anna Dietz

Commonsense Reasoning in Computers


Levesque (2011) proposes a new test for assessing computer intelligence that requires the use of commonsense reasoning.

S: The trophy does not fit into the brown suitcase because it is too [small/large].

Q: What is too [small/large]?

A: The suitcase/the trophy.

Add (least necessary) background knowledge and apply to reasoning algorithm.



Winograd Schema Challenge (WSC)

- Structure of a Winograd Schema:

Sentence containing two nouns	trophy, suitcase
One ambiguous pronoun	it
A special word	small/large
Question about the referent of the pronoun	What is too [small/large]
Two possible answers	The suitcase/the trophy
- Characteristics:
 - Easy to answer for an adult English speaker.
 - Always contains **special word**.
 - Google-proof* - statistical methods over large text corpora should not be able to resolve a WS.

Machine-Learning vs Knowledge-Based Approaches

Technique	PDPs Size Correct	WSC Size Correct	WSC* Size Correct	Remarks
Supervised ranking SVM model [6]	NA	NA	282 - 30% 205 - 73%	-provided additional dataset set -no evaluation on WSC dataset
Classification task with NN [3]	NA	282 - 100% 157 - 56%	282 - 30% 177 - 63%	-first to use substitution of the pronoun with the antecedents
Knowledge Enhanced Embeddings (KEE) [4]	60-100% 40 - 66.7%	NA	NA	-best results in the 2016 WSC competition
Google's language models [10]	60-100% 42 - 70%	273 - 100% 173 - 63.7%	NA	-no reasoning involved in the discovery of the correct answer -state-of-the-art for PDPs
OpenAI language models [5]	NA	273 - 100% 193 - 70.70%	NA	-current state-of-the-art for WSC -requires a lot of data for training -results are not reproducible
Graphs with Relevance theory [8]	NA	4 - 2.6% 4 - 100%	NA	-manual construction of graphs -first representation of WS as dependency graph
2 identified categories [9]	NA	71 -25% 49 - 69%	NA	-first attempt of identifying commonsense knowledge types -developed the KParser
Semantic relations categories [1]	NA	100 - 34% 100 - 100%	138 - 14% 111 - 80%	-provided Reasoning Algorithm -identified 12 commonsense types which capture the entire WSC
Knowledge hunting framework [2]	NA	273 - 100% 119 - 43.5%	NA	-refined query generation -developed an algorithm for scoring the retrieved sentences

*Additional dataset with 943 WS provided in [7] .

References

[1] C. Baral A. Sharma. Commonsense knowledge types identification and reasoning for the winograd schema challenge, 2018.

[2] A. Emami, N. De La Cruz, A. Trischler, K. Suleman, and J. Chi Kit Cheung. A knowledge hunting framework for common sense reasoning. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018*, pages 1949–1958, 2018.

[3] Opitz J. and Frank A. Addressing the winograd schema challenge as a sequence ranking task. In *Proceedings of the First International Workshop on Language Cognition and Computational Models*, pages 41–52. Association for Computational Linguistics, 2018.

[4] Q. Liu, H. Jiang, Z. Ling, X. Zhu, S. Wei, and Y. Hu. Combing context and commonsense knowledge through neural networks for solving winograd schema problems. 2016.

[5] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, and I. Sutskever. Language models are unsupervised multitask learners, 2019.

[6] A. Rahman and V. Ng. Resolving complex cases of definite pronouns: The winograd schema challenge. In *Proceedings of the 2012 Joint Conference on Empirical Methods in Natural Language Processing and Computational Natural Language Learning, EMNLP-CoNLL 2012, July 12-14, 2012, Jeju Island, Korea*, pages 777–789, 2012.

[7] A. Rahman and V. Ng. Resolving complex cases of definite pronouns: The winograd schema challenge. In *Proceedings of the 2012 Joint Conference on Empirical Methods in Natural Language Processing and Computational Natural Language Learning, EMNLP-CoNLL 2012, July 12-14, 2012, Jeju Island, Korea*, pages 777–789, 2012.

[8] P. Schüller. Tackling winograd schemas by formalizing relevance theory in knowledge graphs. In *Principles of Knowledge Representation and Reasoning: Proceedings of the Fourteenth International Conference, KR 2014, Vienna, Austria, July 20-24, 2014*, 2014.

[9] A. Sharma, Nguyen Ha Vo, Somak Aditya, and Chitta Baral. Towards addressing the winograd schema challenge - building and using a semantic parser and a knowledge hunting module. In *Proceedings of the Twenty-Fourth International Joint Conference on Artificial Intelligence, IJCAI 2015, Buenos Aires, Argentina, July 25-31, 2015*, pages 1319–1325, 2015.


[10] Q. V. Le T. H. Trinh. A simple method for commonsense reasoning. 2018.

Knowledge Types Identification and Reasoning (Sharma and Baral, 2018)

- Identified 12 **knowledge types** which cover entire WSC dataset.
 - Categorization based on the structure of the Winograd sentence.
 - 10 knowledge types based on interaction between entities and actions.
 - Provided a **logical reasoning algorithm** in ASP.
 - Evaluated on 100 problems from WSC and achieved **100%** accuracy.
- Extracted knowledge: “small y prevents y fits”.
- Knowledge type “Property prevents Action”.
- ```
%entity y has a trait small 1
has_k(small,is_trait_of,y). 2
%having trait small prevents the entity to fit another entity 3
has_k(small,prevents,fits). 4
%entity y is the recipient of the action fit 5
has_k(fits,recipient,y). 6
```

- Rule 4 **has no effect** in the reasoning procedure!

## The trophy doesn't fit into the brown suitcase because it's too small.



## Reasoning algorithm

Change of the formalization of the background knowledge such that it has effect in the reasoning procedure.

```
%entity y is small if we know it could not fit another entity 1
has_k(small,is_trait_of,y) :- has_k(fit,recipient,y), 2
not has_k(fit,modifier,could). 3
%entity y should fit another entity 4
has_k(fit,recipient,y). 5
```

- Rule 1 **has effect** in the reasoning procedure!
- In rule 5, switching **recipient** with **agent** leads to no answer!

## Categorization of Winograd Schemas

- Inductively analyzed the WSC dataset and identified **6 categories**.
- Categorization based on the **content** of the Winograd sentence.
- Two annotators annotated the entire WSC corpus with these categories.
- Calculated Cohen's kappa - measure for inter-rater agreement  $\kappa = 0.66$

| Category              | Example                                                                                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Physical           | <b>S:</b> John couldn't see the stage with Billy in front of him because he is so [short/tall].<br><b>Q:</b> Who is so [short/tall]?                                           |
| 2. Emotional          | <b>S:</b> Frank felt [vindicated/crushed] when his longtime rival Bill revealed that he was the winner of the competition.<br><b>Q:</b> Who was the winner of the competition? |
| 3. Interactions       | <b>S:</b> Joan made sure to thank Susan for all the help she had [given/received].<br><b>Q:</b> Who had [given/received] help?                                                 |
| 4. Comparison         | <b>S:</b> Joe's uncle can still beat him at tennis, even though he is 30 years [older/younger].<br><b>Q:</b> Who is [older/younger]?                                           |
| 5. Causal             | <b>S:</b> Pete envies Martin [because/although] he is very successful.<br><b>Q:</b> Who is very successful?                                                                    |
| 6. Multiple knowledge | <b>S:</b> Sam and Amy are passionately in love, but Amy's parents are unhappy about it, because they are [snobs/fifteen].<br><b>Q:</b> Who are [snobs/fifteen]?                |

## Conclusions and Outlook

- Most knowledge-based approaches, so far, have concentrated on the semantic structure of the WS sentence.
- None have specified domain specific categories, i.e., the information about the relation between entities and their properties within a certain domain.
- How to identify the most necessary and the least possible knowledge for solving a WS?
- An approach, where knowledge is provided only 'by demand' might be more efficient and adequate.

