

Object Oriented Programming and C++ (1)

Song Liu (song.liu@bristol.ac.uk)

GA 18, Fry Building,

Microsoft Teams (search "song liu").

Structure in C

Define a structure "student"

```
struct student{  
    int ID;  
    char *name;  
    int overall_grade;  
};
```

Declare a structure variable and initialize it:

```
struct student song;  
song.ID = 1024;  
song.name = "song liu";  
song.overall_grade = 70;
```

Two New Structures

Say, I would like to define a struct called `CS_student` .

```
struct CSstudent{  
    int ID;  
    char *name;  
    int overall_grade;  
    int programming_grade;  
};
```

Say, I would like to define a struct called `Mathstudent` .

```
struct Mathstudent{  
    int ID;  
    char *name;  
    int overall_grade;  
    int calculus_grade;  
};
```

Redundancy

- There are a lot of redundancies in these two definitions!
- Redundancy \Leftrightarrow Code is poorly reused!
- Redundancy \Leftrightarrow Confusion

```
struct Lawstudent{  
    int ID;  
    char *name;  
    int final_grade;  
    int law_grade;  
};
```

- Wait, is `final_grade` the same thing as the `overall_grade` ?

Type Hierarchy

- The definition does not reflect that `CSstudent` and `Mathstudent` are sub-types of `student`.
- Imagine I have a function:

```
int print_overall_grade(student s){  
    printf("%d\n", s.overall_grade);  
}
```

- By human logic, you would think the following works:

```
struct CSstudent song = {...}; //initialize "song"  
print_overall_grade(song); //COMPILATION ERROR!
```

- `song` is a `CSstudent` structure. It does not match the input type in `print_overall_grade`.

Setting Variables in Structure

- In C, data and the operations on data are **detached**.
- Imagine I have a function `set_overallscore`.

```
/*set_overallscore, record student's score.  
Pass by reference, do not pass by value!! */  
  
void set_overallscore(student *ps, int score){  
    //Check if score is valid or not.  
    if(score <=100 && score >=0){  
        ps->overall_score = score;  
    }else{  
        printf("Invalid Score!\n");  
    }  
}
```

Structure Pointer

- Note when you have a **structure pointer**, instead of using `.` to refer to its variables, you need to use `->`.

```
student song = {...}; //initialization code
student *psong = &song;
song.ID = 1234;
psong->ID = 1234; //same as above.
```

- Just remember, pointer uses "pointer" (`->`)...

Data Corruption

- Our `set_overallscore` function works:

```
#include <stdio.h>
... //definition of student omitted
void main()
{
    struct student song = {1, "song liu", 0};
    set_overallscore(&song, -2);
    //prints out "invalid score!"
    printf("%d\n", song.overall_score);
    // prints 0
    set_overallscore(&song, 80);
    printf("%d\n", song.overall_score);
    // prints 80
}
```


Data Corruption

- However, nothing prevents a irresponsible programmer from doing this:

```
#include <stdio.h>
... //definition of student omitted
void main()
{
    struct student song = {1, "song liu", 0};
    song.overall_score = 99999;
    printf("%d\n", song.overall_score);
    // prints 99999,
    // Now, song has an invalid score !!
    // no warning message!!
}
```

- Data and operations on data should be bound together
- Data should only be accessed and modified **by using the right procedure.**

Data and Functions are naturally together

- Sometimes, it is just natural that a procedure is bound to the data it operates on.

- Say a student changes his/her name.

```
change_name(&song, "new name");
```

or

```
song.change_name("new name");
```

- The latter feels more natural and "human":
 - You can literally read your code as:
 - `song` changes his name to `"new name"`.

Problem of Structure in C

1. Does not reflect proper hierarchies of data
 - Code is poorly reused, which leads to redundancy and confusion.
2. Data and operations on data are detached.
 - Data may be corrupted by illegal access.
 - This style is arguably less natural and less "human".

Procedural Programming (PP)

- C is a procedural programming language.
 - Your code is divided into several procedures (functions) and you write code for each procedure.
- Lab 7, we wrote the following functions:
 - `read_matrix`,
 - `matrix_multiplication`
 - `write_matrix`.
- Since the task we want to perform naturally splits into these subtasks: **Read** matrices, **multiply** them and **write** to a file.
 - We defined **a function for each verb** in the above description.

Object Oriented Programming (OOP)

- In OOP, your code is divided into small parts called **objects**.
 - These parts can have hierarchies reflecting the real-world relationship between objects.
 - If an object is a `CSstudent`, then it is a `student`.
- Objects contain data **as well as procedures that operates on the data**.
 - Solves the "data-operation detachment" issue.
 - The **procedures** in an object are called "**methods**".
 - The **data** in an object are called "**fields**".

C++

- C++ is an enhancement of C, that allows OOP.
- C++ is a superset of C.
 - C++ contains all language features in C and additional features for OOP.
 - Thus, a valid C program is also a valid C++ program, but not vice versa.

```
#include <stdio.h>
void main(){
    printf("hello world!\n").
} //A valid C++ program!
```

Cautions

- C++ is **not** a language for programming novice.
- C is simple and nimble, like a **swiss army knife**.
 - Anyone can use it.
 - If you program in a principled way, C can do everything.
- C++ is powerful and complex, like a **tank**.
 - It contains powerful features, but mostly geared toward large scale software development.
 - Using it in smaller projects may unnecessarily complicate things (over engineering).
 - If you abuse/misuse language features in C++, your program may be less readable and performant than using just PP in C.

Compiler

- C++ code are contained in `cpp` files.
 - just like C code are contained in `c` files.
- C++ uses a different compiler: `g++` .
 - It has the same usage as `gcc` .
 - `g++ main.cpp -o main.out` compiles `main.cpp` to the executable `main.out` .

Class

- Class is the "structure" in C++.
- It groups related variables as well as procedures together in one entity.

```
#include <stdio.h>
class student{
    int ID;
    char* name;
    int grade;
};
// you do not need typedef to create an alias!
// you can use student as a type directly.
int main(){
    student song;
}
```

- `song` is **an object** or **instance** of class `student`.

Class

- By default, all fields (variables) in a class are private
 - You cannot access those fields.

```
student song;  
song.grade = 70; //WRONG! COMPILATION ERROR
```

- You need to manually declare fields as `public`.

```
class student{  
public:  
    int ID;  
    char* name;  
    int grade;  
};
```

- ```
student song;
song.grade = 70; //OK!
```

# Methods

- Methods are functions that are "attached" to an object.

```
class student{
public:
 int ID;
 char* name;
 int grade;
 int set_grade(int score){
 if(score <= 100 && score > 0){
 grade = score;
 }
 }
 int get_grade(){
 return grade;
 }
};
```

- `set_grade` saves the score to the `grade` field.
- `get_grade` returns the `grade` field.

# Methods

- Methods can be called using the "dot" notation:

```
student song;
song.set_grade(70);
printf("song's grade %d\n", song.get_grade());
//prints out 70
```

- Just like calling a regular function, you need to feed it with appropriate inputs.

# Encapsulation

- Exposing your fields as `public` variables is dangerous.
  - An irresponsible programmer can corrupt your data!
  - Recall the "student score" example.

```
student song;
song.grade = 999;
printf("song's grade %d\n", song.get_grade());
//prints out 999, which is invalid score
```

# Encapsulation

- To protect your data, do

```
class student{
 int ID;
 char* name;
 int grade;

public:
 int set_grade(int score){
 if(score <= 100 && score > 0){
 grade = score;
 }
 }
 int get_grade(){
 return grade;
 }
};
```

# Encapsulation

- Now, nobody can corrupt your data:

```
student song;
song.grade = 999; //WRONG! COMPILATION ERROR!
song.set_grade(999); // Invalid score,
// No change to the grade field.
```

- They can only do it in "the right way":

```
song.set_grade(80); //the field "grade" is changed.
printf("%d\n", song.get_grade());
//prints out 80
```

- Encapsulation is an important idea in OOP. It prevents irresponsible programmers from corrupting and misusing data.
  - Wikipedia page on [Data Hiding](#).

# Constructor

- In C, we can initialize a structure using `{...}` syntax.

```
student song = {1234, "song liu", 70};
```

- How to initialize fields of an object in C++?
  - There is a more principled way to initialize fields in C, called "constructor".
  - Constructor is a public method that has the same name as the class.
    - It does NOT have a return type.



# Constructor

```
class student{
 int ID;
 char* name;
 int grade;

public:
 student(int newID, char* newname, int newgrade){
 ID = newID;
 name = newname;
 grade = newgrade;
 }
 int set_grade(int score){
 if(score <= 100 && score > 0){
 grade = score;
 }
 }
 int get_grade(){
 return grade;
 }
};
```

# Constructor

Then, you can initialize an object like this

```
student song(1234, "song liu", 70);
printf("%d\n");
// prints out 70.
```

# Conclusion

- Structure in C has some issues:
  - It can not reflect the hierarchy of data types.
  - Data and operations on data are detached.
- PP: You divide your program into sub-procedures.
- OOP: You divide your program into small "objects".
  - Objects contains "fields" and "methods".
- C++
  - It is a superset of C.

# Homework 1 Problem with Structure

In lab 7, we have coded structure that contains variables `numrow`, `numcol` and `elements`.

```
struct matrix{
 int numrow;
 int numcol;
 int *elements;
};
typedef struct matrix Matrix;
```

However anyone can modify `numrow` or `numcol` after the matrix has already been initialized. Imagine:

```
Matrix A = read_matrix("A.matrix");
A.numrow = 999999; //someone is being careless...
// a disaster waiting to happen...
multiply(A, B, C)
```

# Homework 1 Problem with Structure

- It is a poor design if anyone can modify your data in a way that can cause a disaster.
- `numrow` and `numcol` should be **locked** once the matrix has been initialized.
- Today, we are going to see how this can be done using C++'s encapsulation.

# Homework 1 Matrix Class

Create a **class** called `Matrix`. This class has the following **private fields**:

1. `numrow`, `int` type, the number of rows
2. `numcol`, `int` type, the number of columns
3. `elements`, `int` type, a **pointer** points to an array, storing the flattened matrix.

# Homework 1 Indexing

## 4. Write a private helper method

```
int idx(int i, int j)
```

- It takes the 2D index `i, j` of the current matrix, and converts it to the linearized index.

- For example, if the current matrix is a 10 by 2 matrix.

Suppose a

- `idx(0, 0)` returns 0
- `idx(0, 1)` returns 1
- `idx(1, 0)` returns 2
- `idx(1, 1)` returns 3
- ...
- The function `idx` should contain only one line of code.

# Homework 1 Matrix Class (submit)

Write public methods:

1. `void zeros(int nrow, int ncol)` : allocate heap space for a `nrow` by `ncol` matrix, and fill it with zeros.
  - Hint: use `calloc`.
2. `void print()` : print all elements in the current matrix.
3. `void fill(int nrow, int ncol, int a[])` : allocate heap space, and fill the matrix with elements in an array `a`.
  - For example,

```
int a[] = {1,2,3,4};
Matrix M;
Matrix.fill(2,2,a);
//M now stores a matrix
//1 2
//3 4
```



# Homework 1 Matrix Class (submit)

4. `int get_nrow()` : returns the number row of the current matrix.
5. `int get_ncol()` : returns the number of columns of the current matrix.
6. `void free()` , releases the memory occupied by elements .
  - Do not forget to release all heap memory you have allocated!
7. `Matrix dot(Matrix B)` : computes the matrix multiplication between the current matrix ( $A$ ) and the other matrix  $B$ . Return  $AB$ .

# Homework 1 Matrix Class (submit)

- Write test code in `main`, testing your methods.
  - Create a `Matrix` object.
  - Fill it with some elements.
  - Print out the matrix.
  - Perform Matrix Multiplication.
  - Print out the outcome of multiplication.
- In this matrix example, we have restricted the access of `numrow` and `numcol`: Once our matrix is initialized by `fill` method, `numrow` and `numcol` are read-only, hence they are "encapsulated" by our design.