Machine-Level Programming IV: Data

15-213/18-213/15-513: Introduction to Computer Systems 8th Lecture, September 21, 2017

Today's Instructor:

Phil Gibbons

Today

Arrays

- One-dimensional
- Multi-dimensional (nested)
- Multi-level

Structures

- Allocation
- Access
- Alignment


Unions

Array Allocation

Basic Principle

```
T \mathbf{A}[L];
```

- Array of data type T and length L
- Contiguously allocated region of L * sizeof (T) bytes in memory




Array Access

■ Basic Principle

```
T A[L];
```

- Array of data type T and length L
- Identifier A can be used as a pointer to array element 0: Type T*




Reference	Type	Value			
val[4]	int	3			
val	int *				
val+1	int *				
&val[2]	int *				
val [5]	int				
* (val+1)	int				
val + i	int *				

Array Access

■ Basic Principle

```
T A[L];
```

- Array of data type T and length L
- Identifier A can be used as a pointer to array element 0: Type T*




Reference	Type	Value
val[4]	int	3
val	int *	x
val+1	int *	x + 4
&val[2]	int *	x + 8
val [5]	int	??
*(val+1)	int	5 //wal[1]
val + <i>i</i>	int *	x + 4 * i //&val[i]

Array Example


```
#define ZLEN 5
typedef int zip_dig[ZLEN];

zip_dig cmu = { 1, 5, 2, 1, 3 };
zip_dig mit = { 0, 2, 1, 3, 9 };
zip_dig ucb = { 9, 4, 7, 2, 0 };
```



- Declaration "zip_dig cmu" equivalent to "int cmu[5]"
- Example arrays were allocated in successive 20 byte blocks
 - Not guaranteed to happen in general

Array Accessing Example



```
int get_digit
  (zip_dig z, int digit)
{
  return z[digit];
}
```

x86-64

```
# %rdi = z
# %rsi = digit
movl (%rdi,%rsi,4), %eax # z[digit]
```

- Register %rdi contains starting address of array
- Register %rsi contains array index
- Desired digit at %rdi + 4*%rsi
- Use memory reference (%rdi,%rsi,4)

Array Loop Example

Array Loop Example

```
void zincr(zip_dig z) {
   size_t i;
   for (i = 0; i < ZLEN; i++)
      z[i]++;
}</pre>
```


Decl	A	1 , A	2	*A1 , *A2			
	Comp	Bad	Size	Comp	Bad	Size	
int A1[3]							
int *A2							


Comp: Compiles (Y/N)

Bad: Possible bad pointer reference (Y/N)

Size: Value returned by sizeof

Decl	A	1 , A	2	*A1 , *A2			
	Comp Bad		Size	Comp	Bad	Size	
int A1[3]	Y	N	12	Y	N	4	
int *A2	Y	N	8	Y	Y	4	






- Comp: Compiles (Y/N)
- Bad: Possible bad pointer reference (Y/N)
- Size: Value returned by sizeof


Decl	A <i>n</i>			*An			**An		
	Cmp	Bad	Size	Cmp	Bad	Size	Cmp	Bad	Size
int A1[3]									
int *A2[3]									
int (*A3)[3]									

Allocated pointer	
Unallocated pointer	
Allocated int	
Unallocated int	

Decl	A <i>n</i>			*A <i>n</i>			**An		
	Cmp	Bad	Size	Cmp	Bad	Size	Cmp	Bad	Size
int A1[3]									
int *A2[3]									
int (*A3)[3]									



Decl	An			*An			**A <i>n</i>		
	Cmp	Bad	Size	Cmp	Bad	Size	Cmp	Bad	Size
int A1[3]	Y	N	12	Y	N	4	N	_	_
int *A2[3]	Y	N	24	Y	N	8	Y	Y	4
int (*A3)[3]	Y	N	8	Y	Y	12	Y	Y	4)



15

Multidimensional (Nested) Arrays

Declaration

 $T \mathbf{A}[R][C];$


- 2D array of data type T
- R rows, C columns

Array Size

R * C * sizeof (T) bytes

Arrangement

Row-Major Ordering



int A[R][C];

	A [0] [0]	• • •	A [0] [C-1]	A [1] [0]	• • •	A [1] [C-1]		•	•	•	A [R-1] [0]		A [R-1] [C-1]
ļ	4*R*C Bytes												

据说是一个面试题

```
1 int function(const int src[16]){
      int val1=0:
 3
       int dst[16]={0};
 4
      int val2=0;
 5
       const int *psrc=src;
      //问题1:如下代码行输出什么?
 6
       fprintf(stdout, "size of src=%lu\n", sizeof(src));
      //问题2:如下代码有什么副作用?
 9
       for(int i=0;i<=16;i++){
10
       dst[i]=*psrc+i;
11
       psrc++;
12
13
      return 0;
14 }
```

Today

Arrays

- One-dimensional
- Multi-dimensional (nested)
- Multi-level


Structures

- Allocation
- Access
- Alignment

Unions

Structure Representation


```
struct rec {
   int a[4];
   size_t i;
   struct rec *next;
};
```



- Structure represented as block of memory
 - Big enough to hold all of the fields
- Fields ordered according to declaration
 - Even if another ordering could yield a more compact representation
- Compiler determines overall size + positions of fields
 - Machine-level program has no understanding of the structures in the source code

Generating Pointer to Structure Member

```
struct rec {
   int a[4];
   size_t i;
   struct rec *next;
};
```



Generating Pointer to Array Element

- Offset of each structure member determined at compile time
- Compute as r + 4*idx


```
int *get_ap
  (struct rec *r, size_t idx)
{
   return &r->a[idx];
}
```

```
# r in %rdi, idx in %rsi
leaq (%rdi,%rsi,4), %rax
ret
```

Following Linked List

C Code


```
void set_val
  (struct rec *r, int val)
{
  while (r) {
    int i = r->i;
    r->a[i] = val;
    r = r->next;
  }
}
```



```
.L11:  # loop:
  movslq 16(%rdi), %rax  # i = M[r+16]
  movl    %esi, (%rdi, %rax, 4) # M[r+4*i] = val
  movq    24(%rdi), %rdi  # r = M[r+24]
  testq    %rdi, %rdi  # Test r
  jne    .L11  # if !=0 goto loop
```

Structures & Alignment


Unaligned Data



```
struct S1 {
  char c;
  int i[2];
  double v;
} *p;
```

Aligned Data

- Primitive data type requires K bytes
- Address must be multiple of K



Alignment Principles

Aligned Data

- Primitive data type requires K bytes
- Address must be multiple of K
- Required on some machines; advised on x86-64

Motivation for Aligning Data

- Memory accessed by (aligned) chunks of 4 or 8 bytes (system dependent)
 - Inefficient to load or store datum that spans cache lines (64 bytes). Intel states should avoid crossing 16 byte boundaries.
 - Virtual memory trickier when datum spans 2 pages (4 KB pages)

Compiler

Inserts gaps in structure to ensure correct alignment of fields

Specific Cases of Alignment (x86-64)

- 1 byte: char, ...
 - no restrictions on address
- 2 bytes: short, ...
 - lowest 1 bit of address must be 02
- 4 bytes: int, float, ...
 - lowest 2 bits of address must be 002
- 8 bytes: double, long, char *, ...
 - lowest 3 bits of address must be 0002

Satisfying Alignment with Structures

Within structure:

Must satisfy each element's alignment requirement

Overall structure placement

- Each structure has alignment requirement K
 - K = Largest alignment of any element
- Initial address & structure length must be multiples of K

Example:

K = 8, due to double element

```
        c
        3 bytes
        i [0]
        i [1]
        4 bytes
        v

        p+0
        p+4
        p+8
        p+16
        p+24


        Multiple of 4
        Multiple of 8
        Multiple of 8

Multiple of 8
```

Meeting Overall Alignment Requirement

- For largest alignment requirement K
- Overall structure must be multiple of K

```
struct S2 {
  double v;
  int i[2];
  char c;
} *p;
```




Arrays of Structures

- Overall structure length multiple of K
- Satisfy alignment requirement for every element


```
struct S2 {
  double v;
  int i[2];
  char c;
} a[10];
```





Accessing Array Elements

- Compute array offset 12*idx
 - sizeof (S3), including alignment spacers
- Element j is at offset 8 within structure
- Assembler gives offset a+8
 - Resolved during linking





```
short get_j(int idx)
{
  return a[idx].j;
}
```

```
# %rdi = idx
leaq (%rdi,%rdi,2),%rax # 3*idx
movzwl a+8(,%rax,4),%eax
```

```
struct S3 {
   short i;
   float v;
   short j;
} a[10];
```


27

Saving Space

Put large data types first

```
struct S4 {
  char c;
  int i;
  char d;
} *p;
struct S5 {
  int i;
  char c;
  char d;
} *p;
```

Effect (largest alignment requirement K=4)




Example Struct Exam Question

Problem 5. (8 points):

Struct alignment. Consider the following C struct declaration:

```
typedef struct {
  char a;
  long b;
  float c;
  char d[3];
  int *e;
  short *f;
} foo;
```

 Show how foo would be allocated in memory on an x86-64 Linux system. Label the bytes with the names of the various fields and clearly mark the end of the struct. Use an X to denote space that is allocated in the struct as padding.



Example Struct Exam Question

Problem 5. (8 points):

Struct alignment. Consider the following C struct declaration:

```
typedef struct {
  char a;
  long b;
  float c;
  char d[3];
  int *e;
  short *f;
} foo;
```

 Show how foo would be allocated in memory on an x86-64 Linux system. Label the bytes with the names of the various fields and clearly mark the end of the struct. Use an X to denote space that is allocated in the struct as padding.


Example Struct Exam Question (Cont'd)

Problem 5. (8 points):

Struct alignment. Consider the following C struct declaration:

```
typedef struct {
  char a;
  long b;
  float c;
  char d[3];
  int *e;
  short *f;
} foo;
```

Rearrange the elements of foo to conserve the most space in memory. Label the bytes with the names of the various fields and clearly mark the end of the struct. Use an X to denote space that is allocated in the struct as padding.



Example Struct Exam Question (Cont'd)

Problem 5. (8 points):

Struct alignment. Consider the following C struct declaration:

```
typedef struct {
  char a;
  long b;
  float c;
  char d[3];
  int *e;
  short *f;
} foo;
```

Rearrange the elements of foo to conserve the most space in memory. Label the bytes with the names of the various fields and clearly mark the end of the struct. Use an X to denote space that is allocated in the struct as padding.



Today

Arrays

- One-dimensional
- Multi-dimensional (nested)
- Multi-level

Structures

- Allocation
- Access
- Alignment


Unions


Union Allocation

- Allocate according to largest element
- Can only use one field at a time

```
union U1 {
  char c;
  int i[2];
  double v;
} *up;
```

```
struct S1 {
  char c;
  int i[2];
  double v;
} *sp;
```





Using Union to Access Bit Patterns

```
typedef union {
  float f;
  unsigned u;
} bit_float_t;
```

```
u
f
) 4
```

```
float bit2float(unsigned u)
{
  bit_float_t arg;
  arg.u = u;
  return arg.f;
}
```

```
unsigned float2bit(float f)
{
  bit_float_t arg;
  arg.f = f;
  return arg.u;
}
```

Same as (float) u?

Same as (unsigned) f?

Byte Ordering Revisited

Idea

- Short/long/quad words stored in memory as 2/4/8 consecutive bytes
- Which byte is most (least) significant?
- Can cause problems when exchanging binary data between machines

■ Big Endian

- Most significant byte has lowest address
- Sparc, Internet

Little Endian

- Least significant byte has lowest address
- Intel x86, ARM Android and IOS

Bi Endian

- Can be configured either way
- ARM

Byte Ordering Example

```
union {
   unsigned char c[8];
   unsigned short s[4];
   unsigned int i[2];
   unsigned long l[1];
} dw;
```

How are the bytes inside short/int/long stored?

Memory addresses growing ———

32-bit

c[0]	c[1]	c[2]	c[3]	c[4]	c[5]	c[6]	c[7]	
s[0] s[1]				s[2]	s[3]		
	i[0]		i[1]				
	1[0]						

64-bit


c[0]	c[1]	c[2]	c[3]	c[4]	c[5]	c[6]	c[7]			
s[s[0] s[1]				2]	s[3]				
	i[0]		i[1]						
1[0]										

Byte Ordering Example (Cont).

```
int j;
for (j = 0; j < 8; j++)
    dw.c[j] = 0xf0 + j;
printf("Characters 0-7 ==
[0x8x, 0x8x, 0x8x, 0x8x, 0x8x, 0x8x, 0x8x, 0x8x, 0x8x] n",
    dw.c[0], dw.c[1], dw.c[2], dw.c[3],
    dw.c[4], dw.c[5], dw.c[6], dw.c[7]);
printf("Shorts 0-3 == [0x8x, 0x8x, 0x8x, 0x8x] n",
    dw.s[0], dw.s[1], dw.s[2], dw.s[3]);
printf("Ints 0-1 == [0x%x, 0x%x] \n",
    dw.i[0], dw.i[1]);
printf("Long 0 == [0x%lx]\n",
    dw.1[0]);
```

Byte Ordering on IA32

Little Endian



Output:

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]
Shorts 0-3 == [0xf1f0,0xf3f2,0xf5f4,0xf7f6]
Ints 0-1 == [0xf3f2f1f0,0xf7f6f5f4]
Long 0 == [0xf3f2f1f0]
```

Byte Ordering on Sun

Big Endian

f0	f1	f2	f3	f4	f5	f6	£7	
c[0]	c[1]	c[2]	c[3]	c[4]	c[5]	c[6]	c[7]	
s[s[0] s[1]				2]	s[3]		
	i[0]		i[1]				
	1[0]						
NACD			LCD	NACD			LCD	

MSB LSB MSB LSB Print

Output on Sun:

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]


Shorts 0-3 == [0xf0f1,0xf2f3,0xf4f5,0xf6f7]

Ints 0-1 == [0xf0f1f2f3,0xf4f5f6f7]

Long 0 == [0xf0f1f2f3]
```

Byte Ordering on x86-64

Little Endian



Output on x86-64:

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]
Shorts 0-3 == [0xf1f0,0xf3f2,0xf5f4,0xf7f6]
Ints 0-1 == [0xf3f2f1f0,0xf7f6f5f4]
Long 0 == [0xf7f6f5f4f3f2f1f0]
```

Summary of Compound Types in C

Arrays

- Contiguous allocation of memory
- Aligned to satisfy every element's alignment requirement
- Pointer to first element
- No bounds checking

Structures

- Allocate bytes in order declared
- Pad in middle and at end to satisfy alignment

Unions

- Overlay declarations
- Way to circumvent type system