

Improving Diffusion Tensor Estimation using Adaptive and Optimized Filtering based on Local Similarity

Andrés F. López-Lopera, Mauricio A. Álvarez and Álvaro Á. Orozco
 Department of Electrical Engineering, Universidad Tecnológica de Pereira, Pereira-Colombia
 IbPRIA 2015: 7th Iberian Conference on Pattern Recognition and Image Analysis
 Santiago de Compostela, Spain. June 17-19

Introduction

- The diffusion-weighted magnetic resonance imaging (DW-MRI or DWI) describes the neuronal pathways which are used for the communication among several centers of brain activity [1].
- The DW-MRI has an inherent low SNR due to a low signal amplitude and a pronounced thermal noise, biasing the estimation of diffusion tensors (DT) [1].
- Classic denoising techniques in DW-MRI filtering assume an equal noise distribution across the image, modifying important information (e.g. edges, structures and type of matter), leading to suboptimal filtering results.
- Methods based on local similarity have the potential to improve the estimation of diffusion information with respect to another filtering techniques [1, 2, 3].
- Moreover, adaptive and optimized filters based on local similarity can mitigate the drawbacks of having to deal with tuning the filter parameters.

Materials and Methods

Non-Local Means filter (NLM): In a 2D set of parallel images \mathbf{u} , the restored intensities $\hat{\mathbf{u}}(x_i)$ of the voxel x_i is given by

$$\hat{\mathbf{u}}(x_i) = \sum_{x_j \in V_i} w(x_i, x_j) \mathbf{u}(x_j). \quad (1)$$

The performance of this filter depends on the hyperparameters of the weight functions and the volume V_i . To avoid this problem, several researches have proposed the following adaptive and optimized filter techniques based on local similarity for brain imaging preprocessing:

- Adaptive and Optimized NLM filter (AONLM) [1]
- Oracle-based 3D Discrete Cosine Transform filter (ODCT) [2]
- Prefiltered Rotationally Invariant NLM filter (PRINLM) [2]
- Local PCA filter (LPCA) [3]

Diffusion Tensors (DT): Stejskal-Tanner in [4], relates the DW-MRI and DT-MRI fields by

$$S_k = S_0 \exp \left\{ -b \hat{\mathbf{g}}_k^\top \mathbf{D} \hat{\mathbf{g}}_k \right\}, \quad (2)$$

where S_k and S_0 are the DW-MRI associated to the $\hat{\mathbf{g}}_k$ diffusion gradient and baseline image, respectively, and \mathbf{D} is the tensor matrix. Several researches have proposed different methods for DT-MRI estimation such as linear systems [5] and methods based on least-squares (e.g. RESTORE) [6].

Dataset experimental Background




Figure : Dataset experimental Background. The dti30.nii is a complete set of DW-MRI images in Nifti format available at <http://www.cabiatl.com/CABI/resources/dti-analysis/>

Filtering techniques and DT estimation method

The parameters for Gaussian filter (GF) and Perona-Malik algorithm (PM) were tuned by cross-validation. For PM, we chose a monotonic function privileging wide regions. For optimized filters, we used the package for 4D-MRI proposed at <https://sites.google.com/site/pierrickcoupe>. We rely on the DT estimation method proposed by Barmpoutis in [5], and we use RESTORE algorithm to evaluate the filtering performance.

Results and Discussion




Figure : DWI and DTI results for the proposed filtering methods using the 38th direction and the 30th slide from the goal starndard. Finally we show the estimated DT-MRI from the yellow square window drawn in (a).

Table : Frobenius norm from the difference of metrics computed from the DT-MRI between the case under study and the goal standard. MD: mean diffusivity error. RA: relative anisotropy error. FA: fractional anisotropy error. Frob: Frobenius error norm.

Scheme	MD ($\times 10^{-4}$)	RA ($\times 10^{-3}$)	FA	Frob ($\times 10^{-3}$)
Noisy	0.1234 ± 0.0131	0.1912 ± 0.0190	0.0061 ± 0.0006	0.9274 ± 0.0974
GF	0.0679 ± 0.0078	0.1366 ± 0.0149	0.0060 ± 0.0006	0.5371 ± 0.0449
PM	0.1234 ± 0.0131	0.1912 ± 0.0190	0.0061 ± 0.0006	0.9274 ± 0.0974
AONLM	0.0145 ± 0.0014	0.0558 ± 0.0070	0.0058 ± 0.0007	0.1960 ± 0.0237
ODCT	0.0112 ± 0.0017	0.0448 ± 0.0059	0.0059 ± 0.0006	0.1453 ± 0.0198
PRINLM	0.0090 ± 0.0019	0.0300 ± 0.0040	0.0059 ± 0.0006	0.1148 ± 0.0239
LPCA	0.0104 ± 0.0017	0.0437 ± 0.0057	0.0058 ± 0.0006	0.1296 ± 0.0161
RESTORE	0.0508 ± 0.0046	0.0857 ± 0.0072	0.0044 ± 0.0005	0.4130 ± 0.0077

Conclusion

- Methods based on local similarity improves the performance of diffusion information but they depend on how well we tune the filtering parameters.
- Adaptive and optimized filter techniques based on local similarity, tend to remove the bias in both DWI filtering and DTI estimation by local information, showing a better performance respect to the classical filters.
- The PRINLM and LPCA filters show the best performances among the optimized filters, making them the most suitable for DWI.

Acknowledgment

This work was funded by COLCIENCIAS under the project 1110-569-34461 and the 617 agreement "Jóvenes Investigadores e Innovadores".

References

- J. V. Manjón, P. Coupé, L. Martí-Bonmatí, D. L. Collins, and M. Robles, "Adaptive non-local means denoising of MR images with spatially varying noise levels." *Magnetic Resonance Imaging*, vol. 31, no. 1, pp. 192–203, 2010.
- J. V. Manjón, P. Coupé, A. Buades, D. L. Collins, and M. Robles, "New methods for MRI denoising based on sparseness and self-similarity." *Medical Image Analysis*, vol. 16, no. 1, pp. 18–27, Jan. 2012.
- J. V. Manjón, P. Coupé, L. Concha, A. Buades, D. L. Collins, and M. Robles, "Diffusion weighted image denoising using overcomplete local PCA," *PLoS ONE*, vol. 8, no. 9, pp. 1 – 12, 2013.
- E. O. Stejskal and J. E. Tanner, "Spin diffusion measurements: Spin echoes in the presence of a time-dependent field gradient," *The Journal of Chemical Physics*, vol. 42, no. 1, pp. 288–292, 1965.
- A. Barmpoutis, *Tutorial on Diffusion Tensor MRI using Matlab*, E. Edition, Ed. University of Florida, 2010.
- L. C. Chang, D. K. Jones, and C. Pierpaoli, "Restore: Robust estimation of tensors by outlier rejection," *Magnetic Resonance in Medicine*, vol. 53, pp. 1088–1095, 2005.