msql8.0 command line

Sql—Structured query language

DATATYPES

- int———34,56,
- bigint———34562967
- float————5.67,5.43
- double———5.78906
- varchar(variable character)(limit)——-like string(can use in any data type we dont know
- date——-yyyy/mm/dd
- date time———yyyy/mm/dd hr:min:sec

#structure of table

- show databases;——shows all databases created
- drop database database-name; ——is to remove database
- create database database-name;———is to create new database
- use database-name;———-database changed-to make tables in that database
- show tables;——— to show tables inside that database
- create table table-name(scheme);——-to create table inside that database
- scheme-(column-name datatype)
- describe table-name;——-to check the structure of the table

how to add new column to table

#add-add new column

- Alter table table-name add new column-name data type;

#added column came last to add the column in the position we want

- alter table table-name add new column-name datatype after columname;

#add new column to the first first —(no before)

- alter table table-name add new column-name datatype first;

#add multiple column same time

- alter table table-name add(newcolumn1 datatype ,newcolumn2 dataype ,…….);

#using after adding multiple column

- alter table table-name add(new column-name datatype after column name,newcolumnname2 datatype after column name);

to change datatype /limit

#modify—-limit/datatype

- alter table table-name modify column-name changed datatype;

#changing limit

- alter table table-name modify column-name varchar(100);

how to change column name

#change

- alter table table-name column-name change column-name datatype;

#drop—to remove table name and column-name,multiple column

- drop table-name;
- alter table table-name drop column-name:
- alter table table-name drop column1 drop column2 drop column3

#to change table-name—-rename

- alter table table-name rename new table-name

Add values

- manually
- export
- #Manually
- use insert

#add values

- insert into table-name (column-name….,)values(……);
- insert into table-name column-name(….)values(…….),(…….),(…….):
- insert into table-name values(…..),(…..),

changing the value entered

#update

- update table-name set column-name=”changed value “ where cus_id=value;

  changing the value after inserting it

#multiple value change

- update table-name set column-name1=value,colum-name2=value where colun-name=value;

#to add same on every one no need to use where

- update table-name set column-name=”flipkart”;
- #not using where it will add on to every column

#to change a column in multiple person

- update table-name set column-name=value where column-name in (…,….);

#to show values inside the table

- select * from table-name;

#to take details with a condition———>Filtering

- select * from table name where condition;
- (condition like price≥6000)
- #and used in multiple condition
- select * from table name where condition1 and condition2
- can use or also
- #between————
- select * from table name where column between 21 and 22
- select * from table name where column-name in(21,22)

#name start with A

- select * from table name where column-name like ‘a%’;

#name end with A

- select * from table name where column name like ‘%a’;

#order by——ascending order

- select * from table name order by age;

- or— select * from table name order by age ASC;

#descending order

- select * from table-name order by mark DESC

#* used to get all details

- select name,mark from table-name orderby colum-name desc;

#limit

- select * from student limit 3;————-details of 1st 3 person;

#distinct——show repeating element once

- select distinct column from table name;

filtering

- greater than
- less than
- equal
- and
- or
- between
- start with like a%
- end with like “ %a
- order by
- order by asc
- order by desc
- limit
- distinct

#Aggregation functions

do calculation

- sum()
- avg()
- count()

- max()
- min()
- select aggfn(column-name) from table-name;

#group by

- select column-name from table-name group by column-name;

#aggfn+groupby

#count the student in each course

- select column name,aggfn(column) from table-name group by columname;
- eg;select course,count(*) from student group by course;

#Having

used to give condition

- always used with group
- select columnname ,aggfn(column) from table-name group by column having aggfn()>condition
- eg; select course,avg(mark) from student group by course having avg(mark)>80;

#joins

- left join
- right join
- inner join
- outer join

#inner join

- taking common columns from two tables
- select table1.column-name,table2.columname from table1 inner join table2 on table1.comon column=table2.commoncolumn;

#left join

- common table+left table
- 1 st table is left table
- select table1.colum,table2.column from table1 left join table2 on table1.commoncolumn=table2.commomcolumn;
-

#right join

- common table+right table
- 2nd table right
- select table1.colum,table2.column from table1 right join table2 on table1.commoncolumn=table2.commomcolumn;

#outer join

- all table
- common,left,right
- cant do like inner ,left,right
- left join+right join
- select table1.column,table2.column,table2.column2 from table1 left join table2 on table1.commoncoumn=table2.commoncolumn union select table1.column,table2.column,table2.column2 from table1 right join table2 on table1.commoncoumn=table2.commoncolumn

---

#Work bench

#schemas———can see the database and the table

#file —-new query tab (to write queries)

#to run the current query or single query (harry potter symbol with line symbol)

#to run all queries (symbol on left side one without the line

#save file by left to this

CRUD OPERATION

---

c——create

r———-select

u———-update

d——delete

#to get year from join date

- select distinct year(join date) as year from table name;
- select——where—order by—-limit

#new table from existing table(sub table)—view table

- create view new table name as select column name1,column2 from table name;

#subquery—query inside query

- select columnname1,columnname2 from table name where column name>(subquery);
- subquery—(select aggfn(column) from table name)

#while using join not need to use table full name

- select c.id ,c.name ,o.amount from custom_windows c inner join order_windows o on c.id=o.id;
- taken custom_windows as c and order_windows as o