

The Computational Complexity of $3k$ -CLIQUE

Craig Alan Feinstein

2712 Willow Glen Drive, Baltimore, Maryland 21209

E-mail: cafeinst@msn.com, BS"D

Abstract: In this note, we show that the fastest deterministic and exact algorithm that solves the $3k$ -CLIQUE problem must run in $\Omega(n^{2k})$ time in the worst-case scenario on a classical computer, where n is the number of vertices in the graph.

Disclaimer: This article was authored by Craig Alan Feinstein in his private capacity. No official support or endorsement by the U.S. Government is intended or should be inferred.

The $3k$ -CLIQUE problem is to determine whether or not a clique of size $3k$ exists in a given undirected graph G , where k is a positive integer that is not part of the input of the problem [4]. In this note, we show that the fastest deterministic and exact algorithm that solves $3k$ -CLIQUE must run in $\Omega(n^{2k})$ time in the worst-case scenario on a classical computer, where n is the number of vertices in the graph:

Let G be an undirected graph with n vertices. For every k -clique C in G , create a corresponding vertex $v(C)$ in an auxiliary graph G' . And for every two vertices $v(C_1)$ and $v(C_2)$ in G' , create an edge connecting them in G' if and only if $C_1 \cup C_2$ forms a $2k$ -clique in G . Then G' will have $O(n^k)$ vertices and $O(n^{2k})$ edges. Note that the 3 -CLIQUE problem on G' is equivalent to the $3k$ -CLIQUE problem on G [4].

Let A be the adjacency matrix of G' . Then G' has a 3 -clique if and only if $A \circ A^2$, the Hadamard product of A and A^2 , is nonzero [2]. The matrix $A \circ A^2$ has $\Theta(n^{2k})$ entries, and it is possible that only a constant number of these entries are nonzero but $\Theta(n^{2k})$ entries of A are nonzero (when there are only a constant number of $3k$ -cliques in G but G is still sufficiently dense); therefore, the fastest deterministic and exact algorithm that determines whether $A \circ A^2$ is nonzero must take $\Omega(n^{2k})$ time in the worst-case scenario. Then since determining whether $A \circ A^2$ is nonzero is equivalent to the $3k$ -CLIQUE problem on G , it must also take $\Omega(n^{2k})$ time in the worst-case scenario for any algorithm to solve the $3k$ -CLIQUE problem on G . And this implies that $P \neq NP$ [1]. \square

This lower bound is confirmed by the fact that the fastest known deterministic and exact algorithm that solves $3k$ -CLIQUE was first published in 1985 and has a running-time of $\Theta(n^{\omega k})$, where $\omega \geq 2$ [1, 3, 4].

References

- [1] F. Eisenbrand and F. Grandoni, "On the complexity of fixed parameter clique and dominating set", *Theoretical Computer Science* 326(1-3): 57-67, 2004.
- [2] A. Itai and M. Rodeh, "Finding a minimum circuit in a graph", *SIAM Journal on Computing* 7(4): 413-423, 1978.
- [3] J. Nešetřil and S. Poljak, "On the complexity of the subgraph problem", *Comment. Math. Univ. Carolin.* 26, 415-419, 1985.
- [4] G. J. Woeginger, "Open problems around exact algorithms", *Discrete Applied Mathematics* 156(3): 397-405, 2008.