

# pandas.DataFrame

`class pandas.DataFrame(data=None, index=None, columns=None, dtype=None, copy=False)` [\[source\]](#)

Two-dimensional size-mutable, potentially heterogeneous tabular data structure with labeled axes (rows and columns). Arithmetic operations align on both row and column labels. Can be thought of as a dict-like container for Series objects. The primary pandas data structure.

**data** : *ndarray (structured or homogeneous), Iterable, dict, or DataFrame*  
Dict can contain Series, arrays, constants, or list-like objects  
*Changed in version 0.23.0:* If data is a dict, argument order is maintained for Python 3.6 and later.

**index** : *Index or array-like*  
Index to use for resulting frame. Will default to RangeIndex if no indexing information part of input data and no index provided

**Parameters:** **columns** : *Index or array-like*  
Column labels to use for resulting frame. Will default to RangeIndex (0, 1, 2, ..., n) if no column labels are provided

**dtype** : *dtype, default None*  
Data type to force. Only a single dtype is allowed. If None, infer

**copy** : *boolean, default False*  
Copy data from inputs. Only affects DataFrame / 2d ndarray input

## See also:

### `DataFrame.from_records`

Constructor from tuples, also record arrays.

### `DataFrame.from_dict`

From dicts of Series, arrays, or dicts.

### `DataFrame.from_items`

From sequence of (key, value) pairs `pandas.read_csv`, `pandas.read_table`, `pandas.read_clipboard`.

## Examples

Constructing DataFrame from a dictionary.

```
>>> d = {'col1': [1, 2], 'col2': [3, 4]}
>>> df = pd.DataFrame(data=d)
>>> df
   col1  col2
0     1     3
1     2     4
```

Notice that the inferred dtype is int64.

```
>>> df.dtypes
col1    int64
col2    int64
dtype: object
```

To enforce a single dtype:

```
>>> df = pd.DataFrame(data=d, dtype=np.int8)
>>> df.dtypes
col1    int8
col2    int8
dtype: object
```

Constructing DataFrame from numpy ndarray:

```
>>> df2 = pd.DataFrame(np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]]),
...                      columns=['a', 'b', 'c'])
>>> df2
   a  b  c
0  1  2  3
1  4  5  6
2  7  8  9
```

## Attributes

<b>T</b>	Transpose index and columns.
<b>at</b>	Access a single value for a row/column label pair.
<b>axes</b>	Return a list representing the axes of the DataFrame.
<b>blocks</b>	(DEPRECATED) Internal property, property synonym for <code>as_blocks()</code> .
<b>columns</b>	The column labels of the DataFrame.
<b>dtypes</b>	Return the dtypes in the DataFrame.
<b>empty</b>	Indicator whether DataFrame is empty.
<b>ftypes</b>	Return the ftypes (indication of sparse/dense and dtype) in DataFrame.
<b>iat</b>	Access a single value for a row/column pair by integer position.
<b>iloc</b>	Purely integer-location based indexing for selection by position.
<b>index</b>	The index (row labels) of the DataFrame.
<b>is_copy</b>	Return the copy.
<b>ix</b>	A primarily label-location based indexer, with integer position fallback.
<b>loc</b>	Access a group of rows and columns by label(s) or a boolean array.
<b>ndim</b>	Return an int representing the number of axes / array dimensions.
<b>shape</b>	Return a tuple representing the dimensionality of the DataFrame.
<b>size</b>	Return an int representing the number of elements in this object.
<b>style</b>	Property returning a Styler object containing methods for building a styled HTML representation for the DataFrame.
<b>values</b>	Return a Numpy representation of the DataFrame.
<b>timetuple</b>	

## Methods

<code>abs()</code>	Return a Series/DataFrame with absolute numeric value of each element.
<code>add(other[, axis, level, fill_value])</code>	Addition of dataframe and other, element-wise (binary operator <i>add</i> ).
<code>add_prefix(prefix)</code>	Prefix labels with string <i>prefix</i> .
<code>add_suffix(suffix)</code>	Suffix labels with string <i>suffix</i> .
<code>agg(func[, axis])</code>	Aggregate using one or more operations over the specified axis.
<code>aggregate(func[, axis])</code>	Aggregate using one or more operations over the specified axis.
<code>align(other[, join, axis, level, copy, ...])</code>	Align two objects on their axes with the specified join method for each axis Index.
<code>all([axis, bool_only, skipna, level])</code>	Return whether all elements are True, potentially over an axis.
<code>any([axis, bool_only, skipna, level])</code>	Return whether any element is True, potentially over an axis.
<code>append(other[, ignore_index, ...])</code>	Append rows of <i>other</i> to the end of caller, returning a new object.
<code>apply(func[, axis, broadcast, raw, reduce, ...])</code>	Apply a function along an axis of the DataFrame.
<code>applymap(func)</code>	Apply a function to a Dataframe elementwise.
<code>as_blocks([copy])</code>	(DEPRECATED) Convert the frame to a dict of dtype -> Constructor Types that each has a homogeneous dtype.
<code>as_matrix([columns])</code>	(DEPRECATED) Convert the frame to its Numpy-array representation.
<code>asfreq(freq[, method, how, normalize, ...])</code>	Convert TimeSeries to specified frequency.
<code>asof(where[, subset])</code>	Return the last row(s) without any NaNs before <i>where</i> .
<code>assign(**kwargs)</code>	Assign new columns to a DataFrame.
<code>astype(dtype[, copy, errors])</code>	Cast a pandas object to a specified dtype dtype.
<code>at_time(time[, asof, axis])</code>	Select values at particular time of day (e.g.
<code>between_time(start_time, end_time[, ...])</code>	Select values between particular times of the day (e.g., 9:00-9:30 AM).
<code>bfill([axis, inplace, limit, downcast])</code>	Synonym for <code>DataFrame.fillna()</code> with <code>method='bfill'</code> .
<code>bool()</code>	Return the bool of a single element PandasObject.
<code>boxplot([column, by, ax, fontsize, rot, ...])</code>	Make a box plot from DataFrame columns.
<code>clip([lower, upper, axis, inplace])</code>	Trim values at input threshold(s).
<code>clip_lower(threshold[, axis, inplace])</code>	(DEPRECATED) Trim values below a given threshold.
<code>clip_upper(threshold[, axis, inplace])</code>	(DEPRECATED) Trim values above a given threshold.
<code>combine(other, func[, fill_value, overwrite])</code>	Perform column-wise combine with another DataFrame based on a passed function.
<code>combine_first(other)</code>	Update null elements with value in the same location in <i>other</i> .
<code>compound([axis, skipna, level])</code>	Return the compound percentage of the values for the requested axis.
<code>convert_objects([convert_dates, ...])</code>	(DEPRECATED) Attempt to infer better dtype for object columns.

<code>copy([deep])</code>	Make a copy of this object's indices and data.
<code>corr([method, min_periods])</code>	Compute pairwise correlation of columns, excluding NA/null values.
<code>corrwith(other[, axis, drop, method])</code>	Compute pairwise correlation between rows or columns of DataFrame with rows or columns of Series or DataFrame.
<code>count([axis, level, numeric_only])</code>	Count non-NA cells for each column or row.
<code>cov([min_periods])</code>	Compute pairwise covariance of columns, excluding NA/null values.
<code>cummax([axis, skipna])</code>	Return cumulative maximum over a DataFrame or Series axis.
<code>cummin([axis, skipna])</code>	Return cumulative minimum over a DataFrame or Series axis.
<code>cumprod([axis, skipna])</code>	Return cumulative product over a DataFrame or Series axis.
<code>cumsum([axis, skipna])</code>	Return cumulative sum over a DataFrame or Series axis.
<code>describe([percentiles, include, exclude])</code>	Generate descriptive statistics that summarize the central tendency, dispersion and shape of a dataset's distribution, excluding NaN values.
<code>diff([periods, axis])</code>	First discrete difference of element.
<code>div(other[, axis, level, fill_value])</code>	Floating division of dataframe and other, element-wise (binary operator <i>truediv</i> ).
<code>divide(other[, axis, level, fill_value])</code>	Floating division of dataframe and other, element-wise (binary operator <i>truediv</i> ).
<code>dot(other)</code>	Compute the matrix multiplication between the DataFrame and other.
<code>drop([labels, axis, index, columns, level, ...])</code>	Drop specified labels from rows or columns.
<code>drop_duplicates([subset, keep, inplace])</code>	Return DataFrame with duplicate rows removed, optionally only considering certain columns.
<code>droplevel(level[, axis])</code>	Return DataFrame with requested index / column level(s) removed.
<code>dropna([axis, how, thresh, subset, inplace])</code>	Remove missing values.
<code>uplicated([subset, keep])</code>	Return boolean Series denoting duplicate rows, optionally only considering certain columns.
<code>eq(other[, axis, level])</code>	Equal to of dataframe and other, element-wise (binary operator <i>eq</i> ).
<code>equals(other)</code>	Test whether two objects contain the same elements.
<code>eval(expr[, inplace])</code>	Evaluate a string describing operations on DataFrame columns.
<code>ewm([com, span, halflife, alpha, ...])</code>	Provides exponential weighted functions.
<code>expanding([min_periods, center, axis])</code>	Provides expanding transformations.
<code>ffill([axis, inplace, limit, downcast])</code>	Synonym for <code>DataFrame.fillna()</code> with <code>method='ffill'</code> .
<code>fillna([value, method, axis, inplace, ...])</code>	Fill NA/NaN values using the specified method.
<code>filter([items, like, regex, axis])</code>	Subset rows or columns of dataframe according to labels in the specified index.
<code>first(offset)</code>	Convenience method for subsetting initial periods of time series data based on a date offset.
<code>first_valid_index()</code>	Return index for first non-NA/null value.
<code>floordiv(other[, axis, level, fill_value])</code>	Integer division of dataframe and other, element-wise (binary operator <i>floordiv</i> ).

<code>from_csv(path[, header, sep, index_col, ...])</code>	(DEPRECATED) Read CSV file.
<code>from_dict(data[, orient, dtype, columns])</code>	Construct DataFrame from dict of array-like or dicts.
<code>from_items(items[, columns, orient])</code>	(DEPRECATED) Construct a DataFrame from a list of tuples.
<code>from_records(data[, index, exclude, ...])</code>	Convert structured or record ndarray to DataFrame.
<code>ge(other[, axis, level])</code>	Greater than or equal to of dataframe and other, element-wise (binary operator <i>ge</i> ).
<code>get(key[, default])</code>	Get item from object for given key (DataFrame column, Panel slice, etc.).
<code>get_dtype_counts()</code>	Return counts of unique dtypes in this object.
<code>get_ftype_counts()</code>	(DEPRECATED) Return counts of unique ftypes in this object.
<code>get_value(index, col[, takeable])</code>	(DEPRECATED) Quickly retrieve single value at passed column and index.
<code>get_values()</code>	Return an ndarray after converting sparse values to dense.
<code>groupby([by, axis, level, as_index, sort, ...])</code>	Group DataFrame or Series using a mapper or by a Series of columns.
<code>gt(other[, axis, level])</code>	Greater than of dataframe and other, element-wise (binary operator <i>gt</i> ).
<code>head([n])</code>	Return the first <i>n</i> rows.
<code>hist([column, by, grid, xlabelsize, xrot, ...])</code>	Make a histogram of the DataFrame's.
<code>idxmax([axis, skipna])</code>	Return index of first occurrence of maximum over requested axis.
<code>idxmin([axis, skipna])</code>	Return index of first occurrence of minimum over requested axis.
<code>infer_objects()</code>	Attempt to infer better dtypes for object columns.
<code>info([verbose, buf, max_cols, memory_usage, ...])</code>	Print a concise summary of a DataFrame.
<code>insert(loc, column, value[, allow_duplicates])</code>	Insert column into DataFrame at specified location.
<code>interpolate([method, axis, limit, inplace, ...])</code>	Interpolate values according to different methods.
<code>isin(values)</code>	Whether each element in the DataFrame is contained in values.
<code>isna()</code>	Detect missing values.
<code>isnull()</code>	Detect missing values.
<code>items()</code>	Iterator over (column name, Series) pairs.
<code>iteritems()</code>	Iterator over (column name, Series) pairs.
<code>iterrows()</code>	Iterate over DataFrame rows as (index, Series) pairs.
<code>itertuples([index, name])</code>	Iterate over DataFrame rows as namedtuples.
<code>join(other[, on, how, lsuffix, rsuffix, sort])</code>	Join columns of another DataFrame.
<code>keys()</code>	Get the 'info axis' (see Indexing for more)
<code>kurt([axis, skipna, level, numeric_only])</code>	Return unbiased kurtosis over requested axis using Fisher's definition of kurtosis (kurtosis of normal == 0.0).
<code>kurtosis([axis, skipna, level, numeric_only])</code>	Return unbiased kurtosis over requested axis using Fisher's definition of kurtosis (kurtosis of normal == 0.0).
<code>last(offset)</code>	Convenience method for subsetting final periods of time series data based on a date offset.
<code>last_valid_index()</code>	Return index for last non-NA/null value.

<code>le(other[, axis, level])</code>	Less than or equal to of dataframe and other, element-wise (binary operator <i>le</i> ).
<code>lookup(row_labels, col_labels)</code>	Label-based “fancy indexing” function for DataFrame.
<code>lt(other[, axis, level])</code>	Less than of dataframe and other, element-wise (binary operator <i>lt</i> ).
<code>mad([axis, skipna, level])</code>	Return the mean absolute deviation of the values for the requested axis.
<code>mask(cond[, other, inplace, axis, level, ...])</code>	Replace values where the condition is True.
<code>max([axis, skipna, level, numeric_only])</code>	Return the maximum of the values for the requested axis.
<code>mean([axis, skipna, level, numeric_only])</code>	Return the mean of the values for the requested axis.
<code>median([axis, skipna, level, numeric_only])</code>	Return the median of the values for the requested axis.
<code>melt([id_vars, value_vars, var_name, ...])</code>	Unpivots a DataFrame from wide format to long format, optionally leaving identifier variables set.
<code>memory_usage([index, deep])</code>	Return the memory usage of each column in bytes.
<code>merge(right[, how, on, left_on, right_on, ...])</code>	Merge DataFrame or named Series objects with a database-style join.
<code>min([axis, skipna, level, numeric_only])</code>	Return the minimum of the values for the requested axis.
<code>mod(other[, axis, level, fill_value])</code>	Modulo of dataframe and other, element-wise (binary operator <i>mod</i> ).
<code>mode([axis, numeric_only, dropna])</code>	Get the mode(s) of each element along the selected axis.
<code>mul(other[, axis, level, fill_value])</code>	Multiplication of dataframe and other, element-wise (binary operator <i>mul</i> ).
<code>multiply(other[, axis, level, fill_value])</code>	Multiplication of dataframe and other, element-wise (binary operator <i>mul</i> ).
<code>ne(other[, axis, level])</code>	Not equal to of dataframe and other, element-wise (binary operator <i>ne</i> ).
<code>nlargest(n, columns[, keep])</code>	Return the first <i>n</i> rows ordered by <i>columns</i> in descending order.
<code>notna()</code>	Detect existing (non-missing) values.
<code>notnull()</code>	Detect existing (non-missing) values.
<code>nsmallest(n, columns[, keep])</code>	Return the first <i>n</i> rows ordered by <i>columns</i> in ascending order.
<code>nunique([axis, dropna])</code>	Count distinct observations over requested axis.
<code>pct_change([periods, fill_method, limit, freq])</code>	Percentage change between the current and a prior element.
<code>pipe(func, *args, **kwargs)</code>	Apply func(self, *args, **kwargs).
<code>pivot([index, columns, values])</code>	Return reshaped DataFrame organized by given index / column values.
<code>pivot_table([values, index, columns, ...])</code>	Create a spreadsheet-style pivot table as a DataFrame.
<code>plot</code>	alias of <code>pandas.plotting._core.FramePlotMethods</code>
<code>pop(item)</code>	Return item and drop from frame.
<code>pow(other[, axis, level, fill_value])</code>	Exponential power of dataframe and other, element-wise (binary operator <i>pow</i> ).
<code>prod([axis, skipna, level, numeric_only, ...])</code>	Return the product of the values for the re-



	requested axis.
<code>product</code> ([axis, skipna, level, numeric_only, ...])	Return the product of the values for the requested axis.
<code>quantile</code> ([q, axis, numeric_only, interpolation])	Return values at the given quantile over requested axis.
<code>query</code> (expr[, inplace])	Query the columns of a DataFrame with a boolean expression.
<code>radd</code> (other[, axis, level, fill_value])	Addition of dataframe and other, element-wise (binary operator <i>radd</i> ).
<code>rank</code> ([axis, method, numeric_only, ...])	Compute numerical data ranks (1 through n) along axis.
<code>rdiv</code> (other[, axis, level, fill_value])	Floating division of dataframe and other, element-wise (binary operator <i>rtruediv</i> ).
<code>reindex</code> ([labels, index, columns, axis, ...])	Conform DataFrame to new index with optional filling logic, placing NA/NaN in locations having no value in the previous index.
<code>reindex_axis</code> (labels[, axis, method, level, ...])	(DEPRECATED) Conform input object to new index.
<code>reindex_like</code> (other[, method, copy, limit, ...])	Return an object with matching indices as other object.
<code>rename</code> ([mapper, index, columns, axis, copy, ...])	Alter axes labels.
<code>rename_axis</code> ([mapper, index, columns, axis, ...])	Set the name of the axis for the index or columns.
<code>reorder_levels</code> (order[, axis])	Rearrange index levels using input order.
<code>replace</code> ([to_replace, value, inplace, limit, ...])	Replace values given in <i>to_replace</i> with <i>value</i> .
<code>resample</code> (rule[, how, axis, fill_method, ...])	Resample time-series data.
<code>reset_index</code> ([level, drop, inplace, ...])	Reset the index, or a level of it.
<code>rfloordiv</code> (other[, axis, level, fill_value])	Integer division of dataframe and other, element-wise (binary operator <i>rfloordiv</i> ).
<code>rmod</code> (other[, axis, level, fill_value])	Modulo of dataframe and other, element-wise (binary operator <i>rmod</i> ).
<code>rmul</code> (other[, axis, level, fill_value])	Multiplication of dataframe and other, element-wise (binary operator <i>rmul</i> ).
<code>rolling</code> (window[, min_periods, center, ...])	Provides rolling window calculations.
<code>round</code> ([decimals])	Round a DataFrame to a variable number of decimal places.
<code>rpow</code> (other[, axis, level, fill_value])	Exponential power of dataframe and other, element-wise (binary operator <i>rpow</i> ).
<code>rsub</code> (other[, axis, level, fill_value])	Subtraction of dataframe and other, element-wise (binary operator <i>rsub</i> ).
<code>rtruediv</code> (other[, axis, level, fill_value])	Floating division of dataframe and other, element-wise (binary operator <i>rtruediv</i> ).
<code>sample</code> ([n, frac, replace, weights, ...])	Return a random sample of items from an axis of object.
<code>select</code> (crit[, axis])	(DEPRECATED) Return data corresponding to axis labels matching criteria.
<code>select_dtypes</code> ([include, exclude])	Return a subset of the DataFrame's columns based on the column dtypes.
<code>sem</code> ([axis, skipna, level, ddof, numeric_only])	Return unbiased standard error of the mean over requested axis.
<code>set_axis</code> (labels[, axis, inplace])	Assign desired index to given axis.
<code>set_index</code> (keys[, drop, append, inplace, ...])	Set the DataFrame index using existing columns.
<code>set_value</code> (index, col, value[, takeable])	(DEPRECATED) Put single value at passed column and index.

<code>shift([periods, freq, axis, fill_value])</code>	Shift index by desired number of periods with an optional time <i>freq</i> .
<code>skew([axis, skipna, level, numeric_only])</code>	Return unbiased skew over requested axis. Normalized by N-1.
<code>slice_shift([periods, axis])</code>	Equivalent to <i>shift</i> without copying data.
<code>sort_index([axis, level, ascending, ...])</code>	Sort object by labels (along an axis)
<code>sort_values(by[, axis, ascending, inplace, ...])</code>	Sort by the values along either axis
<code>squeeze([axis])</code>	Squeeze 1 dimensional axis objects into scalars.
<code>stack([level, dropna])</code>	Stack the prescribed level(s) from columns to index.
<code>std([axis, skipna, level, ddof, numeric_only])</code>	Return sample standard deviation over requested axis.
<code>sub(other[, axis, level, fill_value])</code>	Subtraction of dataframe and other, element-wise (binary operator <i>sub</i> ).
<code>subtract(other[, axis, level, fill_value])</code>	Subtraction of dataframe and other, element-wise (binary operator <i>sub</i> ).
<code>sum([axis, skipna, level, numeric_only, ...])</code>	Return the sum of the values for the requested axis.
<code>swapaxes(axis1, axis2[, copy])</code>	Interchange axes and swap values axes appropriately.
<code>swaplevel([i, j, axis])</code>	Swap levels <i>i</i> and <i>j</i> in a MultiIndex on a particular axis.
<code>tail([n])</code>	Return the last <i>n</i> rows.
<code>take(indices[, axis, convert, is_copy])</code>	Return the elements in the given <i>positional</i> indices along an axis.
<code>to_clipboard([excel, sep])</code>	Copy object to the system clipboard.
<code>to_csv([path_or_buf, sep, na_rep, ...])</code>	Write object to a comma-separated values (csv) file.
<code>to_dense()</code>	Return dense representation of NDFrame (as opposed to sparse).
<code>to_dict([orient, into])</code>	Convert the DataFrame to a dictionary.
<code>to_excel(excel_writer[, sheet_name, na_rep, ...])</code>	Write object to an Excel sheet.
<code>to_feather(fname)</code>	Write out the binary feather-format for DataFrames.
<code>to_gbq(destination_table[, project_id, ...])</code>	Write a DataFrame to a Google BigQuery table.
<code>to_hdf(path_or_buf, key, **kwargs)</code>	Write the contained data to an HDF5 file using HDFStore.
<code>to_html([buf, columns, col_space, header, ...])</code>	Render a DataFrame as an HTML table.
<code>to_json([path_or_buf, orient, date_format, ...])</code>	Convert the object to a JSON string.
<code>to_latex([buf, columns, col_space, header, ...])</code>	Render an object to a LaTeX tabular environment table.
<code>to_msgpack([path_or_buf, encoding])</code>	Serialize object to input file path using msgpack format.
<code>to_numpy([dtype, copy])</code>	Convert the DataFrame to a NumPy array.
<code>to_panel()</code>	(DEPRECATED) Transform long (stacked) format (DataFrame) into wide (3D, Panel) format.
<code>to_parquet(fname[, engine, compression, ...])</code>	Write a DataFrame to the binary parquet format.
<code>to_period([freq, axis, copy])</code>	Convert DataFrame from DatetimeIndex to PeriodIndex with desired frequency (inferred from index if not passed).
<code>to_pickle(path[, compression, protocol])</code>	Pickle (serialize) object to file.
<code>to_records([index, convert_datetime64, ...])</code>	Convert DataFrame to a NumPy record array.



<code>to_sparse([fill_value, kind])</code>	Convert to SparseDataFrame.
<code>to_sql(name, con[, schema, if_exists, ...])</code>	Write records stored in a DataFrame to a SQL database.
<code>to_stata(fname[, convert_dates, ...])</code>	Export DataFrame object to Stata dta format.
<code>to_string([buf, columns, col_space, header, ...])</code>	Render a DataFrame to a console-friendly tabular output.
<code>to_timestamp([freq, how, axis, copy])</code>	Cast to DatetimeIndex of timestamps, at <i>beginning</i> of period.
<code>to_xarray()</code>	Return an xarray object from the pandas object.
<code>transform(func[, axis])</code>	Call <code>func</code> on self producing a DataFrame with transformed values and that has the same axis length as self.
<code>transpose(*args, **kwargs)</code>	Transpose index and columns.
<code>truediv(other[, axis, level, fill_value])</code>	Floating division of dataframe and other, element-wise (binary operator <i>truediv</i> ).
<code>truncate([before, after, axis, copy])</code>	Truncate a Series or DataFrame before and after some index value.
<code>tshift([periods, freq, axis])</code>	Shift the time index, using the index's frequency if available.
<code>tz_convert(tz[, axis, level, copy])</code>	Convert tz-aware axis to target time zone.
<code>tz_localize(tz[, axis, level, copy, ...])</code>	Localize tz-naive index of a Series or DataFrame to target time zone.
<code>unstack([level, fill_value])</code>	Pivot a level of the (necessarily hierarchical) index labels, returning a DataFrame having a new level of column labels whose inner-most level consists of the pivoted index labels.
<code>update(other[, join, overwrite, ...])</code>	Modify in place using non-NA values from another DataFrame.
<code>var([axis, skipna, level, ddof, numeric_only])</code>	Return unbiased variance over requested axis.
<code>where(cond[, other, inplace, axis, level, ...])</code>	Replace values where the condition is False.
<code>xs(key[, axis, level, drop_level])</code>	Return cross-section from the Series/DataFrame.