

Branch: master ▾

Find file

Copy path

## lendingclub-default-predictor / lc-app.py



orangganjil Adjust when pickled objects load

d5c47b7 on Aug 14, 2016

1 contributor

Raw Blame History



84 lines (74 sloc) 3.53 KB

Jump to definition is available! Beta

Navigate your code with ease. In select public repositories, you can now click on function and method calls to jump to their definitions in the same repository. [Learn more](#)

● Jump to definition is still being calculated for this commit. Check back in a bit. Beta[Learn more](#) or [give us feedback](#)

```
1  #!flask/bin/python
2
3  from __future__ import division
4  from flask import Flask, request
5  from flask_restful import Api, Resource, reqparse
6  import pandas as pd
7  import numpy as np
8  from sklearn.ensemble import RandomForestClassifier
9  from sklearn.preprocessing import LabelEncoder
10 from sklearn.externals import joblib
11
12 app = Flask(__name__)
13 api = Api(app)
14
15 parser = reqparse.RequestParser()
16
17 # Load the pickled label encoder and Random Forest Classifier
18 le = joblib.load("./lc-label-encoder.pkl")
19 rfc = joblib.load("./lc-rfc-model.pkl")
20
21 class Proba(Resource):
22     def post(self):
23         json_data = request.get_json()
24         df = pd.DataFrame(json_data)
25         # Create new DataFrame from nested JSON
26         df2 = pd.concat([pd.DataFrame.from_dict(item, orient='index').T for item in df['loans']])
27         # Rename some of the columns to match what model expects
28         # (LendingClub used different naming conventions for historical data and new data in JSON format)
29         df2.rename(columns={'intRate': 'int_rate', 'annualInc': 'annual_inc', 'accNowDelinq': 'acc_now_delinq'},
30                  inplace=True)
31         # Adjust data types for columns we will use
32         df2['memberId'] = df2['memberId'].astype(str)
33         df2['int_rate'] = df2['int_rate'].astype(int)
34         df2['annual_inc'] = df2['annual_inc'].astype(int)
35         df2['acc_now_delinq'] = df2['acc_now_delinq'].astype(int)
36         df2['term'] = df2['term'].astype(int)
37         df2['last_fico_range_high'] = df2['last_fico_range_high'].astype(int)
38         df2['last_fico_range_low'] = df2['last_fico_range_low'].astype(int)
39         df2['tot_cur_bal'] = df2['tot_cur_bal'].astype(int)
40         df2['tot_hi_cred_lim'] = df2['tot_hi_cred_lim'].astype(int)
41         # Clean up NaNs and other empty fields (shouldn't be any, but just in case)
42         df2['num_tl_30dpd'].fillna(0, inplace=True)
```

```
42 df2['int_rate'].fillna(df2['int_rate'].mean(), inplace=True)
43 df2['percent_bc_gt_75'].fillna(0, inplace=True)
44 df2['dti'].fillna(df2['dti'].mean(), inplace=True)
45 # Encode the "term" and "grade" features
46 var_mod = ['term', 'grade']
47 for i in var_mod:
48     df2[i] = le.fit_transform(df2[i])
49 # List the features to be used in the prediction
50 predict_cols = ['int_rate', 'annual_inc', 'dti', 'acc_now_delinq', 'term', 'grade', 'last_fico_range_high', 'la
51 # Create X (predictors)
52 X = df2[predict_cols]
53 # Make predictions
54 y_preds = rfc.predict_proba(X)
55 # Retrieve probabilities of default from nested arrays returned by predictor
56 proba_defaults = []
57 temp_probas = []
58 for i in y_preds:
59     temp_probas.append(i[1])
60 for x in temp_probas:
61     proba_defaults.append(x)
62 # Create new column for probability of default and round to two decimal places
63 df2['defaultProb'] = proba_defaults
64 df2['defaultProb'] = df2['defaultProb'].round(decimals=2)
65 # Create new series consisting of memberId and probability of default columns and return it
66 temp_series = df2[['memberId', 'defaultProb']]
67 json_out = temp_series.to_json(orient='records')
68 return json_out
69
70 class Version(Resource):
71     def get(self):
72         return {'version': '1.0'}
73
74 class ReadMe(Resource):
75     def get(self):
76         return "Submit a list of LendingClub loans in JSON format. A machine learning model will return the membe
77
78
79 api.add_resource(Proba, '/predict')
80 api.add_resource(Version, '/version')
81 api.add_resource(ReadMe, '/')
82
83 if __name__ == '__main__':
84     app.run(debug=False)
```