
Sawtooth sequences**X76165_en**

A sequence of integers x_1, \dots, x_n is said to be a *sawtooth sequence* if and only if it alternates between ups and downs, more formally, if and only if for all i in $\{2, \dots, n-1\}$, either x_i is larger than its predecessor and its successor, or x_i is smaller than its predecessor and its successor. In symbols, it is a sawtooth sequence if and only if for all i in $\{2, \dots, n-1\}$, either $x_i > x_{i-1}$ and $x_i > x_{i+1}$, or $x_i < x_{i-1}$ and $x_i < x_{i+1}$. By convention, a sequence of length ≤ 2 is a sawtooth sequence.

Write a program that reads a sequence of integers from the standard input channel (cin) and tells whether the sequence is a sawtooth sequence or not. To this end, your program must define and use a Boolean function

```
bool is_sawtooth();
```

which reads elements from cin and returns true if and only if they form a sawtooth sequence.

Note: A function reading as few elements from the input as possible will be scored better, as it has less execution time.

Note: Recall that at this point of the course using vectors or any other method to store massive data is not allowed.

Exam score: 2.5 **Automatic part:** 40%

Input

A sequence of $n \geq 0$ integers.

Output

The program outputs "yes" if the given sequence is a sawtooth sequence, and "no" otherwise.

Sample input 1

2 4 3 7 2 5 3

Sample output 1

yes

Sample input 2

2 4 5

Sample output 2

no

Sample input 3**Sample output 3**

yes

Sample input 4

-1

Sample output 4

yes

Sample input 5

2 6 1 3 2 10 4 7 8

Sample output 5

no

Sample input 6

1 2

Sample output 6

yes

Problem information

Author : PRO1

Generation : 2015-11-02 12:57:57

© *Jutge.org*, 2006–2015.

<http://www.jutge.org>