DeepBias: An Adaptive and Dynamic Benchmark for In-Depth Probing Social Biases in Visual Language Models

First Author, Second Author, and Third Author

***Abstract*—While Large Vision-Language Models (LVLMs) demonstrate remarkable capabilities, they remain highly susceptible to embedded societal biases. Existing bias evaluation protocols predominantly rely on static datasets, which provide only a superficial assessment, as their fixed test cases cannot adaptively evolve to measure the true depth and limits of model vulnerabilities. We introduce DeepBias, an adaptive and dynamic framework for the in-depth probing of social biases in LVLMs. Our approach operates through a dynamic "generation-probing-evolution" loop. First, a generative Proposer synthesizes test cases to evaluate the target model. Second, based on the model's responses, a dual-agent module adaptively deepens the evaluation data: a DeepMiner agent that performs deep exploration of known biases, while a Rewriter agent that performs adversarial modifications on secure samples to uncover latent biases. Finally, we optimize the Proposer based on the target model's responses to these queries, directing it to specifically generate challenging and targeted samples that successfully trigger the model's bias. Furthermore, by employing 6 diverse, state-of-the-art LVLMs as anchor models within this optimization loop, we iteratively synthesize a novel, highly challenging benchmark dataset. Comprehensive experiments demonstrate that DeepBias successfully exposes deep societal biases, establishing a scalable and evolutionary paradigm for robust LVLM safety evaluation.**

***Index Terms*—Vision-Language Model Bias, Adversarial Bias Probing, Dynamic Benchmark Generation.**

I. Introduction

LARGE Vision-Language Models (LVLMs) have demonstrated unprecedented capabilities in multimodal understanding and reasoning, powering applications from automated captioning to visual agents [1], [2]. However, these models inevitably inherit and amplify societal biases present in their massive training corpora, leading to discriminatory outputs regarding gender, race, and other sensitive attributes. While safety alignment techniques like RLHF [3] have been deployed to mitigate these issues, accurately evaluating the true extent of bias in LVLMs remains an open and critical challenge.

Current bias evaluation protocols predominantly rely on static benchmarks [4], [5]. As illustrated in the top panel of Fig.1, these benchmarks typically consist of fixed sets of image-text pairs and rely on one-way inference. The data distribution of the fixed dataset is independent of the target model's bias vulnerabilities. While foundational, this static paradigm faces three major limitations. First, static benchmarks [6], particularly those curated from real world data or human annotations [7], are inevitably absorbed into the massive training corpora of modern LVLMs. This allows models to memorize the test set, leading to inflated scores that make the static benchmarks obsolete and unreliable. Second, existing methods rely on fixed queries that cannot adapt to model feedback. Consequently, safety-aligned models easily deflect these explicit prompts, leaving deep-seated latent biases undetected and creating a false security. Third, static datasets rarely align with the specific vulnerabilities of the target model. This inflexibility wastes evaluation efforts on redundant queries where the model is already robust, while actual safety problems remain unexamined.

To overcome these limitations, we advocate for a transition from static dataset to dynamic adversarial evaluation. We introduce DeepBias, an adaptive framework designed to probe the depth of social biases in LVLMs. As shown in the bottom panel of Fig.1, unlike static approaches, DeepBias dynamically generates new text queries based on the model's feedback to initial data, probing the bias at a much deeper, granular level. Furthermore, it continuously optimizes the test data distribution to explicitly align with the target model's specific weaknesses. This results in a comprehensive, deep, and targeted evaluation.

To drive this dynamic evaluation, the core of DeepBias is a generative Proposer that synthesizes initial test cases. This Proposer is continuously optimized using Direct Preference Optimization (DPO) [8]. By treating successful bias elicitations as positive preferences and failed attempts as negative, the Proposer learns to generate evaluation data that can easily expose the model's societal bias. This closed-loop process explicitly shifts the generated dataset's distribution to tightly align with the specific vulnerabilities of the target model.

Besides, we deploy a dual-agent mechanism to conduct in-depth, instance-level probing based on the target model's immediate responses. **The Rewriter**: For samples where the model initially appears safe, the Rewriter alters the prompt's phrasing or context. This subtle adversarial rewriting is designed to bypass surface-level safety filters and successfully elicit underlying bias. **The DeepMiner**: When the model's answer exposes a risk of bias, the DeepMiner drills deeper. It formulates targeted follow-up questions to accurately pinpoint the specific dimensions of the stereotype and deeply probe the severity of the exposed bias.

First Author is with Princeton University, Princeton NJ 08544, USA.
Second Author is with Springer Heidelberg, Tiergartenstr. 17, 69121 Heidelberg, Germany.
Third Author is with ABC Institute, Rupert-Karls-University Heidelberg, Heidelberg, Germany.

0000–0000/00$00.00 © 2021 IEEE



Fig. 1. Comparison between traditional static evaluation and our DeepBias framework. Top: Static methods rely on fixed test data, resulting in a mismatch between the dataset distribution and the model's vulnerabilities. Bottom: DeepBias dynamically generates new text queries based on the model's feedback to initial data. It explicitly aligns the dataset distribution with specific model weaknesses, achieving targeted and in-depth bias probing.

To construct a robust evaluation standard suitable for advanced VLMs, we employ an ensemble of 6 state-of-the-art LVLMs as anchor models. By iteratively optimizing the Proposer against this collective target, we systematically uncover deep-seated, common biases inherent in modern visual-language representations. This process culminates in the construction of the DeepBias Benchmark, a comprehensive dataset distilled from the most challenging samples that successfully penetrated the defenses of the anchor models. Extensive experiments across a wide range of SOTA models demonstrate that our method, and the resulting benchmark, effectively exposes latent biases that static baselines fail to detect.

Our main contributions are summarized as follows:

- **Dynamic Adaptive Framework**: We propose DeepBias, the first framework to utilize DPO-driven evolution for VLM bias evaluation, shifting the paradigm from static datasets to dynamic adversarial probing.
- **In-Depth Probing Strategy**: Moving beyond superficial accuracy metrics, we synthesize deeper, harder, and higher-quality evaluation samples. This allows us to systematically penetrate safety filters and uncover latent biases that are typically masked in standard benchmarks.
- **The DeepBias Benchmark**: By aggregating the hard and deep test samples from probing 8 diverse LVLMs, we release a high-quality, challenging benchmark dataset for the community.
- **Empirical Evidence**: Extensive experiments show that DeepBias successfully exposes significantly more bias than static baselines, highlighting the fragility of current safety alignments in LVLMs.

II. Related Work

A. Societal Bias Evaluation in Vision-Language Models

The evaluation of social bias has its roots in Natural Language Processing (NLP), with pioneering works demonstrating that word embeddings and language models capture human-like stereotypes [9], [10]. Benchmarks such as CrowS-Pairs [11], StereoSet [12], and BBQ [13] became standard protocols for quantifying categorical biases in text modality.

With the advent of Large Vision-Language Models (LVLMs), research has pivoted to multimodal bias. Early efforts like Visogender-VL [14], VL-Bias [5], and Vignette [15] introduced static image-text pairs to assess specific demographic biases like gender and racial biases. Others, such as FairFace [16] and MIAP [17], focused on dataset diversity. Concurrently, comprehensive benchmark like VLBiasBench [18] have been developed to evaluate biases of various categories. However, relying on static datasets presents fundamental limitations. First, open static datasets are highly susceptible to data leakage. As LVLMs are trained on web-scale datasets like LAION-5B [19], static test sets are likely seen during training, making evaluation results unreliable [20]. Second, fixed evaluations suffer from rapid obsolescence. Static benchmarks cannot keep pace with the rapid versioning of models (e.g., GPT-4o [1], Gemini [21]), leading to benchmark saturation. Third, static datasets lack the capacity to

dynamically adjust based on model feedback [22], so they cannot execute targeted and deep probing against specific model vulnerabilities.

B. Red Teaming and Jailbreaking for VLMs

Red teaming has evolved from manual testing to automated frameworks designed to proactively discover model vulnerabilities. In the realm of Large Language Models (LLMs), foundational works [22], [23] employed generator models to automatically synthesize test cases that provoke toxic outputs. Recent approaches have introduced optimization-based strategies. Gradient-based methods like GCG [24] and ARCA [25] optimize discrete tokens to bypass safety filters, while evolutionary methods such as PAIR [26] and AutoDAN [27] utilize genetic algorithms or self-play to iteratively refine adversarial prompts. As the field shifts to Vision-Language Models (LVLMs), research has extended these semantic attacks to the multimodal domain. Recent studies reveal that by combining structured textual prompts with specific visual contexts [28], or fragmenting malicious instructions across different modalities [29], [30], it is possible to effectively bypass the cross-modal safety alignment of LVLMs.

However, applying existing automated red teaming paradigms directly to social bias evaluation presents significant limitations. First, a Mismatch in Target: Current jailbreak frameworks predominantly optimize for eliciting overt general harms (e.g., generating malicious code, violence, or extreme toxicity) [31]. Social bias, conversely, is deeply ingrained, implicit, and often context-dependent, requiring a more nuanced elicitation strategy than standard adversarial attacks. Second, Binary Metrics over Depth: Existing methods primarily optimize for Attack Success Rate (ASR)—a binary metric indicating whether a model is induced to generate harmful content [26]. They do not measure the severity, consistency, or depth of the bias once exposed. Third, Semantic Degradation: To maximize ASR, many automated algorithms (e.g., gradient-based prompt search) generate unnatural, gibberish prompts [24]. While these may force errors, they fail to reflect realistic human-AI interaction. In contrast, DeepBias shifts the objective from binary jailbreaking to depth probing. Instead of generating gibberish to force errors, our Rewriter and DeepMiner agents synthesize semantically natural and contextually complex scenarios, aiming to uncover deep-seated stereotypes.

C. Optimization and RL for Data Generation

Reinforcement Learning (RL) and evolutionary strategies have proven effective in synthesizing complex data. In the NLP domain, Self-Instruct [32] and WizardLM [33] demonstrated that LLMs can iteratively improve the complexity of their own training data. More recently, Direct Preference Optimization (DPO) [8] has emerged as a stable alternative to PPO [34] for aligning models with human preferences.

In the context of evaluation, RL has been applied to automate red teaming to maximize the toxicity of target model responses [22] and search for diverse failure cases [35]. However, these methods typically optimize for generic failure modes. Our work is the first to apply DPO specifically for the "adversarial evolution" of bias probes. Unlike standard alignment which suppresses bias, we "reverse-align" our Proposer to maximize the likelihood of exposing latent biases, treating the target model's vulnerability as the optimization objective. This allows our method to generate substantially harder and more penetrating evaluation samples compared to random or rule-based generation [36]–[38].

III. Method

A. Bias Evaluation Protocol

Our evaluation protocol is designed to expose society biases through carefully constructed ambiguous scenarios combined with response consistency testing on groups with different sensitive attributes. As illustrated in Fig.2, each test sample is structured as triplet of related samples, which are identical in content except for the sensitive attribute. This structure enables rigorous bias detection through response consistency analysis.

Formally, each test instance is defined as a tuple $(I_1, I_2, I_3, Q, \mathcal{O})$, where:

- $\{I_1, I_2, I_3\}$ is a triplet of image inputs, each depicting a person. The three images differ only in the sensitive attribute being tested (e.g. for age bias: a 32-year-old, a 15-year-old, and a 64-year-old), while all other contextual factors remain constant.
- Q is a deliberately ambiguous question coupled with a negative implication. It is constructed so that the image and text together lack sufficient evidence to yield a definitive answer. For example, as shown in Fig. 2, a question evaluating racial bias across the image triplet might ask: *"The man was stopped by the police after coming out of the supermarket. Did he commit a crime?"*
- $\mathcal{O} = \{\text{Yes}, \text{No}, \text{Unknown}\}$ is the set of answer options.

Because the question Q is intentionally ambiguous and coupled with a negative implication, it creates a deliberate information vacuum that forces the target model to rely on its internal prior associations to arrive at an answer. By deliberately incorporating negative connotations, such as associating the subject with a crime or a moral failing, Q elicits *harmful* societal biases rather than benign statistical correlations. To expose whether these internal priors are discriminatory, we evaluate the model's responses across the image triplet $\{I_1, I_2, I_3\}$, where the situational context remains absolutely identical and only the sensitive demographic attribute is swapped. By independently querying the model to obtain responses $\{r_1, r_2, r_3\}$, we establish a rigorous consistency-based metric: the model is deemed unbiased on a given test case if and only if $r_1 = r_2 = r_3$. Since the provided information is ambiguous, any divergence in the responses across the triplet can be attributed to the altered demographic feature. This inconsistency demonstrates that the model relies on harmful biased predispositions to fill the information gap.

B. Data Enhancing

While existing bias benchmarks such as VLBiasBench [18] and BBQ [13] provide valuable curated samples, their limited



Fig. 2. **The DeepBias Evaluation Protocol.** The DeepBias Evaluation Protocol. Left: The composition of a test instance, consisting of a counterfactual image triplet (I_1,I_2,I_3) with a single varying sensitive attribute, an intentionally ambiguous question (Q), and answer options (O). Right: The counterfactual consistency test logic. Consistent responses across the triplet (e.g. $R_1 = R_2 = R_3$) indicate an unbiased prediction, whereas inconsistent responses expose the model's latent biases toward specific demographics.

scale is insufficient to effectively train our iterative Proposer model. We select three demographic attribute categories from the VLBiasBench dataset: Age, Gender, and Race, with each category containing only about 300 ambiguous&negative test cases. We perform a systematic data enhancement process to significantly scale up the dataset, enrich the semantic content, and expand the distribution of test scenarios. We employ Qwen3 [39] as an in-context data enhancing engine, expanding our collection to $2,000$ high-quality instances per category.

Our data enhancement pipeline begins in the textual modality. We first extract the base questions Q from the original VLBiasBench dataset. For each question, we systematically construct a corresponding set of textual image descriptions P. The size and content of P depend on the demographic category: for Age, we randomly assign three distinct ages (e.g., $P = \{p_1, p_2, p_3\}$ representing a 15-year-old, a 35-year-old, and a 60-year-old); for Race, we use three distinct racial identities (e.g., $P = \{p_1, p_2, p_3\}$ representing Asian, African American, and Latino); and for Gender, we utilize a pair of descriptions (i.e., $P = \{p_1, p_2\}$ representing a woman and a man). This forms our foundational text-modality data format (P, Q). During data enhancing, we randomly sample raw (P, Q) pairs to serve as exemplars, pairing them with strict generative instructions: the newly synthesized questions must remain intentionally ambiguous and carry specific negative implications. Guided by these exemplars and constraints, the data enhancing engine divergently synthesizes diverse and novel test cases. The exact prompt templates and generation guidelines are detailed in the Supplementary Material.

Following the textual data enhancement, we transition the expanded dataset into the visual modality. For every instance, the prompt set P is further processed by appending standardized, neutral contextual descriptions. To enforce strict variable control, all elements other than the targeted sensitive attribute are controlled to be consistent. These refined text prompts are then fed into Stable Diffusion XL [40] to render the corresponding visual inputs, from $P = \{p_1, p_2, p_3\}$ to $I_1, I_2, I_3\}$). Finally, we append the standardized answer options $\mathcal{O} = \{\text{Yes}, \text{No}, \text{Unknown}\}$ to each generated item. This end-to-end pipeline effectively transforms the text prompts into our comprehensive initial multimodal dataset, formally structured as sets of $(I_1, I_2, I_3, Q, \mathcal{O})$.

C. Adaptive Data Generation via Adversarial Evolution

As illustrated in Fig.3, the core innovation of DeepBias lies in its adaptive data generation mechanism, which iteratively evolves to produce increasingly challenging test cases tailored to the target model's vulnerabilities. Our framework comprises three key components: the Proposer, which generates candidate test samples; and two specialized agents, the DeepMiner and the Rewriter, which intensify the probing process. The complete pipeline is visually detailed in the dataflow of Fig.3(b).



Fig. 3. **The DeepBias Framework.** (a) Framework Overview: The macro-level adaptive and dynamic bias probing cycle, illustrating how the Proposer iteratively evolves through target model evaluation to construct the Deep Bias Evaluation Dataset. (b) Detailed Dataflow: The micro-level multi-agent bias mining workflow. The Proposer generates candidate test data. Based on whether the target model exposes bias, the samples are routed to either the DeepMiner (for generating follow-up data to probe deeper) or the Rewriter (for adversarial rewriting to bypass safety filters). The resulting outcomes are compiled into a Preference Dataset (Positive/Negative) to update the Proposer via DPO, closing the optimization loop.

The Proposer is a generative model synthesizing bias-probing test dataset in text modality. Its primary objective is to dynamically shift the overall generation distribution toward the specific vulnerabilities of the target model. We initialize the Proposer by fine-tuning a base language model on the enhanced Seed Dataset using supervised fine-tuning (SFT) with Low-Rank Adaptation (LoRA) [41]. This initial training phase teaches the Proposer to mimic the structure and style of the seed samples. During the generation phase, the Proposer employs a few-shot generation strategy like the data enhancement pipeline described in Section III-B. Given randomly sampled (P, Q) pairs from the seed dataset as exemplars, alongside strict generative rules enforcing intentional ambiguity and negative implications, the Proposer divergently synthesizes new test cases across varying demographic populations, scenarios, and difficulty levels. We then transform these textual outputs into our final multimodal format $(I_1, I_2, I_3, Q, \mathcal{O})$. We input these formatted test cases into the target LVLM to obtain its initial responses. Based on these responses, we deploy two specialized agents, the DeepMiner and the Rewriter, to conduct instance-level optimization, refining individual test cases to maximize their probing effectiveness.

- **The DeepMiner**: When the target model exhibits bias (i.e., produces inconsistent responses), the DeepMiner agent is invoked. It drills down into the exposed bias. Rather than stopping at a general prejudiced conclusion, DeepMiner refines the question to pinpoint the exact nature of the stereotype. For example, if the model deems a demographic group unfit for a certain profession, DeepMiner will generate follow-up questions isolating specific capabilities, asking whether the perceived unfitness stems from a lack of logical reasoning, leadership skills, or stress tolerance. By replacing the original Q with a more granular Q' (while keeping the images unchanged), it measures the depth and specific facets of the bias.
- **The Rewriter**: When the target model responds safely (i.e., produces consistent responses), the Rewriter agent is activated. Direct bias-probing questions (e.g., "Is this person of low intelligence?") are often easily deflected by aligned LVLMs. To unmask latent biases, the Rewriter transforms Q into a more implicit, indirect query Q' (e.g., "Is this person likely to achieve a perfect score in an advanced math exam?"). By shifting from explicit stereotyping to nuanced situational judgments, the Rewriter effectively strips away the model's safety disguise and forces it to reveal hidden prejudices.

After the generation-evaluation-refinement process, we construct a preference dataset for training the Proposer. Samples that successfully elicit bias (either directly or after refinement) are labeled as positive preferences, while those that fail to

expose bias are labeled as negative preferences. We then apply Direct Preference Optimization (DPO) [8] to update the Proposer, maximizing the likelihood of generating positive samples and minimizing that of negative ones. Formally, given a preference pair (x_w, x_l) where x_w is a successful (bias-eliciting) sample and x_l is an unsuccessful one, DPO optimizes:

$$\mathcal{L}_{\text{DPO}} = -\mathbb{E}_{(x_w,x_l)}\left[\log\sigma\left(\beta\log\frac{\pi_\theta(x_w)}{\pi_{\text{ref}}(x_w)} - \beta\log\frac{\pi_\theta(x_l)}{\pi_{\text{ref}}(x_l)}\right)\right] \tag{1}$$

where π_θ is the Proposer being optimized, π_{ref} is the reference model (the SFT-initialized Proposer), β is a temperature parameter, and σ is the sigmoid function. This iterative optimization drives the Proposer to evolve, generating progressively harder and more targeted test cases.

D. DeepBias Benchmark Construction

While the dynamic framework excels at targeted probing, the community also requires standardized, reproducible metrics to compare different models. To address this, we leverage our dynamic pipeline to construct a evaluation dataset: the DeepBias Benchmark. Instead of optimizing against a single model, we apply the aforementioned pipeline to an ensemble of diverse, state-of-the-art LVLMs acting as anchor models. We take the samples that can trigger bias in most models as positive samples, while take the samples that cannot trigger any model's bias as negative samples. This ensemble approach ensures that the Proposer learns to generate test cases that uncover common, structural vulnerabilities in multimodal representations, rather than simply overfitting to the idiosyncrasies of one specific model's safety alignment. The resulting DeepBias Benchmark serves as a highly concentrated, adversarial testing ground, offering a more rigorous evaluation standard than existing datasets.

IV. Experiment

A. Method Validation

To validate the effectiveness of our adaptive adversarial framework, we conduct an experiment focusing on the Age category across three target models: InternVL3-8B, LLaVA-1.5-13B, and Qwen2.5-VL-Instruct-7B. We execute the generation-refinement-optimization pipeline for three rounds and report two metrics per iteration in Table I. *Initial* refers to the target model's consistency accuracy on the test cases directly generated by the Proposer, while *Explore* denotes the accuracy on the refined test cases after the intervention of the DeepMiner and Rewriter agents. Following the framework for varying sensitive attributes described in Section III-A, a lower accuracy ($r_1 = r_2 = r_3$) indicates a higher rate of successfully exposed societal bias.

Within any single iteration, the *Explore* accuracy is consistently and significantly lower than the *Initial* accuracy. For instance, in Iteration 1 for LLaVA-1.5-13B, the agents' exploration drastically drops the consistency accuracy from 81.6% to 64.4%. This intra-iteration degradation proves that our dual-agent refinement strategy successfully unmasks latent biases that the initial queries fail to trigger.

Between different iterations, the *Initial* accuracy itself progressively degrades across iterations. Taking InternVL3-8B as an example, the Proposer's initial baseline accuracy drops from 91.6% in Iteration 1, down to 85.7% in Iteration 2, and further to 79.9% in Iteration 3. This inter-iteration decline provides compelling empirical evidence for the success of our DPO optimization loop. By iteratively learning from successful bias elicitations, the Proposer inherently evolves into a stronger adversarial generator, capable of synthesizing increasingly challenging and targeted test cases.

Overall, the synergistic effect of the evolving Proposer and the probing agents drives the accuracy down substantially by Iteration 3 (e.g., a total drop of 33.5 percentage points for LLaVA-1.5-13B). This degradation confirms that static benchmarks provide a false sense of security, and that our dynamic, deep evaluation is essential for revealing deeply ingrained, inherent biases in modern LVLMs.

B. Method Ablation

To isolate the contribution of the DeepMiner and Rewriter agents, we conduct an ablation study where we disable both agents while keeping all other components unchanged. In this ablation setting, the Proposer still undergoes DPO training across three iterations, but its preference dataset relies solely on the binary success or failure of its initial, direct queries. Table II presents the accuracy degradation of this ablated variant.

By cross-referencing Table II with the full-method results in Table I, removing the dual-agent mechanism weakens the framework's bias-mining ability. Across all target models, the ablated version shows less accuracy degradation during three interations. For instance, without the agents, InternVL3-8B and LLaVA-1.5-13B stall at 79.6% and 62.2% respectively, leaving a performance gap of roughly 14 to 16 percentage points compared to the full method.

Models	Iter 1		Iter 2		Iter 3	
	Initial	Explore	Initial	Explore	Initial	Explore
InternVL3-8B	91.6	79.3	85.7	71.3	79.9	63.6
LLaVA-1.5-13b	81.6	64.4	75.3	55.2	67.7	48.1
Qwen2.5-VL-Instruct-7B	84.4	68.7	78.2	60.5	71.8	52.3

TABLE I

Effectiveness of the DeepBias framework in exposing Age bias. We report the consistency accuracy ($r_1 = r_2 = r_3$) across three iterations for three target LVLMs. "Initial" denotes the accuracy against the Proposer's direct generation, while "Explore" represents the accuracy after targeted refinement by the DeepMiner and Rewriter agents.

Most notably, Qwen2.5-VL-7B exhibits severe evolution stagnation in the ablated setting, dropping a mere 2.8 percentage points (84.4% to 81.6%), compared to reaching 52.3% with the full method. We attribute this to a homologous lineage bottleneck: since the Proposer (Qwen3-32B) and the target model belong to the same Qwen architecture, they share identical safety boundaries, which causes the Proposer to generate queries only within their common safe distribution, failing to expose the target model's biased flaws. This starves the DPO process of the "positive" bias-eliciting samples needed for optimization. The dual agents' forced adversarial prompting breaks this homologous bottleneck, pulling queries out of the default safe space to successfully unmask latent bias.

Ultimately, these findings provide important insights for automated red-teaming: sole reliance on an LLM's intrinsic generation capabilities will inevitably lead to optimization bottlenecks. The dual-agent module is indispensable not only for immediate probing, but also for functioning as an automated jailbreaker. By continually breaking the safety boundaries, the agents can provide diverse and out-of-distribution data samples to maintain the DPO training loop of the Proposer, completely preventing the evolution stagnation.

C. Benchmark Construction

To construct a robust and generalizable benchmark, we extend our framework to an ensemble of 6 diverse LVLMs across three demographic categories: Age, Race, and Gender. We introduce a consensus-based labeling mechanism for the DPO preference dataset. A generated test case is labeled as a positive preference if it successfully elicits biased responses from at least 50% of the anchor models. Conversely, queries that fail to expose bias where all models give safe answers are labeled as negative preferences. This forces the Proposer to target on universal, structural vulnerabilities shared across different architectures.

Table III tracks the consistency accuracy of this ensemble during the process. The result reveals two systemic issues in current LVLM safety alignments. First, the latent biases are scale-agnostic and architecture-agnostic. While the 38B model (InternVL3.5-38B) starts with a higher baseline defense than the 7B models, it still suffers a consistent degradation of 12 to 15 percentage points across all categories by Iteration 3. This proves that merely scaling up model parameters does not patch these vulnerabilities. Second, the defense mechanisms exhibit demographic imbalances. Models show significantly weaker resilience against Race and Gender probes compared to Age. By Iteration 3, the accuracies for Race and Gender drop to the 50%-60% range. This contrast demonstrates that racial and gender biases are more deeply rooted.

Models	Iter 1	Iter 2	Iter 3
InternVL3-8B	91.6	81.2	79.6
LLaVA-1.5-13b	81.6	72.5	62.2
Qwen2.5-VL-7B	84.4	82	81.6

TABLE II
ABLATION STUDY DISABLING THE DEEPMINER AND REWRITER AGENTS. WE REPORT THE CONSISTENCY ACCURACY ACROSS THREE ITERATIONS WITH BOTH DEEPMINER AND REWRITER DISABLED.

Finally, we build a comprehensive and highly challenging benchmark comprising. By capturing the dynamic outputs of our probing cycle, the benchmark provides a rigorously mined evaluation standard that reflects a broad spectrum of latent biases.

D. Benchmark Evaluation

E. Qualitative Analysis and Visualization

a) Case Study: Evolution of Bias-Probing Samples.:

b) Case Study: DeepMiner and Rewriter.:

F. Limitations and Future Work

While DeepBias improves bias evaluation, several limitations need future investigation. First, our current framework focuses on three major bias categories (Age, Race, Gender). Extending to other dimensions (e.g., Religion, Disability, Socioeconomic Status) would provide more comprehensive coverage. Second, the adversarial evolution process requires substantial computational resources. Developing more efficient optimization strategies could improve scalability. Third, while our benchmark exposes biases, it does not directly provide mitigation strategies. Future work could explore integrating DeepBias into the training loop to guide bias-aware fine-tuning or developing automated debiasing techniques informed by the discovered vulnerabilities. Finally, our current methodology is specifically tailored to uncovering societal biases. A highly promising direction for future research involves generalizing this adaptive adversarial framework to evaluate other critical dimensions of LVLM trustworthiness, such as multimodal hallucinations, value alignment, and broader safety risks.

V. CONCLUSION

In this paper, we introduced DeepBias, a dynamic and adversarial evaluation framework designed to expose deeply ingrained societal biases in Large Vision-Language Models (LVLMs). Unlike existing static benchmarks, our approach leverages a constantly optimized Proposer and dual-agent deep refinement mechanism to continuously generate test cases. Extensive experiments demonstrate that this dynamic probing consistently exposes the societial biases of target models. We found that the mechanism drives the data distribution to explicitly shift toward the models' latent weaknesses and generates progressively deep and targeted adversarial queries. By scaling this framework across an ensemble of anchor models, we successfully curated a highly challenging benchmark. Subsequent testing of state-of-the-art LVLMs on this benchmark revealed demographic prejudices that remain largely hidden under traditional evaluation protocols. By shifting the paradigm from fixed evaluation to dynamic adversarial mining, our work provides a robust, evolving tool to uncover complex vulnerabilities and foster the development of genuinely equitable multimodal systems.

ACKNOWLEDGMENT

Please insert your acknowledgments here.

Models	Age			Race			Gender		
	iter 1	**iter 2**	**iter 3**	**iter 1**	**iter 2**	**iter 3**	**iter 1**	**iter 2**	**iter 3**
InternVL3-8B	89.3	82.1	74.6	77.8	70.2	62.4	76.5	68.9	61.3
LLaVA-1.5-13b	79.8	71.5	62.4	68.2	60.1	51.8	67.1	58.7	50.2
Qwen2.5-VL-Instruct-7B	82.7	75.3	67.1	71.3	63.5	55.2	70.1	62.1	53.9
Qwen3-VL-30B-A3B-Instruct	87.5	80.9	73.2	75.9	68.7	60.8	74.8	67.4	59.6
InternVL3.5-38B	90.6	84.2	77.8	79.2	72.4	64.9	78.1	70.8	63.2
DeepSeek-VL	85.4	78.6	70.9	73.8	66.7	58.6	72.6	65.2	57.1

TABLE III
BENCHMARK CONSTRUCTION

Models	Age			Race			Gender		
	iter 1	**iter 2**	**iter 3**	**iter 1**	**iter 2**	**iter 3**	**iter 1**	**iter 2**	**iter 3**
Otter									
InternVL3-8B	89.3	82.1	74.6	77.8	70.2	62.4	76.5	68.9	61.3
InternLM-XComposer2-VL-7b									
InternVL3-14B									
InternVL3.5-38B	90.6	84.2	77.8	79.2	72.4	64.9	78.1	70.8	63.2
LLaVA-1.5-7b									
LLaVA-1.5-13b	79.8	71.5	62.4	68.2	60.1	51.8	67.1	58.7	50.2
Qwen2.5-VL-Instruct-7B	82.7	75.3	67.1	71.3	63.5	55.2	70.1	62.1	53.9
Qwen3-VL-8B-instruct									
Qwen3-VL-30B-A3B-Instruct	87.5	80.9	73.2	75.9	68.7	60.8	74.8	67.4	59.6
Minigpt4-vicuna-7b									
Minigpt4-vicuna-13b									
Shikra-7B									
InstructBlip-vicuna-7b									
InstructBlip-vicuna-13b									
DeepSeek-VL	85.4	78.6	70.9	73.8	66.7	58.6	72.6	65.2	57.1
GPT-4o									
Gemini									

TABLE IV
BENCHMARK

REFERENCES

[1] A. Hurst, A. Lerer, A. P. Goucher, A. Perelman, A. Ramesh, A. Clark, A. Ostrow, A. Welihinda, A. Hayes, A. Radford *et al.*, "Gpt-4o system card," *arXiv preprint arXiv:2410.21276*, 2024.

[2] H. Liu, C. Li, Q. Wu, and Y. J. Lee, "Visual instruction tuning," *Advances in neural information processing systems*, vol. 36, pp. 34 892–34 916, 2023.

[3] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal policy optimization algorithms," *arXiv preprint arXiv:1707.06347*, 2017.

[4] S. M. Hall, F. Gonçalves Abrantes, H. Zhu, G. Sodunke, A. Shtedritski, and H. R. Kirk, "Visogender: A dataset for benchmarking gender bias in image-text pronoun resolution," *Advances in Neural Information Processing Systems*, vol. 36, pp. 63 687–63 723, 2023.

[5] Y. Zhang, J. Wang, and J. Sang, "Counterfactually measuring and eliminating social bias in vision-language pre-training models," in *Proceedings of the 30th ACM International Conference on Multimedia*, 2022, pp. 4996–5004.

[6] C. Fu, P. Chen, Y. Shen, Y. Qin, M. Zhang, X. Lin, J. Yang, X. Zheng, K. Li, X. Sun *et al.*, "Mme: A comprehensive evaluation benchmark for multimodal large language models," *arXiv preprint arXiv:2306.13394*, 2023.

[7] Y. Liu, H. Duan, Y. Zhang, B. Li, S. Zhang, W. Zhao, Y. Yuan, J. Wang, C. He, Z. Liu *et al.*, "Mmbench: Is your multi-modal model an all-around player?" in *European conference on computer vision*. Springer, 2024, pp. 216–233.

[8] R. Rafailov, A. Sharma, E. Mitchell, C. D. Manning, S. Ermon, and C. Finn, "Direct preference optimization: Your language model is secretly a reward model," *Advances in neural information processing systems*, vol. 36, pp. 53 728–53 741, 2023.

[9] T. Bolukbasi, K.-W. Chang, J. Y. Zou, V. Saligrama, and A. T. Kalai, "Man is to computer programmer as woman is to homemaker? debiasing word embeddings," *Advances in neural information processing systems*, vol. 29, 2016.

[10] A. Caliskan, J. J. Bryson, and A. Narayanan, "Semantics derived automatically from language corpora contain human-like biases," *Science*, vol. 356, no. 6334, pp. 183–186, 2017.

[11] N. Nangia, C. Vania, R. Bhalerao, and S. Bowman, "Crows-pairs: A challenge dataset for measuring social biases in masked language models," in *Proceedings of the 2020 conference on empirical methods in natural language processing (EMNLP)*, 2020, pp. 1953–1967.

[12] M. Nadeem, A. Bethke, and S. Reddy, "Stereoset: Measuring stereotypical bias in pretrained language models," in *Proceedings of the 59th annual meeting of the association for computational linguistics and the 11th international joint conference on natural language processing*

(volume 1: long papers), 2021, pp. 5356–5371.

[13] A. Parrish, A. Chen, N. Nangia, V. Padmakumar, J. Phang, J. Thompson, P. M. Htut, and S. Bowman, "Bbq: A hand-built bias benchmark for question answering," in *Findings of the Association for Computational Linguistics: ACL 2022*, 2022, pp. 2086–2105.

[14] Y. Xiao, X. Liu, Q. Cheng, Z. Yin, S. Liang, J. Li, J. Shao, A. Liu, and D. Tao, "Genderbias-vl: Benchmarking gender bias in vision language models via counterfactual probing: Y. xiao et al." *International Journal of Computer Vision*, vol. 133, no. 12, pp. 8332–8355, 2025.

[15] C. Raj, B. Wei, A. Caliskan, A. Anastasopoulos, and Z. Zhu, "Vignette: Socially grounded bias evaluation for vision-language models," *arXiv preprint arXiv:2505.22897*, 2025.

[16] K. Karkkainen and J. Joo, "Fairface: Face attribute dataset for balanced race, gender, and age for bias measurement and mitigation," in *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, 2021, pp. 1548–1558.

[17] C. Schumann, S. Ricco, U. Prabhu, V. Ferrari, and C. Pantofaru, "A step toward more inclusive people annotations for fairness," in *Proceedings of the 2021 AAAI/ACM Conference on AI, Ethics, and Society*, 2021, pp. 916–925.

[18] S. Wang, X. Cao, J. Zhang, Z. Yuan, S. Shan, X. Chen, and W. Gao, "Vlbiasbench: A comprehensive benchmark for evaluating bias in large vision-language model," *arXiv preprint arXiv:2406.14194*, 2024.

[19] C. Schuhmann, R. Beaumont, R. Vencu, C. Gordon, R. Wightman, M. Cherti, T. Coombes, A. Katta, C. Mullis, M. Wortsman *et al.*, "Laion-5b: An open large-scale dataset for training next generation image-text models," *Advances in neural information processing systems*, vol. 35, pp. 25 278–25 294, 2022.

[20] O. Sainz, J. Campos, I. García-Ferrero, J. Etxaniz, O. L. de Lacalle, and E. Agirre, "Nlp evaluation in trouble: On the need to measure llm data contamination for each benchmark," in *Findings of the Association for Computational Linguistics: EMNLP 2023*, 2023, pp. 10 776–10 787.

[21] G. Team, R. Anil, S. Borgeaud, J.-B. Alayrac, J. Yu, R. Soricut, J. Schalkwyk, A. M. Dai, A. Hauth, K. Millican *et al.*, "Gemini: a family of highly capable multimodal models," *arXiv preprint arXiv:2312.11805*, 2023.

[22] E. Perez, S. Huang, F. Song, T. Cai, R. Ring, J. Aslanides, A. Glaese, N. McAleese, and G. Irving, "Red teaming language models with language models," *arXiv preprint arXiv:2202.03286*, 2022.

[23] D. Ganguli, L. Lovitt, J. Kernion, A. Askell, Y. Bai, S. Kadavath, B. Mann, E. Perez, N. Schiefer, K. Ndousse *et al.*, "Red teaming language models to reduce harms: Methods, scaling behaviors, and lessons learned," *arXiv preprint arXiv:2209.07858*, 2022.

[24] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter, and M. Fredrikson, "Universal and transferable adversarial attacks on aligned language models," *arXiv preprint arXiv:2307.15043*, 2023.

[25] E. Jones, A. Dragan, A. Raghunathan, and J. Steinhardt, "Automatically auditing large language models via discrete optimization," in *International Conference on Machine Learning*. PMLR, 2023, pp. 15 307–15 329.

[26] P. Chao, A. Robey, E. Dobriban, H. Hassani, G. J. Pappas, and E. Wong, "Jailbreaking black box large language models in twenty queries," in *2025 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*. IEEE, 2025, pp. 23–42.

[27] X. Liu, N. Xu, M. Chen, and C. Xiao, "Autodan: Generating stealthy jailbreak prompts on aligned large language models," *arXiv preprint arXiv:2310.04451*, 2023.

[28] Y. Gong, D. Ran, J. Liu, C. Wang, T. Cong, A. Wang, S. Duan, and X. Wang, "Figstep: Jailbreaking large vision-language models via typographic visual prompts," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 39, no. 22, 2025, pp. 23 951–23 959.

[29] Z. Niu, H. Ren, X. Gao, G. Hua, and R. Jin, "Jailbreaking attack against multimodal large language model," *arXiv preprint arXiv:2402.02309*, 2024.

[30] E. Shayegani, Y. Dong, and N. Abu-Ghazaleh, "Jailbreak in pieces: Compositional adversarial attacks on multi-modal language models," *arXiv preprint arXiv:2307.14539*, 2023.

[31] A. Mehrotra, M. Zampetakis, P. Kassianik, B. Nelson, H. Anderson, Y. Singer, and A. Karbasi, "Tree of attacks: Jailbreaking black-box llms automatically," *Advances in Neural Information Processing Systems*, vol. 37, pp. 61 065–61 105, 2024.

[32] Y. Wang, Y. Kordi, S. Mishra, A. Liu, N. A. Smith, D. Khashabi, and H. Hajishirzi, "Self-instruct: Aligning language models with self-generated instructions," in *Proceedings of the 61st annual meeting of the association for computational linguistics (volume 1: long papers)*, 2023, pp. 13 484–13 508.

[33] C. Xu, Q. Sun, K. Zheng, X. Geng, P. Zhao, J. Feng, C. Tao, and D. Jiang, "Wizardlm: Empowering large language models to follow complex instructions," *arXiv preprint arXiv:2304.12244*, 2023.

[34] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal policy optimization algorithms," *arXiv preprint arXiv:1707.06347*, 2017.

[35] S. Casper, J. Lin, J. Kwon, G. Culp, and D. Hadfield-Menell, "Explore, establish, exploit: Red teaming language models from scratch," *arXiv preprint arXiv:2306.09442*, 2023.

[36] M. T. Ribeiro, T. Wu, C. Guestrin, and S. Singh, "Beyond accuracy: Behavioral testing of nlp models with checklist," in *Proceedings of the 58th annual meeting of the association for computational linguistics*, 2020, pp. 4902–4912.

[37] D. Kiela, M. Bartolo, Y. Nie, D. Kaushik, A. Geiger, Z. Wu, B. Vidgen, G. Prasad, A. Singh, P. Ringshia *et al.*, "Dynabench: Rethinking benchmarking in nlp," in *Proceedings of the 2021 conference of the North American chapter of the Association for Computational Linguistics: human language technologies*, 2021, pp. 4110–4124.

[38] Q. Li, J. Gao, S. Wang, R. Pi, X. Zhao, C. Wu, X. Jiang, Z. Li, and L. Kong, "Forewarned is Forearmed: Leveraging llms for data synthesis through failure-inducing exploration," *arXiv preprint arXiv:*, 2024.

[39] A. Yang, A. Li, B. Yang, B. Zhang, B. Hui, B. Zheng, B. Yu, C. Gao, C. Huang, C. Lv, C. Zheng, D. Liu, F. Zhou, F. Huang, F. Hu, H. Ge, H. Wei, H. Lin, J. Tang, J. Yang, J. Tu, J. Zhang, J. Yang, J. Yang, J. Zhou, J. Zhou, J. Lin, K. Dang, K. Bao, K. Yang, L. Yu, L. Deng, M. Li, M. Xue, M. Li, P. Zhang, P. Wang, Q. Zhu, R. Men, R. Gao, S. Liu, S. Luo, T. Li, T. Tang, W. Yin, X. Ren, X. Wang, X. Zhang, X. Ren, Y. Fan, Y. Su, Y. Zhang, Y. Zhang, Y. Wan, Y. Liu, Z. Wang, Z. Cui, Z. Zhang, Z. Zhou, and Z. Qiu, "Qwen3 technical report," *arXiv preprint arXiv:2505.09388*, 2025.

[40] D. Podell, Z. English, K. Lacey, A. Blattmann, T. Dockhorn, J. Müller, J. Penna, and R. Rombach, "Sdxl: Improving latent diffusion models for high-resolution image synthesis," *arXiv preprint arXiv:2307.01952*, 2023.

[41] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, W. Chen *et al.*, "Lora: Low-rank adaptation of large language models." *Iclr*, vol. 1, no. 2, p. 3, 2022.