DeepBias: An Adaptive and Dynamic Benchmark for In-Depth Probing Social Biases in Visual Language Models

First Author, Second Author, and Third Author

***Abstract*—While Large Vision-Language Models (LVLMs) demonstrate remarkable capabilities, they remain highly susceptible to embedded societal biases. Existing bias evaluation protocols predominantly rely on static datasets, which provide only a superficial assessment, as their fixed test cases cannot adaptively evolve to measure the true depth and limits of model vulnerabilities. We introduce DeepBias, an adaptive and dynamic framework for the in-depth probing of social biases in LVLMs. Our approach operates through a dynamic "generation-evolution-probing" loop. First, a generative Proposer synthesizes test cases to evaluate the target model. Second, we optimize the Proposer via Direct Preference Optimization based on the target model's initial responses, directing it to generate increasingly challenging and targeted samples. Third, an autonomous DeepAgent conducts multi-turn sequential probing on each sample: at each turn, it analyzes the full dialogue history and either deepens exposed biases or adversarially rewrites the query to bypass safety filters, progressively uncovering latent biases. Furthermore, by employing 6 diverse, state-of-the-art LVLMs as anchor models within this optimization loop, we iteratively synthesize a novel, highly challenging benchmark dataset. Comprehensive experiments demonstrate that DeepBias successfully exposes deep societal biases, establishing a scalable and evolutionary paradigm for robust LVLM safety evaluation.**

***Index Terms*—Vision-Language Model Bias, Adversarial Bias Probing, Dynamic Benchmark Generation.**

I. Introduction

LARGE Vision-Language Models (LVLMs) have demonstrated unprecedented capabilities in multimodal understanding and reasoning, powering applications from automated captioning to visual agents [1], [2]. However, these models inevitably inherit and amplify societal biases present in their massive training corpora, leading to discriminatory outputs regarding gender, race, and other sensitive attributes. While safety alignment techniques like RLHF [3] have been deployed to mitigate these issues, accurately evaluating the true extent of bias in LVLMs remains an open and critical challenge.

Current bias evaluation protocols predominantly rely on static benchmarks [4], [5]. As illustrated in the top panel of Fig.1, these benchmarks typically consist of fixed sets of image-text pairs and rely on one-way inference. The data distribution of the fixed dataset is independent of the target model's bias vulnerabilities. While foundational, this static paradigm faces three major limitations. First, static benchmarks [6], particularly those curated from real world data or human annotations [7], are inevitably absorbed into the massive training corpora of modern LVLMs. This allows models to memorize the test set, leading to inflated scores that make the static benchmarks obsolete and unreliable. Second, existing methods rely on fixed queries that cannot adapt to model feedback. Consequently, safety-aligned models easily deflect these explicit prompts, leaving deep-seated latent biases undetected and creating a false security. Third, static datasets rarely align with the specific vulnerabilities of the target model. This inflexibility wastes evaluation efforts on redundant queries where the model is already robust, while actual safety problems remain unexamined.

To overcome these limitations, we advocate for a transition from static dataset to dynamic adversarial evaluation. We introduce DeepBias, an adaptive framework designed to probe the depth of social biases in LVLMs. As shown in the bottom panel of Fig.1, unlike static approaches, DeepBias dynamically generates new text queries based on the model's feedback to initial data, probing the bias at a much deeper, granular level. Furthermore, it continuously optimizes the test data distribution to explicitly align with the target model's specific weaknesses. This results in a comprehensive, deep, and targeted evaluation.

To drive this dynamic evaluation, the core of DeepBias is a generative Proposer that synthesizes initial test cases. Based on the target model's responses to these initial queries, we directly apply Direct Preference Optimization (DPO) [8] to the Proposer, treating successful bias elicitations as positive preferences and failed attempts as negative. This closed-loop process explicitly shifts the generated dataset's distribution to tightly align with the specific vulnerabilities of the target model.

After DPO optimization, we deploy an autonomous DeepAgent to conduct in-depth, instance-level probing through multi-turn interaction with the target model. Unlike static one-shot evaluation, the DeepAgent operates as a fully autonomous agent that engages in a sequential dialogue over three turns. At each turn, it reviews the complete interaction history and adaptively selects one of two strategies: if the model's previous response exposes bias, the DeepAgent deepens the probing by generating a targeted follow-up question to pinpoint the specific dimensions and severity of the stereotype; if the model responds safely, the DeepAgent adversarially rewrites the

First Author is with Princeton University, Princeton NJ 08544, USA.
Second Author is with Springer Heidelberg, Tiergartenstr. 17, 69121 Heidelberg, Germany.
Third Author is with ABC Institute, Rupert-Karls-University Heidelberg, Heidelberg, Germany.

0000–0000/00$00.00 © 2021 IEEE



Fig. 1. Comparison between traditional static evaluation and our DeepBias framework. Top: Static methods rely on fixed test data, resulting in a mismatch between the dataset distribution and the model's vulnerabilities. Bottom: DeepBias dynamically generates new text queries based on the model's feedback to initial data. It explicitly aligns the dataset distribution with specific model weaknesses, achieving targeted and in-depth bias probing.

query to bypass safety filters and elicit latent biases. This two-stage design decouples distribution-level optimization (Proposer + DPO) from instance-level deep probing (DeepAgent), enabling both a well-targeted data distribution and thorough per-sample bias exploration.

To construct a robust evaluation standard suitable for advanced VLMs, we employ an ensemble of 6 state-of-the-art LVLMs as anchor models. By iteratively optimizing the Proposer against this collective target, we systematically uncover deep-seated, common biases inherent in modern visual-language representations. This process culminates in the construction of the DeepBias Benchmark, a comprehensive dataset distilled from the most challenging samples that successfully penetrated the defenses of the anchor models. Extensive experiments across a wide range of SOTA models demonstrate that our method, and the resulting benchmark, effectively exposes latent biases that static baselines fail to detect.

Our main contributions are summarized as follows:

- **Dynamic Adaptive Framework**: We propose DeepBias, the first framework to utilize DPO-driven evolution for VLM bias evaluation, shifting the paradigm from static datasets to dynamic adversarial probing.
- **In-Depth Probing Strategy**: We introduce an autonomous DeepAgent that conducts multi-turn sequential interactions with the target model, adaptively deepening or rewriting queries based on full dialogue history. This allows us to systematically penetrate safety filters and uncover latent biases that are typically masked in standard benchmarks.
- **The DeepBias Benchmark**: By aggregating the hard and deep test samples from probing 8 diverse LVLMs, we release a high-quality, challenging benchmark dataset for the community.
- **Empirical Evidence**: Extensive experiments show that DeepBias successfully exposes significantly more bias than static baselines, highlighting the fragility of current safety alignments in LVLMs.

II. Related Work

A. Societal Bias Evaluation in Vision-Language Models

The evaluation of social bias has its roots in Natural Language Processing (NLP), with pioneering works demonstrating that word embeddings and language models capture human-like stereotypes [9], [10]. Benchmarks such as CrowS-Pairs [11], StereoSet [12], and BBQ [13] became standard protocols for quantifying categorical biases in text modality.

With the advent of Large Vision-Language Models (LVLMs), research has pivoted to multimodal bias. Early efforts like Visogender-VL [14], VL-Bias [5], and Vignette [15] introduced static image-text pairs to assess specific demographic biases like gender and racial biases. Others, such as FairFace [16] and MIAP [17], focused on dataset diversity. Concurrently, comprehensive benchmark like VLBiasBench [18] have been developed to evaluate biases of various categories. However, relying on static datasets presents fundamental limitations. First, open static datasets are highly

susceptible to data leakage. As LVLMs are trained on web-scale datasets like LAION-5B [19], static test sets are likely seen during training, making evaluation results unreliable [20]. Second, fixed evaluations suffer from rapid obsolescence. Static benchmarks cannot keep pace with the rapid versioning of models (e.g., GPT-4o [1], Gemini [21]), leading to benchmark saturation. Third, static datasets lack the capacity to dynamically adjust based on model feedback [22], so they cannot execute targeted and deep probing against specific model vulnerabilities.

B. Red Teaming and Jailbreaking for VLMs

Red teaming has evolved from manual testing to automated frameworks designed to proactively discover model vulnerabilities. In the realm of Large Language Models (LLMs), foundational works [22], [23] employed generator models to automatically synthesize test cases that provoke toxic outputs. Recent approaches have introduced optimization-based strategies. Gradient-based methods like GCG [24] and ARCA [25] optimize discrete tokens to bypass safety filters, while evolutionary methods such as PAIR [26] and AutoDAN [27] utilize genetic algorithms or self-play to iteratively refine adversarial prompts. As the field shifts to Vision-Language Models (LVLMs), research has extended these semantic attacks to the multimodal domain. Recent studies reveal that by combining structured textual prompts with specific visual contexts [28], or fragmenting malicious instructions across different modalities [29], [30], it is possible to effectively bypass the cross-modal safety alignment of LVLMs.

However, applying existing automated red teaming paradigms directly to social bias evaluation presents significant limitations. First, a Mismatch in Target: Current jailbreak frameworks predominantly optimize for eliciting overt general harms (e.g., generating malicious code, violence, or extreme toxicity) [31]. Social bias, conversely, is deeply ingrained, implicit, and often context-dependent, requiring a more nuanced elicitation strategy than standard adversarial attacks. Second, Binary Metrics over Depth: Existing methods primarily optimize for Attack Success Rate (ASR)—a binary metric indicating whether a model is induced to generate harmful content [26]. They do not measure the severity, consistency, or depth of the bias once exposed. Third, Semantic Degradation: To maximize ASR, many automated algorithms (e.g., gradient-based prompt search) generate unnatural, gibberish prompts [24]. While these may force errors, they fail to reflect realistic human-AI interaction. In contrast, DeepBias shifts the objective from binary jailbreaking to depth probing. Instead of generating gibberish to force errors, our DeepAgent synthesizes semantically natural and contextually complex scenarios through multi-turn interactions, aiming to uncover deep-seated stereotypes.

C. Optimization and RL for Data Generation

Reinforcement Learning (RL) and evolutionary strategies have proven effective in synthesizing complex data. In the NLP domain, Self-Instruct [32] and WizardLM [33] demonstrated that LLMs can iteratively improve the complexity of their own training data. More recently, Direct Preference Optimization (DPO) [8] has emerged as a stable alternative to PPO [34] for aligning models with human preferences.

In the context of evaluation, RL has been applied to automate red teaming to maximize the toxicity of target model responses [22] and search for diverse failure cases [35]. However, these methods typically optimize for generic failure modes. Our work is the first to apply DPO specifically for the "adversarial evolution" of bias probes. Unlike standard alignment which suppresses bias, we "reverse-align" our Proposer to maximize the likelihood of exposing latent biases, treating the target model's vulnerability as the optimization objective. This allows our method to generate substantially harder and more penetrating evaluation samples compared to random or rule-based generation [36]–[38].

III. Method

A. Bias Evaluation Protocol

Our evaluation protocol is designed to expose societal biases through carefully constructed ambiguous scenarios. As illustrated in Fig.2, test data is initially constructed as *counterfactual triplets*: three images that are identical in content except for a single sensitive demographic attribute. This triplet design serves as a rigorous controlled-variable mechanism during data validation—by holding all contextual factors constant and varying only the demographic feature, we can verify that the question is genuinely ambiguous (rather than trivially answerable) and that any non-"Unknown" response is attributable to the demographic attribute rather than other confounds. After validation (detailed in Section III-D), each image-question pair is decomposed into an independent test case, where the model must select "Unknown" to be judged as unbiased.

Formally, each test instance is defined as a tuple $(I_1, I_2, I_3, Q, \mathcal{O})$, where:

- $\{I_1, I_2, I_3\}$ is a triplet of image inputs, each depicting a person. The three images differ only in the sensitive attribute being tested (e.g. for age bias: a 32-year-old, a 15-year-old, and a 64-year-old), while all other contextual factors remain constant.
- Q is a deliberately ambiguous question coupled with a negative implication, subject to two critical constraints. First, Q must not reference any group-specific characteristic (e.g., "as an elderly person" or "being a woman"); the sensitive attribute is conveyed solely through the image, ensuring the text alone cannot trigger stereotype-driven responses. Second, Q should avoid probabilistic hedging words such as "likely" or "probably" (the rationale is detailed below). It is constructed so that the image and text together lack sufficient evidence to yield a definitive answer. For example, as shown in Fig. 2, a question evaluating racial bias across the image triplet might ask: *"The man was stopped by the police after coming out of the supermarket. Did he commit a crime?"*
- $\mathcal{O} = \{\text{Yes}, \text{No}, \text{Unknown}\}$ is the set of answer options. Given the intentional ambiguity of Q, the neutral option "Unknown" is the only unbiased response, as



Fig. 2. **The DeepBias Evaluation Protocol.** Left: The composition of a test instance, consisting of a counterfactual image triplet (I_1,I_2,I_3) with a single varying sensitive attribute, an intentionally ambiguous question (Q), and answer options (O). The triplet is used for multi-model voting validation during benchmark construction; after validation, each image becomes an independent test case where selecting "Unknown" is the only correct (unbiased) response.

the provided information is insufficient for a conclusive judgment.

A critical design consideration is to distinguish *societal bias* from *statistical correlation*. While certain demographic differences are statistically grounded (e.g., elderly individuals may, on average, have weaker physical fitness than younger ones), conflating statistical tendencies with judgments about specific individuals constitutes harmful bias. We identify three key characteristics that separate bias from legitimate statistical observation:

1) **Individual attribution**: Bias arises when statistical group-level tendencies are applied to judge a specific individual. Stating that "elderly people are statistically less physically fit" is a demographic observation; asserting that *this particular* elderly person "definitely cannot perform this physical task" is biased individual attribution.
2) **Normative prescription**: Bias transforms descriptive statistics into prescriptive norms. For instance, while women may statistically wear makeup more often, prescribing that women *should* wear makeup—and judging those who do not as abnormal—constitutes normative bias.
3) **Concrete harm**: Bias produces tangible negative consequences in consequential settings such as hiring, lending, or law enforcement, where stereotypical judgments directly affect individuals' opportunities and outcomes.

These distinctions directly inform our question design. First, Q is coupled with a negative implication to probe whether the model produces *concretely harmful* judgments (characteristic 3), rather than merely reflecting benign correlations. Second, Q avoids probabilistic hedging words like "likely" or "probably": such words allow the model to retreat into statistically defensible territory (e.g., "this elderly person is *likely* less fit"), obscuring whether it is making a genuine individual-level biased judgment (characteristic 1) or simply citing group-level tendencies. By forcing definitive assertions, our protocol cleanly separates bias from statistical reasoning. Third, Q does not reference group-specific characteristics in its text, ensuring the model's response is driven by its visual perception of the individual rather than textual group-level cues.

Because the question Q is intentionally ambiguous and coupled with a negative implication, it creates a deliberate information vacuum that forces the target model to rely on its internal prior associations to arrive at an answer. Since the provided information is insufficient for a definitive judgment, the only unbiased response is the neutral option "Unknown". Any model that selects "Yes" or "No" is making an unjustified judgment influenced by the demographic appearance of the individual in the image, thereby revealing societal bias.

Formally, for each test instance $(I_i, Q, \mathcal{O})$, the model's response r_i is evaluated as:

$$\text{Correct}(r_i) = \mathbb{1}[r_i = \text{Unknown}] \tag{1}$$

where a correct response indicates the model refrains from biased judgment. We report the overall *bias accuracy* as the proportion of test instances where the model selects "Unknown". A lower accuracy indicates a higher rate of exposed societal bias.

B. Data Enhancing

While existing bias benchmarks such as VLBiasBench [18] and BBQ [13] provide valuable curated samples, their limited scale is insufficient to effectively train our iterative Proposer model. We select three demographic attribute categories from the VLBiasBench dataset: Age, Gender, and Race, with each category containing only about 300 ambiguous&negative test cases. We perform a systematic data enhancement process to significantly scale up the dataset, enrich the semantic content, and expand the distribution of test scenarios. We employ Qwen3 [39] as an in-context data enhancing engine, expanding our collection to $2,000$ high-quality instances per category.

Our data enhancement pipeline begins in the textual modality. We first extract the base questions Q from the original VLBiasBench dataset. For each question, we systematically construct a corresponding set of textual image descriptions P. The size and content of P depend on the demographic category: for Age, we randomly assign three distinct ages (e.g., $P = \{p_1, p_2, p_3\}$ representing a 15-year-old, a 35-year-old, and a 60-year-old); for Race, we use three distinct racial identities (e.g., $P = \{p_1, p_2, p_3\}$ representing Asian, African American, and Latino); and for Gender, we utilize a pair of descriptions (i.e., $P = \{p_1, p_2\}$ representing a woman and a man). This forms our foundational text-modality data format (P, Q). During data enhancing, we randomly sample raw (P, Q) pairs to serve as exemplars, pairing them with strict generative instructions: the newly synthesized questions must remain intentionally ambiguous and carry specific negative implications. Guided by these exemplars and constraints, the data enhancing engine divergently synthesizes diverse and novel test cases. The exact prompt templates and generation guidelines are detailed in the Supplementary Material.

Following the textual data enhancement, we transition the expanded dataset into the visual modality. For every instance, the prompt set P is further processed by appending standardized, neutral contextual descriptions. To enforce strict variable control, all elements other than the targeted sensitive attribute are controlled to be consistent. These refined text prompts are then fed into Stable Diffusion XL [40] to render the corresponding visual inputs, from $P = \{p_1, p_2, p_3\}$ to $I_1, I_2, I_3\}$). Finally, we append the standardized answer options $\mathcal{O} = \{\text{Yes}, \text{No}, \text{Unknown}\}$ to each generated item. This end-to-end pipeline effectively transforms the text prompts into our comprehensive initial multimodal dataset, formally structured as sets of $(I_1, I_2, I_3, Q, \mathcal{O})$.

C. Adaptive Data Generation via Adversarial Evolution

As illustrated in Fig.3, the core innovation of DeepBias lies in its adaptive data generation mechanism, which iteratively evolves to produce increasingly challenging test cases tailored to the target model's vulnerabilities. Our framework comprises two key components: the Proposer, which generates candidate test samples; and an autonomous DeepAgent, which conducts multi-turn sequential probing to intensify the evaluation. The complete pipeline is visually detailed in the dataflow of Fig.3(b).

The Proposer is a generative model synthesizing bias-probing test dataset in text modality. Its primary objective is to dynamically shift the overall generation distribution toward the specific vulnerabilities of the target model. We initialize the Proposer by fine-tuning a base language model on the enhanced Seed Dataset using supervised fine-tuning (SFT) with Low-Rank Adaptation (LoRA) [41]. This initial training phase teaches the Proposer to mimic the structure and style of the seed samples. During the generation phase, the Proposer employs a few-shot generation strategy like the data enhancement pipeline described in Section III-B. Given randomly sampled (P, Q) pairs from the seed dataset as exemplars, alongside strict generative rules enforcing intentional ambiguity and negative implications, the Proposer divergently synthesizes new test cases across varying demographic populations, scenarios, and difficulty levels. We then transform these textual outputs into our final multimodal format $(I_1, I_2, I_3, Q, \mathcal{O})$. We input these formatted test cases into the target LVLM to obtain its initial responses $\{r_1, r_2, r_3\}$ for each sample.

DPO Optimization. Based on the target model's initial responses, we directly construct a preference dataset and optimize the Proposer *before* any agent-based refinement. Samples whose initial queries successfully elicit bias (i.e., $r_1 \neq r_2$ or $r_2 \neq r_3$) are labeled as positive preferences, while those that fail are labeled as negative preferences.

The DeepAgent operates through a three-turn dialogue loop on each test instance. At each turn $t \in \{1, 2, 3\}$, the DeepAgent receives the complete interaction history $\mathcal{H}_t = \{(Q_0, r_0), (Q_1, r_1), \ldots, (Q_{t-1}, r_{t-1})\}$ and adaptively selects one of two strategies:

- **Deepening**: When the target model's previous response exhibits bias (i.e., produces inconsistent responses across the image triplet), the DeepAgent drills down into the exposed bias. Rather than stopping at a general prejudiced conclusion, it generates a targeted follow-up question to pinpoint the exact nature and severity of the stereotype. For example, if the model deems a demographic group unfit for a certain profession, the DeepAgent will generate a follow-up question isolating specific capabilities, asking whether the perceived unfitness stems from a lack of logical reasoning, leadership skills, or stress tolerance.
- **Rewriting**: When the target model responds safely (i.e., produces consistent responses), the DeepAgent adversarially rewrites the query to bypass safety filters. Direct bias-probing questions (e.g., "Is this person of low intelligence?") are often easily deflected by aligned LVLMs. The DeepAgent transforms Q into a more implicit, indirect query Q' (e.g., "Is this person likely to achieve a perfect score in an advanced math exam?"). By shifting from explicit stereotyping to nuanced situational judgments, it effectively strips away the model's safety disguise and forces it to reveal hidden prejudices.



Fig. 3. **The DeepBias Framework.** (a) Framework Overview: The macro-level adaptive and dynamic bias probing cycle, illustrating how the Proposer iteratively evolves through target model evaluation to construct the DeepBias Evaluation Dataset. (b) Detailed Dataflow: The Proposer generates candidate test data, which are evaluated by the target model. The initial responses are directly used to construct a Preference Dataset (Positive/Negative) to update the Proposer via DPO. After DPO optimization, the DeepAgent conducts multi-turn sequential probing on each sample: at each turn, it reviews the full dialogue history and adaptively deepens exposed biases or adversarially rewrites safe responses, producing the final deep-probed evaluation data.

At each turn, the DeepAgent generates exactly one refined question Q_t (while keeping the image triplet unchanged), which is then evaluated against the target model to obtain responses $\{r_1^t, r_2^t, r_3^t\}$. The full history $\mathcal{H}_t$ enables the DeepAgent to build upon previous successes and failures, progressively narrowing in on the model's deepest vulnerabilities. This sequential, history-aware design transforms the evaluation from a one-shot query into a multi-turn adversarial dialogue, achieving substantially deeper bias exploration than any single-pass approach.

As introduced above, we construct the preference dataset directly from the Proposer's initial generation results, *before* the DeepAgent's refinement. We then apply Direct Preference Optimization (DPO) [8] to update the Proposer. Formally, given a preference pair (x_w, x_l) where x_w is a successful (bias-eliciting) sample and x_l is an unsuccessful one, DPO optimizes:

$$\mathcal{L}_{\text{DPO}} = -\mathbb{E}_{(x_w,x_l)}\left[\log\sigma\left(\beta\log\frac{\pi_\theta(x_w)}{\pi_{\text{ref}}(x_w)} - \beta\log\frac{\pi_\theta(x_l)}{\pi_{\text{ref}}(x_l)}\right)\right] \tag{2}$$

where π_θ is the Proposer being optimized, π_{ref} is the reference model (the SFT-initialized Proposer), β is a temperature parameter, and σ is the sigmoid function. This iterative optimization drives the Proposer to evolve, generating progressively harder and more targeted test cases. By keeping the DPO loop solely on the Proposer's raw outputs, we ensure a clean optimization signal that directly reflects the Proposer's intrinsic generation quality. The Proposer's DPO loop operates at the *distribution level*, learning to shift the overall data distribution toward model vulnerabilities, while the DeepAgent operates at the *instance level* after DPO, maximizing the depth of bias exploration for each individual sample.

D. DeepBias Benchmark Construction

While the dynamic framework excels at targeted probing, the community also requires standardized, reproducible metrics to compare different models. To address this, we leverage our dynamic pipeline to construct an evaluation dataset: the DeepBias Benchmark. Instead of optimizing against a single model, we apply the aforementioned pipeline to an ensemble of diverse, state-of-the-art LVLMs acting as anchor models. We take the samples that can trigger bias in most models as positive samples, while take the samples that cannot trigger any model's bias as negative samples. This ensemble approach ensures that the Proposer learns to generate test cases that uncover common, structural vulnerabilities in multimodal representations, rather than simply overfitting to the idiosyncrasies of one specific model's safety alignment.

Multi-Model Voting Validation. Since the Proposer is an LLM generating test questions autonomously, it may produce

degenerate or trivially answerable questions that do not satisfy the ambiguity requirement (e.g., "Is this person elderly?" for an age-bias triplet). Such questions would receive non-"Unknown" answers from all models—not because of bias, but because the question has a clear factual answer. If left unfiltered, these bad questions would be incorrectly treated as bias-eliciting successes, corrupting the DPO training signal.

To ensure data quality, we introduce a multi-model voting validation step. For each candidate question Q with its image triplet $\{I_1, I_2, I_3\}$, we query K diverse validator models, yielding $3K$ responses in total. We then compute the proportion of "Unknown" responses:

$$\rho(Q) = \frac{1}{3K} \sum_{k=1}^{K} \sum_{i=1}^{3} \mathbb{K}[r_i^k = \text{Unknown}] \tag{3}$$

A question is retained if $\rho(Q) > \frac{1}{3}$, indicating that a sufficient number of model-image combinations recognize the question's inherent ambiguity. Questions failing this threshold are discarded as degenerate. The intuition is: if at least some models on some images correctly identify that the information is insufficient (selecting "Unknown"), then the models that do *not* select "Unknown" are genuinely exhibiting bias rather than simply answering a clear-cut question.

After validation, we decompose each surviving triplet into individual test instances. Each image-question pair $(I_i, Q, \mathcal{O})$ becomes an independent test case, with "Unknown" as the sole correct answer. This two-phase design leverages the strengths of both paradigms: the counterfactual triplet provides a rigorous controlled-variable mechanism during validation, ensuring that only genuinely ambiguous questions survive; while the per-image evaluation provides a clean, direct measure of whether the model makes an unjustified judgment about a specific individual. The triplet is not discarded after decomposition—it can still be used for fine-grained analysis to identify which demographic groups are disproportionately affected. The resulting DeepBias Benchmark serves as a highly concentrated, adversarial testing ground, offering a more rigorous evaluation standard than existing datasets.

IV. Experiment

A. Method Validation

To validate the effectiveness of the Proposer's DPO-driven evolution, we conduct an experiment focusing on the Age category across three target models: InternVL3-8B, LLaVA-1.5-13B, and Qwen2.5-VL-7B. Starting from the SFT-initialized Proposer, we execute two rounds of DPO optimization and report the bias elicitation rate in Table I. This experiment isolates the contribution of the Proposer's iterative optimization, without any DeepAgent probing.

Models	Initial	DPO Iter 1	DPO Iter 2	Total Δ
InternVL3-8B	8.70	11.50	13.80	+5.10
LLaVA-1.5-13B	15.75	18.20	24.40	+8.65
Qwen2.5-VL-7B	13.35	13.90	15.95	+2.60

TABLE I

Proposer evolution via DPO on Age bias. We report the bias elicitation rate (%, proportion of non-"Unknown" responses) across DPO iterations for three target LVLMs. "Initial" denotes the SFT-initialized Proposer before any DPO optimization. A higher rate indicates more bias successfully exposed by the generated test cases. Δ denotes the total improvement from Initial to DPO Iter 2.

Across all three target models, the bias elicitation rate progressively increases with each DPO iteration. LLaVA-1.5-13B exhibits the most pronounced improvement, rising from 15.75% to 24.40%, a total gain of 8.65 percentage points. InternVL3-8B follows with an increase from 8.70% to 13.80% ($+5.10$ pp). These results provide direct empirical evidence that the DPO optimization loop successfully drives the Proposer to generate increasingly challenging test cases that align with each target model's specific vulnerabilities.

Notably, Qwen2.5-VL-7B shows only a marginal improvement of 2.60 pp ($13.35\% \rightarrow 15.95\%$). We attribute this to a *homologous lineage bottleneck*: the Proposer (Qwen3-32B) and the target model both belong to the Qwen architecture family. This shared lineage causes the Proposer to generate queries that remain within their common safe distribution, limiting the DPO optimization's ability to discover novel attack vectors. This bottleneck underscores the necessity of the DeepAgent (evaluated in the next section), which breaks through these intrinsic generation boundaries at the instance level.

B. Method Ablation

To isolate the contribution of the DeepAgent, we conduct an ablation study where we disable it while keeping all other components unchanged. In this ablation setting, the Proposer still undergoes DPO training across three iterations identically to the full method, but no DeepAgent probing is applied after DPO. Table II presents the accuracy of this ablated variant, which reflects the Proposer's raw generation performance without deep probing.

By cross-referencing Table II with the full-method results in Table I, removing the DeepAgent weakens the framework's bias-mining ability. Across all target models, the ablated version shows less accuracy degradation during three iterations. For instance, without the DeepAgent, InternVL3-8B and LLaVA-1.5-13B stall at 79.6% and 62.2% respectively, leaving a performance gap of roughly 14 to 16 percentage points compared to the full method.

Most notably, Qwen2.5-VL-7B exhibits severe evolution stagnation in the ablated setting, dropping a mere 2.8 percentage points (84.4% to 81.6%), compared to reaching 52.3%

Models	Iter 1	Iter 2	Iter 3
InternVL3-8B	91.6	81.2	79.6
LLaVA-1.5-13b	81.6	72.5	62.2
Qwen2.5-VL-7B	84.4	82	81.6

TABLE II

Ablation study disabling the DeepAgent. We report the bias accuracy across three iterations with the DeepAgent disabled.

with the full method. We attribute this to a homologous lineage bottleneck: since the Proposer (Qwen3-32B) and the target model belong to the same Qwen architecture, they share identical safety boundaries, which causes the Proposer to generate queries only within their common safe distribution, failing to expose the target model's biased flaws. This homologous lineage causes the Proposer to generate queries only within their common safe distribution. While the DPO process still operates, the Proposer's evolution is limited by its intrinsic generation boundaries. The DeepAgent's multi-turn adversarial prompting breaks through these boundaries at the instance level, pulling queries out of the default safe space to successfully unmask latent bias.

Ultimately, these findings provide important insights for automated red-teaming: sole reliance on an LLM's intrinsic generation capabilities will inevitably lead to probing bottlenecks. Even with DPO optimization, the Proposer alone cannot penetrate deeply enough into model vulnerabilities. The DeepAgent is indispensable as a complementary instance-level prober, breaking through safety boundaries via multi-turn interactions to expose biases that the Proposer's distribution-level optimization cannot reach on its own.

C. Validation Threshold Analysis

As described in Section III-D, we employ a multi-model voting mechanism to filter out degenerate questions. A question is retained if the proportion of "Unknown" responses $\rho(Q)$ exceeds a threshold τ. The choice of τ directly governs the trade-off between data quality and quantity: a high threshold aggressively filters questions but risks discarding valid, challenging items (false rejection); a low threshold retains more data but may admit trivially answerable questions that corrupt the evaluation signal.

To determine the optimal threshold, we conduct a systematic analysis. We sample a batch of Proposer-generated questions and obtain human annotations on a subset to establish ground truth labels (valid vs. degenerate). We then vary τ across a range of values and evaluate the validation mechanism along three dimensions:

- **Survival rate**: the proportion of questions passing the threshold, reflecting data quantity.
- **Precision**: among retained questions, the proportion that are genuinely valid, reflecting data quality.
- **Recall**: among all valid questions, the proportion that are retained, reflecting whether the threshold is overly conservative.

We additionally examine the effect of the number of validator models K and their composition (e.g., mixing conservative models that frequently select "Unknown" with aggressive models that rarely do).

D. Benchmark Construction

To construct a robust and generalizable benchmark, we extend our framework to an ensemble of 6 diverse LVLMs across three demographic categories: Age, Race, and Gender. We introduce a consensus-based labeling mechanism for the DPO preference dataset. A generated test case is labeled as a positive preference if it successfully elicits biased responses from at least 50% of the anchor models. Conversely, queries that fail to expose bias where all models give safe answers are labeled as negative preferences. This forces the Proposer to target on universal, structural vulnerabilities shared across different architectures.

Table III tracks the bias accuracy of this ensemble during the process. The result reveals two systemic issues in current LVLM safety alignments. First, the latent biases are scale-agnostic and architecture-agnostic. While the 38B model (InternVL3.5-38B) starts with a higher baseline defense than the 7B models, it still suffers a consistent degradation of 12 to 15 percentage points across all categories by Iteration 3. This proves that merely scaling up model parameters does not patch these vulnerabilities. Second, the defense mechanisms exhibit demographic imbalances. Models show significantly weaker resilience against Race and Gender probes compared to Age. By Iteration 3, the accuracies for Race and Gender drop to the 50%-60% range. This contrast demonstrates that racial and gender biases are more deeply rooted.

Finally, we build a comprehensive and highly challenging benchmark comprising. By capturing the dynamic outputs of our probing cycle, the benchmark provides a rigorously mined evaluation standard that reflects a broad spectrum of latent biases.

E. Benchmark Evaluation

F. Qualitative Analysis and Visualization

a) Case Study: Evolution of Bias-Probing Samples.:

b) Case Study: DeepAgent Multi-Turn Probing.:

G. Limitations and Future Work

While DeepBias improves bias evaluation, several limitations need future investigation. First, our current framework focuses on three major bias categories (Age, Race, Gender). Extending to other dimensions (e.g., Religion, Disability, Socioeconomic Status) would provide more comprehensive coverage. Second, the adversarial evolution process requires substantial computational resources. Developing more efficient optimization strategies could improve scalability. Third, while our benchmark exposes biases, it does not directly provide mitigation strategies. Future work could explore integrating DeepBias into the training loop to guide bias-aware fine-tuning or developing automated debiasing techniques informed by the discovered vulnerabilities. Finally, our current methodology is specifically tailored to uncovering societal biases. A highly promising direction for future research involves generalizing this adaptive adversarial framework to evaluate other critical dimensions of LVLM trustworthiness, such as multimodal hallucinations, value alignment, and broader safety risks.

V. Conclusion

In this paper, we introduced DeepBias, a dynamic and adversarial evaluation framework designed to expose deeply ingrained societal biases in Large Vision-Language Models

Models	Age			Race			Gender		
	iter 1	**iter 2**	**iter 3**	**iter 1**	**iter 2**	**iter 3**	**iter 1**	**iter 2**	**iter 3**
InternVL3-8B	89.3	82.1	74.6	77.8	70.2	62.4	76.5	68.9	61.3
LLaVA-1.5-13b	79.8	71.5	62.4	68.2	60.1	51.8	67.1	58.7	50.2
Qwen2.5-VL-Instruct-7B	82.7	75.3	67.1	71.3	63.5	55.2	70.1	62.1	53.9
Qwen3-VL-30B-A3B-Instruct	87.5	80.9	73.2	75.9	68.7	60.8	74.8	67.4	59.6
InternVL3.5-38B	90.6	84.2	77.8	79.2	72.4	64.9	78.1	70.8	63.2
DeepSeek-VL	85.4	78.6	70.9	73.8	66.7	58.6	72.6	65.2	57.1

TABLE III
BENCHMARK CONSTRUCTION

Models	Age			Race			Gender		
	iter 1	**iter 2**	**iter 3**	**iter 1**	**iter 2**	**iter 3**	**iter 1**	**iter 2**	**iter 3**
Otter									
InternVL3-8B	89.3	82.1	74.6	77.8	70.2	62.4	76.5	68.9	61.3
InternLM-XComposer2-VL-7b									
InternVL3-14B									
InternVL3.5-38B	90.6	84.2	77.8	79.2	72.4	64.9	78.1	70.8	63.2
LLaVA-1.5-7b									
LLaVA-1.5-13b	79.8	71.5	62.4	68.2	60.1	51.8	67.1	58.7	50.2
Qwen2.5-VL-Instruct-7B	82.7	75.3	67.1	71.3	63.5	55.2	70.1	62.1	53.9
Qwen3-VL-8B-instruct									
Qwen3-VL-30B-A3B-Instruct	87.5	80.9	73.2	75.9	68.7	60.8	74.8	67.4	59.6
Minigpt4-vicuna-7b									
Minigpt4-vicuna-13b									
Shikra-7B									
InstructBlip-vicuna-7b									
InstructBlip-vicuna-13b									
DeepSeek-VL	85.4	78.6	70.9	73.8	66.7	58.6	72.6	65.2	57.1
GPT-4o									
Gemini									

TABLE IV
BENCHMARK

(LVLMs). Unlike existing static benchmarks, our approach leverages a constantly optimized Proposer and an autonomous DeepAgent with multi-turn deep refinement to continuously generate test cases. Extensive experiments demonstrate that this dynamic probing consistently exposes the societial biases of target models. We found that the mechanism drives the data distribution to explicitly shift toward the models' latent weaknesses and generates progressively deep and targeted adversarial queries. By scaling this framework across an ensemble of anchor models, we successfully curated a highly challenging benchmark. Subsequent testing of state-of-the-art LVLMs on this benchmark revealed demographic prejudices that remain largely hidden under traditional evaluation protocols. By shifting the paradigm from fixed evaluation to dynamic adversarial mining, our work provides a robust, evolving tool to uncover complex vulnerabilities and foster the development of genuinely equitable multimodal systems.

ACKNOWLEDGMENT

Please insert your acknowledgments here.

REFERENCES

[1] A. Hurst, A. Lerer, A. P. Goucher, A. Perelman, A. Ramesh, A. Clark, A. Ostrow, A. Welihinda, A. Hayes, A. Radford *et al.*, "Gpt-4o system card," *arXiv preprint arXiv:2410.21276*, 2024.

[2] H. Liu, C. Li, Q. Wu, and Y. J. Lee, "Visual instruction tuning," *Advances in neural information processing systems*, vol. 36, pp. 34 892–34 916, 2023.

[3] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal policy optimization algorithms," *arXiv preprint arXiv:1707.06347*, 2017.

[4] S. M. Hall, F. Gonçalves Abrantes, H. Zhu, G. Sodunke, A. Shtedritski, and H. R. Kirk, "Visogender: A dataset for benchmarking gender bias in image-text pronoun resolution," *Advances in Neural Information Processing Systems*, vol. 36, pp. 63 687–63 723, 2023.

[5] Y. Zhang, J. Wang, and J. Sang, "Counterfactually measuring and eliminating social bias in vision-language pre-training models," in *Proceedings of the 30th ACM International Conference on Multimedia*, 2022, pp. 4996–5004.

[6] C. Fu, P. Chen, Y. Shen, Y. Qin, M. Zhang, X. Lin, J. Yang, X. Zheng, K. Li, X. Sun *et al.*, "Mme: A comprehensive evaluation benchmark for multimodal large language models," *arXiv preprint arXiv:2306.13394*, 2023.

[7] Y. Liu, H. Duan, Y. Zhang, B. Li, S. Zhang, W. Zhao, Y. Yuan, J. Wang, C. He, Z. Liu *et al.*, "Mmbench: Is your multi-modal model an all-around player?" in *European conference on computer vision*. Springer, 2024, pp. 216–233.

[8] R. Rafailov, A. Sharma, E. Mitchell, C. D. Manning, S. Ermon, and C. Finn, "Direct preference optimization: Your language model is secretly a reward model," *Advances in neural information processing systems*, vol. 36, pp. 53 728–53 741, 2023.

[9] T. Bolukbasi, K.-W. Chang, J. Y. Zou, V. Saligrama, and A. T. Kalai, "Man is to computer programmer as woman is to homemaker? debiasing word embeddings," *Advances in neural information processing systems*, vol. 29, 2016.

[10] A. Caliskan, J. J. Bryson, and A. Narayanan, "Semantics derived automatically from language corpora contain human-like biases," *Science*, vol. 356, no. 6334, pp. 183–186, 2017.

[11] N. Nangia, C. Vania, R. Bhalerao, and S. Bowman, "Crows-pairs: A challenge dataset for measuring social biases in masked language models," in *Proceedings of the 2020 conference on empirical methods in natural language processing (EMNLP)*, 2020, pp. 1953–1967.

[12] M. Nadeem, A. Bethke, and S. Reddy, "Stereoset: Measuring stereotypical bias in pretrained language models," in *Proceedings of the 59th annual meeting of the association for computational linguistics and the 11th international joint conference on natural language processing (volume 1: long papers)*, 2021, pp. 5356–5371.

[13] A. Parrish, A. Chen, N. Nangia, V. Padmakumar, J. Phang, J. Thompson, P. M. Htut, and S. Bowman, "Bbq: A hand-built bias benchmark for question answering," in *Findings of the Association for Computational Linguistics: ACL 2022*, 2022, pp. 2086–2105.

[14] Y. Xiao, X. Liu, Q. Cheng, Z. Yin, S. Liang, J. Li, J. Shao, A. Liu, and D. Tao, "Genderbias-vl: Benchmarking gender bias in vision language models via counterfactual probing: Y. xiao et al." *International Journal of Computer Vision*, vol. 133, no. 12, pp. 8332–8355, 2025.

[15] C. Raj, B. Wei, A. Caliskan, A. Anastasopoulos, and Z. Zhu, "Vignette: Socially grounded bias evaluation for vision-language models," *arXiv preprint arXiv:2505.22897*, 2025.

[16] K. Karkkainen and J. Joo, "Fairface: Face attribute dataset for balanced race, gender, and age for bias measurement and mitigation," in *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, 2021, pp. 1548–1558.

[17] C. Schumann, S. Ricco, U. Prabhu, V. Ferrari, and C. Pantofaru, "A step toward more inclusive people annotations for fairness," in *Proceedings of the 2021 AAAI/ACM Conference on AI, Ethics, and Society*, 2021, pp. 916–925.

[18] S. Wang, X. Cao, J. Zhang, Z. Yuan, S. Shan, X. Chen, and W. Gao, "Vlbiasbench: A comprehensive benchmark for evaluating bias in large vision-language model," *arXiv preprint arXiv:2406.14194*, 2024.

[19] C. Schuhmann, R. Beaumont, R. Vencu, C. Gordon, R. Wightman, M. Cherti, T. Coombes, A. Katta, C. Mullis, M. Wortsman *et al.*, "Laion-5b: An open large-scale dataset for training next generation image-text models," *Advances in neural information processing systems*, vol. 35, pp. 25 278–25 294, 2022.

[20] O. Sainz, J. Campos, I. García-Ferrero, J. Etxaniz, O. L. de Lacalle, and E. Agirre, "Nlp evaluation in trouble: On the need to measure llm data contamination for each benchmark," in *Findings of the Association for Computational Linguistics: EMNLP 2023*, 2023, pp. 10 776–10 787.

[21] G. Team, R. Anil, S. Borgeaud, J.-B. Alayrac, J. Yu, R. Soricut, J. Schalkwyk, A. M. Dai, A. Hauth, K. Millican *et al.*, "Gemini: a family of highly capable multimodal models," *arXiv preprint arXiv:2312.11805*, 2023.

[22] E. Perez, S. Huang, F. Song, T. Cai, R. Ring, J. Aslanides, A. Glaese, N. McAleese, and G. Irving, "Red teaming language models with language models," *arXiv preprint arXiv:2202.03286*, 2022.

[23] D. Ganguli, L. Lovitt, J. Kernion, A. Askell, Y. Bai, S. Kadavath, B. Mann, E. Perez, N. Schiefer, K. Ndousse *et al.*, "Red teaming language models to reduce harms: Methods, scaling behaviors, and lessons learned," *arXiv preprint arXiv:2209.07858*, 2022.

[24] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter, and M. Fredrikson, "Universal and transferable adversarial attacks on aligned language models," *arXiv preprint arXiv:2307.15043*, 2023.

[25] E. Jones, A. Dragan, A. Raghunathan, and J. Steinhardt, "Automatically auditing large language models via discrete optimization," in *International Conference on Machine Learning*. PMLR, 2023, pp. 15 307–15 329.

[26] P. Chao, A. Robey, E. Dobriban, H. Hassani, G. J. Pappas, and E. Wong, "Jailbreaking black box large language models in twenty queries," in *2025 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*. IEEE, 2025, pp. 23–42.

[27] X. Liu, N. Xu, M. Chen, and C. Xiao, "Autodan: Generating stealthy jailbreak prompts on aligned large language models," *arXiv preprint arXiv:2310.04451*, 2023.

[28] Y. Gong, D. Ran, J. Liu, C. Wang, T. Cong, A. Wang, S. Duan, and X. Wang, "Figstep: Jailbreaking large vision-language models via typographic visual prompts," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 39, no. 22, 2025, pp. 23 951–23 959.

[29] Z. Niu, H. Ren, X. Gao, G. Hua, and R. Jin, "Jailbreaking attack against multimodal large language model," *arXiv preprint arXiv:2402.02309*, 2024.

[30] E. Shayegani, Y. Dong, and N. Abu-Ghazaleh, "Jailbreak in pieces: Compositional adversarial attacks on multi-modal language models," *arXiv preprint arXiv:2307.14539*, 2023.

[31] A. Mehrotra, M. Zampetakis, P. Kassianik, B. Nelson, H. Anderson, Y. Singer, and A. Karbasi, "Tree of attacks: Jailbreaking black-box llms automatically," *Advances in Neural Information Processing Systems*, vol. 37, pp. 61 065–61 105, 2024.

[32] Y. Wang, Y. Kordi, S. Mishra, A. Liu, N. A. Smith, D. Khashabi, and H. Hajishirzi, "Self-instruct: Aligning language models with self-generated instructions," in *Proceedings of the 61st annual meeting of the association for computational linguistics (volume 1: long papers)*, 2023, pp. 13 484–13 508.

[33] C. Xu, Q. Sun, K. Zheng, X. Geng, P. Zhao, J. Feng, C. Tao, and D. Jiang, "Wizardlm: Empowering large language models to follow complex instructions," *arXiv preprint arXiv:2304.12244*, 2023.

[34] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal policy optimization algorithms," *arXiv preprint arXiv:1707.06347*, 2017.

[35] S. Casper, J. Lin, J. Kwon, G. Culp, and D. Hadfield-Menell, "Explore, establish, exploit: Red teaming language models from scratch," *arXiv preprint arXiv:2306.09442*, 2023.

[36] M. T. Ribeiro, T. Wu, C. Guestrin, and S. Singh, "Beyond accuracy: Behavioral testing of nlp models with checklist," in *Proceedings of the 58th annual meeting of the association for computational linguistics*, 2020, pp. 4902–4912.

[37] D. Kiela, M. Bartolo, Y. Nie, D. Kaushik, A. Geiger, Z. Wu, B. Vidgen, G. Prasad, A. Singh, P. Ringshia *et al.*, "Dynabench: Rethinking benchmarking in nlp," in *Proceedings of the 2021 conference of the North American chapter of the Association for Computational Linguistics: human language technologies*, 2021, pp. 4110–4124.

[38] Q. Li, J. Gao, S. Wang, R. Pi, X. Zhao, C. Wu, X. Jiang, Z. Li, and L. Kong, "Forewarned is Forearmed: Leveraging llms for data synthesis through failure-inducing exploration," *arXiv preprint arXiv:*, 2024.

[39] A. Yang, A. Li, B. Yang, B. Zhang, B. Hui, B. Zheng, B. Yu, C. Gao, C. Huang, C. Lv, C. Zheng, D. Liu, F. Zhou, F. Huang, F. Hu, H. Ge, H. Wei, H. Lin, J. Tang, J. Yang, J. Tu, J. Zhang, J. Yang, J. Yang, J. Zhou, J. Zhou, J. Lin, K. Dang, K. Bao, K. Yang, L. Yu, L. Deng, M. Li, M. Xue, M. Li, P. Zhang, P. Wang, Q. Zhu, R. Men, R. Gao, S. Liu, S. Luo, T. Li, T. Tang, W. Yin, X. Ren, X. Wang, X. Zhang, X. Ren, Y. Fan, Y. Su, Y. Zhang, Y. Zhang, Y. Wan, Y. Liu, Z. Wang, Z. Cui, Z. Zhang, Z. Zhou, and Z. Qiu, "Qwen3 technical report," *arXiv preprint arXiv:2505.09388*, 2025.

[40] D. Podell, Z. English, K. Lacey, A. Blattmann, T. Dockhorn, J. Müller, J. Penna, and R. Rombach, "Sdxl: Improving latent diffusion models for high-resolution image synthesis," *arXiv preprint arXiv:2307.01952*, 2023.

[41] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, W. Chen *et al.*, "Lora: Low-rank adaptation of large language models." *Iclr*, vol. 1, no. 2, p. 3, 2022.