

PROBLEM

- Assume that there are three paths ($\alpha(0)=0.3$, $\alpha(1)=1$, and $\alpha(2)=0.3$) in a wireless channel and the delay between any two paths is a symbol period. Find the equivalent baseband ZF equalizer.
- With the built platform in Practice 1 and the assumed channels, conduct digital ZF equalization to recovery the transmit symbol signal (QPSK).



I. Find the equivalent baseband ZF equalizer

$$H(z) = 0.3 + z^{-1} + 0.3z^{-2}$$

$$\Rightarrow E(z) = \frac{1}{H(z)} = \frac{1}{0.3 + z^{-1} + 0.3z^{-2}} = \frac{\frac{15}{4}}{1 + 3z^{-1}} + \frac{-\frac{5}{12}}{1 + \frac{1}{3}z^{-1}} = E_1(z) + E_2(z)$$

$$\text{for stable system, } \begin{cases} E_1(z) = \frac{\frac{15}{4}}{1 + 3z^{-1}} \\ E_2(z) = \frac{-\frac{5}{12}}{1 + \frac{1}{3}z^{-1}} \end{cases} \Rightarrow \begin{cases} e_1[n] = -\frac{15}{4}(-3)^n u[-n-1] \\ e_2[n] = \left(-\frac{5}{12}\right)\left(-\frac{1}{3}\right)^n u[n] \end{cases} \Rightarrow e[n] = e_1[n] + e_2[n]$$

設定 equalizer 長度為 20，做 truncation 成為下圖左，再 delay 10 成為下圖右的 causal filter。




equalizer 有 delay 10

\Rightarrow equalizer 和 baseband channel response 做 convolution 後得到的 delta function 也會 delay 10。


\Rightarrow 最後做 recovery 的訊號也會 delay 10，需要額外補回來。

```
91 % equalizer
92 rxd1 = conv(rxd1, e);
93 rxd1 = rxd1(1+Ne:end);
```



II. Conduct digital ZF equalization to recovery the transmit symbol signal (QPSK)

A. Transmit symbol signal = delta function



B. Transmit symbol signal = QPSK signal

