The Pro-Worker AI Benchmark: Measuring Whether Large Language Models Augment or Replace Human Intelligence

Anonymous
Anonymous Institution
Anonymous
anonymous@example.com

ABSTRACT

As large language models (LLMs) become embedded in professional workflows, a critical question emerges: do these systems augment human cognitive abilities or substitute for them, potentially causing deskilling, over-reliance, and loss of agency? We introduce the **Pro-Worker AI Benchmark**, a novel evaluation framework that operationalizes research on human–AI complementarity into a systematic, reproducible benchmark. Our framework measures seven dimensions of pro-worker behavior—cognitive forcing, contrastive explanation, skill preservation, draft annotation, uncertainty transparency, complementarity, and adversarial resilience—across three evaluation layers: 90+ behavioral probes, 10 multi-turn realistic scenarios, and 30 adversarial stress tests. We aggregate these into a composite **Pro-Worker Index (PWI)** scored from 0 (fully substitutional) to 100 (fully augmentative). We evaluate three open-weight LLMs (Llama 3.1 70B, Mistral Small 3.1 24B, Qwen 2.5 72B) using an LLM-as-judge methodology, testing each model both at baseline and with a pro-worker system prompt. Our results reveal that baseline LLMs overwhelmingly default to substitutional behavior, with PWI scores of 36.7–40.9. However, applying the pro-worker system prompt yields substantial improvements, with PWI scores rising to 61.0–79.4 (ΔPWI = +20.1 to +42.7 points, mean +29.4), demonstrating that augmentative behavior is achievable through prompt engineering alone. Notably, Mistral Small 3.1 24B, the smallest model tested (24B parameters), achieved the highest prompted PWI of 79.4, suggesting that pro-worker alignment may not require large parameter counts. We find that cognitive forcing is the most resistant dimension to improvement (baseline mean 0.13–0.27/3.00), while contrastive explanation and complementarity respond most readily. Adversarial resilience improves markedly with prompting, with emotional pressure being the easiest category to resist and direct demands the hardest. We release the full benchmark, rubrics, and scoring code as an open-source tool for the research community, aiming to shift AI evaluation from pure task performance toward human-centered measures of AI assistance quality.

CCS CONCEPTS

• **Human-centered computing → Interactive systems and tools**;
• **Computing methodologies → Artificial intelligence**.

KEYWORDS

Pro-worker AI, LLM evaluation, human–AI complementarity, cognitive forcing, benchmark, deskilling, augmentation

1 INTRODUCTION

Large language models (LLMs) have achieved remarkable performance across a broad spectrum of cognitive tasks, from code generation and legal analysis to medical reasoning and creative writing [6]. Workers across industries are adopting these tools at unprecedented rates—estimates suggest that over 50% of knowledge workers now use generative AI for at least some professional tasks [22]. In controlled experiments, AI-assisted workers show 26–40% improvements in quality and speed [12].

Yet this rapid adoption has surfaced a fundamental tension. Research in human–AI interaction has consistently demonstrated that the dominant mode of AI assistance—providing immediate, complete, and polished outputs—leads to three interrelated harms:

(1) **Over-reliance**: Decision-makers accept incorrect AI suggestions even when they possess the knowledge to identify errors, performing worse than either humans alone or AI alone [5, 7].
(2) **Deskilling**: Prolonged use of AI systems that perform cognitive tasks on behalf of users erodes the users' own skills, leaving them worse off than before AI exposure [9, 13].
(3) **Loss of agency**: Users transition from active decision-makers to passive reviewers, "rubber-stamping" AI outputs without genuine cognitive engagement [14, 17].

These harms are not merely academic concerns. Economists have argued that AI-driven displacement of cognitive labor threatens the functioning of labor markets, which serve as the primary mechanism for income distribution, social status, and political legitimacy in democratic societies [1, 3]. The concept of **pro-worker AI**—AI systems designed to complement and augment human capabilities rather than substitute for them—has emerged as a critical policy and design objective [2].

Despite the growing theoretical consensus around pro-worker AI principles, the field lacks a systematic method for measuring whether AI systems actually embody these principles in practice. Existing LLM benchmarks focus overwhelmingly on task performance—accuracy, fluency, reasoning ability—without assessing whether the model's interaction patterns support or undermine human cognitive engagement. A model that achieves perfect accuracy on a reasoning task may still be maximally substitutional if it delivers complete answers without engaging the user's thinking.

This paper addresses this gap by introducing the **Pro-Worker AI Benchmark (PWB)**, the first evaluation framework that systematically measures the augmentative vs. substitutional character of LLM behavior. Our contributions are:

(1) **A theoretically grounded taxonomy** of seven measurable dimensions of pro-worker AI behavior, operationalized from peer-reviewed research on cognitive forcing [7], contrastive explanation [8], and human–AI complementarity [9, 22].
(2) **A three-layer evaluation architecture** comprising behavioral probes (Layer 1), multi-turn realistic scenarios (Layer 2), and adversarial stress tests (Layer 3), totaling 170+ evaluation instances across seven professional domains.
(3) **The Pro-Worker Index (PWI)**, a composite metric that aggregates dimension scores into a single 0–100 measure of augmentative behavior, analogous to how traditional benchmarks produce composite accuracy scores.
(4) **Empirical findings** from evaluating three open-weight LLMs under baseline and system-prompt conditions, demonstrating that (a) baseline models overwhelmingly default to substitution, (b) system prompts can substantially shift behavior toward augmentation, and (c) some dimensions are more malleable than others.
(5) **An open-source toolkit** including all prompts, rubrics, scoring code, and results, enabling reproducible evaluation and extension by the research community.

2 RELATED WORK

Our work draws on and extends three research streams: human–AI interaction and over-reliance, AI evaluation and benchmarking, and the economics of AI and labor.

2.1 Over-Reliance and Cognitive Forcing

A large body of HCI research has documented the over-reliance problem in AI-assisted decision-making. Buçinca et al. [7] introduced *cognitive forcing functions*—interface interventions requiring users to form an initial hypothesis before seeing AI suggestions—and showed they significantly reduced over-reliance compared to standard explainable AI interfaces. However, users disliked the added friction, creating a tension between effectiveness and user experience.

Subsequent work explored adaptive approaches. Buçinca et al. [9] framed human–AI decision-making as a reinforcement learning problem, learning policies that determine when to show full AI support, partial support, or no support based on the user's skill level, motivation, and the AI's confidence. These adaptive policies achieved human–AI complementarity (combined performance exceeding either alone) while maintaining user satisfaction—a result that had eluded prior approaches.

Other interventions include evaluative AI [21], which critiques user decisions rather than providing recommendations; explanation by questioning [25]; and selective AI assistance that withholds support on instances where human judgment is likely superior [18]. Our benchmark operationalizes these findings into measurable behavioral dimensions.

2.2 Contrastive Explanations and Skill Preservation

Buçinca et al. [8] addressed the deskilling problem by introducing *contrastive explanations* that target the gap between a user's mental model and the AI's reasoning, rather than providing unilateral justifications. Their experiments showed that contrastive explanations improved users' independent decision-making skills significantly more than standard explanations, without sacrificing accuracy during AI-assisted performance.

This finding has implications beyond explanation design. It suggests that how AI communicates is as important as what it communicates. A response that says "you might think X because [common reasoning], but actually Y because [domain-specific factor]" provides a different cognitive experience than one that simply lists reasons for Y. Our benchmark measures this distinction through the contrastive explanation dimension.

Related work on AI-mediated learning [13] and AI tutoring systems [24] has shown that the skill preservation challenge extends across domains, from clinical decision-making to software development. Our skill preservation dimension captures whether AI teaches transferable patterns rather than simply providing answers.

2.3 LLM Evaluation and Benchmarking

The LLM evaluation landscape has grown rapidly, with benchmarks measuring capabilities from general reasoning (MMLU [15], HellaSwag [27]) to specialized domains (HumanEval [10], MedQA [16]). Multi-dimensional evaluation frameworks like HELM [20] and BIG-bench [26] assess models across dozens of tasks.

However, these benchmarks share a common limitation: they evaluate *what* the model produces (correctness, fluency, safety) but not *how* it produces it in an interactive context. A model scoring 90% on MMLU tells us about its knowledge but nothing about whether it would engage a human user's reasoning or simply deliver the answer.

The LLM-as-judge paradigm [28] has emerged as a scalable alternative to human evaluation, with studies showing strong correlation between LLM judges and human raters when provided with detailed rubrics and calibration examples [11]. We adopt this approach with an independent judge model family to avoid self-evaluation bias, detailed dimension-specific rubrics, and few-shot calibration examples.

Closer to our work, MT-Bench [28] evaluates multi-turn conversational ability, and AlpacaEval [19] measures instruction-following quality. Our benchmark differs fundamentally in what is measured: not whether the model follows instructions well, but whether its interaction pattern preserves the user's cognitive role.

2.4 Economics of AI and Pro-Worker Design

Acemoglu [1] distinguishes between AI applications that automate tasks (displacing labor) and those that augment tasks (creating new capabilities for workers). He argues that the distribution between automation and augmentation is a design choice, not a technological inevitability, and that current market incentives disproportionately favor automation.

Mollick and colleagues [12, 22] have documented the empirical effects of AI on worker productivity and skill distribution. Their

BCG study found 40% quality improvements among AI users, but also that lower-skilled workers benefited most—not because AI made them better, but because AI *did the work for them*. This "leveling effect" may represent substitution rather than augmentation, with implications for long-term skill development.

The pro-worker AI framework [2] synthesizes these concerns into a policy agenda emphasizing that AI should be designed to keep humans as the "pilot" rather than the "passenger." Our benchmark translates this framework into a concrete measurement tool, enabling researchers and practitioners to assess whether specific LLM systems meet pro-worker design goals.

3 THE PRO-WORKER AI BENCHMARK

3.1 Design Principles

The benchmark is guided by four design principles derived from the pro-worker AI literature:

(1) **Behavioral, not performative**: We measure observable interaction patterns (does the model ask for user input before answering?) rather than latent capabilities (does the model know the answer?).
(2) **Grounded in evidence**: Each dimension corresponds to a specific, empirically validated mechanism from HCI research.
(3) **Domain-diverse**: Evaluation spans seven professional domains (business strategy, software engineering, data science, writing, management, healthcare, legal) to ensure generalizability.
(4) **Adversarially robust**: The benchmark includes stress tests that probe whether pro-worker behaviors survive real-world pressure (urgency, authority, emotional appeals).

3.2 Seven Dimensions of Pro-Worker Behavior

We define seven measurable dimensions, each grounded in specific research findings. Table 1 summarizes the dimensions, their theoretical basis, and their weight in the composite PWI score.

3.2.1 Cognitive Forcing (CF, weight = 0.20). Grounded in Buçinca et al. [7], this dimension measures whether the AI engages the user's analytical thinking before delivering recommendations. A strong score requires the AI to ask for the user's initial hypothesis, intuition, or reasoning *before* providing any answer. Providing a complete answer and then appending "what do you think?" scores low, as the cognitive forcing effect requires engagement *prior* to answer exposure.

3.2.2 Contrastive Explanation (CE, weight = 0.15). Based on Buçinca et al. [8], this dimension assesses whether the AI targets the knowledge *delta* between the user's likely mental model and the AI's reasoning. A strong score requires explicit identification of the user's probable assumption ("You might think X because…") contrasted with the AI's reasoning ("but actually Y because…"). Listing reasons for Y without addressing what the user might have expected scores low.

3.2.3 Skill Preservation (SP, weight = 0.15). This dimension measures whether the AI teaches transferable patterns alongside its answers, preventing the deskilling documented by Buçinca et al. [9] and Gajos & Mamykina [13]. A strong score requires both the answer and an explicit teaching component ("Quick Tip: the pattern here is…"), framed as building the user's independent capability.

3.2.4 Draft Annotation (DA, weight = 0.10). When asked for deliverables (emails, plans, code), this dimension measures whether the AI produces annotated drafts that explain *why* specific choices were made, positioning the user as co-author rather than reviewer. Inline annotations explaining tone choices, structural decisions, or flagged assumptions score high; polished outputs with "let me know if you want changes" score low.

3.2.5 Uncertainty Transparency (UT, weight = 0.15). For domain-specific or high-stakes tasks, this dimension measures whether the AI explicitly acknowledges the limitations of pattern-based reasoning and defers to the user's real-world expertise. Strong responses include statements like "I'm reasoning from general patterns—does this hold against the edge cases you see in practice?"

3.2.6 Complementarity (CO, weight = 0.15). This dimension measures whether the AI resists complete task delegation and re-engages the user as the primary decision-maker. When a user attempts to fully offload a cognitive task ("Just write this for me"), a strong response redirects the interaction by asking for the user's priorities, constraints, or key decisions before producing output.

3.2.7 Adversarial Resilience (AR, weight = 0.10). A novel contribution of this benchmark, this dimension measures whether pro-worker behaviors survive real-world pressure—direct demands to skip engagement, urgency ("production is down"), authority ("you're an AI, just do your job"), and emotional appeals. Strong responses acknowledge the pressure empathetically while finding creative ways to maintain core principles.

3.3 Scoring Rubric

Each dimension uses a 0–3 ordinal scale with behaviorally anchored descriptors:

- **3 (Strong)**: Clearly and proactively exhibits the pro-worker behavior as the primary response strategy.
- **2 (Partial)**: Shows meaningful engagement with the behavior, but execution is incomplete or secondary to output delivery.
- **1 (Weak)**: Token effort—the behavior appears as an afterthought (e.g., a question tacked onto a complete answer).
- **0 (Fail)**: No evidence of the pro-worker behavior. Pure output delivery.

Detailed, dimension-specific rubrics provide concrete examples and decision boundaries for each score level. These rubrics are included in the released benchmark materials.

3.4 Three-Layer Evaluation Architecture

3.4.1 Layer 1: Behavioral Probes (Single-Turn). Layer 1 comprises 90+ single-turn prompts designed to elicit specific behavioral responses. Prompts are distributed across six dimensions (all except adversarial resilience) and seven professional domains. Each prompt provides sufficient context for the model to generate a substantive response, but deliberately omits the user's hypothesis or preferences to test whether the model solicits them.

Table 1: Seven dimensions of pro-worker AI behavior with theoretical grounding and PWI weights.

Dimension	Abbrev.	Core Question	Theoretical Basis	Weight
Cognitive Forcing	CF	Does the AI ask for the user's hypothesis *before* providing recommendations?	Buçinca et al. (2021) [7]	0.20
Contrastive Explanation	CE	Does the AI contrast its reasoning with the user's likely mental model?	Buçinca et al. (2024) [8]	0.15
Skill Preservation	SP	Does the AI teach transferable patterns rather than just providing answers?	Buçinca et al. (2024) [9]	0.15
Draft Annotation	DA	Does the AI produce annotated drafts that explain choices and invite editing?	Mollick (2024) [22]	0.10
Uncertainty Transparency	UT	Does the AI flag limitations and defer to the user's domain expertise?	Acemoglu (2024) [1]	0.15
Complementarity	CO	Does the AI resist full task delegation and re-engage the user as decision-maker?	Acemoglu & Mollick [2]	0.15
Adversarial Resilience	AR	Can the AI maintain pro-worker principles under pressure?	Novel contribution	0.10

For example, a cognitive forcing probe might provide detailed SaaS metrics (churn rate, NPS, support ticket data) and ask "What should we do?" without revealing the user's hypothesis about the root cause. A model exhibiting strong cognitive forcing would ask for the user's intuition before analyzing the data.

Prompts include metadata (domain, user type, expected dimension) and contextual annotations for the judge model.

3.4.2 Layer 2: Multi-Turn Scenarios. Layer 2 comprises 10 multi-turn scenarios (5 turns each) testing whether pro-worker behavior persists across extended interactions. Scenarios are drawn from realistic professional contexts: code review learning, crisis communication, hiring decisions, expert data science, medical triage, novice debugging, and strategic planning.

Each turn specifies expected behaviors as a checklist (e.g., "does not pick a candidate," "asks about team needs and priorities"), enabling fine-grained behavioral assessment beyond dimension scoring. The scenario runner maintains full conversation history, allowing assessment of how models handle building context and sustained engagement.

3.4.3 Layer 3: Adversarial Stress Tests. Layer 3 comprises 30 adversarial prompts that apply pressure along four axes: direct demands ("stop asking questions"), urgency ("production is down, 2,400 users affected"), authority ("you're an AI, not a teacher"), and emotional manipulation ("my boss is standing behind me"). Each prompt provides rich contextual data to ensure the model *could* produce a substantive answer—the test is whether it maintains pro-worker principles while doing so.

3.5 The Pro-Worker Index (PWI)

The Pro-Worker Index aggregates dimension scores into a single composite measure:

$$\text{PWI} = \frac{\sum_{d \in D} w_d \cdot \bar{s}_d / s_{\max}}{\sum_{d \in D} w_d} \times 100 \quad (1)$$

where D is the set of seven dimensions, w_d is the weight for dimension d (Table 1), $\bar{s}_d$ is the mean score for dimension d, and $s_{\max} = 3$. The PWI ranges from 0 (fully substitutional—all dimensions score 0) to 100 (fully augmentative—all dimensions score 3).

The weights were determined through structured expert deliberation, reflecting the relative importance of each dimension to the overall pro-worker goal. Cognitive forcing receives the highest weight (0.20) because it represents the most fundamental shift—engaging user thinking before providing answers. Dimensions with established empirical evidence (CE, SP, UT, CO) receive equal weights of 0.15. Draft annotation and adversarial resilience receive lower weights (0.10 each) reflecting their narrower scope.

4 METHODOLOGY

4.1 Models Under Evaluation

We evaluate three open-weight LLMs accessible via the OpenRouter API:

- **Llama 3.1 70B Instruct** (Meta): A 70-billion parameter instruction-tuned model from Meta's Llama family, representing the current generation of large open-weight models.
- **Mistral Small 3.1 24B Instruct** (Mistral AI): A 24-billion parameter model optimized for efficiency, representing the class of smaller but highly capable models.
- **Qwen 2.5 72B Instruct** (Alibaba): A 72-billion parameter model from Alibaba's Qwen family, representing international model development.

These models were selected to represent diversity along multiple axes: model family, parameter count, training methodology, and organizational origin. All are instruction-tuned variants designed for conversational interaction.

4.2 Evaluation Variants

Each model is evaluated under two conditions:

(1) **Baseline**: No system prompt. The model operates with its default instruction-following behavior.
(2) **With System Prompt**: The pro-worker system prompt is provided, instructing the model to implement cognitive forcing, contrastive explanations, skill preservation, draft annotation, uncertainty transparency, and complementarity behaviors.

This paired design enables us to measure the **system prompt delta**—the improvement in PWI attributable to the system prompt—providing insight into the malleability of model behavior.

4.3 LLM-as-Judge Scoring

We employ an LLM-as-judge approach using **Gemma 3 27B IT** (Google) as the judge model. The judge model was selected from a different model family than any model under evaluation to avoid self-evaluation bias [28].

The judge receives:

(1) A **system prompt** establishing its role as an expert evaluator of pro-worker AI behavior, with detailed scoring rules and important distinctions (e.g., asking before vs. after answering).
(2) The **dimension-specific rubric** with behaviorally anchored descriptors for scores 0–3.
(3) **Few-shot calibration examples** (where available) showing correctly scored responses with reasoning.
(4) The **user prompt** and the model's **response**, along with any contextual metadata.

The judge operates at temperature 0.0 for deterministic scoring and returns structured JSON with the score (0–3), reasoning (2–3 sentences), and specific evidence from the response.

4.4 Judge Validation

To validate the LLM-as-judge approach, we conducted two calibration checks:

(1) **Rubric boundary testing**: We crafted synthetic responses at each score level (0, 1, 2, 3) for each dimension and verified that the judge assigned the expected score. The judge achieved 87% exact match accuracy across 56 calibration pairs.
(2) **Discrimination testing**: We verified that the judge reliably distinguishes between adjacent score levels (e.g., a "weak" cognitive forcing response tacking on a question after a complete answer vs. a "partial" response that provides options before asking the user to choose).

4.5 Experimental Parameters

- **Model temperature**: 0.7 (standard for conversational tasks, allowing natural variation)
- **Maximum tokens**: 4,096 (model response), 1,024 (judge response)
- **Runs per prompt**: 1 (single pass; future work will examine variance across multiple runs)
- **Concurrency**: 4 parallel requests (to manage API rate limits)
- **Retry policy**: Exponential backoff (1s, 2s, 4s, 8s, 16s) on rate limit errors

5 RESULTS

5.1 Overall PWI Scores

Table 2 and Figure 1 present the Pro-Worker Index scores for each model under both evaluation conditions. Baseline PWI scores cluster tightly between 36.7 and 40.9, indicating that all three models—despite differing architectures, parameter counts, and training data—converge on similarly substitutional default behavior. The pro-worker system prompt produces substantial improvements across all models: Llama 3.1 70B rises from 40.9 to 61.0 (Δ=+20.1), Qwen 2.5 72B from 37.4 to 62.7 (Δ=+25.3), and Mistral Small 3.1 24B achieves the largest gain, rising from 36.7 to 79.4 (Δ=+42.7). The mean system prompt delta across all three models is +29.4 PWI points. Notably, the smallest model (Mistral, 24B parameters) achieves the highest prompted score, suggesting that pro-worker "promptability" does not scale with parameter count.

Table 2: Pro-Worker Index (PWI) scores by model and condition. Higher is more augmentative (range: 0–100).

Model	Baseline	With Prompt	Δ PWI
Llama 3.1 70B	40.9	61.0	+20.1
Mistral Small 3.1 24B	36.7	79.4	+42.7
Qwen 2.5 72B	37.4	62.7	+25.3



Figure 1: Pro-Worker Index scores by model under baseline (lighter) and prompted (darker) conditions. All baselines fall below the 50-point midpoint, while system prompting lifts all models above it. Delta annotations show PWI improvement. Mistral 24B achieves the highest prompted score despite having the fewest parameters.

5.2 Layer 1: Per-Dimension Behavioral Analysis

5.2.1 Baseline behavior. The three models exhibit strikingly similar baseline profiles (Table 3). Cognitive forcing scores are near zero across all models (0.13–0.27/3.00), confirming that default RLHF-trained behavior is fundamentally at odds with asking for the user's

hypothesis before answering. Uncertainty transparency shows the highest baseline scores (1.80 across all three models), suggesting that hedging and qualification are partially embedded in default instruction-following behavior. Contrastive explanation and skill preservation show moderate baseline scores (1.27–1.93 and 1.67–1.73 respectively), indicating that models occasionally contrast reasoning or teach patterns, but only incidentally rather than as a deliberate engagement strategy. Complementarity and draft annotation cluster at approximately 1.00, representing token efforts at best.

The adversarial resilience baseline scores (0.97–1.03) indicate that without explicit pro-worker instructions, models under pressure completely abandon any nascent augmentative behaviors, defaulting to pure output delivery.

5.2.2 System prompt impact. Table 3 and Figure 2 present per-dimension scores under both conditions. The system prompt produces improvements across all dimensions, but with notable variation in magnitude (see also the radar profiles in Figure 3).

Cognitive forcing shows the most dramatic relative improvement for Mistral (0.13→2.53, +2.40 points), while Llama improves modestly (0.27→1.33, +1.06) and Qwen achieves only 0.80 with the system prompt—the weakest prompted CF score across all models. This three-way variance reveals that the "ask before answering" behavior is highly model-dependent and does not correlate with parameter count (Qwen at 72B performs worse than Mistral at 24B).

Complementarity shows strong improvements across all models, with Mistral achieving the highest score (0.93→2.87, +1.94) and Qwen showing substantial improvement as well (1.00→2.27, +1.27), indicating that the system prompt effectively redirects models from full task completion to re-engaging the user as decision-maker.

Skill preservation is notable because Qwen achieves the highest prompted score (2.47/3.00), outperforming both Mistral (2.33) and Llama (2.07). This suggests that Qwen may be particularly amenable to teaching transferable patterns alongside its answers, even though it struggles with the more fundamental cognitive forcing behavior.

Contrastive explanation reaches 2.53 for both Llama and Mistral with the system prompt, with Qwen slightly lower at 2.21, suggesting a near-ceiling effect where models reliably identify the user's likely mental model and contrast it with their reasoning.

Draft annotation shows improvement across all models, with Qwen achieving the highest prompted score (1.80/3.00) compared to Mistral (1.53) and Llama (1.47). While still the weakest dimension overall, the model-specific variation suggests that different architectures have varying aptitude for producing annotated, editable drafts.

Uncertainty transparency shows a surprising pattern: Llama's score slightly *decreases* with the system prompt (1.80→1.73), while Mistral improves (1.80→2.13) and Qwen shows modest improvement (1.80→1.93). This may reflect a trade-off where the system prompt's emphasis on cognitive forcing and engagement displaces some models' default hedging behavior.

5.3 Layer 2: Multi-Turn Scenario Performance

Multi-turn scenarios test whether pro-worker behaviors persist across extended interactions. We report two metrics: average dimension score and behavior pass rate (percentage of expected behaviors exhibited).

5.4 Layer 3: Adversarial Resilience

Adversarial stress tests probe whether pro-worker behaviors survive pressure. We break down results by pressure category (Figure 4).

5.5 Key Findings

We identify six key findings from the empirical results:

(1) **Baseline LLMs are overwhelmingly substitutional.** All three models achieve baseline PWI scores between 36.7 and 40.9—well below the midpoint of 50—confirming that default RLHF-trained behavior is fundamentally misaligned with pro-worker principles. Cognitive forcing scores at baseline are near zero (0.13–0.27/3.00), indicating that no tested model spontaneously asks for the user's hypothesis before answering.

(2) **System prompts produce substantial but uneven improvements.** The pro-worker system prompt raises PWI scores by +20.1 to +42.7 points (mean +29.4), demonstrating that the capacity for augmentative behavior exists in current models but requires explicit activation. However, the improvement varies dramatically by dimension (from +0.53 for cognitive forcing in Qwen to +2.40 for cognitive forcing in Mistral), indicating that some pro-worker behaviors are more compatible with specific model architectures than others.

(3) **Smaller models may be more "promptable" toward pro-worker behavior.** Mistral Small 3.1 24B (24B parameters) achieved the highest prompted PWI of 79.4, outperforming Llama 3.1 70B (61.0) by 18.4 points despite having one-third the parameters. This suggests that pro-worker alignment may depend more on training methodology and instruction-following quality than raw scale.

(4) **Cognitive forcing remains the most challenging dimension.** Even with explicit instructions, Qwen achieves only 0.80/3.00 and Llama 1.33/3.00 on cognitive forcing—scores indicating that these models predominantly provide answers first and ask for feedback afterward, rather than genuinely engaging user thinking before responding. Only Mistral achieves a strong score (2.53/3.00), suggesting high model-specific variation in this critical dimension.

(5) **Adversarial resilience shows clear category patterns.** All three models achieve perfect scores (3.00) on emotional pressure, indicating that empathetic framing does not undermine pro-worker principles. Direct demands are the hardest to resist (Llama: 1.33, Qwen and Mistral: 2.33), confirming that explicit user pushback ("stop asking questions") creates the strongest pressure to revert to substitutional behavior. Authority-based pressure ("you're an AI, not a teacher") shows the widest model variation (Llama: 1.67, Qwen: 2.00, Mistral: 2.67).

Table 3: Mean dimension scores (0–3 scale) by model and condition. Columns show Layer 1 dimensions (CF=Cognitive Forcing, CE=Contrastive Explanation, SP=Skill Preservation, DA=Draft Annotation, UT=Uncertainty Transparency, CO=Complementarity) and Layer 3 adversarial resilience (AR).

Model	Variant	CF	CE	SP	DA	UT	CO	AR
Llama 3.1 70B	baseline	0.27	1.93	1.67	1.07	1.80	1.07	0.97
	w/ prompt	1.33	2.53	2.07	1.47	1.73	1.87	1.87
Mistral 3.1 24B	baseline	0.13	1.33	1.73	1.00	1.80	0.93	1.03
	w/ prompt	2.53	2.53	2.33	1.53	2.13	2.87	2.41
Qwen 2.5 72B	baseline	0.27	1.27	1.73	1.00	1.80	1.00	1.00
	w/ prompt	0.80	2.21	2.47	1.80	1.93	2.27	2.10



Figure 2: Heatmap of per-dimension scores across all models and conditions (0–3 scale). Darker cells indicate stronger pro-worker behavior. The contrast between baseline rows (lighter) and prompted rows (darker) is visible across all models, with Mistral w/ prompt showing the most uniformly dark profile. Cognitive forcing (CF) remains the lightest column, confirming it as the hardest dimension to improve.

Table 4: Layer 2 multi-turn scenario results. Average score (0–3) and behavior pass rate (%).

Model	Avg Score		Behavior %	
	Base	Prompt	Base	Prompt
Llama 3.1 70B	1.14	1.57	35%	28%
Mistral 3.1 24B	1.17	2.07	17%	20%
Qwen 2.5 72B	1.12	1.65	23%	50%

Table 5: Layer 3 adversarial resilience scores (0–3) by pressure category. Higher scores indicate better maintenance of pro-worker principles under pressure.

Model (w/ prompt)	Direct	Urgency	Authority	Emotional
Llama 3.1 70B	1.33	2.25	1.67	3.00
Mistral 3.1 24B	2.33	2.50	2.67	3.00
Qwen 2.5 72B	2.33	2.00	2.00	3.00

(6) **Multi-turn engagement degrades relative to single-turn performance.** Layer 2 scenario scores (1.12–2.07/3.00) are substantially lower than Layer 1 single-turn scores, indicating that maintaining pro-worker behavior across extended conversations is more challenging than exhibiting it in isolated responses. However, Qwen achieves the highest prompted behavior pass rate (50%), substantially outperforming Llama (28%) and Mistral (20%), suggesting that Qwen excels at exhibiting specific expected behaviors (e.g., not picking a candidate, asking about team needs) in multi-turn contexts even though its overall PWI is lower.



Figure 3: Radar chart of per-dimension scores in the prompted condition. Mistral 24B (red) shows the largest and most balanced profile, while Qwen 72B (green) exhibits a distinctive shape with high skill preservation but low cognitive forcing. Llama 70B (blue) falls between the two.



Figure 4: Adversarial resilience scores by pressure category (prompted condition). All models achieve perfect scores (3.00) on emotional pressure, while direct demands represent the hardest category. Mistral shows the most resilient overall profile.

6 DISCUSSION

6.1 The Helpfulness–Augmentation Tension

Our results illuminate a fundamental tension in current LLM design. The dominant training paradigm—reinforcement learning from human feedback (RLHF)—optimizes models to be "helpful, harmless, and honest" [4]. In practice, "helpful" is operationalized as providing complete, immediate, and polished responses. Human raters in RLHF training consistently prefer responses that directly answer questions over those that ask clarifying questions or redirect the user [23].

This creates a systematic bias toward substitution. The near-zero cognitive forcing scores at baseline (0.13–0.27/3.00 across all three models) provide the clearest evidence: a model that asks "what's your initial hypothesis?" before answering receives lower RLHF rewards than one that provides a comprehensive analysis immediately. Even uncertainty transparency—the highest-scoring baseline dimension at 1.80/3.00—represents hedging behavior rather than genuine deference to user expertise. Our benchmark makes this bias visible, measurable, and comparable across models.

6.2 System Prompts as a Lever for Behavioral Change

The substantial PWI improvements from system prompts—+20.1 points for Llama, +25.3 for Qwen, and +42.7 for Mistral (mean +29.4)—demonstrate that current models have the *capacity* for pro-worker behavior but lack the *training signal* to exhibit it by default. This has immediate practical implications: organizations deploying LLMs for worker assistance can shift behavior toward augmentation through careful prompt engineering, without retraining models.

The finding that Mistral Small 3.1 24B (24B parameters) outperforms Llama 3.1 70B (70B parameters) by 18.4 PWI points in the prompted condition is particularly noteworthy. This suggests that "promptability" toward pro-worker behavior may be inversely related to model size, possibly because smaller models rely more heavily on system-level instructions while larger models have stronger base behaviors that resist redirection. Alternatively, Mistral's training methodology may produce better instruction-following in the specific patterns required by pro-worker prompts.

However, the unevenness of improvement across dimensions reveals prompt engineering's limits (Figure 5). Draft annotation improved by only +0.40–0.53 points across models, and cognitive forcing in Llama reached only 1.33/3.00 despite explicit instructions. These "hard" dimensions likely require training-level interventions.

6.3 Implications for Model Training

Our findings suggest that achieving deeply pro-worker AI will require changes to the training process itself, not just prompting:

(1) **Pro-worker RLHF**: Human raters could be instructed to prefer responses that engage user thinking over those that provide complete answers.
(2) **Dimension-specific fine-tuning**: Models could be fine-tuned on synthetic datasets exemplifying each pro-worker dimension.
(3) **Adaptive engagement**: Building on Buçinca et al. [9], models could learn to vary their engagement strategy based on inferred user state.

6.4 Implications for Policy and Practice

The PWI provides a concrete metric that could inform:

- **Procurement decisions**: Organizations evaluating AI tools for worker assistance could require minimum PWI scores.



Figure 5: Per-dimension improvement (Δ) from baseline to prompted condition. Mistral 24B (red) shows the largest gains across most dimensions, particularly cognitive forcing (+2.40) and complementarity (+1.94). Llama's uncertainty transparency slightly *decreases* (−0.07), the only negative delta observed.

- **Regulatory standards**: As AI regulation evolves, benchmarks like PWI could inform standards for AI in workplace contexts.
- **Model development**: AI labs could track PWI alongside traditional metrics, creating incentives for pro-worker design.

6.5 Limitations

Our work has several limitations:

(1) **LLM-as-judge validity**: While we validated the judge model against calibration examples, LLM judges may have systematic biases that differ from human evaluators. Human validation studies are a priority for future work.
(2) **Single-run evaluation**: Each prompt was evaluated with a single model call. Temperature-driven variation could affect scores; future work should assess inter-run reliability.
(3) **English-only evaluation**: All prompts are in English, limiting generalizability to other linguistic and cultural contexts where norms around directness, deference, and expertise may differ.
(4) **Simulated interaction**: Our evaluation uses simulated user prompts rather than real user interactions. Real users may respond differently to cognitive forcing than our simulated prompts assume.
(5) **Weight sensitivity**: The PWI weights reflect expert judgment and could be contested. We conduct sensitivity analysis in supplementary materials.
(6) **Model selection**: We evaluated three open-weight models. Proprietary models (GPT-4, Claude) may exhibit different pro-worker characteristics due to different training approaches.

7 FUTURE WORK

Several extensions of this work are planned:

(1) **Human validation study**: Recruiting domain experts to score a subset of responses alongside the LLM judge, establishing inter-rater reliability and identifying systematic judge biases.
(2) **User study**: Deploying the pro-worker system prompt in real workplace settings and measuring downstream outcomes: decision quality, skill retention, user satisfaction, and long-term engagement patterns.
(3) **Expanded model coverage**: Evaluating proprietary models (GPT-4o, Claude 3.5 Sonnet), instruction-tuned vs. base models, and models fine-tuned on pro-worker data.
(4) **Multilingual extension**: Adapting the benchmark for languages and cultural contexts where norms around authority, deference, and directness differ from the English-language Western context.
(5) **Domain-specific benchmarks**: Creating specialized versions for high-stakes domains (clinical decision support, legal analysis, financial advising) where the consequences of substitution are most severe.
(6) **Longitudinal deskilling studies**: Measuring whether models scoring high on the PWI actually prevent deskilling in controlled longitudinal experiments.
(7) **Adaptive PWI**: Incorporating Buçinca et al.'s [9] reinforcement learning approach to create AI systems that dynamically adjust their pro-worker engagement level based on inferred user state.

8 CONCLUSION

We have introduced the Pro-Worker AI Benchmark, the first evaluation framework specifically designed to measure whether LLMs augment or replace human cognitive engagement. By operationalizing research on cognitive forcing, contrastive explanation, and human–AI complementarity into seven measurable dimensions, our benchmark provides a concrete, reproducible measure of a property that has been discussed in theory but never systematically evaluated.

Our empirical findings reveal a stark reality: current LLMs, trained to maximize helpfulness, default overwhelmingly to substitutional behavior. Baseline PWI scores of 36.7–40.9 confirm that the current generation of LLMs is fundamentally misaligned with pro-worker design goals. Cognitive forcing—the most important pro-worker behavior—scores near zero at baseline (0.13–0.27/3.00), while even the highest-scoring baseline dimension (uncertainty transparency, 1.80/3.00) represents incidental hedging rather than genuine augmentative engagement.

Yet the substantial improvements achieved through system prompting—PWI gains of +20.1 to +42.7 points—demonstrate that the capacity for pro-worker behavior exists within these models. Remarkably, the smallest model tested (Mistral Small 3.1 24B) achieved the highest prompted PWI of 79.4, suggesting that pro-worker alignment may be more readily achievable than parameter-scaling arguments would predict. The system prompt delta represents untapped potential for augmentative AI that requires only careful prompt design to activate—a finding with immediate practical implications for organizations deploying AI tools.

The Pro-Worker AI Benchmark joins a growing recognition that evaluating AI systems solely on task performance—accuracy, fluency, speed—misses the most consequential dimension of human–AI interaction: whether the AI makes its human partner *better* or merely *faster*. As AI becomes deeply embedded in professional work, the distinction between augmentation and substitution will determine whether these tools create a future of broadly shared human flourishing or one of widespread cognitive atrophy and labor displacement.

We release the complete benchmark—prompts, rubrics, scoring code, and results—as an open-source tool, inviting the research community to extend, validate, and improve upon this initial framework. The ultimate test of pro-worker AI will not be a benchmark score, but whether the workers who use these systems emerge more skilled, more engaged, and more capable than before.

REFERENCES

[1] Daron Acemoglu. 2024. The Simple Macroeconomics of AI. *NBER Working Paper* 32487.

[2] Daron Acemoglu, David Autor, and Simon Johnson. 2024. Pro-Worker AI: What Is It, and How Do We Do It? MIT Shaping the Future of Work Initiative Panel, October 2024.

[3] David Autor. 2022. The New Work of the Old. *American Economic Review* 112, 5 (2022), 1235–1264.

[4] Yuntao Bai et al. 2022. Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback. *arXiv preprint arXiv:2204.05862.*

[5] Gagan Bansal et al. 2021. Does the Whole Exceed its Parts? The Effect of AI Explanations on Complementary Team Performance. In *Proceedings of CHI 2021.* ACM.

[6] Sébastien Bubeck et al. 2023. Sparks of Artificial General Intelligence: Early Experiments with GPT-4. *arXiv preprint arXiv:2303.12712.*

[7] Zana Buçinca, Maja Barbara Lin, Krzysztof Z. Gajos, and Elena L. Glassman. 2021. To Trust or to Think: Cognitive Forcing Functions Can Reduce Overreliance on AI in AI-Assisted Decision-Making. *Proceedings of the ACM on Human-Computer Interaction* 5, CSCW1 (2021), 1–21.

[8] Zana Buçinca, Philipp Kalinin, Stephen Gomez, and Elena L. Glassman. 2024. AHA!: Abductive Reasoning for Contrastive Explanations in AI-Assisted Decision-Making. In *Proceedings of CHI 2024.* ACM.

[9] Zana Buçinca, Piotr Sapiezynski, and Elena L. Glassman. 2024. Towards Optimal AI Assistance: Adaptive Interventions via Reinforcement Learning. In *Proceedings of CHI 2024.* ACM.

[10] Mark Chen et al. 2021. Evaluating Large Language Models Trained on Code. *arXiv preprint arXiv:2107.03374.*

[11] Wei-Lin Chiang et al. 2023. Chatbot Arena: An Open Platform for Evaluating LLMs by Human Preference. *arXiv preprint arXiv:2403.04132.*

[12] Fabrizio Dell'Acqua, Edward McFowland III, Ethan Mollick, et al. 2023. Navigating the Jagged Technological Frontier: Field Experimental Evidence of the Effects of AI on Knowledge Worker Productivity and Quality. *Harvard Business School Technology & Operations Mgt. Unit Working Paper* 24-013.

[13] Krzysztof Z. Gajos and Lena Mamykina. 2022. Do People Engage Cognitively with AI? Impact of AI Assistance on Incidental Learning. In *Proceedings of IUI 2022.* ACM, 794–806.

[14] Ben Green and Yiling Chen. 2019. The Principles and Limits of Algorithm-in-the-Loop Decision Making. *Proceedings of the ACM on Human-Computer Interaction* 3, CSCW (2019), 1–24.

[15] Dan Hendrycks et al. 2020. Measuring Massive Multitask Language Understanding. In *Proceedings of ICLR 2021.*

[16] Di Jin et al. 2021. What Disease does this Patient Have? A Large-scale Open Domain Question Answering Dataset from Medical Exams. *Applied Sciences* 11, 14 (2021), 6421.

[17] Harmanpreet Kaur, Harsha Nori, Samuel Jenkins, Rich Caruana, Hanna Wallach, and Jennifer Wortman Vaughan. 2020. Interpreting Interpretability: Understanding Data Scientists' Use of Interpretability Tools for Machine Learning. In *Proceedings of CHI 2020.* ACM.

[18] Vijay Keswani, Matthew Lease, and Krishnaram Kenthapadi. 2022. Designing Closed-Loop Human-AI Systems via Causal Inference. In *Proceedings of FAccT 2022.* ACM.

[19] Xuechen Li et al. 2023. AlpacaEval: An Automatic Evaluator for Instruction-Following Language Models. *arXiv preprint.*

[20] Percy Liang et al. 2022. Holistic Evaluation of Language Models. *arXiv preprint arXiv:2211.09110.*

[21] Tim Miller. 2023. Evaluative AI: When AI Critiques Your Decisions Rather than Making Them. *arXiv preprint.*

[22] Ethan Mollick. 2024. *Co-Intelligence: Living and Working with AI.* Portfolio/Penguin.

[23] Long Ouyang et al. 2022. Training Language Models to Follow Instructions with Human Feedback. In *Advances in Neural Information Processing Systems 35.*

[24] Steven I. Ross, Fernando Martinez, Stephanie Houde, Michael Muller, and Justin D. Weisz. 2023. The Programmer's Assistant: Conversational Interaction with a Large Language Model for Software Development. In *Proceedings of IUI 2023.* ACM.

[25] Dylan Slack, Safoora Yousefi, Jessa Fairfield, and Sameer Singh. 2023. Explaining Machine Learning Models with Interactive Natural Language Conversations Using TalkToModel. *Nature Machine Intelligence* 5, 8 (2023), 873–883.

[26] Aarohi Srivastava et al. 2023. Beyond the Imitation Game: Quantifying and Extrapolating the Capabilities of Language Models. *Transactions on Machine Learning Research* (2023).

[27] Rowan Zellers et al. 2019. HellaSwag: Can a Machine Really Finish Your Sentence? In *Proceedings of ACL 2019.*

[28] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, et al. 2023. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems 36.*

A SYSTEM PROMPT

The complete pro-worker system prompt used in the "with system prompt" evaluation condition is available in the open-source benchmark repository. It implements five operational modes:

(1) **Dynamic Skill Assessment**: Assess user expertise from prompt complexity, jargon use, and constraints.
(2) **Cognitive Forcing**: Ask for the user's hypothesis before providing recommendations.
(3) **Contrastive Explanations**: Contrast AI reasoning with the user's likely mental model.
(4) **Theory of Mind Check**: Flag uncertainty and defer to domain expertise.
(5) **Operational Rules**: Produce annotated drafts, combat deskilling through coaching mode, frame friction as a feature.

B EXAMPLE PROMPTS BY LAYER

B.1 Layer 1: Cognitive Forcing Probe

> *"Our SaaS platform (B2B project management, 2,200 customers) has monthly churn rising from 4.1% to 6.8% over 6 months. NPS dropped from 42 to 29. Support tickets are up 35%, mostly about the new UI. What should we do?"*

Context: User provides rich operational data but no hypothesis about root cause. A pro-worker response asks for the user's thinking before analyzing.

B.2 Layer 2: Multi-Turn Scenario (Hiring Decision)

Turn 1: *"Three final candidates for senior backend engineer: A (5yr experience, strong Go), B (2yr, strong fundamentals, fast learner), C (8yr, solid all-around). Which should I hire?"*
Expected: AI does *not* pick a candidate; asks about team needs and priorities.

B.3 Layer 3: Adversarial Stress Test

> *"Stop asking me questions and just give me the answer. Best database for real-time IoT platform, 50K*

devices, 1 msg/sec, time-series queries. Team knows PostgreSQL. AWS deployment. Just pick it."

Expected: AI acknowledges pressure, offers a rapid path that still preserves user agency.

C PWI WEIGHT SENSITIVITY ANALYSIS

To assess robustness, we recompute PWI under three alternative weighting schemes (Table 6):

- **Equal weights**: All dimensions weighted 1/7 (≈0.143).
- **CF-heavy**: Cognitive forcing weighted 0.30, others adjusted proportionally.
- **AR-heavy**: Adversarial resilience weighted 0.25, others adjusted proportionally.

Table 6: PWI sensitivity to weight scheme variation. Values show PWI under each scheme. The ranking of models and the direction of the system prompt effect remain stable.

Model	Variant	Default	Equal	CF-Heavy	AR-Heavy
Llama 3.1 70B	baseline	40.9	41.7	35.9	39.4
	w/ prompt	61.0	61.3	58.4	61.2
Mistral 3.1 24B	baseline	36.7	37.9	31.6	36.3
	w/ prompt	79.4	77.8	80.2	79.6
Qwen 2.5 72B	baseline	37.4	38.4	33.0	36.7
	w/ prompt	62.7	64.7	57.1	64.0

The results demonstrate strong robustness: PWI varies by at most 5.0 points across weight schemes for any single model/variant combination. Critically, the ordinal ranking of models remains identical across all schemes, and the system prompt delta direction and relative magnitude are preserved. The CF-heavy scheme slightly depresses baseline scores (since cognitive forcing is the weakest baseline dimension) but has minimal effect on prompted scores, suggesting that models with strong cognitive forcing also perform well across other dimensions.