

cpt_s 350

Homework 3

11641327 Yu-Chieh Wang

2020/2/20

1. Given: An array A of n elements.

Question: Find an algorithm can select both maximal and minimal elements by running at most $1.5n$ comparisons.

A[1]	A[2]	A[3]	A[4]	A[5]	A[6]	A[7]	A[8]	A[9]	A[10]	A[11]	A[12]	...	A[n]
------	------	------	------	------	------	------	------	------	-------	-------	-------	-----	------

Solution 1:

Use quick sort on the array A . Then, we can pick the maximal and minimal elements directly.

Solution 2:

Bigger value:	A[1]	A[4]	A[5]	A[7]	A[10]	A[11]	...	A[n-1]
							...	
Smeller value:	A[2]	A[3]	A[6]	A[8]	A[9]	A[12]	...	A[n]

First, We make every two elements a smell group, and do one comparison in each group. we will have $0.5n$ groups, so it's going to run $0.5n$ comparisons. Then, we make two large groups: One to combine the bigger value in each smell group. The other one combine the smeller value. Now, each large group has $0.5n$ elements.

Finally, when we do select number, we only compare to a large group ($0.5n$ comparisons). As a result, we spend $0.5n$ comparisons on separating an array to two groups, $0.5n$ comparisons on selecting the largest element, and $0.5n$ comparisons on

selecting the minimal element, which is totally $1.5n$ comparisons.

2. Compare the average-case complexities of two algorithm.

3. The worst-case complexities for $k=3$ and $k=7$.

4. Given: an algorithm called $\text{ilselect}(A, n, i)$.

Question: Find the worst-case and the average-case complexities.

We learn the time complexities of following algorithms, so we can do it directly.

	Best-case	Worst-case	Average-case
Quickselect	$O(1)$	$O(n^2)$	$O(n)$
Linearselect	$O(1)$	$O(n^2)$	$O(n)$

First of all, we separate the process of ilselect to three steps:

- (1) Do partition.
- (2) Run quickselect on the low part.
- (3) Run linearselect on the high part.

low part ($r-1$)	r	high part ($n-r$)
-----------------------	-----	------------------------

Then, we count the complexities by these steps:

(a) The worst-case complexities:

$$(1) T_{\text{WORST}}(n) = O(n)$$

$$(2) T_{\text{WORST}}(n) = \min_{1 \leq r \leq n} \{T_{\text{WORST}}(r-1)\} = O(r^2)$$

$$(3) \ T_{WORST}(n) = \min_{1 \leq r \leq n} \{T_{WORST}(n-r)\} = O((n-r)^2)$$

$$T_{WORST}(n) = O(n) + O(r^2) + O((n-r)^2) = O(n^2)$$

(b) The average-case complexities:

$$(1) \ T_{AVG}(n) = O(n)$$

$$(2) \ T_{AVG}(n) = \frac{1}{n} \sum_{r=1}^n \{T_{AVG}(r-1)\} = O(r)$$

$$(3) \ T_{AVG}(n) = \frac{1}{n} \sum_{r=1}^n \{T_{AVG}(n-r)\} = O(n-r)$$

$$T_{AVG}(n) = O(n) + O(r) + O(n-r))\} = O(n)$$

5. 5com