


MECHANICAL ENGINEERING PORTFOLIO

Angga Surya Anggana, B.S.M.E.

All descriptive works on this portfolio are made by permission from original copyright holder (employer) or fair usage with modification. No further original or derivatives works from all these materials to be reproduced, shared, or stored without prior permission from the author.


Auto Meganetoshi (New Development)

Automation can reduce labour costs and avoid human work accidents.
Precise production equipment for automation is needed for the constant desired quality of the product made.






Projected Assembly Drawing

0004	Bar Holder
0003	Plate Guide Bar
0002	Indexed Bar
0001	Guide Pin
Part No.	



Perspective View Made with SolidWorks



Minimum Factor of Safety
(FoS) = 21.1

Stress Distribution on Guide Pin (SUS 304)
when Handling Calculated with CalculiX


Services Include

Mechanical Concept Development, Detailed Design for Manufacturing, Material Selection, Analysis, Prototyping, Trial, and Vendor Liaison.


Rack Tube Silicon (New Development)

The proper place for placing process equipment can make longer usage ages of its equipment. Space availability on the production floor has become a common issue for layout.

Save spacing production floor mostly needed for an efficient layout.



Standard Three Views
Created



Two Rows Hanger Position Designed
Instead of Single Row for Save Spacing
Production Floor



Perspective View Made
with SolidWorks

Services Include


Mechanical Concept Initiation and Development,
Detailed Design for Manufacturing, Material
Selection, Trial, and Vendor Liaison.

Cover NC Grip (Renewal/Localization)


Cover NC Grip is part of the machine attachment enclosure. When this component brake out, it needs reparation if possible. Otherwise making of renewal component needed for replacement.

Measurement, modelling, and drawing from the existing physical object was taken due to the unavailable of drawing in Toyo Seal Indonesia. SolidWorks was used for modelling and drawing.

All parts components use fibreglass material.



Isometric View with Finish Assembly Shown with Three Parts Joined



Rendered Perspective View

Services Include

Reverse Engineering, Detailed Design for Manufacturing, and Vendor Liaison.

Rubber Seal Jig Dryer (Renewal/Localization)



Due to lack of quantity available of specific process equipment regarding of increase order from an external customer for Rubber Seal AMNR type, Toyo Seal Indonesia needs extra additional jig quantity. The jig is already available in small quantities but the drawing is not available yet.

New drawing needed to produce this jig, so measurement was taken and modeling of physical object with its drawing done with SolidWorks.



Rendered Perspective View

No.	Part Name	Qty.
1	L-Bolt M5	8
2	Holder	2
3	V Plate	2
4	Hexagonal Nut M6	4
5	L-Bolt M6	4
6	Washer M6	4
7	Washer M4	2
8	L-Bolt M4	2
9	Slide Frame	2
10	Hexagonal Nut M5	8
11	Spring Washer M5	8
12	Center Shaft	1
13	Round Bar	40




Standard 3 Views

Exploded View with Bill of Material of Rubber Seal Jig Dryer
Shown for Clarity of Its Component



All sheet metal parts are made from aluminium alloy, fasteners from carbon steel, and other parts from stainless steel. No issues were encountered during process of using this renewal jig.

Services Include

Reverse Engineering, Detailed Design for Manufacturing, Material Selection, Trial, and Vendor Liaison.



ITEM NO.	PART NUMBER	QTY.
1	Center Shaft	1
2	Side Frame	2
3	Holder	2
4	V Plate	2
5	Round Bar	40
6	ISO 4762 M5 x 10 - 10N	8
7	ISO - 4032 - M5 - W - N	8
8	ISO 4762 M6 x 12 - 12N	4
9	ISO - 4032 - M6 - W - N	4
10	ISO 4762 M4 x 6 - 6N	2



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE AUTHOR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE AUTHOR IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:
		DIMENSIONS ARE IN MILLIMETERS
		TOLERANCES:
		FRACTIONAL \pm
		ANGULAR: MACH \pm BEND \pm
		TWO PLACE DECIMAL \pm
		THREE PLACE DECIMAL \pm
		INTERPRET GEOMETRIC TOLERANCING PER:
		MATERIAL
		FINISH
NEXT ASSY	USED ON	
APPLICATION		DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	ANGGA	23/09/19
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		

SEAL POST CURE DRAINER

TITLE:

GENERAL ASSEMBLY

SIZE	DWG. NO.	REV
A		
SCALE: FREE		SHEET 1 OF 7


2

1

B

B

988



52

206

A

A

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE AUTHOR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE AUTHOR IS PROHIBITED.

NEXT ASSY

USED ON

APPLICATION

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN MILLIMETERS
TOLERANCES:
FRACTIONAL \pm
ANGULAR: MACH \pm BEND \pm
TWO PLACE DECIMAL \pm
THREE PLACE DECIMAL \pm

INTERPRET GEOMETRIC
TOLERANCING PER:

MATERIAL

FINISH

DO NOT SCALE DRAWING

NAME

ANGGA

DATE

23/09/19

DRAWN

CHECKED

ENG APPR.

MFG APPR.

Q.A.

COMMENTS:

SEAL POST CURE DRAINER

TITLE:

STANDARD 3 VIEWS

SIZE

A

DWG. NO.

REV

SCALE: FREE

SHEET 2 OF 7

2




1

2

1

B

B



A

A

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE AUTHOR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE AUTHOR IS PROHIBITED.

NEXT ASSY

USED ON

APPLICATION

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN MILLIMETERS
TOLERANCES:
FRACTIONAL \pm
ANGULAR: MACH \pm BEND \pm
TWO PLACE DECIMAL \pm
THREE PLACE DECIMAL \pm

INTERPRET GEOMETRIC
TOLERANCING PER:MATERIAL **SUS 304**

FINISH

DO NOT SCALE DRAWING

NAME

DATE

DRAWN

ANGGA

23/09/19

CHECKED

ENG APPR.

MFG APPR.

Q.A.

COMMENTS:

SEAL POST CURE DRAINER

TITLE:

CENTER SHAFT

SIZE

A

DWG. NO.

REV

SCALE: FREE



SHEET 3 OF 7

2

1

1

B








A

SHEET 4 OF 7



1

Tag	Direction	Angle	Inner Radius
A	UP	90°	1
B	DOWN	90°	1
C	DOWN	90°	1



<div>NO</div>		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	SEAL POST CURE DRAINER			
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ± 0.05 FRACTIONAL ± ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±		DRAWN	ANGGA	23/09/19	TITLE: HOLDER		
				CHECKED					
				ENG APPR.					
				MFG APPR.					
		INTERPRET GEOMETRIC TOLERANCING PER:		Q.A.			SIZE DWG. NO. REV A		
		MATERIAL AL 6063		COMMENTS:					
NEXT ASSY		USED ON		FINISH			SCALE: FREE		
APPLICATION		DO NOT SCALE DRAWING					SHEET 5 OF 7		




Tag	Direction	Angle	Inner Radius
A	UP	90°	1
B	UP	90°	1
C	UP	90°	1
D	UP	90°	1
E	DOWN	90°	1



<div>NO</div>		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	SEAL POST CURE DRAINER										
		DIMENSIONS ARE IN MILLIMETERS		DRAWN	ANGGA	23/09/19	TITLE: V PLATE									
		TOLERANCES: ±0.05		CHECKED												
		FRACTIONAL ±		ENG APPR.												
		ANGULAR: MACH± BEND ±		MFG APPR.												
		TWO PLACE DECIMAL ±		Q.A.			SIZE A				DWG. NO.		REV			
		THREE PLACE DECIMAL ±		COMMENTS:												
		INTERPRET GEOMETRIC TOLERANCING PER:							SCALE: FREE						SHEET 6 OF 7	
		MATERIAL		AL 6063												
NEXT ASSY		USED ON		FINISH												
APPLICATION				DO NOT SCALE DRAWING												

B

B

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE AUTHOR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE AUTHOR IS PROHIBITED.

NEXT ASSY

USED ON

APPLICATION

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN MILIMETERS
TOLERANCES:
FRACTIONAL \pm
ANGULAR: MACH \pm BEND \pm
TWO PLACE DECIMAL \pm
THREE PLACE DECIMAL \pm

INTERPRET GEOMETRIC
TOLERANCING PER:MATERIAL **SUS 304**

FINISH

DO NOT SCALE DRAWING

NAME

DATE

DRAWN

ANGGA

23/09/19

CHECKED

ENG APPR.

MFG APPR.

Q.A.

COMMENTS:

SEAL POST CURE DRAINER

TITLE:

ROUND BAR

SIZE

A

DWG. NO.

REV

SCALE: FREE

SHEET 7 OF 7

2


1

Page 13/22


Cover Radiator (New Development)

A Motorcycle radiator needs protection from external matters that can create physical or functional damage. For overcome this requirement, cover radiator is used and also to prevent accidental contact with the hot radiator.

Many mesh implemented to channel airflow efficiently with aesthetic design and branding (NSA) with aluminum as based material. Used as replacement variation of standard OEM parts.



Standard 2 (Two) Views with Colors Illustration




Rendered Perspective View
Made with Fusion 360

Services Include

Product benchmark, feasibility study, and preliminary design.

Cover Radiator with Spinner (New Development)

Cover radiator with additional spinner adds more aesthetic look for motorcycle and dynamic feel impression to attract attention when riding while still maintain cover radiator function as well. Use aluminum as base material with color combination. Used as replacement variation of standard OEM parts.



Standard 2 (Two) Views with Back View




Rendered Perspective View
Made with Fusion 360

Services Include

Product benchmark, feasibility study, and preliminary design.

Goods Hanger (New Development)


When small items need spillage or damage prevention and are carried safely on a motorcycle, it needs goods hanger that located in adequate position. This hanger uses titanium premium material for aesthetic look and for more durable usage. Used with branding (NSA) as replacement variation of standard OEM parts.




Standard 3 (Three) Projection Views



Rendered Perspective View Made with Fusion 360



Minimum Factor of Safety (FoS) = 9.6



Maximum Displacement = 0.03 mm


Numerical simulation when hanger handling goods (expected max. load 15 kg) carried by Fusion 360.

Services Include


Market research, product benchmark, feasibility study, finite element analysis, and preliminary design.

Pillion Footrest (New Development)


A motorcycle passenger needs a stable place to rest their feet and helps for balance, comfort, and safety. Pillion footrests used to accommodate those. Aluminum is used as the material for pillion footrests due to its lightweight and strength. Used with branding (NSA) as replacement variation of standard OEM parts.




Standard 3 (Three) Projection Views with Shown Attached Parts



Rendered Perspective View Made with Fusion 360



Minimum Factor of Safety (FoS) = 2



Maximum Displacement = 0.1 mm

Numerical simulation when a footrest withstands the expected maximum load of 40 kg carried by Fusion 360.


Services Include

Market research, product benchmark, feasibility study, finite element analysis, and preliminary design.



License Plate Cover (New Development)

Over time and use, motorcycle license plates can become dirty, peeled, and faded. To avoid these risks, a cover is needed as a protector. However, it is important to note that the license plate remains clearly visible.


Acrylic with branding (NSA) is used to make this cover with an aesthetic appearance as an additional accessory.





Standard 3 (Three) Projection Views



Rendered Perspective View Made with Fusion 360



Minimum Factor of Safety (FoS) = 15



Maximum Displacement = 0.22 mm


Services Include

Market research, product benchmark, feasibility study, finite element analysis, and preliminary design.

Numerical simulation when cover withstands on 120 km/h when rain carried by Fusion 360.

Frameless License Plate (New Development)


When a floating appearance is desired for a license plate, a frameless plate is used. Aluminum and Velcro with adhesive are used as materials due to its lightweight and strength. Branding (NSA) and pattern add an aesthetic impression for this additional accessory.



Isometric Exploded View
Shown Components



Rendered Perspective View Made
with Fusion 360



Minimum Factor of Safety
(FoS) = 15

Numerical simulation when cover withstands on 120 km/h when rain carried by Fusion 360.


Services Include

Market research, product benchmark, feasibility study, finite element analysis, and preliminary design.

Grab Rail (New Development)

Motorcycle passengers need safety and convenience when riding. A Grab Rail is used to accommodate those needs. Also, it helps riders to move their bike when not to ride and can be used for securing luggage.



Titanium with branding (NSA) is used as premium material due to its strength and elegance. Used as replacement variation of standard OEM parts.



Standard 3 (Three) Projection Views




Rendered Perspective View Made with Fusion 360



Minimum Factor of Safety (FoS) = 15

Numerical simulation when the grab rail withstands expected max. load of 25 kg carried by Fusion 360.



Maximum Displacement = 2 mm

Services Include

Market research, product benchmark, feasibility study, finite element analysis, and preliminary design.



