CONSOLIDATED MOCK-DEFENSE REPORT

BSIT 3-B Calleja - Neotech University SIMS

System flow, JavaScript, validation, QA, loopholes, vibe-coding indicators, panel questions, and improvements in one reviewer-friendly document.

Review date: 2026-09-28
Evidence-aware analysis - Confirmed, code-evidenced, suspected, and blocked results remain distinct.

Review date: 2026-09-28

Review mode: Standard system-only mock-defense analysis
Submitted source: `E:\3rdYEAR WEBSITE 100%\BSIT 3-B CALLEJA`
Evidence rule: Confirmed = reproduced in a clean local browser. Code-evidenced = directly supported by source but not executed end to end. Suspected and Not testable are labeled.

One-page panel brief

Ano ang system?

Ang Neotech University SIMS ay browser-based academic records prototype para sa dalawang active roles: **Administrator** at **Teacher**. May login, account management, sections, students, attendance, class records, grade review, reports, deletion requests, at trash/restore. Walang student login sa submitted source; ang student ay record/data subject lamang.

Readiness verdict

Prototype-ready for UI demonstration, not ready for real multi-user school deployment. Maayos at malawak ang interface, maraming useful validation at workflow screens, at syntactically valid ang tatlong inline JavaScript programs. Pero ang authentication, records, approvals, at audit data ay nasa browser `localStorage` lang. Ibig sabihin, madaling baguhin sa browser, hindi shared sa ibang browser/device, at puwedeng mawala kapag na-clear ang site data.

Strengths na puwedeng ipagtanggol

- Confirmed na nagre-redirect sa login ang admin page kapag walang session.
- Confirmed na nire-reject ang maling password at inactive account sa normal login form.
- May escaping helpers (`esc` , `escapeHTML`) sa maraming dynamic table output.
- May password length/username/email uniqueness checks para sa admin-created accounts.
- May score bounds, category weights totaling 100%, return reason, history entries, at trash/restore concepts.
- Lahat ng inline scripts passed syntax parsing: login 1/1, admin 2/2, teacher 1/1.

Top five risks

1. **Critical - Admin takeover:** role-only value sa `localStorage` is enough para magbukas ang admin dashboard.
2. **High - Teacher access without login:** direct URL opens a demo/first-teacher dashboard kahit walang session.
3. **High - No shared authoritative data:** isolated ang records per browser context; walang real server/database sync.
4. **High - Grade integrity:** fully blank class records can be submitted as Pending Review.
5. **High - Attendance integrity:** 1 of 2 students marked can be submitted and displayed as 100% attendance.

QA snapshot

Result	Count	Meaning
Passed	4	Expected control observed at runtime
Failed	8	Reproduced behavior differs from safe/required result
Not Run	2	Code reviewed, but no separate runtime case executed
Total	14	Risk-based Standard review set

Immediate panel focus: Hingin ang live explanation ng auth boundary, cross-device data flow, grade completion rule, attendance completeness rule, at teacher record scoping.

System explained simply

Actors and permissions

Actor	Intended actions	Actual boundary
Administrator	Manage academic reference data and accounts; review records; view reports; approve deletion	UI has these actions, but access is decided by editable client storage
Teacher	Manage own sections/students; record attendance and grades; submit to admin; view own history	Many records are filtered by teacher ID, but unassigned records leak into Class Record and direct access needs no valid session
Student	Represented in records only	No student account, portal, consent flow, or self-service module in submitted source
Browser storage	Holds accounts, sessions, records, settings, logs, and approvals	Acts like the database even though it has no server authorization, sharing, backup, or integrity controls

Modules and technology

- **Stack:** three standalone HTML files with embedded CSS and vanilla JavaScript; local JPG/PNG assets; no package manifest, backend, API, or database source.
- **Entry points:** `index.html`, `admin/dashboard.html`, `teacher/dashboard.html`.
- **Persistence:** browser `localStorage` keys such as `nt_admins`, `nt_teachers`, `nt_students`, `nt_sections`, `nt_attendance`, `nt_class_records`, and `nt_record_submissions`.
- **Main flow:** login reads accounts from the browser, writes a session object, redirects by role, and dashboards read/write the same browser store.

Overall actual flow

 Overall actual system flow

What this means: Mukhang complete multi-role system sa UI, pero ang shared point ay browser storage, hindi central service. Same browser profile/tab family lang ang naturally nagkakakita ng records.

Critical use cases

Use case	Preconditions	Main/alternate flow	Postcondition
Login	Account exists in localStorage	Match identifier, password, active status; else show error	Session JSON stored, role dashboard opened
Encode grades	Teacher and section/student records available	Select period, enter scores, save draft or submit	Class record and optional review snapshot stored
Attendance	Teacher section/student list available	Mark status per student, draft or submit	Attendance rows and review snapshot stored
Admin review	Submission exists in same browser storage	Approve or return with reason	Submission status/history updated
Delete/restore	Record exists	Move generic record to trash; restore or purge	Record moves between local arrays

Paper-to-system traceability: Not applicable. No capstone paper or formal requirements document was supplied, so intended behavior is reconstructed from UI labels, comments, and code. Any business expectation below is labeled as expected process, not a paper claim.

Essential flowcharts

Main transaction: class-record submission and review

 Class record review flow

Actual behavior: `submitSectionToAdmin()` sends every draft/returned student record to `submitClassRecordForReview()` without requiring a score, computed average, or completion percentage. The admin queue can therefore receive an empty record. Evidence: `teacher/dashboard.html:9520-9565`, `teacher/dashboard.html:8656-8715`.

Riskiest security flow: route guards

 Access control bypass flow

Actual behavior: Admin route checks only `session.role === "admin"`, then falls back to the first/hardcoded admin. Teacher route falls back to the first teacher or demo teacher and does not redirect. Evidence: `admin/dashboard.html:1596-1626`, `teacher/dashboard.html:5279-5361`.

Top findings

F-01 - Role-only session opens the admin dashboard

Severity: Critical | **Confidence:** High | **Status:** Confirmed
Affected: Administrator role, all academic records and account controls
Saan: `admin/dashboard.html:1596-1626`

- **Problema:** Editable browser data ang ginagamit bilang authorization proof.
- **Paano mabubutas:** In a clean browser, set `nt_current_user` to `{ "role": "admin" }`, then open the admin URL.
- **Expected vs Actual:** Expected rejection because no authenticated admin identity exists. Actual: dashboard opens as System Administrator.
- **Effect:** Full admin UI access, including accounts, records, approvals, settings, and trash.
- **Ayusin:** Server-issued secure session, server-side role check on every protected operation, and removal of account fallbacks.
- **Verification:** A forged/missing/expired token must return 401/403 and must not expose data.
- **Panel question:** Ano ang trusted proof na authenticated admin ang user, at bakit hindi editable ng browser?

Runtime evidence: clean Edge context opened the dashboard with only a role field; screenshot `admin-forged-session.png`.

F-02 - Teacher dashboard opens without a valid session

Severity: High | **Confidence:** High | **Status:** Confirmed
Affected: Teacher functions and student academic data
Saan: `teacher/dashboard.html:5279-5361`

- **Problema:** Kapag walang matching session, ginagamit ang first teacher o hardcoded demo teacher.
- **Paano mabubutas:** Open `/teacher/dashboard.html` directly in a clean browser.
- **Expected vs Actual:** Expected redirect to login. Actual: Juan Dela Cruz demo dashboard opens with full teacher controls.
- **Effect:** Anonymous user can enter the teacher workflow and create/edit browser-local school records.
- **Ayusin:** Require a valid server session and active teacher account before rendering or running any module.
- **Verification:** Direct URL and expired-session tests must always return to login.
- **Panel question:** Bakit may demo fallback sa production route, at paano ninyo pinipigilan ang anonymous write actions?

F-03 - No shared authoritative persistence

Severity: High | **Confidence:** High | **Status:** Confirmed
Affected: All users, accounts, grades, attendance, approvals, audit/history
Saan: `admin/dashboard.html:1471-1508`, `teacher/dashboard.html:5258-5270`, `teacher/dashboard.html:8616-8621`

- **Problema:** Browser-local arrays ang database at ang teacher-admin connection.
- **Paano mabubutas/fail:** Create data in browser context A, then open the same site in isolated context B.
- **Expected vs Actual:** Expected both authorized users to see the same data. Actual: A had 1 student while B had 0; clearing A removed the student and only reseeded the default admin.
- **Effect:** Hindi gumagana ang real cross-device collaboration; easy data loss and inconsistent school records.
- **Ayusin:** Central transactional database/API with authenticated CRUD, constraints, backups, and migration from local prototype data.
- **Verification:** Two separate devices must see the same committed record and approval history.
- **Panel question:** Paano makikita ng admin sa ibang computer ang submission ng teacher?

F-04 - Plaintext, default, and predictable passwords

Severity: High | **Confidence:** High | **Status:** Confirmed and code-evidenced
Affected: Admin and teacher accounts
Saan: `index.html:1854-1884`, `index.html:2084-2093`, `admin/dashboard.html:3672-3691`

- **Problema:** Default admin is `admin/admin123`; passwords are directly compared strings and stored as readable JSON. Teacher reset always becomes `neotech123`.
- **Expected vs Actual:** Expected one-time setup, hashed password verification, unique temporary secret, forced change, and no readable password. Actual: known/static secrets remain in client storage.
- **Effect:** Credential disclosure and easy account guessing/takeover.
- **Ayusin:** Server-side salted password hashing, bootstrap setup, unique expiring reset links/tokens, forced change, rate limiting, and generic login errors.
- **Verification:** No password appears in browser storage or API responses; reset tokens expire and cannot be reused.
- **Panel question:** Saan naka-hash ang password, at paano pinoprotektahan ang default/reset accounts?

F-05 - Completely blank grades can be submitted

Severity: High | **Confidence:** High | **Status:** Confirmed
Affected: Teacher, admin reviewer, students, grade integrity
Saan: `teacher/dashboard.html:9404-9449`, `teacher/dashboard.html:9520-9565`

- **Problema:** Status lang ang basis ng eligibility; walang completeness gate for score cells or calculated average.
- **Paano mababutas:** With two enrolled students, leave all score cells blank and click Submit to Admin.
- **Expected vs Actual:** Expected block with missing-score list. Actual: one Pending Review group was created for 2 students; both snapshots had `average: null` and empty item arrays.
- **Effect:** Admin can review/approve an academically incomplete record.
- **Ayusin:** Define completion rules per category/item/student and block submission until all required data is valid or an approved exception exists.
- **Verification:** Blank or incomplete required scores must never enter Pending Review.
- **Panel question:** Ano ang objective rule na nagsasabing complete na ang class record bago ma-submit?

F-06 - Partial attendance can be submitted and shown as 100%

Severity: High | **Confidence:** High | **Status:** Confirmed
Affected: Attendance records and admin review
Saan: `teacher/dashboard.html:11282-11347`, `teacher/dashboard.html:11390-11404`

- **Problema:** At least one marked student lang ang requirement. Rate denominator is only existing attendance rows.
- **Paano mababutas:** In a two-student section, mark only Student One as Present, leave Student Two blank, then submit.
- **Expected vs Actual:** Expected block or explicit Incomplete state. Actual: submission had `studentCount: 1`, UI said 1 of 2 marked, and rate displayed 100%.
- **Effect:** Misleading attendance and incomplete official records.
- **Ayusin:** Require one valid status for every active enrolled student, or document an explicit absent-by-default policy with confirmation.
- **Verification:** 1/2 marked cannot submit and cannot display 100% completion/attendance.
- **Panel question:** Ano ang denominator ng attendance rate, at paano hinahandle ang unmarked student?

F-07 - Unassigned records are exposed in Class Record

Severity: High | **Confidence:** High | **Status:** Confirmed
Affected: Teacher data scope and student privacy
Saan: strict manager filter at `teacher/dashboard.html:6505-6516`; permissive class-record filter at `teacher/dashboard.html:8547-8567`

- **Problema:** Sections manager hides records without a teacher ID, but Class Record explicitly treats unassigned items as a match for every teacher.
- **Paano mababutas:** Seed an unassigned section/student, sign in as another teacher, then open Class Record.
- **Expected vs Actual:** Dashboard showed 0 assigned sections, while Class Record listed the unassigned section and student `PRIVATE-1`.
- **Effect:** Cross-scope exposure and possible modification of records not assigned to the teacher.
- **Ayusin:** Deny by default; authorize every query and write by server-side teacher-section assignment.
- **Verification:** Unassigned and other-teacher data never appears in options, tables, reports, exports, or writes.
- **Panel question:** Bakit magkaiba ang scoping rule ng My Sections at Class Record?

F-08 - Partial grade categories are renormalized

Severity: Medium | **Confidence:** High | **Status:** Code-evidenced
Affected: Grade computation and dashboards
Saan: `teacher/dashboard.html:8792-8820`

- **Problema:** Blank categories are omitted, then completed category weights are renormalized to 100%.
- **Expected vs Actual:** Expected missing requirements to remain incomplete or follow a documented grading policy. Actual: a student with only one populated category can receive a complete-looking percentage based only on that category.
- **Effect:** Inflated or misleading interim grades, especially when submission is also allowed with missing data.
- **Ayusin:** Adopt and document one policy: treat required missing work as zero, mark grade Incomplete, or allow excused items only through an auditable exception.
- **Verification:** Test all combinations of missing category/item data against the approved formula.
- **Panel question:** Bakit hindi kasama sa denominator ang category na walang encoded score?

F-09 - Data-integrity rules are inconsistent and relationships can orphan

Severity: Medium | **Confidence:** High | **Status:** Code-evidenced
Affected: Students, sections, courses, class records, attendance
Saan: `admin/dashboard.html:1878-1915`, `admin/dashboard.html:2225-2298`, `admin/dashboard.html:2355-2396`, `teacher/dashboard.html:7015-7027`

- **Problema:** Teacher student form blocks duplicate Student IDs, but the generic admin student edit has no student uniqueness validator. Generic trash removal also removes a parent record without a referential constraint/cascade policy.
- **Effect:** Duplicate IDs can make grade/student lookups ambiguous; deleted sections/courses can leave linked student, attendance, or class-record rows inconsistent.
- **Ayusin:** Central database unique keys and foreign-key rules; explicit archive/cascade/reassignment workflow.
- **Verification:** Duplicate IDs must fail from every UI/API; deleting a referenced parent must be blocked or reconciled transactionally.
- **Panel question:** Aling layer ang final authority for uniqueness at relationships?

F-10 - Login reveals account existence and has no throttling

Severity: Medium | **Confidence:** High | **Status:** Code-evidenced
Affected: Login and account privacy
Saan: `index.html:2072-2105`

- **Problema:** Separate messages reveal Account not found, Incorrect password, and inactive account. The handler has no attempt counter, delay, lockout, or server rate limit.
- **Effect:** Easier username/email enumeration and automated guessing.
- **Ayusin:** Generic credential error, server-side throttling/lockout, monitoring, and secure recovery.
- **Verification:** Response should not reveal whether an identifier exists; repeated attempts must be rate limited.
- **Panel question:** Paano ninyo mapipigilan ang unlimited password guessing at account enumeration?

Recommended system improvements

Priority	Current condition	Add or change and intended process	Benefit	Success indicator
Critical	Client storage decides identity and permissions	Add backend authentication, secure server session, and role/ownership checks on every read/write	Prevents forged roles and direct-route bypass	Forged, expired, missing, and wrong-role sessions always return 401/403
Critical	Browser is the database	Add central transactional database/API; migrate prototype records through validated import	Shared, durable source of truth	Separate authorized devices see the same committed records
High	Known/plaintext passwords	Hash passwords server-side; bootstrap first admin; unique expiring resets; force first-login change	Protects credentials and account lifecycle	No password in browser/API; reset token is single-use and expires
High	Blank/incomplete grade submission	Add completion checklist per student/category/item before Pending Review	Protects grade integrity	Submission count is zero until all required data or approved exceptions are complete
High	Partial attendance can submit	Require every active student to have a status; show Completion separately from Attendance Rate	Prevents misleading totals	1 of 2 marked shows 50% completion and submission remains blocked
High	Teacher filters differ by module	Centralize assignment-based authorization with deny-by-default rules	Prevents cross-scope data exposure	Same allowed section set across dashboard, records, reports, and exports
Medium	IDs and relationships rely on UI logic	Add unique constraints, foreign keys, archive/reassign rules, and duplicate detection	Prevents ambiguous/orphan records	Duplicate and referenced-delete test cases fail safely
Medium	Audit/history is editable local data	Add append-only server audit events with actor, action, before/after, timestamp, and reason	Enables accountability and investigation	Ordinary users cannot edit/delete audit events
Medium	Site-data clearing loses records	Add automated backup, restore drill, export policy, and retention rules	Recovery and operational continuity	Restore drill meets defined recovery time/data-loss targets

Validation and process correctness

Boundary/process	Present control	Missing/incorrect control	Verdict
Client inputs	Required fields, email/number input types, password length, duplicate checks in selected forms	Client rules can be bypassed and differ by module	Partial
Server validation	None supplied	No API-side schema, ownership, uniqueness, transaction, or concurrency control	Incorrect for deployment
Database/business rules	Category total 100; score upper bound; some history/status rules	No authoritative database, foreign keys, or full completion rule	Partial prototype only
Authentication	Password and active-status check on normal login	Plaintext/default passwords, no secure session, route fallbacks	Incorrect
Authorization	Some teacher-ID filters	Client-controlled role; unassigned records visible; no operation-level server check	Incorrect
Grade workflow	Draft, submit, return, approve, history	Blank submission and partial-weight renormalization	Partial/incorrect
Attendance workflow	Per-student status and review snapshot	Partial roster accepted; misleading 100%	Incorrect
Admin review	Approve/return, reason required on return	Same editable browser store; no independent reviewer authority	UI-correct, trust model incorrect
Delete/restore	Trash and restore concepts	Generic parent deletion may orphan dependent data	Partial
Multi-user operation	Tabs in one browser share storage	Different browser/device does not share data	Incorrect

Important JavaScript functions

Function/responsibility	Location	What it does	User-visible/system effect
`matchAccount()` and login submit handler	`index.html:2009-2163`	Finds admin/teacher by username, email, or ID; compares password/status; stores session; redirects by role	Normal login works, but all trust remains client-side
Admin `guard()`	`admin/dashboard.html:1596-1628`	Checks only session role, then chooses matching, first, or fallback admin	Role-only session can become admin
`getCurrentTeacher()`	`teacher/dashboard.html:5279-5367`	Finds current teacher, otherwise first teacher or demo object	Direct route opens teacher dashboard without login
`renderCrud()` and form save handler	`admin/dashboard.html:2057-2146`, `2225-2303`	Renders tables/forms and writes arrays to localStorage	Fast prototype CRUD, no authoritative validation
`componentAverage()`	`teacher/dashboard.html:8792-8820`	Computes weighted grade using only categories with scored items	Missing categories are ignored and remaining weights renormalized
`submitClassRecordForReview()`	`teacher/dashboard.html:8656-8715`	Builds/updates one review group and snapshots per student	Teacher submission appears in same browser's admin queue
`submitSectionToAdmin()`	`teacher/dashboard.html:9520-9566`	Submits every draft/returned record in a section	Blank records can be moved to Pending Review
`submitAttendanceForReview()`	`teacher/dashboard.html:11282-11347`	Saves marked students and statuses as an attendance review group	Unmarked students are omitted, not blocked
`approveReview()` / `returnReview()`	`admin/dashboard.html:4188-4217`	Changes submission status and appends history; return requires reason	Approval UI works in same local store
`moveToTrash()`	`admin/dashboard.html:2355-2403`	Removes a record from one array and saves it in trash	Recoverable deletion, but no general relationship reconciliation

What the JavaScript does well

- Uses shared helpers for escaping and local read/write.
- Includes status history and version metadata in review submissions.
- Requires correction reason before returning a submission.
- Rejects score values above item total or below zero at save time.
- Requires category weights to total exactly 100%.

These are useful prototype behaviors, but they need equivalent server/database enforcement before deployment.

Vibe-coding implementation-risk indicators

These are observable implementation risks, **not proof of AI authorship**.

V-01 - Production route contains a demo fallback

Location: `teacher/dashboard.html:5327-5361`
Responsibility: `getCurrentTeacher()`
Confidence: High

```
if (teachers.length > 0) {
    return teachers[0];
}
return {
    id: "TCH-DEMO",
    fullName: "Juan Dela Cruz",
    teacherId: "TCH-2026-001"
};
```

What it does: Supplies an identity when authentication cannot resolve one.
Why signal: Test/demo convenience is mixed into the protected runtime path.
System effect: Anonymous direct access opens full teacher controls.

V-02 - Missing admin identity becomes a hardcoded administrator

Location: `admin/dashboard.html:1610-1625`
Responsibility: Admin session guard
Confidence: High

```
currentAdmin = admins.find(item =>
    item.id === session.id ||
    item.username === session.username ||
    item.email === session.email
) || admins[0] || {
    id: "ADM-DEFAULT",
    username: "admin",
    password: "admin123"
};
```

What it does: Replaces a missing match with another account/default.
Why signal: Happy-path display fallback overrides identity verification.
System effect: A role-only session becomes an administrator.

V-03 - UI text says send to admin, code writes localStorage

Location: `teacher/dashboard.html:8616-8621`, `teacher/dashboard.html:8715`
Responsibility: Class-record submission bridge
Confidence: High

```
/* Bridges this teacher dashboard to the Admin Dashboard's
   "nt_record_submissions" review queue, so "Submit to admin",
   "Approve", and "Return for Correction" stay in sync on both
   sides even across separate open tabs. */
localStorage.setItem(SUBMISSIONS_KEY, JSON.stringify(submissions));
```

What it does: Shares state across tabs in one browser origin.
Why signal: UI/business wording implies a multi-user handoff, while implementation only supports local tabs.
System effect: Another browser/device does not receive the submission.

V-04 - Two modules apply opposite ownership rules

Location: `teacher/dashboard.html:6505-6516`, `teacher/dashboard.html:8556-8567`
Responsibility: Teacher section scoping
Confidence: High

```
// Sections manager: unassigned is rejected.
return false;

// Class Record: unassigned is accepted for every teacher.
return !item?.teacherId && !item?.teacherID && !item?.teacher_id
    ? true
    : [item.teacherId, item.teacherID, item.teacher_id]
        .some(v => teacherIds.includes(String(v)));
```

What it does: Produces different accessible datasets for the same teacher.
Why signal: Local fixes were added per module without one authorization policy.
System effect: Dashboard shows 0 assigned sections while Class Record exposes an unassigned section/student.

V-05 - Validation coverage depends on which screen edits the record

Location: `admin/dashboard.html:1878-1915`, `teacher/dashboard.html:7015-7027`
Responsibility: Student create/edit validation
Confidence: High

```
// Teacher form checks duplicate Student ID.
const duplicate = students.some(student => {
    const existingStudentId = String(student.studentId || "").trim().toLowerCase();
    return existingStudentId === studentId.toLowerCase() && existingId !== editId;
});

// Admin student model has normalize only; no validate function.
```

What it does: One UI blocks duplicates while another generic edit path does not.
Why signal: Business rules are duplicated/incomplete at individual screens instead of enforced centrally.
System effect: Same data rule can pass or fail depending on the editor used.

QA summary and high-value test cases

ID	Test	Expected	Actual	Status	Severity
QA-01	Parse every inline script	No syntax error	Login 1/1, admin 2/2, teacher 1/1 passed	Passed	High
QA-02	Submit wrong admin password	Stay on login with safe rejection	Incorrect password shown; no session	Passed	Medium
QA-03	Login inactive teacher	Reject and create no session	Inactive message shown; session null	Passed	High
QA-04	Open admin URL without session	Redirect to login	Redirected to `index.html`	Passed	High
QA-05	Forge `{role:"admin"}` only	Reject identity-less session	Admin dashboard opened	Failed	Critical
QA-06	Open teacher URL without session	Redirect to login	Demo teacher dashboard opened	Failed	High
QA-07	First-run credentials	Require secure setup	`admin/admin123` seeded in readable storage	Failed	High
QA-08	Data in isolated browser contexts	Authorized users share one dataset	Context A had 1 student; context B had 0	Failed	High
QA-09	Clear site storage	Records recover from server/backup	Student disappeared; only default admin reseeded	Failed	High
QA-10	Submit all-blank section grades	Block and list missing requirements	2 blank student records became Pending Review	Failed	High
QA-11	Submit 1 of 2 attendance rows	Block as incomplete	Submitted 1 student and displayed 100%	Failed	High
QA-12	View unassigned data as teacher	Hide unless assigned	Unassigned section/student appeared in Class Record	Failed	High
QA-13	Edit duplicate Student ID through admin	Reject from every path	Admin student model has no uniqueness validator	Not Run	Medium
QA-14	Return review with blank reason	Require non-empty reason	Code has trim check; separate runtime case not executed	Not Run	Medium

Evidence-aware interpretation

- A Failed result is not theoretical: QA-05, QA-06, QA-08 to QA-12 were reproduced in clean local browser contexts.
- QA-13 and QA-14 are not called Passed because no separate runtime interaction was executed.
- No destructive, production, real-account, network, dependency-install, seed, or migration test was performed.

Five strongest panel questions

1. What makes an admin session trustworthy?

Why ask: Runtime test showed `{role:"admin"}` alone opens the dashboard.
Strong answer: Dapat sabihin na current prototype has no secure trust boundary, then propose server-issued HttpOnly secure session, expiry/rotation, and server-side RBAC per operation.
Follow-up: Show the exact code that rejects a role-only forged session.
Red flags: "Nakatago naman ang localStorage", "front end lang ang puwedeng gumamit", or relying on disabled buttons.

2. How does a teacher submission reach an admin on another computer?

Why ask: Current code writes `nt_record_submissions` only to localStorage.
Strong answer: Admit same-browser limitation and describe authenticated API/database write, server transaction, notification/queue, reviewer query, and audit event.
Follow-up: What happens if teacher and admin use different browsers at the same time?
Red flags: "Automatic sync" without backend/database evidence, or confusing tabs with devices.

3. What exact rule makes a class record complete enough to submit?

Why ask: Fully blank records became Pending Review.
Strong answer: Required roster, required category items, score range, missing/excused policy, completeness summary, and a server-side submission gate.
Follow-up: Should a missing category be zero, Incomplete, or excluded? Who approved that policy?
Red flags: "Admin will notice", visual checking only, or no documented grading rule.

4. Why did 1 of 2 marked students show 100% attendance?

Why ask: It confuses attendance rate with completion rate.
Strong answer: Attendance rate denominator must be the active roster or explicitly defined eligible roster; unmarked count must remain visible and block submission.
Follow-up: How are late, excused, added/dropped, and duplicate roster cases handled?
Red flags: Counting only existing attendance rows or defaulting blanks silently.

5. How is teacher ownership enforced consistently?

Why ask: My Sections hid unassigned records while Class Record exposed them.
Strong answer: One server-side authorization query based on teacher-section assignment, deny by default, reused for list/detail/export/write operations, with tests for unassigned and other-teacher data.
Follow-up: Why does `crTeacherMatches()` return true when all teacher IDs are missing?
Red flags: Per-page filters, trusting hidden UI, or allowing unassigned data to everyone.

Limited defense-time answer guide

If five minutes lang, the honest strong position is: **This is a functional front-end prototype. The next required phase is a real backend security and persistence layer, followed by complete grade/attendance submission rules and consistent assignment-based authorization.** Do not claim production security or cross-device synchronization from this submission.

Coverage, assumptions, limitations, and evidence

Reviewed

- All six submitted files inventoried; all three HTML/JavaScript entry points inspected.
- Authentication/session, accounts, teacher/admin route guards, academic CRUD, section/student scoping, attendance, class records, grade calculation, review workflow, reports, trash/restore, and settings sampled by risk.
- 14 QA cases designed; 12 executed or directly reproduced through syntax/runtime checks, 2 retained as Not Run.
- Three implementation-accurate flowcharts created from source and runtime behavior.

Confirmed runtime environment

- Local read-only HTTP serving at `127.0.0.1`.
- Clean headless Microsoft Edge browser contexts.
- No submitted file was edited; all generated artifacts are outside the app under workspace `analysis/`.

Assumptions

- UI wording "Submit to admin" implies teacher and admin may be separate people/devices.
- Grade and attendance records are expected to be complete and authoritative before approval.
- Unassigned or another teacher's records should not be visible/editable without explicit authorization.

These assumptions should be validated against the capstone paper or school policy if later supplied.

Not testable / not supplied

- No capstone paper, formal requirements, grading policy, data-retention policy, deployment guide, backend/API, database schema, server logs, production environment, real multi-user network, or automated test suite.
- Cross-device synchronization cannot exist in the submitted source; isolated browser-context behavior was confirmed instead.
- Accessibility, load/performance, recovery under storage quota/corruption, and full CRUD combinations were not exhaustively tested in Standard mode.
- No claim is made that vibe-coding indicators prove AI authorship.

Compact evidence summary

Evidence	Result	Source
Source inventory	3 HTML, 3 image/settings assets; no paper/backend/manifest	Workspace file inventory
JavaScript syntax	4 of 4 inline scripts passed parser	Node `vm.Script` check
Default login	`admin/admin123` succeeded	Clean browser runtime plus `index.html:1854-1884`
Admin direct no session	Correctly redirected	Clean browser runtime
Forged admin	Role-only session opened dashboard	Clean browser runtime plus `admin/dashboard.html:1596-1626`
Teacher direct no session	Demo teacher dashboard opened	Clean browser runtime plus `teacher/dashboard.html:5279-5361`
Blank grades	2 empty records became Pending Review	Clean browser runtime plus `teacher/dashboard.html:9520-9565`
Partial attendance	1 of 2 submitted; UI displayed 100%	Clean browser runtime plus `teacher/dashboard.html:11390-11404`
Ownership inconsistency	Unassigned section/student visible in Class Record	Clean browser runtime plus `teacher/dashboard.html:8547-8567`
Persistence isolation	Context A data absent in context B; clear removed it	Clean isolated browser contexts

Bottom line: The strongest defense is to present this honestly as a broad front-end prototype, show the working UI and validation strengths, then clearly scope the missing backend, security, authoritative persistence, and completeness rules as required next work.