Database Programming with SQL 6-1: Cross Joins and Natural Joins

Objectives

- Construct and execute a natural join using ANSI-99 SQL join syntax
- Create a cross join using ANSI-99 SQL join syntax
- Explain the importance of having a standard for SQL as defined by ANSI
- Describe a business need for combining information from multiple data sources

Vocabulary

Identify the vocabulary word for each definition below.

\

- Returns the Cartesian product from two tables. Cross join
- Joins two tables based on the same column name. Inner join

Try It / Solve It

Use the Oracle database for problems 1-3.

1. Create a cross-join that displays the last name and department name from the employees and departments tables.

SELECT last_name, department_name

FROM employees

CROSS JOIN departments;

2. Create a query that uses a natural join to join the departments table and the locations table. Display the department id, department name, location id, and city.

SELECT department_id, department_name, location_id, city

FROM departments

NATURAL JOIN locations;

3. Create a query that uses a natural join to join the departments table and the locations table. Restrict the output to only department IDs of 20 and 50. Display the department id, department name, location id, and city.

SELECT department_id, department_name, location_id, city

FROM departments

NATURAL JOIN locations

WHERE department_id IN (20, 50);

Database Programming with SQL

6-2: Join Clauses

Objectives

- Construct and execute a natural join using ANSI-99 SQL join syntax
- Create a cross join using ANSI-99 SQL join syntax
- Explain the importance of having a standard for SQL as defined by ANSI
- Describe a business need for combining information from multiple data sources

Vocabulary

Identify the vocabulary word for each definition below.

- Allows a natural join based on an arbitrary condition or two columns with different names, JOIN USING
- Performs an equijoin based on one specified column name JOIN ON

Try It / Solve It

Use the Oracle database for problems 1-6.

1. Join the Oracle database locations and departments table using the location_id column. Limit the results to location 1400 only.

SELECT department id, department name, location id, city

FROM departments

INNER JOIN locations

ON departments.location id = locations.location id

WHERE locations.location_id = 1400;

2. Join DJs on Demand d_play_list_items, d_track_listings, and d_cds tables with the JOIN USING syntax. Include the song ID, CD number, title, and comments in the output.

SELECT d_play_list_items.song_id, d_cds.cd_number, d_track_listings.title,

d_play_list_items.comments

FROM d_play_list_items

JOIN d_track_listings USING (song_id)

JOIN d cds USING (cd number);

3. Display the city, department name, location ID, and department ID for departments 10, 20, and 30 for the city of Seattle.

SELECT locations.city, departments.department_name, departments.location_id,

departments.department_id

FROM departments

INNER JOIN locations

ON departments.location_id = locations.location_id

WHERE departments.department_id IN (10, 20, 30)

AND locations.city = 'Seattle';

4. Display country name, region ID, and region name for Americas.

SELECT countries.country_name, countries.region_id, regions.region_name

FROM countries

INNER JOIN regions

ON countries.region_id = regions.region_id

WHERE regions.region_name = 'Americas';

5. Write a statement joining the employees and jobs tables. Display the first and last names, hire date, job id, job title, and maximum salary. Limit the query to those employees who are in jobs that can earn more than \$12,000.

SELECT employees.first_name, employees.last_name, employees.hire_date, employees.job_id, jobs.job_title, jobs.max_salary

FROM employees

INNER JOIN jobs

ON employees.job_id = jobs.job_id

WHERE jobs.max_salary > 12000;

6. Display job title, employee first name, last name, and email for all employees who are stock Clerks. The following questions use the JOIN...ON syntax:

SELECT jobs.job_title, employees.first_name, employees.last_name, employees.email FROM employees

JOIN jobs

ON employees.job_id = jobs.job_id

WHERE jobs.job_title = 'Stock Clerk';

7. Write a statement that displays the employee ID, first name, last name, manager ID, manager first name, and manager last name for every employee in the employees table. Hint: this is a self-join.

SELECT employee_id, first_name AS employee_first_name, last_name AS employee_last_name, manager_id, first_name AS manager_first_name, last_name AS manager_last_name

FROM employees

LEFT JOIN employees

ON e.manager_id = employee_id;

8. Use JOIN ON syntax to query and display the location ID, city, and department name for all Canadian locations.

SELECT locations.location_id, locations.city, departments.department_name FROM locations

JOIN departments

ON locations.location_id = departments.location_id

WHERE locations.country_id = 'CA'; -- Assuming 'CA' is the country ID for Canada

9. Query and display manager ID, department ID, department name, first name, and last name for all employees in departments 80, 90, 110, and 190.

SELECT manager_id, department_id, department_name, first_name, last_name FROM employees

JOIN departments ON department_id = department_id

WHERE department id IN (80, 90, 110, 190);

10. Display employee ID, last name, department ID, department name, and hire date for those employees whose hire date was June 7, 1994.

SELECT employee_id, last_name, department_id, department_name, hire_date FROM employees

JOIN departments ON department_id = department_id

WHERE hire date = TO DATE('1994-06-07', 'YYYY-MM-DD');

_

Database Programming with SQL 6-3: Inner versus Outer Joins

Objectives

- Compare and contrast an inner and an outer join
- Construct and execute a query to use a left outer join
- Construct and execute a query to use a right outer join
- Construct and execute a guery to use a full outer join

Vocabulary

Identify the vocabulary word for each definition below.

- Performs a join on two tables, retrieves all the rows in the Left table, even if there is no match in the Right table. It also retrieves all the rows in the Right table, even if there is no match in the Left table. FULL OUTER JOIN
- A join that returns the unmatched rows as well as matched rows OUTER JOIN
- Performs a join on two tables, retrieves all the rows in the Left table even if there is no match in the Right table. LEFT OUTER JOIN
- Performs a join on two tables, retrieves all the rows in the Right table even if there is no match in the Left table. RIGHT OUTER JOIN

• A join of two or more tables that returns only matched rows **INNER JOIN**

Try It / Solve It

Use the Oracle database for problems 1-7.

1. Return the first name, last name, and department name for all employees including those employees not assigned to a department.

SELECT e.first_name, e.last_name, d.department_name

FROM employees e

LEFT JOIN departments d

ON e.department_id = d.department_id;

2. Return the first name, last name, and department name for all employees including those departments that do not have an employee assigned to them.

SELECT e.first_name, e.last_name, d.department_name

FROM employees e

RIGHT JOIN departments d

ON e.department_id = d.department_id;

3. Return the first name, last name, and department name for all employees including those departments that do not have an employee assigned to them and those employees not assigned to a department.

SELECT e.first_name, e.last_name, d.department_name

FROM employees e

FULL OUTER JOIN departments d

ON e.department_id = d.department_id;

4. Create a query of the DJs on Demand database to return the first name, last name, event date, and description of the event the client held. Include all the clients even if they have not had an event scheduled.

SELECT c.first_name, c.last_name, e.event_date, e.description

FROM clients c

LEFT JOIN events e

ON c.client_id = e.client_id;

5. Using the Global Fast Foods database, show the shift description and shift assignment date even if there is no date assigned for each shift description.

SELECT s.shift_description, sa.assignment_date

FROM shifts s

LEFT JOIN shift_assignments sa

ON s.shift_id = sa.shift_id;

_

Database Programming with SQL

6-4: Self Joins and Hierarchical Queries

Objectives

- Construct and execute a SELECT statement to join a table to itself using a self-join
- Interpret the concept of a hierarchical query
- Create a tree-structured report
- Format hierarchical data
- Exclude branches from the tree structure

Vocabulary

Identify the vocabulary word for each definition below.

- Joins a table to itself Self-Join
- Retrieves data based on a natural hierarchical relationship between rows in a table.
 Hierarchy Query
- Determines the number of steps down from the beginning row that should be returned by a hierarchical query LEVEL
- Identifies the beginning row for a hierarchical query Root Row
- Specifies the relationship between parent rows and child rows of a hierarchical query CONNECT BY

Try It / Solve It

For each problem, use the Oracle database.

1. Display the employee's last name and employee number along with the manager's last name and manager number. Label the columns: Employee, Emp#, Manager, and Mgr#, respectively. SELECT last_name AS Employee, employee_id AS Emp#, last_name AS Manager, employee_id AS Mgr#

FROM employees

JOIN employees ON manager_id = employee_id;

2. Modify question 1 to display all employees and their managers, even if the employee does not have a manager. Order the list alphabetically by the last name of the employee.

SELECT last_name AS Employee, e.employee_id AS Emp#, last_name AS Manager, employee_id AS Mgr#

FROM employees

LEFT JOIN employees ON manager id = employee id

ORDER BY last name:

3. Display the names and hire dates for all employees who were hired before their managers, along with their managers' names and hire dates. Label the columns Employee, Emp Hired, Manager and Mgr Hired, respectively.

SELECT last_name AS Employee, hire_date AS "Emp Hired", last_name AS Manager, hire_date AS "Mgr Hired"

FROM employees

JOIN employees ON manager_id = employee_id

WHERE hire_date < hire_date;

4. Write a report that shows the hierarchy for Lex De Haans department. Include last name, salary, and department id in the report.

SELECT last_name, salary, department_id

FROM employees

START WITH last name = 'De Haan'

CONNECT BY PRIOR employee_id = manager_id;

5. What is wrong in the following statement?

SELECT last_name, department_id, salary

FROM employees

START WITH last_name = 'King'

CONNECT BY PRIOR manager_id = employee_id;

Change "CONNECT BY PRIOR manager_id = employee_id" to "CONNECT BY PRIOR employee_id = manager_id"

6. Create a report that shows the organization chart for the entire employee table. Write the report so that each level will indent each employee 2 spaces. Since Oracle Application Express cannot display the spaces in front of the column, use - (minus) instead.

SELECT LPAD('-', 2 * (LEVEL - 1)) || last_name AS Employee, employee_id, manager_id FROM employees

START WITH manager_id IS NULL

CONNECT BY PRIOR employee_id = manager_id;

7. Re-write the report from 6 to exclude De Haan and all the people working for him

SELECT LPAD('-', 2 * (LEVEL - 1)) \parallel last_name AS Employee, employee_id, manager_id FROM employees

START WITH manager_id IS NULL

CONNECT BY PRIOR employee_id = manager_id

AND PRIOR employee_id NOT IN (SELECT employee_id FROM employees WHERE last_name = 'De Haan');