

Db2 Cheat Sheet for development



Created by:
Andres Gomez Casanova
(@angoca)
Version: 2019-08-04

Get the most recent version at

<https://github.com/angoca/db2-cheat-sheet/Db2CheatSheetForDev.pdf>

Execution of a file in the console (db2clp)

- Semi-colon separated sentences:

```
db2 -t
```

- At sign separated sentences (when there is SQL PL code):

```
db2 -td@
```

Define a terminator character

```
--#SET TERMINATOR @
```

List all databases (aliases)

```
LIST DB DIRECTORY
```

Connect to a database (alias)

```
CONNECT TO mydb
```

Disconnect from a database

```
CONNECT RESET  
TERMINATE
```

Get values from the environment (registry values)

- Current timestamp

```
VALUES CURRENT_TIMESTAMP
```
- Connected user

```
VALUES CURRENT_USER
```
- Current database

```
VALUES CURRENT_SERVER
```

List all tables

```
LIST TABLES  
LIST TABLES FOR SCHEMA myuser  
LIST TABLES FOR ALL
```

Change current schema

```
SET CURRENT_SCHEMA otherschema
```

Change the isolation level (RR, RS, CS, UR)

```
SET ISOLATION RR
```

List all tablespaces with their status

```
LIST TABLESPACES
```

Describe the structure of the table

```
DESCRIBE TABLE tb11
```

Describe the result of a query

```
DESCRIBE SELECT * FROM tb11
```

Get help for a Db2 command

```
? command
```

Get help for a SQL code (SQLXXXX) or SQLstate (YYYYY)

```
? SQLXXX
```

```
? YYYYY
```

DDL

Create a schema

```
CREATE SCHEMA sch1
```

Create a table specifying primary key

```
CREATE TABLE tb11 (col1 CHAR(1) NOT NULL  
PRIMARY KEY)
```

```
CREATE TABLE tb12 (col1 INT NOT NULL, col2  
DATE NOT NULL, PRIMARY KEY (col1, col2))
```

Create a table specifying tablespaces

```
CREATE TABLE tb13 (col1 INT NOT NULL, col2  
CHAR(1)) IN ts1 INDEX IN ts2
```

Create a table specifying schema

```
CREATE TABLE sch1.tb14 (col1 INT)
```

Create a table with auto incremental column

```
CREATE TABLE tb15 (col1 INT NOT NULL  
GENERATED AS IDENTITY)
```

Create a table like another one

```
CREATE TABLE tb16 LIKE tb11 IN ts1 INDEX IN  
ts2
```

Comment on table and column

```
COMMENT ON TABLE tb11 IS 'Comment in table'  
COMMENT ON COLUMN tb11.col1 IS 'Description  
of the field'
```

Declare a temporary table (session schema)

```
DECLARE GLOBAL TEMPORARY TABLE tmp1 (col1  
INT, col2 DATE) ON COMMIT PRESERVE ROWS
```

Create a global temporary tablespace

```
CREATE GLOBAL TEMPORARY TABLE tmp2 (col1  
INT)
```

Create an index

```
CREATE INDEX idx1 ON tb12 (col2)
```

Create a unique index

```
CREATE UNIQUE INDEX idx2 ON tb15 (col1)
```

Drop an index

```
DROP INDEX idx1
```

Add a column (requires Reorg table)

```
ALTER TABLE tb11 ADD COLUMN col3 timestamp
```

Change nullability

```
ALTER TABLE tb11 ALTER COLUMN col3 SET NOT  
NULL
```

Drop nullability

```
ALTER TABLE tb11 ALTER COLUMN col3 DROP NOT  
NULL
```

Rename a column

```
ALTER TABLE tb11 RENAME COLUMN col3 TO new3
```

Drop column

```
ALTER TABLE tb11 DROP COLUMN new3
```

Create a primary key constraint

```
ALTER TABLE tb15 ADD CONSTRAINT pkt5  
PRIMARY KEY (col1)
```

Drop primary key

```
ALTER TABLE tb15 DROP PRIMARY KEY
```

Add identity

```
ALTER TABLE tb12 ALTER col1 SET GENERATED  
ALWAYS AS IDENTITY
```

Restart identity

```
ALTER TABLE tb12 ALTER col1 RESTART WITH 1
```

Drop identity

```
ALTER TABLE tb12 ALTER col1 DROP IDENTITY
```

Create a foreign key

```
ALTER TABLE tb15 ADD CONSTRAINT fkt5  
FOREIGN KEY (col1) REFERENCES tb111 (col1)
```

Create a check constraint

```
ALTER TABLE tb11 ADD CONSTRAINT chk CHECK  
(col1 in ('a', 'b', 'c'))
```

Enforce a constraint

```
ALTER TABLE tb11 ALTER CHECK chk ENFORCED
```

Not enforce a constraint

```
ALTER TABLE tb15 ALTER FOREIGN KEY fkt5 NOT  
ENFORCED
```

Change the granularity of the locks

```
ALTER TABLE tb11 LOCKSIZE TABLE
```

Drop a table

```
DROP TABLE tb11
```

Rename a table

```
RENAME TABLE tb12 AS table2
```

Truncate a table

```
TRUNCATE TABLE tb11 IMMEDIATE
```

Create a sequence

```
CREATE SEQUENCE seq AS INTEGER
```

Restart sequence

```
ALTER SEQUENCE seq RESTART WITH 15
```



This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).

Create a stored procedure

```
CREATE OR REPLACE PROCEDURE prc1 (IN val  
INT, OUT ret DATE) SPECIFIC mypr BEGIN SET  
ret = (SELECT col2 FROM tb12 WHERE col1 =  
val); END @
```

Create a trigger

```
CREATE TRIGGER cp_val AFTER INSERT ON tb11  
REFERENCING NEW AS n FOR EACH ROW INSERT  
INTO tb12 VALUES (n.col1, n.col2)
```

Create a view

```
CREATE VIEW vw1 AS SELECT col2 FROM tb11
```

DCL

Grant on a table

```
GRANT SELECT, INSERT ON TABLE tb11 TO user
```

Grant execution on a stored procedure

```
GRANT EXECUTE ON PROCEDURE prc1(INT, DATE)  
TO USER jdoe  
GRANT EXECUTE ON SPECIFIC PROCEDURE mypr TO  
GROUP admins
```

Revoke on a table

```
REVOKE DELETE ON TABLE mytable FROM recur
```

DML

Insert values on a table

```
INSERT INTO tb13 VALUES (2, 'b')  
INSERT INTO tb13 VALUES (3, 'c'), (4, 'd'),  
(5, 'e') --Atomic
```

Insert certain columns

```
INSERT INTO tb11 (col1) VALUES (6)
```

Insert values from a select

```
INSERT INTO tb16 SELECT col1 FROM tb11
```

Insert in temporary table

```
INSERT INTO session.tmp1 VALUES (1)
```

Update fields

```
UPDATE tb13 SET col1 = 5, mycol2 = 'e' --  
all table  
UPDATE tb13 SET col2 = 'd' WHERE col1 = 7
```

Merge (upsert)

```
MERGE INTO tb13 AS t USING (SELECT col1  
FROM tb11) s ON (t.col1 = s.col1) WHEN  
MATCHED THEN UPDATE SET col2 = 'X' WHEN  
NOT MATCHED THEN INSERT VALUES (10, 'X')
```

Delete rows

```
DELETE FROM tb11 --all table  
DELETE FROM tb11 WHERE col1 > 5
```

Export

```
EXPORT TO myfile OF DEL SELECT * FROM tb11
```

Import

```
IMPORT FROM myfile OF DEL INSERT INTO  
mytable1
```

Cursor

```
DECLARE cur1 CURSOR FOR SELECT * FROM tb11
```

Load

```
LOAD FROM myfile OF DEL INSERT INTO tb11  
LOAD FROM cur1 OF CURSOR INSERT INTO tb11
```

Query the status of the load in a table

```
LOAD QUERY TABLE tb11
```

Set integrity

```
SET INTEGRITY FOR tb11 IMMEDIATE CHECKED
```

Ingest

```
INGEST FROM FILE myfile FORMAT DELIMITED  
INSERT INTO tb11
```

Get the next value from a sequence

```
VALUES NEXT VALUE FOR seq  
INSERT INTO tb13 (col1) VALUES (NEXT VALUE  
FOR seq)
```

TCL

Commit changes

```
COMMIT
```

Create a savepoint

```
SAVEPOINT sp1 ON ROLLBACK RETAIN CURSORS
```

Undo changes until savepoint

```
ROLLBACK TO SAVEPOINT sp1
```

Undo changes

```
ROLLBACK
```

Queries

Put a lock at table level

```
LOCK TABLE tb11 IN EXCLUSIVE MODE
```

Execute a query without regard of commit rows

```
SELECT * FROM tb11 WITH UR --RR,RS,CS
```

Execute a query with only 5 rows

```
SELECT * FROM tb11 FETCH FIRST 5 ROWS ONLY
```

Perform a query to a dummy table (dual)

```
SELECT 'Any string' FROM SYSIBM.SYSDUMMY1
```

Perform a query calling a function

```
SELECT HEX(col2) FROM tb15
```

Call a function

```
VALUES HEX('AnyText')
```

Perform a cast

```
VALUES CAST('123' AS INTEGER)
```

Concatenate

```
VALUES 'AnyText' || 5  
VALUES 'AnyText' concat 5
```

Escape a single quote in a text field

```
VALUES 'Sinead o''Connor'
```

Query the database catalog

```
SELECT * FROM SYSCAT.TABLES  
SELECT * FROM SYSCAT.TABAUTH  
SELECT * FROM SYSCAT.ROUTINES
```

SQL PL

Create a compound statement – Anonymous block

```
BEGIN DECLARE val SMALLINT; SET val = 1;  
WHILE (val <= 5) DO INSERT INTO tb15  
VALUES (val, val); SET val = val + 1; END  
WHILE; END @
```

Perform a reorg via ADMIN_CMD (Sometimes required after “alter table”)

```
CALL SYSPROC.ADMIN_CMD('REORG TABLE tb11')
```

Call a stored procedure with an IN and an OUTPUT parameter

```
CALL prc1(5, ?)
```



This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).