Stepper Motor 4: Integrated Stepper Driver Control Interfaces

TI Precision Labs - Motor Drivers


Presented and prepared by James Lockridge




Control interfaces


Phase-enable (PH/EN)

Step-direction (STEP/DIR)






PWM (INx)




STEP/DIR interface


- Driver integrates an indexer with adjustable microstepping level
- On each STEP input, the indexer advances one place in the table



Microstepping on a STEP/DIR interface




Microstepping on a PH/EN interface



EN pin enables the outputs to drive the motor windings


PH pin controls the polarity of the voltage on the winding

Microstepping on a PWM interface




The signals on the INx pins select the direction for driving the motor.

Voltage control on a PH/EN interface





Voltage control on a PWM (INx) interface



Control interfaces

STEP/DIR	Parallel (PWM or PH/EN)
Less control pins required	More control pins required
Easier control	More complex control
Only one voltage reference required	May need two independent VREFs
Indexer sets current waveform	MCU can control wave shaping
Max microstepping set by driver	Max microstepping controlled by MCU





To find more stepper driver technical resources and search products, visit http://www.ti.com/motor-drivers/stepper-driver/overview.html



© Copyright 2018 Texas Instruments Incorporated. All rights reserved.

This material is provided strictly "as-is," for informational purposes only, and without any warranty. Use of this material is subject to TI's **Terms of Use**, viewable at TI.com