



TI Precision Labs – Introduction to temperature sensing


Presented and prepared by Nicole Khoury


#### **Temperature fundamentals**



#### **Interface**








3

### **Accuracy**

#### 6.5 Electrical Characteristics

Over free-air temperature range and V = 1.7 V to 5.5 V for  $T_A = -55 ^{\circ}\text{C}$  to  $70 ^{\circ}\text{C}$ . or V = 1.8 V to 5.5 V for  $T_A = -55 ^{\circ}\text{C}$  to  $150 ^{\circ}\text{C}$  (unless otherwise noted). Typical specifications are at  $T_A = 25 ^{\circ}\text{C}$  and V = 3.3 V (unless otherwise noted).

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
MPERATURE TO DIGI	TAL CONVERT	ER	u s				
	TMP117	-20 °C to 50 °C		-0.1	±0.05	0.1	
		-40 °C to 70 °C	8 averages Thermal Pad unsoldered	-0.15	±0.05	0.15	
		-40 °C to 100 °C		-0.2	±0.1	0.2	
		-55 °C to 125 °C		-0.25	±0.1	0.25	
_		-55 °C to 150 °C		-0.3	±0.1	0.3	
Temperature accuracy	TMP117M	25 °C to 50 °C	(DRV Package) I <sup>2</sup> C Input voltages: V <sub>IL</sub> ≤ 0.05 * V+, V <sub>IH</sub> ≥ 0.95 * V+	-0.1	±0.05	0.1	°C
docuracy		0°C to 70 °C		-0.15	±0.05	0.15	
		0 °C to 85 °C		-0.2	±0.1	0.2	
	TMP117N	-40 °C to 100 °C		-0.2	±0.1	0.2	
		-55 °C to 125 °C		-0.25	±0.1	0.25	
		-55 °C to 150 °C		-0.3	±0.1	0.3	




#### 6.5 Electrical Characteristics

at  $T_A = 25^{\circ}$ C and  $V^+ = 1.4 \text{ V}$  to 3.6 V (unless otherwise noted)

,								
TEST CONDITIONS	MIN	TYP	MAX	UNIT				
TEMPERATURE INPUT								
	<b>–40</b>		125	°C				
$-10^{\circ}$ C to $100^{\circ}$ C, V <sup>+</sup> = 1.8 V	-2	0	2	°C				
-40°C to 125°C, V <sup>+</sup> = 1.8 V	-3	±1	3					
vs supply	-0.5	±0.2	0.5	°C/V				
		1		°C				
	-10°C to 100°C, V <sup>+</sup> = 1.8 V -40°C to 125°C, V <sup>+</sup> = 1.8 V	-40 -10°C to 100°C, V <sup>+</sup> = 1.8 V -2 -40°C to 125°C, V <sup>+</sup> = 1.8 V -3	-40 -10°C to 100°C, V <sup>+</sup> = 1.8 V -2 0 -40°C to 125°C, V <sup>+</sup> = 1.8 V -3 ±1					

#### Placement and package type




### Placement and package type







### Component temperature monitoring




### Component temperature monitoring



## **Ambient temperature monitoring**



### **Ambient temperature monitoring**



#### **Summary**

Interface

- Analog
- Digital

Accuracy

- Note system requirements
- Maximum and typical temperature error

**Placement** 

- Package size
- Ambient or board temperature sensing

# Thank you!

To find more temperature sensor resources and products, visit <u>ti.com/temperature</u>.