Advanced Power Electronics Corp.

N-CHANNEL ENHANCEMENT MODE POWER MOSFET

- ▼ **Dynamic dv/dt Rating**
- ▼ **Repetitive Avalanche Rated**
- ▼ **Fast Switching**
- ▼ **Simple Drive Requirement**



BV_{DSS}	600/650/700V
$R_{DS(ON)}$	3.6Ω
I_D	3.3A



TO-220

Description

AP03N70 series are specially designed as main switching devices for universal 90~265VAC off-line AC/DC converter applications.TO-220 type provide high blocking voltage to overcome voltage surge and sag in the toughest power system with the best combination of fast switching,ruggedized design and cost-effectiveness.

The TO-220 package is universally preferred for all commercial-industrial applications. The device is suited for switch mode power supplies ,DC-AC converters and high current high speed switching circuits.

Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage - /A/H	600/650/700	V
V_{GS}	Gate-Source Voltage	± 30	V
I_D@T_C=25℃	Continuous Drain Current, V_{GS} @ 10V	3.3	A
I_D@T_C=100℃	Continuous Drain Current, V_{GS} @ 10V	2.1	A
I_{DM}	Pulsed Drain Current[1]	13.2	A
P_D@T_C=25℃	Total Power Dissipation	45	W
	Linear Derating Factor	0.36	W/℃
E_{AS}	Single Pulse Avalanche Energy[2]	85	mJ
I_{AR}	Avalanche Current	3.3	A
E_{AR}	Repetitive Avalanche Energy	3.3	mJ
T_{STG}	Storage Temperature Range	-55 to 150	℃
T_J	Operating Junction Temperature Range	-55 to 150	℃

Thermal Data

Symbol	Parameter		Value	Unit
Rthj-c	Thermal Resistance Junction-case	Max.	2.8	℃/W
Rthj-a	Thermal Resistance Junction-ambient	Max.	62	℃/W

Electrical Characteristics@T_j=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=1mA / -	600	-	-	V
		V_{GS}=0V, I_D=1mA / A	650	-	-	V
		V_{GS}=0V, I_D=1mA / H	700	-	-	V
$\Delta BV_{DSS}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25℃, I_D=1mA	-	0.6	-	V/℃
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=1.6A	-	-	3.6	Ω
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=250uA	2	-	4	V
g_{fs}	Forward Transconductance	V_{DS}=10V, I_D=1.6A	-	2	-	S
I_{DSS}	Drain-Source Leakage Current (T_j=25°C)	V_{DS}=600V, V_{GS}=0V	-	-	10	uA
	Drain-Source Leakage Current (T_j=150°C)	V_{DS}=480V, V_{GS}=0V	-	-	100	uA
I_{GSS}	Gate-Source Leakage	V_{GS}= ± 30V	-	-	±100	nA
Q_g	Total Gate Charge[3]	I_D=3.3A	-	11.4	-	nC
Q_{gs}	Gate-Source Charge	V_{DS}=480V	-	3.1	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	V_{GS}=10V	-	4.2	-	nC
$t_{d(on)}$	Turn-on Delay Time[3]	V_{DD}=300V	-	8.4	-	ns
t_r	Rise Time	I_D=3.3A	-	6	-	ns
$t_{d(off)}$	Turn-off Delay Time	R_G=10Ω,V_{GS}=10V	-	17.7	-	ns
t_f	Fall Time	R_D=91Ω	-	5.9	-	ns
C_{iss}	Input Capacitance	V_{GS}=0V	-	600	-	pF
C_{oss}	Output Capacitance	V_{DS}=25V	-	45	-	pF
C_{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	4	-	pF

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
I_S	Continuous Source Current (Body Diode)	V_D=V_G=0V , V_S=1.5V	-	-	3.3	A
I_{SM}	Pulsed Source Current (Body Diode)[1]		-	-	13.2	A
V_{SD}	Forward On Voltage[3]	T_j=25℃, I_S=3.3A, V_{GS}=0V	-	-	1.5	V

Notes:

1.Pulse width limited by safe operating area.

2.Starting T_j=25°C , V_{DD}=50V , L=15mH , R_G=25Ω , I_{AS}=3.3A.

3.Pulse width ≤300us , duty cycle ≤2%.

Ordering Code

AP03N70P- X : X Denote BV_{DSS} Grade

Blank = BV_{DSS} 600V

A = BV_{DSS} 650V

H = BV_{DSS} 700V



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Normalized BV_{DSS} v.s. Junction Temperature



Fig 4. Normalized On-Resistance v.s. Junction Temperature



Fig 5. Maximum Drain Current v.s. Case Temperature



Fig 6. Typical Power Dissipation



Fig 7. Maximum Safe Operating Area



Fig 8. Effective Transient Thermal Impedance



Fig 9. Gate Charge Characteristics



Fig 10. Typical Capacitance Characteristics



Fig 11. Forward Characteristic of Reverse Diode



Fig 12. Gate Threshold Voltage v.s. Junction Temperature



Fig 13. Switching Time Circuit



Fig 14. Switching Time Waveform



Fig 15. Gate Charge Circuit



Fig 16. Gate Charge Waveform