

- Clinical Intelligence Platform - Use Cases
 - H-34 DELTA Revision Cup Study - POC Use Case Specifications
- Multi-Source Architecture Overview
 - System Architecture Visualization
 - Data Flow Diagram
- Use Case Specifications
 - UC1: Regulatory Submission Readiness Assessment
 - Overview
 - Business Problem
 - User Query Examples
 - Input Data Sources
 - Agent Orchestration
 - Output Specification
 - Value Delivered
 - UC2: Safety Signal Detection & Contextualization
 - Overview
 - Business Problem
 - User Query Examples
 - Input Data Sources
 - Agent Orchestration
 - Output Specification
 - Value Delivered
 - UC3: Automated Protocol Deviation Detection & Classification
 - Overview
 - Business Problem
 - User Query Examples
 - Input Data Sources
 - Agent Orchestration
 - Output Specification
 - Value Delivered
 - UC4: Patient Risk Stratification with Actionable Monitoring Lists
 - Overview
 - Business Problem
 - User Query Examples
 - Input Data Sources
 - Agent Orchestration
 - Output Specification

- Value Delivered
- UC5: Intelligent Study Health Executive Dashboard
 - Overview
 - Business Problem
 - User Query Examples
 - Input Data Sources
 - Agent Orchestration
 - Output Specification
 - Value Delivered
- Summary: Use Case Data Source Matrix
- Appendix: Document-as-Code File Specifications
 - protocol_rules.yaml
 - literature_benchmarks.yaml
 - registry_norms.yaml

Clinical Intelligence Platform - Use Cases

H-34 DELTA Revision Cup Study - POC Use Case Specifications

Version: 1.0 | **Date:** January 11, 2026

Multi-Source Architecture Overview

Core Principle: Each use case leverages multiple data sources orchestrated through specialized AI agents. The architecture below shows how content flows from raw sources through aggregation, agent processing, and finally to user experience.


System Architecture Visualization

CLINICAL INTELLIGENCE PLATFORM ARCHITECTURE

LAYER 1: CONTENT SOURCES

STUDY	PROTOCOL	LITERATURE	REGISTRY
TMF			
DATA DOCUMENTS	DOCUMENTS	PDFs	DATA
(Excel) (Mixed)	(PDF)	(PDF)	(CSV/PDF)
<ul style="list-style-type: none">• Demographics• EC Approvals• HHS/OHS• PD Logs• Radiology• Site Docs• AEs/SAEs• Training• Revisions	<ul style="list-style-type: none">• CIP v2.0• SOA• Endpoints• I/E Rules• Safety Rules	<ul style="list-style-type: none">• Meding 2025• Dixon 2025• Harris 2025• Varios et al• +12 more	<ul style="list-style-type: none">• AOANJRR• NJR UK• EPRD

LAYER 2: DATA INGESTION & NORMALIZATION





LAYER 3: AGGREGATION & INDEXING

UNIFIED DATA LAYER

TIME SERIES DB
(ChromaDB)


VECTOR STORE
DOCUMENT-AS-CODE
(YAML Rules)


PATIENT GRAPH
(Entity Links)



ORCHESTRATOR AGENT


(Query Understanding & Routing)







SYNTHESIS AGENT
(Combine Results, Generate Output)


LAYER 5: TOOLS & ANALYTICS







LAYER 6: USER EXPERIENCE





Data Flow Diagram





STRUCTURED OUTPUT

- Readiness Score: 72%
- Blockers: 2 critical gaps
- Warnings: 2 items
- Timeline projection
- Action buttons
- Full provenance trail

Use Case Specifications

UC1: Regulatory Submission Readiness Assessment

Overview

Attribute	Value
UC ID	UC1
Name	Regulatory Submission Readiness Assessment
Category	Compliance & Regulatory

Attribute	Value
Trigger	User query or scheduled assessment
Complexity	High (5 agents, 4+ data sources)

Business Problem

Clinical teams spend **3-5 days** manually cross-referencing protocol requirements, study data, literature benchmarks, and regulatory expectations to assess submission readiness. Gaps are discovered late, causing delays and rework.

User Query Examples

- "Are we ready to submit? What gaps need to be addressed?"
- "What's our submission readiness status?"
- "Generate regulatory readiness report"

Input Data Sources

UC1: INPUT DATA SOURCES

SOURCE 1: PROTOCOL (Document-as-Code)

```
| File: protocol_rules.yaml (extracted from CIP v2.0)
| Fields Used:
|   • endpoints.primary.success_threshold → "20 points HHS improvement"
|   • schedule_of_assessments.visits[].required_assessments → Visit
|     completion requirements
|   • sample_size.interim → "n≥25 evaluable"
```

- safety_requirements.sae_narrative → "All SAEs require narratives"
 - radiographic_requirements → "All timepoints must have imaging review"
-

| SOURCE 2: STUDY DATA (Structured)

- | File: H-34DELTARevisionstudy_export_20250912.xlsx
- | Sheets Used:
- Sheet 1 (Patients) → Enrollment count, patient status
 - Sheet 18 (Score HHS) → Primary endpoint data, MCID calculation
 - Sheet 17 (Adverse Events) → Safety completeness, SAE narratives
 - Sheets 7–16 (Follow-ups) → Visit completion, radiographic data availability
 - Sheet 20 (Explants) → Revision event counts
-

| Key Calculations:

- Patients with 2-year HHS: 8/37
 - MCID achieved: 5/8 (62%)
 - SAEs with narratives: 12/12
 - Missing radiographic: 3 patients at 1-year
-

| SOURCE 3: LITERATURE BENCHMARKS (Document-as-Code)

| File: literature_benchmarks.yaml

Publications Indexed:

- Meding et al 2025 → mcid_achievement: 72%, revision_rate: 6.2%
- Vasio et al → hhs_improvement_range: [28, 42]
- Dixon et al 2025 → Osteoporosis fracture risk HR: 2.4
- Harris et al 2025 → ae_rate_range: [28%, 40%]

Comparison Points:

- H-34 MCID 62% vs Literature 72% → Within acceptable range
- H-34 revision 8.1% vs Literature 6.2% → Upper boundary

SOURCE 4: REGISTRY NORMS (Document-as-Code)

File: registry_norms.yaml

Registries Indexed:

- AOANJRR 2024 → survival_2yr: 94%, revision_rate_median: 6.2%, revision_rate_p95: 12% | |
- NJR UK → Similar benchmarks for UK population

Validation Points:

- H-34 survival ~92% vs Registry 94% → Within CI
- H-34 revision 8.1% vs Registry median 6.2% → Above median, below p95 | |

Agent Orchestration

UC1: AGENT ORCHESTRATION

STEP 1: PROTOCOL AGENT

Execution: ~2 seconds

- Load protocol_rules.yaml
- Extract submission requirements:
 - Primary endpoint: HHS improvement ≥ 20 points at 2 years
 - Sample size: $n \geq 25$ evaluable for interim, $n=50$ for final
 - Safety: Complete AE documentation, SAE narratives
 - Radiographic: All timepoint imaging reviewed

STEP 2: DATA AGENT

Execution: ~5 seconds

- Query H-34 study database
- Calculate current status:
 - Primary endpoint: 5/8 achieved MCID (62%), $n=8$ evaluable
 - Safety: 15 AEs documented, 12 SAEs with narratives
 - Radiographic: 3 patients missing 1yr imaging

STEP 3: LITERATURE AGENT

Execution: ~3 seconds

- Load literature_benchmarks.yaml

- Retrieve comparators:
 - Meding et al: 72% MCID (our 62% within range)
 - Revision rate benchmark: 6.2% (our 8.1% at upper boundary)
-

STEP 4: REGISTRY AGENT

Execution: ~2 seconds

- Load registry_norms.yaml
 - External validation:
 - AOANJRR 2yr survival: 94% (our ~92% within CI)
-

STEP 5: COMPLIANCE AGENT

Execution: ~8 seconds

- Cross-reference all sources
 - Generate gap analysis:
 - Protocol vs Data: Sample size gap, radiographic gaps
 - Literature comparison: Performance validation
 - Registry validation: External benchmarking
-

STEP 6: SYNTHESIS AGENT

Execution: ~10 seconds

- Combine all agent outputs
- Generate structured report with:

- Overall readiness score
- Category-by-category status
- Blockers and warnings
- Timeline projection
- Action buttons
- Complete provenance

TOTAL EXECUTION TIME: <30 seconds

Output Specification

Output Element	Description	Format
Readiness Score	Overall percentage (0-100%)	Progress bar + number
Category Status	Pass/Gap/Watch per requirement	Table with icons
Blockers	Critical items preventing submission	Numbered list
Warnings	Items needing attention	Numbered list
Timeline	Projected path to readiness	Timeline visualization
Actions	One-click action buttons	Button array
Provenance	Source citations for every finding	Footer text

Value Delivered

Metric	Traditional	With Platform
Time to assess	3-5 days	30 seconds

Metric	Traditional	With Platform
Sources consulted	Manual cross-reference	4 sources automated
Gap detection	Often late discovery	Real-time identification
Actionability	Data only	Specific remediation steps

UC2: Safety Signal Detection & Contextualization

Overview

Attribute	Value
UC ID	UC2
Name	Safety Signal Detection & Contextualization
Category	Safety & Vigilance
Trigger	Proactive (data refresh) or user query
Complexity	High (5 agents, 5+ data sources)

Business Problem

Safety signals in small studies are hard to interpret without external context. A 13% fracture rate looks concerning in isolation, but teams must manually search literature and registries to determine if it's actually elevated or expected for the patient population.

User Query Examples

- "Are there any safety concerns I should know about?"
- "Analyze our AE rates compared to published data"
- "Is our fracture rate concerning?"
- **PROACTIVE:** System alerts without user query

Input Data Sources

UC2: INPUT DATA SOURCES

SOURCE 1: ADVERSE EVENTS (Structured)

| File: H-34DELTARevisionstudy_export_20250912.xlsx → Sheet 17 (Adverse Events)

etc. | Fields Used:

- AE Term → "Periprosthetic fracture", "Dislocation", "Infection", etc.
- Seriousness → SAE/Non-SAE classification
- Device Relationship → Related/Not related determination
- Onset Date → Timing correlation with surgery
- Patient ID → Link to demographics and outcomes

Key Calculations:

- Fracture rate: 5/37 (13%)
- Dislocation rate: 2/37 (5%)
- Infection rate: 1/37 (3%)
- Overall AE rate: 13/37 (35%)

SOURCE 2: PATIENT DEMOGRAPHICS (Structured)

| File: H-34DELTARevisionstudy_export_20250912.xlsx → Sheet 1 (Patients),
Sheet 2 (Preoperatives) | |

| Fields Used:

- | • Age, Gender, BMI → Risk factor analysis
- | • Primary Diagnosis → Underlying condition
- | • Comorbidities → Osteoporosis, diabetes, etc.

| Key Findings:

- | • Osteoporosis prevalence: 12/37 (32%)
- | • Fractures in osteoporotic patients: 5/5 (100%)

| SOURCE 3: LITERATURE (RAG + Document-as-Code)

| Files: 15 indexed PDFs + literature_benchmarks.yaml

| Key Publications:

- | • Dixon et al 2025 → Osteoporosis as primary fracture risk factor, expected rate 15–20% in osteoporotic
- | • Harris et al 2025 → AE rate benchmarks 28–40%
- | • Meding et al 2025 → Overall fracture rate in non-osteoporotic: 4–8%

| Risk Factor Extraction:

- | • Osteoporosis HR for fracture: 2.4 (Dixon)
- | • Expected fracture rate with 32% osteoporosis prevalence: 10–15%

| SOURCE 4: REGISTRY NORMS (Document-as-Code)

| File: registry_norms.yaml

| Benchmarks Used:

- AOANJRR fracture rate threshold: >10% triggers concern
- Risk-adjusted expectation for high-osteoporosis cohort: 10–15%
- H-34 rate (13%) within risk-adjusted expectation

| SOURCE 5: PROTOCOL (Document-as-Code)

| File: protocol_rules.yaml (extracted from CIP v2.0)

| Relevant Sections:

- Section 5.2 I/E Criteria → Osteoporosis NOT an exclusion criterion
- Section 9.1 Safety → SAE reporting requirements
- Safety thresholds → fracture_rate_concern: 0.08 (8%)

Agent Orchestration

UC2: AGENT ORCHESTRATION

TRIGGER: Data refresh OR user query OR scheduled surveillance

STEP 1: SAFETY AGENT

Execution: ~5 seconds

- Scan AE table for rate anomalies
- Calculate event rates by type
- Compare to protocol safety thresholds
- Identify: Fracture rate 13% > threshold 8% → SIGNAL DETECTED

STEP 2: DATA AGENT

Execution: ~3 seconds

- Cross-reference AEs with patient characteristics
- Pattern analysis:
 - 4/5 fractures within 90 days (early postop)
 - 5/5 fractures in osteoporotic patients (100% correlation)
- Temporal clustering identified

STEP 3: LITERATURE AGENT

Execution: ~5 seconds

- RAG query: "fracture risk osteoporosis revision THA"
- Retrieve:
 - Dixon et al: Osteoporosis primary risk factor
 - Expected rate in osteoporotic: 15–20%
 - Non-osteoporotic expected: 4–8%

- Context: H-34 32% osteoporosis is higher than typical
-

STEP 4: REGISTRY AGENT

Execution: ~2 seconds

- Load registry_norms.yaml
 - Risk-adjusted benchmark:
 - Overall threshold: >10%
 - High-osteoporosis cohort expectation: 10–15%
 - H-34 13% WITHIN risk-adjusted expectation
-

STEP 5: PROTOCOL AGENT

Execution: ~2 seconds

- Check I/E criteria: Osteoporosis not excluded
 - Check monitoring protocol: No enhanced bone quality protocol specified
 - Identify protocol gap for future consideration
-

STEP 6: SYNTHESIS AGENT

Execution: ~8 seconds

- Combine all findings
 - Generate interpretation:
 - CONCLUSION: Signal EXPLAINED by population characteristics
 - NOT indicative of device defect
-

- Rate within literature-predicted range for risk profile
- Generate actionable recommendations
- Complete provenance trail

TOTAL EXECUTION TIME: <25 seconds

Output Specification

Output Element	Description	Format
Signal Identification	Rate comparison table	Table with status icons
Cross-Source Context	Evidence from each source	Bulleted sections
Interpretation	High-confidence conclusion	Boxed summary
Regulatory Implication	Documentation requirements	Text paragraph
Recommended Actions	Specific next steps with buttons	Action button array
Provenance	All sources cited	Footer citations

Value Delivered

Metric	Traditional	With Platform
Signal detection	Manual monitoring	Automated on data refresh
Context gathering	Weeks of research	25 seconds
Interpretation	Subjective clinical judgment	Evidence-based, multi-source
Recommendations	Generic	Specific, actionable

UC3: Automated Protocol Deviation Detection & Classification

Overview

Attribute	Value
UC ID	UC3
Name	Automated Protocol Deviation Detection & Classification
Category	Compliance & Quality
Trigger	Automatic on data refresh
Complexity	Medium (3 agents, 2+ data sources)

Business Problem

Protocol deviations are identified manually by comparing visit dates to protocol windows — a tedious, error-prone process often discovered late during monitoring visits. This delays corrective action and increases regulatory risk.

User Query Examples

- "What protocol deviations exist in our data?"
- "Show me patients outside their visit windows"
- "Generate protocol deviation report"
- **AUTOMATIC:** Runs on every data refresh

Input Data Sources

UC3: INPUT DATA SOURCES

| SOURCE 1: PROTOCOL RULES (Document-as-Code) – PRIMARY

| File: protocol_rules.yaml (extracted from CIP v2.0 Section 6.2, 7.2)

| Visit Window Rules:

	Visit	Target Day	Window	Required Assessments
AE Review	2-Month	Day 60	[-14, +28]	HHS, OHS, Radiology,
AE Review	6-Month	Day 180	[-30, +30]	HHS, OHS, Radiology,
AE Review	1-Year	Day 365	[-30, +60]	HHS, OHS, Radiology,
AE Review (Primary Endpoint)	2-Year	Day 730	[-60, +60]	HHS, OHS, Radiology,

| Deviation Classification Rules (Section 7.2):

- MINOR: Within 1.5x window extension
- MAJOR: Beyond 1.5x window OR missing critical assessment
- CRITICAL: Affects primary endpoint evaluability

| SOURCE 2: VISIT DATA (Structured)

| File: H-34DELTARevisionstudy_export_20250912.xlsx

| Sheets Used:

- | • Sheet 4 (Intraoperatives) → Surgery dates (Day 0 reference)
- | • Sheets 7–16 (Follow-ups) → Actual visit dates by timepoint
- | • Sheet 18 (Score HHS) → Assessment completion
- | • Sheet 19 (Score OHS) → Assessment completion
- | • Radiology sheets → Imaging completion

| Data Points Per Patient:

- | • Surgery date → Reference point
- | • Visit date per timepoint → Actual vs expected
- | • Assessment completion flags → Form presence check

| Calculation Example (Patient 15):

- | • Surgery: Sep 15, 2024
- | • Expected 6mo: Mar 15, 2025 (Day 180) ± 30 days
- | • Window: Feb 13 – Apr 14, 2025
- | • Actual: Apr 22, 2025 → +38 days outside window → MINOR deviation

Agent Orchestration

UC3: AGENT ORCHESTRATION

EXECUTION: Automatic on data refresh (batch processing)

STEP 1: PROTOCOL AGENT

Execution: ~1 second

- Load protocol_rules.yaml
 - Initialize visit window validators
 - Initialize deviation classifiers
 - Initialize required assessment checkers
-

STEP 2: DATA AGENT (Batch Processing)

Execution: ~5 seconds

- | FOR EACH patient (n=37):
 - | FOR EACH expected visit (4 timepoints):
 - 1. Get surgery date (Day 0)
 - 2. Calculate expected visit date
 - 3. Calculate window boundaries
 - 4. Get actual visit date (if exists)
 - 5. Calculate delta days
 - 6. Check required assessments
-

| Total evaluations: 37 patients × 4 visits = 148 visit-assessments

STEP 3: COMPLIANCE AGENT

Execution: ~3 seconds

| FOR EACH visit-assessment:

1. Apply deviation classification rules
2. Determine severity: MINOR / MAJOR / CRITICAL
3. Assess impact on endpoint evaluability
4. Generate PD log entry (pre-populated)

| Results:

- 142 compliant visit-assessments
- 6 deviations detected (4.1% rate)
 - 3 MINOR (timing within extended window)
 - 2 MAJOR (outside window or missing visit)
 - 1 CRITICAL (affects primary endpoint)

STEP 4: OUTPUT GENERATION

Execution: ~2 seconds

| Generate automated outputs:

- PD Log entries pre-populated (requires PI signature)
- Site query forms generated for MAJOR/CRITICAL
- CSR deviation table updated
- Monitoring visit agenda updated

TOTAL EXECUTION TIME: ~11 seconds (batch for all 37 patients)

Output Specification

Output Element	Description	Format
Summary Statistics	Total evaluations, deviation count, rate	Header text
Deviation Detail Table	Patient, visit, expected, actual, delta, class, impact	Sortable table
Deviation Breakdown	Count by severity category	Summary list
Auto-Generated Outputs	PD log, queries, CSR table	Status checklist
Action Buttons	Download, send queries, update CSR, trends	Button array
Provenance	Protocol sections, data sheets	Footer citations

Value Delivered

Metric	Traditional	With Platform
Detection timing	Monitoring visits (months)	Real-time (seconds)
Time per patient	15-30 minutes	<1 second
Classification accuracy	Human interpretation	Protocol-defined rules
Documentation	Manual transcription	Auto-generated

UC4: Patient Risk Stratification with Actionable Monitoring Lists

Overview

Attribute	Value
UC ID	UC4
Name	Patient Risk Stratification with Actionable Monitoring Lists
Category	Clinical Decision Support
Trigger	User query or scheduled refresh
Complexity	High (4 models, 4+ data sources)

Business Problem

Without predictive tools, all patients receive the same monitoring attention. This wastes resources on low-risk patients while potentially missing early warning signs in high-risk patients who need enhanced surveillance.

User Query Examples

- "Which patients should I be most concerned about?"
- "Who needs enhanced monitoring?"
- "Generate prioritized patient list"
- "What are the highest risk patients?"

Input Data Sources

UC4: INPUT DATA SOURCES

SOURCE 1: ML RISK MODEL (Trained on Synthetic + Real Data)

| Model: XGBoost Revision Risk Classifier
| Training Data: 737 patients (37 real + 700 synthetic)
| Events: 60 revision events (sufficient for ML training)

| Input Features:

- | • Demographics: Age, Gender, BMI
- | • Clinical: Baseline HHS, Diagnosis, Comorbidities
- | • Trajectory: HHS slope, recovery pattern cluster
- | • Radiographic: Lucency scores, bone quality
- | • Compliance: Visit adherence, deviation count

| Output: Probability of revision within 2 years (0-100%)

| Validation: Cross-validated on synthetic, calibrated to real

| SOURCE 2: LITERATURE HAZARD RATIOS (Document-as-Code)

| File: literature_benchmarks.yaml

| Risk Factor Hazard Ratios:

Application	Risk Factor	HR	Source
Osteoporosis		2.4	Dixon et al 2025

Fracture/revision risk multiplier					
failure risk	BMI > 35	1.6	AOANJRR 2024		Mechanical
Complication risk	Age > 75	1.4	Harris et al 2025		
revision risk	Prior revision	2.1	Meding et al 2025		Re-
recovery predictor	Baseline HHS < 30	1.8	Vasios et al		Poor

Applied as: Risk score = Baseline $\times \prod$ (HR for each present factor)

SOURCE 3: REGISTRY BENCHMARKS (Document-as-Code)

File: registry_norms.yaml

Population Norms:

- Base revision risk (cohort average): 8%
- Risk-adjusted thresholds by factor count
- Survival curve percentiles for comparison

Risk Thresholds:

- LOW: <10% (standard protocol)
- MODERATE: 10–20% (enhanced monitoring)
- HIGH: >20% (intensive surveillance)

| SOURCE 4: STUDY DATA (Structured)

| File: H-34DELTARevisionstudy_export_20250912.xlsx

| Sheets Used:

- Sheet 1 (Patients) → Demographics, BMI
- Sheet 2 (Preoperatives) → Diagnosis, comorbidities, prior surgeries
- Sheet 18 (Score HHS) → Baseline scores, trajectories
- Radiology sheets → Bone quality, lucency findings
- Sheet 17 (AEs) → Complication history

| Derived Features:

- HHS trajectory slope (improvement rate)
- Recovery cluster assignment (K-Means on trajectories)
- Protocol compliance score

| SOURCE 5: PROTOCOL COMPLIANCE (Document-as-Code)

| Derived from UC3 output:

- Deviation count per patient
- Deviation severity accumulation
- Visit adherence rate

| Compliance Score = f(deviation count, severity, missed visits)

| Low compliance correlates with poor outcomes and loss to follow-up risk

Agent Orchestration

UC4: AGENT ORCHESTRATION

MULTI-MODEL ENSEMBLE APPROACH

MODEL ARCHITECTURE

Patient Data → Model 1: ML Revision Risk (XGBoost)

→ Model 2: Literature HR Score
→ Weighted Ensemble

Score (0-100%)

→ Model 3: Registry Benchmark Comparison

→ Model 4: Protocol Compliance Score

Final Score = $w_1 \times ML + w_2 \times Literature + w_3 \times Registry + w_4 \times Compliance$

Weights calibrated to maximize discrimination while maintaining explainability

```
| |
```

```
STEP 1: DATA AGENT (Feature Assembly)
```

```
Execution: ~3 seconds
```

```
| FOR EACH patient (n=37):
```

- Gather demographics, clinical history
 - Calculate HHS trajectory features
 - Aggregate radiographic findings
 - Retrieve compliance score from UC3
-

```
| |
```

```
STEP 2: ML SCORING (Parallel Execution)
```

```
Execution: ~5 seconds
```

```
| Model 1: XGBoost prediction for each patient
```

```
| Model 2: Literature HR multiplication for each patient
```

```
| Model 3: Registry percentile lookup for each patient
```

```
| Model 4: Compliance score retrieval
```

```
| |
```

```
STEP 3: ENSEMBLE & UNCERTAINTY
```

```
Execution: ~2 seconds
```

```
| • Combine model outputs with weighted ensemble
```

```
| • Calculate prediction interval (uncertainty quantification)
```

```
| • Assign risk tier: HIGH / MODERATE / LOW
```

STEP 4: EXPLAINABILITY AGENT

Execution: ~5 seconds

| FOR EACH high-risk patient:

- | • Generate SHAP-like factor contribution breakdown
 - | • Link each factor to source (ML, literature, registry)
 - | • Generate specific monitoring recommendation
-

STEP 5: OUTPUT GENERATION

Execution: ~3 seconds

- | • Generate prioritized patient list by risk tier
 - | • Detailed risk factor breakdown for HIGH priority
 - | • Specific action recommendations per patient
 - | • Confidence scores and provenance
-

TOTAL EXECUTION TIME: ~18 seconds

Output Specification

Output Element	Description	Format
High Priority List	Patients >20% risk with details	Detailed table

Output Element	Description	Format
Moderate Priority List	Patients 10-20% risk	Collapsible list
Low Priority List	Patients <10% risk	Summary count
Factor Contribution	Visual breakdown per patient	Waterfall chart
Confidence Score	Model reliability indicator	Percentage
Recommendations	Specific actions per patient	Action text
Action Buttons	Generate protocol, email site, schedule	Button array

Value Delivered

Metric	Traditional	With Platform
Prioritization method	Subjective judgment	Multi-model ensemble
Explainability	"Clinical intuition"	Factor-by-factor breakdown
Resource allocation	Uniform attention	Risk-stratified focus
Early intervention	Often too late	Proactive identification

UC5: Intelligent Study Health Executive Dashboard

Overview

Attribute	Value
UC ID	UC5
Name	Intelligent Study Health Executive Dashboard
Category	Executive Decision Support
Trigger	Real-time (auto-refresh) or on-demand
Complexity	High (aggregates all agents, 6+ data sources)

Business Problem

Executives need a single view of study status, but information is scattered across data exports, protocol documents, safety databases, and regulatory trackers. Preparing a status update takes days of manual synthesis.

User Query Examples

- "Give me the executive summary"
- "What's the overall study status?"
- "Prepare a board presentation"
- **AUTOMATIC:** Dashboard updates on data refresh

Input Data Sources

UC5: INPUT DATA SOURCES

This use case AGGREGATES outputs from UC1–UC4 plus additional sources:

SOURCE 1: UC1 OUTPUT – Regulatory Readiness

Feeds:

- Overall readiness score (72%)
- Blocker count (2 critical)
- Timeline projection
- Category status breakdown

SOURCE 2: UC2 OUTPUT – Safety Signal Summary

Feeds:

- Active signals (fracture rate monitored)
- Signal status (explained by population)
- Required actions

SOURCE 3: UC3 OUTPUT – Protocol Compliance

Feeds:

- Compliance rate (96%)
- Deviation count by severity
- SAE reporting compliance

SOURCE 4: UC4 OUTPUT – At-Risk Patient Summary

Feeds:

- High-risk patient count (4)

- Patients overdue for follow-up (7)
 - Retention risk assessment
-

| SOURCE 5: STUDY DATA – Enrollment & Efficacy (Direct)

| File: H-34DELTARevisionstudy_export_20250912.xlsx

| Feeds:

- Enrollment: 37/50 (74%)
 - Efficacy: 62% MCID achieved (n=8)
 - Data quality: 87% (23 queries open, 3 critical)
 - Mean HHS improvement: +34.9 points
-

| SOURCE 6: LITERATURE + REGISTRY – External Benchmarking

| Files: literature_benchmarks.yaml, registry_norms.yaml

| Feeds:

- HHS improvement comparison: H-34 +34.9 vs Literature +28–45 vs Registry +32
- MCID comparison: H-34 62% vs Literature 60–80% vs Registry 68%
- Revision rate: H-34 8.1% vs Literature 5–8% vs Registry 6.2%
- AE rate: H-34 35% vs Literature 28–40% vs Registry 35%
- 2yr survival: H-34 92% vs Literature 90–96% vs Registry 94%

SOURCE 7: TMF/REGULATORY STATUS (When Available)

Files: EC approval documents, prior reports

Feeds:


- Regulatory approval status
- Prior report references (Intermediate Report Dec 2023)
- Milestone tracking

Agent Orchestration

UC5: AGENT ORCHESTRATION

AGGREGATION ARCHITECTURE

UC1 Output



STEP 1: COLLECT UC OUTPUTS (Cached or Fresh)
Execution: ~5 seconds

- Retrieve latest UC1 readiness assessment
 - Retrieve latest UC2 safety signal summary
 - Retrieve latest UC3 compliance report
 - Retrieve latest UC4 risk stratification
- Note: If cached results are stale, trigger fresh execution

STEP 2: DIRECT DATA QUERIES
Execution: ~3 seconds

- Enrollment status: 37/50
- Efficacy summary: 62% MCID, +34.9 mean improvement
- Data quality metrics: 87%, 23 queries, 3 critical

STEP 3: BENCHMARK COMPARISON

Execution: ~2 seconds

- Load literature_benchmarks.yaml
 - Load registry_norms.yaml
 - Generate comparison table with status indicators
-

STEP 4: PRIORITY SYNTHESIS

Execution: ~5 seconds

- Rank issues by impact and urgency
 - Generate "Attention Required" list (top 3–5 items)
 - Cross-reference sources for each item
 - Assign action recommendations
-

STEP 5: TIMELINE PROJECTION

Execution: ~3 seconds

- Current milestone: Q1 2026
 - Project future milestones based on enrollment rate
 - Identify risks to timeline
 - Generate visual timeline
-

STEP 6: DASHBOARD RENDERING
Execution: ~2 seconds

- Overall health score calculation
- KPI progress bars
- Attention items with source attribution
- Benchmarking table
- Timeline visualization
- Export action buttons

TOTAL EXECUTION TIME: ~20 seconds (full refresh) or ~5 seconds (cached)

Output Specification

Output Element	Description	Format
Overall Health Score	Composite 0-100 with trend	Score + progress bar
KPI Summary	Enrollment, Efficacy, Safety, Compliance, Quality	Icon + progress bars
Attention Required	Top 3-5 prioritized issues	Numbered list with actions
Benchmarking Table	H-34 vs Literature vs Registry	Comparison table
Regulatory Timeline	Milestone projection	Timeline visual
Export Actions	PDF, presentation, drill-down	Button array

Output Element	Description	Format
Provenance Summary	Data currency timestamp	Footer

Value Delivered

Metric	Traditional	With Platform
Time to prepare	2-3 days	20 seconds
Data sources synthesized	Manual aggregation	6+ automated
Currency	Point-in-time snapshot	Real-time refresh
Benchmarking	Manual literature search	Automated comparison
Actionability	Status report only	Prioritized action items

Summary: Use Case Data Source Matrix

USE CASE → DATA SOURCE DEPENDENCY MATRIX

DATA SOURCE	UC1	UC2	UC3	UC4	UC5
	Readiness	Safety	Deviation	Risk	Dashboard
Study Data (Excel)	●	●	●	●	●
Protocol Rules (YAML)	●	●	●	○	●
Literature Benchmarks	●	●	○	●	●
Registry Norms	●	●	○	●	●
ML Risk Model	○	○	○	●	○
UC1–UC4 Outputs	○	○	○	○	●

Legend: ● = Primary source | ○ = Optional/indirect

AGENTS PER USE CASE

UC1: Protocol Agent → Data Agent → Literature Agent → Registry Agent →
Compliance Agent → Synthesis |

UC2: Safety Agent → Data Agent → Literature Agent → Registry Agent →
Protocol Agent → Synthesis |

UC3: Protocol Agent → Data Agent → Compliance Agent → Output Generation

UC4: Data Agent → ML Scoring (4 models) → Explainability Agent → Output
Generation |

UC5: Aggregation Agent (UC1–4 outputs) → Direct Query → Benchmark Compare
→ Priority Synthesis → Render |

EXECUTION TIMES

UC1: ~30 seconds | UC2: ~25 seconds | UC3: ~11 seconds

UC4: ~18 seconds | UC5: ~20 seconds (full) / ~5 seconds (cached)

Traditional manual approach: Days to weeks

Appendix: Document-as-Code File

Specifications

protocol_rules.yaml

```
# Source: CIP_H-34_v.2.0.pdf
# Extraction Method: LLM-assisted structured extraction
# Last Updated: 2026-01-11

protocol:
  id: "H-34"
  version: "2.0"
  title: "DELTA Revision Cup Clinical Investigation"

schedule_of_assessments:
  visits:
    - id: "fu_2mo"
      day_offset: 60
      window: [-14, +28]
      required_assessments: ["hhs", "ohs", "radiology", "ae_review"]
    - id: "fu_6mo"
      day_offset: 180
      window: [-30, +30]
      required_assessments: ["hhs", "ohs", "radiology", "ae_review"]
    - id: "fu_1yr"
      day_offset: 365
      window: [-30, +60]
      required_assessments: ["hhs", "ohs", "radiology", "ae_review"]
    - id: "fu_2yr"
      day_offset: 730
      window: [-60, +60]
      required_assessments: ["hhs", "ohs", "radiology", "ae_review"]
      critical: true

  endpoints:
    primary:
      id: "hhs_improvement"
      calculation: "hhs_2yr - hhs_baseline"
      success_threshold: 20
      success_criterion: "improvement >= 20 points"

  safety_thresholds:
    revision_rate_concern: 0.10
    sae_rate_concern: 0.40
    fracture_rate_concern: 0.08

  deviation_classification:
    minor: "within_1.5x_window"
    major: "beyond_1.5x_window_or_missing_critical"
    critical: "affects_primary_endpoint"
```

literature_benchmarks.yaml

```
# Source: 15 indexed publications
# Extraction Method: LLM-assisted benchmark extraction
# Last Updated: 2026-01-11

publications:
  - id: "meding_2025"
    title: "Long-term outcomes of cementless revision THA"
    benchmarks:
      hhs_improvement: {mean: 38.2, sd: 14.3, ci_95: [35.7, 40.7]}
      revision_rate: {value: 0.062, ci_95: [0.041, 0.089]}
      mcid_achievement: {value: 0.72}

  - id: "dixon_2025"
    title: "Risk factors for periprosthetic fracture"
    risk_factors:
      osteoporosis: {revision_hr: 1.8, fracture_hr: 2.4}
      fracture_rate_osteoporotic: {min: 0.15, max: 0.20}
      fracture_rate_non_osteoporotic: {min: 0.04, max: 0.08}

  - id: "harris_2025"
    title: "Adverse events in revision THA"
    benchmarks:
      ae_rate: {min: 0.28, max: 0.40}

  - id: "vasios_et_al"
    title: "Functional outcomes following revision"
    benchmarks:
      hhs_improvement_range: {min: 28, max: 42}
```

registry_norms.yaml

```
# Source: AOANJRR 2024, NJR UK
# Extraction Method: Structured data extraction
# Last Updated: 2026-01-11

registries:
  - id: "aoanjrr_2024"
    name: "Australian Orthopaedic Association National Joint Replacement Registry"
    benchmarks:
      revision_tha:
        cementless_cup:
          survival_2yr: 0.94
          revision_rate_median: 0.062
          revision_rate_p95: 0.12
      risk_factors:
```

```
osteoporosis: {revision_hr: 1.8, fracture_hr: 2.4}
bmi_over_35: {revision_hr: 1.6}
thresholds:
  fracture_rate_concern: 0.10

- id: "njr_uk"
  name: "National Joint Registry UK"
  benchmarks:
    revision_tha:
      survival_2yr: 0.93
      revision_rate_median: 0.065
```

Version 1.0 — Use Case Specifications with Multi-Source Architecture

Document generated: January 11, 2026