


Visitor Pattern

Contents

1	Intent	2
2	Problem	2
3	Solution	3
4	Real-World Analogy	5
5	Structure	6
6	Pseudocode	7
7	Applicability	9
8	How to Implement	10
9	Pros and Cons	10
10	Relations with Other Patterns	11
11	Examples	11


1 Intent

Visitor is a behavioral design pattern that lets you separate algorithms from the objects on which they operate.



2 Problem

Imagine that your team develops an app which works with geographic information structured as one colossal graph. Each node of the graph may represent a complex entity such as a city, but also more granular things like industries, sightseeing areas, etc. The nodes are connected with others if there's a road between the real objects that they represent. Under the hood, each node type is represented by its own class, while each specific node is an object.




Exporting the graph into XML.

At some point, you got a task to implement exporting the graph into XML format. At first, the job seemed pretty straightforward. You planned to add an export method to each

node class and then leverage recursion to go over each node of the graph, executing the export method. The solution was simple and elegant: thanks to polymorphism, you weren't coupling the code which called the export method to concrete classes of nodes.

Unfortunately, the system architect refused to allow you to alter existing node classes. He said that the code was already in production and he didn't want to risk breaking it because of a potential bug in your changes.



The XML export method had to be added into all node classes, which bore the risk of breaking the whole application if any bugs slipped through along with the change.

Besides, he questioned whether it makes sense to have the XML export code within the node classes. The primary job of these classes was to work with geodata. The XML export behavior would look alien there.

There was another reason for the refusal. It was highly likely that after this feature was implemented, someone from the marketing department would ask you to provide the ability to export into a different format, or request some other weird stuff. This would force you to change those precious and fragile classes again.

3 Solution

The Visitor pattern suggests that you place the new behavior into a separate class called visitor, instead of trying to integrate it into existing classes. The original object that had to perform the behavior is now passed to one of the visitor's methods as an argument, providing the method access to all necessary data contained within the object.

Now, what if that behavior can be executed over objects of different classes? For example, in our case with XML export, the actual implementation will probably be a little bit different across various node classes. Thus, the visitor class may define not one, but a set of methods, each of which could take arguments of different types, like this:

PSEUDO-CODE

```

1 class ExportVisitor implements Visitor is
    method doForCity(City c) { ... }
3    method doForIndustry(Industry f) { ... }
    method doForSightSeeing(SightSeeing ss) { ... }
5    // ...

```

But how exactly would we call these methods, especially when dealing with the whole graph? These methods have different signatures, so we can't use polymorphism. To pick a proper visitor method that's able to process a given object, we'd need to check its class. Doesn't this sound like a nightmare?

PSEUDO-CODE

```

1 foreach (Node node in graph)
    if (node instanceof City)
3        exportVisitor.doForCity((City) node)
    if (node instanceof Industry)
5        exportVisitor.doForIndustry((Industry) node)
    // ...
7 }

```

You might ask, why don't we use method overloading? That's when you give all methods the same name, even if they support different sets of parameters. Unfortunately, even assuming that our programming language supports it at all (as Java and C# do), it won't help us. Since the exact class of a node object is unknown in advance, the overloading mechanism won't be able to determine the correct method to execute. It'll default to the method that takes an object of the base **Node** class.

However, the Visitor pattern addresses this problem. It uses a technique called **Double Dispatch**, which helps to execute the proper method on an object without cumbersome conditionals. Instead of letting the client select a proper version of the method to call, how about we delegate this choice to objects we're passing to the visitor as an argument? Since the objects know their own classes, they'll be able to pick a proper method on the visitor less awkwardly. They "accept" a visitor and tell it what visiting method should be executed.

PSEUDO-CODE

```

1 // Client code
    foreach (Node node in graph)
3        node.accept(exportVisitor)

5 // City
    class City is
7        method accept(Visitor v) is
            v.doForCity(this)

```




```
9 // ...  
  
11 // Industry  
   class Industry is  
13     method accept(Visitor v) is  
       v.doForIndustry(this)  
15 // ...
```

I confess. We had to change the node classes after all. But at least the change is trivial and it lets us add further behaviors without altering the code once again.

Now, if we extract a common interface for all visitors, all existing nodes can work with any visitor you introduce into the app. If you find yourself introducing a new behavior related to nodes, all you have to do is implement a new visitor class.

4 Real-World Analogy




A good insurance agent is always ready to offer different policies to various types of organizations.

Imagine a seasoned insurance agent who's eager to get new customers. He can visit every building in a neighborhood, trying to sell insurance to everyone he meets. Depending on the type of organization that occupies the building, he can offer specialized insurance policies:

- If it's a residential building, he sells medical insurance.
- If it's a bank, he sells theft insurance.
- If it's a coffee shop, he sells fire and flood insurance.

5 Structure




Structure of Visitor Pattern.

1. The **Visitor** interface declares a set of visiting methods that can take concrete elements of an object structure as arguments. These methods may have the same names if the program is written in a language that supports overloading, but the type of their parameters must be different.
2. Each **Concrete Visitor** implements several versions of the same behaviors, tailored for different concrete element classes.
3. The **Element** interface declares a method for "accepting" visitors. This method should have one parameter declared with the type of the visitor interface.
4. Each **Concrete Element** must implement the acceptance method. The purpose of this method is to redirect the call to the proper visitor's method corresponding to the current element class. Be aware that even if a base element class implements this method, all subclasses must still override this method in their own classes and call the appropriate method on the visitor object.

5. The **Client** usually represents a collection or some other complex object (for example, a Composite tree). Usually, clients aren't aware of all the concrete element classes because they work with objects from that collection via some abstract interface.

6 Pseudocode

In this example, the Visitor pattern adds XML export support to the class hierarchy of geometric shapes.



Exporting various types of objects into XML format via a visitor object.



```

1 // The element interface declares an 'accept' method that takes
  // the base visitor interface as an argument.
3 interface Shape is
  method move(x, y)
  method draw()
  method accept(v: Visitor)
7

```



```
9 // Each concrete element class must implement the 'accept'
// method in such a way that it calls the visitor's method that
11 // corresponds to the element's class.
class Dot implements Shape is
13 // ...

15 // Note that we're calling 'visitDot', which matches the
// current class name. This way we let the visitor know the
17 // class of the element it works with.
method accept(v: Visitor) is
19     v.visitDot(this)

21
class Circle implements Shape is
23 // ...
method accept(v: Visitor) is
25     v.visitCircle(this)

27
class Rectangle implements Shape is
29 // ...
method accept(v: Visitor) is
31     v.visitRectangle(this)

33
class CompoundShape implements Shape is
35 // ...
method accept(v: Visitor) is
37     v.visitCompoundShape(this)

39
// The Visitor interface declares a set of visiting methods that
41 // correspond to element classes. The signature of a visiting method
// lets the visitor identify the exact class of the element that
43 // it's dealing with.
interface Visitor is
45     method visitDot(d: Dot)
method visitCircle(c: Circle)
47     method visitRectangle(r: Rectangle)
method visitCompoundShape(cs: CompoundShape)

49
// Concrete visitors implement several versions of the same
51 // algorithm, which can work with all concrete element classes.
//
53 // You can experience the biggest benefit of the Visitor pattern
// when using it with a complex object structure such as a
55 // Composite tree. In this case, it might be helpful to store
// some intermediate state of the algorithm while executing the
57 // visitor's methods over various objects of the structure.
class XMLExportVisitor implements Visitor is
59     method visitDot(d: Dot) is
// Export the dot's ID and center coordinates.
```




```
61 method visitCircle(c: Circle) is
62     // Export the circle's ID, center coordinates and radius.
63
64 method visitRectangle(r: Rectangle) is
65     // Export the rectangle's ID, left-top coordinates, width and height.
66
67 method visitCompoundShape(cs: CompoundShape) is
68     // Export the shape's ID as well as the list of its children's IDs.
69
70
71 // The client code can run visitor operations over any set of
72 // elements without figuring out their concrete classes. The
73 // accept operation directs a call to the appropriate operation
74 // in the visitor object.
75
76 class Application is
77     field allShapes: array of Shapes
78
79     method export() is
80         exportVisitor = new XMLExportVisitor()
81
82         foreach (shape in allShapes) do
83             shape.accept(exportVisitor)
```

If you wonder why we need the accept method in this example, my article [Visitor and Double Dispatch](#) addresses this question in detail.

7 Applicability

- **Use the Visitor when you need to perform an operation on all elements of a complex object structure (for example, an object tree).**
 - ▷ The Visitor pattern lets you execute an operation over a set of objects with different classes by having a visitor object implement several variants of the same operation, which correspond to all target classes.
- **Use the Visitor to clean up the business logic of auxiliary behaviors.**
 - ▷ The pattern lets you make the primary classes of your app more focused on their main jobs by extracting all other behaviors into a set of visitor classes.
- **Use the pattern when a behavior makes sense only in some classes of a class hierarchy, but not in others.**
 - ▷ You can extract this behavior into a separate visitor class and implement only those visiting methods that accept objects of relevant classes, leaving the rest empty.

8 How to Implement

1. Declare the visitor interface with a set of “visiting” methods, one per each concrete element class that exists in the program.
2. Declare the element interface. If you’re working with an existing element class hierarchy, add the abstract “acceptance” method to the base class of the hierarchy. This method should accept a visitor object as an argument.
3. Implement the acceptance methods in all concrete element classes. These methods must simply redirect the call to a visiting method on the incoming visitor object which matches the class of the current element.
4. The element classes should only work with visitors via the visitor interface. Visitors, however, must be aware of all concrete element classes, referenced as parameter types of the visiting methods.
5. For each behavior that can’t be implemented inside the element hierarchy, create a new concrete visitor class and implement all of the visiting methods.

You might encounter a situation where the visitor will need access to some private members of the element class. In this case, you can either make these fields or methods public, violating the element’s encapsulation, or nest the visitor class in the element class. The latter is only possible if you’re lucky to work with a programming language that supports nested classes.

6. The client must create visitor objects and pass them into elements via "acceptance" methods.

9 Pros and Cons

- + **Open/Closed Principle**. You can introduce a new behavior that can work with objects of different classes without changing these classes.
- + **Single Responsibility Principle**. You can move multiple versions of the same behavior into the same class.
- + A visitor object can accumulate some useful information while working with various objects. This might be handy when you want to traverse some complex object structure, such as an object tree, and apply the visitor to each object of this structure.
- You need to update all visitors each time a class gets added to or removed from the element hierarchy.
- Visitors might lack the necessary access to the private fields and methods of the elements that they’re supposed to work with.

10 Relations with Other Patterns

- You can treat **Visitor** as a powerful version of the Command pattern. Its objects can execute operations over various objects of different classes.
- You can use **Visitor** to execute an operation over an entire **Composite** tree.
- You can use **Visitor** along with Iterator to traverse a complex data structure and execute some operation over its elements, even if they all have different classes.

11 Examples

Without Visitor Pattern:



```
1 public interface MailClient {  
    void sendMail(String [] mailInfo);  
3    void receiveMail(String [] mailInfo);  
    boolean configureForMac();  
5    boolean configureForWindows();  
}
```



```
public class OperaMailClient implements MailClient {  
2    @Override  
    public void sendMail(String [] mailInfo) {  
4        System.out.println(" OperaMailClient: Sending mail");  
    }  
6  
    @Override  
8    public void receiveMail(String [] mailInfo) {  
        System.out.println(" OperaMailClient: Receiving mail");  
10    }  
12  
    @Override  
    public boolean configureForMac() {  
14        System.out.println("Configuration of Opera mail client for Mac complete");  
        return true;  
16    }  
18  
    @Override  
    public boolean configureForWindows() {  
20        System.out.println("Configuration of Opera mail client for Windows complete");  
        return true;  
22    }  
}
```



```
public class SquirrelMailClient implements MailClient {
2  @Override
  public void sendMail(String[] mailInfo) {
4    System.out.println("SquirrelMailClient: Sending mail");
  }

6

  @Override
8  public void receiveMail(String[] mailInfo) {
  System.out.println("SquirrelMailClient: Receiving mail");
10 }

12 @Override
  public boolean configureForMac() {
14   System.out.println("Configuration of Squirrel mail client for Mac complete");
   return true;
16 }

18 @Override
  public boolean configureForWindows() {
20   System.out.println("Configuration of Squirrel mail client for Windows complete");
   return true;
22 }
}
```



```
1 public class MailClientTest {

3   public void testConfigureMailClientForDifferentEnvironments()
       throws Exception {

5

       MailClient operaMailClient = new OperaMailClient();
7       operaMailClient.configureForMac();
       operaMailClient.configureForWindows();
9

       MailClient squirrelMailClient = new SquirrelMailClient();
11      squirrelMailClient.configureForMac();
       squirrelMailClient.configureForWindows();
13   }
}
```

Using Visitor Patterns:



```
package com.patterns.visitor.structure;
2
```



```
import com.patterns.visitor.visitors.MailClientVisitor;

4
public interface MailClient {
6     void sendMail(String[] mailInfo);
        void receiveMail(String[] mailInfo);
8     boolean accept(MailClientVisitor visitor);
    }
}
```



```
1 package com.patterns.visitor.structure;

3 import com.patterns.visitor.visitors.MailClientVisitor;

5 public class OperaMailClient implements MailClient{
    @Override
7     public void sendMail(String[] mailInfo) {
        System.out.println(" OperaMailClient: Sending mail");
9     }

11    @Override
    public void receiveMail(String[] mailInfo) {
13        System.out.println(" OperaMailClient: Receiving mail");
    }

15    @Override
    public boolean accept(MailClientVisitor visitor) {
17        visitor.visit(this);
19        return true;
    }
21 }
```



```
1 package com.patterns.visitor.structure;

3 import com.patterns.visitor.visitors.MailClientVisitor;

5 public class SquirrelMailClient implements MailClient{
    @Override
7     public void sendMail(String[] mailInfo) {
        System.out.println(" SquirrelMailClient: Sending mail");
9     }

11    @Override
    public void receiveMail(String[] mailInfo) {
13        System.out.println(" SquirrelMailClient: Receiving mail");
    }

15 }
```



```
@Override
17 public boolean accept(MailClientVisitor visitor) {
    visitor.visit(this);
19     return true;
    }
21 }
```



```
1 package com.patterns.visitor.structure;

3 import com.patterns.visitor.visitors.MailClientVisitor;

5 public class ZimbraMailClient implements MailClient{
    @Override
7     public void sendMail(String[] mailInfo) {
        System.out.println(" ZimbraMailClient: Sending mail");
9     }

11     @Override
    public void receiveMail(String[] mailInfo) {
13         System.out.println(" ZimbraMailClient: Receiving mail");
    }

15     @Override
    public boolean accept(MailClientVisitor visitor) {
17         visitor.visit(this);
19         return true;
    }
21 }
```



```
1 package com.patterns.visitor.visitors;

3 import com.patterns.visitor.structure.OperaMailClient;
import com.patterns.visitor.structure.SquirrelMailClient;
5 import com.patterns.visitor.structure.ZimbraMailClient;

7 public interface MailClientVisitor {
    void visit(OperaMailClient mailClient);
9     void visit(SquirrelMailClient mailClient);
    void visit(ZimbraMailClient mailClient);
11 }
```



```
1 package com.patterns.visitor.visitors;

3 import com.patterns.visitor.structure.OperaMailClient;
  import com.patterns.visitor.structure.SquirrelMailClient;
5 import com.patterns.visitor.structure.ZimbraMailClient;

7 public class WindowsMailClientVisitor implements MailClientVisitor{
    @Override
9     public void visit(OperaMailClient mailClient) {
        System.out.println("Configuration of Opera mail client for Windows complete");
11    }

13    @Override
        public void visit(SquirrelMailClient mailClient) {
15        System.out.println("Configuration of Squirrel mail client for Windows complete");
        }

17    @Override
        public void visit(ZimbraMailClient mailClient) {
19        System.out.println("Configuration of Zimbra mail client for Windows complete");
21    }
}
```



```
package com.patterns.visitor.visitors;

2
import com.patterns.visitor.structure.OperaMailClient;
4 import com.patterns.visitor.structure.SquirrelMailClient;
import com.patterns.visitor.structure.ZimbraMailClient;

6
public class MacMailClientVisitor implements MailClientVisitor{
8    @Override
        public void visit(OperaMailClient mailClient) {
10        System.out.println("Configuration of Opera mail client for Mac complete");
        }

12    @Override
        public void visit(SquirrelMailClient mailClient) {
14        System.out.println("Configuration of Squirrel mail client for Mac complete");
16    }

18    @Override
        public void visit(ZimbraMailClient mailClient) {
20        System.out.println("Configuration of Zimbra mail client for Mac complete");
22    }
}
```



```

package com.patterns.visitor.visitors;

2
import com.patterns.visitor.structure.OperaMailClient;
4 import com.patterns.visitor.structure.SquirrelMailClient;
import com.patterns.visitor.structure.ZimbraMailClient;

6
public class LinuxMailClientVisitor implements MailClientVisitor{
8     @Override
    public void visit(OperaMailClient mailClient) {
10         System.out.println("Configuration of Opera mail client for Linux complete");
    }

12
    @Override
14     public void visit(SquirrelMailClient mailClient) {
        System.out.println("Configuration of Squirrel mail client for Linux complete");
16     }

18
    @Override
    public void visit(ZimbraMailClient mailClient) {
20         System.out.println("Configuration of Zimbra mail client for Linux complete");
    }
22 }

```



```

package com.patterns.visitor.visitors;

2
import com.patterns.visitor.structure.OperaMailClient;
4 import com.patterns.visitor.structure.SquirrelMailClient;
import com.patterns.visitor.structure.ZimbraMailClient;

6
public class MailClientVisitorTest {
8     private MacMailClientVisitor macVisitor;
    private LinuxMailClientVisitor linuxVisitor;
10    private WindowsMailClientVisitor windowsVisitor;
    private OperaMailClient operaMailClient;
12    private SquirrelMailClient squirrelMailClient;
    private ZimbraMailClient zimbraMailClient;

14
    public static void main(String[] args) {
16        setup();

18        testOperaMailClient();
        testSquirrelMailClient();
20        testZimbraMailClient()
    }

22
    public void setup() {
24        macVisitor = new MacMailClientVisitor();
        linuxVisitor = new LinuxMailClientVisitor();

```




```

26 windowsVisitor = new WindowsMailClientVisitor();
   operaMailClient = new OperaMailClient();
28 squirrelMailClient = new SquirrelMailClient();
   zimbraMailClient = new ZimbraMailClient();
30 }

32 public void testOperaMailClient() throws Exception {
   System.out.println("—Testing Opera Mail Client for different environments—");
34   operaMailClient.accept(macVisitor);
   operaMailClient.accept(linuxVisitor);
36   operaMailClient.accept(windowsVisitor);
   }
38

40 public void testSquirrelMailClient() throws Exception {
   System.out.println("\n—Testing Squirrel Mail Client for different environments—");
42   squirrelMailClient.accept(macVisitor);
   squirrelMailClient.accept(linuxVisitor);
   squirrelMailClient.accept(windowsVisitor);
44 }

46 public void testZimbraMailClient() throws Exception {
   System.out.println("\n—Testing Zimbra Mail Client for different environments—");
48   zimbraMailClient.accept(macVisitor);
   zimbraMailClient.accept(linuxVisitor);
50   zimbraMailClient.accept(windowsVisitor);
   }
52 }

```

Command window

```

----Testing Opera Mail Client for different environments----
2 Configuration of Opera mail client for Mac complete
  Configuration of Opera mail client for Linux complete
4 Configuration of Opera mail client for Windows complete

6 ----Testing Squirrel Mail Client for different environments----
  Configuration of Squirrel mail client for Mac complete
8 Configuration of Squirrel mail client for Linux complete
  Configuration of Squirrel mail client for Windows complete
10

12 ----Testing Zimbra Mail Client for different environments----
  Configuration of Zimbra mail client for Mac complete
  Configuration of Zimbra mail client for Linux complete
14 Configuration of Zimbra mail client for Windows complete

```