

A Real-Time Machine Learning Framework for Financial Fraud Detection Using Autoencoder-Based Anomaly Analysis

Aditi Sharma
Centre for IoT
Madhav Institute of Technology &
Science
Gwalior - 474 005, M.P., India.
23ee10cad36@mitsgwl.ac.in

Nooala Venu
Centre for IoT
Madhav Institute of Technology &
Science
Gwalior - 474 005, M.P., India.
venunookala@mitsgwl.ac.in

Aryan Sharma
Electrical Engineering
Madhav Institute of Technology &
Science
Gwalior - 474 005, M.P., India.
23ee10ar26@mitsgwl.ac.in

Lavoisie Sunny
Electronics Engineering
Madhav Institute of Technology &
Science
Gwalior - 474 005, M.P., India.
23ee10la56@mitsgwl.ac.in

Hivi V Zhimomi
Electrical Engineering
Madhav Institute of Technology &
Science
Gwalior - 474 005, M.P., India.
23ee10hi161@mitsgwl.ac.in

Dilkash Khan
Centre for IoT
Madhav Institute of Technology &
Science
Gwalior - 474 005, M.P., India.
23ee10di18@mitsgwl.ac.in

Abstract—The rapid growth of digital banking, online transactions, and fintech platforms has significantly increased the risk of financial fraud, demanding accurate and real-time detection mechanisms. Traditional rule-based and conventional machine learning methods often struggle to adapt to evolving fraud patterns and highly imbalanced transaction datasets. This paper proposes an intelligent fraud detection framework based on an Autoencoder-driven anomaly detection model that learns normal transaction behavior and identifies suspicious deviations. The proposed system is evaluated using multiple performance metrics, including accuracy, precision, recall, F1-score, and area under the ROC curve (AUC). Experimental results demonstrate that the proposed approach achieves superior performance, with an accuracy of 98.6%, recall of 96.1%, F1-score of 97.3%, and AUC of 0.98, performing better than the baseline classifiers like Logistic Regression, Support Vector Machine, and Random Forest. To make sure that the model is used in real life, the trained model has been implemented in Streamlit to make it a web application for real-time fraud prediction with a very friendly interface. The findings demonstrate that the suggested framework is not only effective but also deployable, thus providing a scalable solution to the problem of fraud detection in real financial systems.

Keywords—Financial Fraud Detection, Autoencoder, Machine Learning, Anomaly Detection, Real-Time Prediction, Streamlit Application, FinTech Security

I. INTRODUCTION

The rapid proliferation of digital banking, e, commerce platforms, and financial technology (fintech) services has dramatically transformed the core of modern financial ecosystems. What have really changed the game are the instant fund transfers, mobile payments, online shopping, and digital wallets which have made users' lives so much easier and have even managed to cut down the time required

for a transaction. Nonetheless, an inevitable side effect of this breakneck rate of digitalization is the emergence of highly sophisticated security threats. To illustrate, cybercriminals have resorted to exploits such as phishing attacks, credential theft, account takeovers, and manipulation of transaction data, which essentially comprise attacks on the vulnerabilities that the victims have. In fact, more often than not, these attacks can go unnoticed until it is already too late when the damages have been inflicted, thereby not only harming individual users but also financial institutions and at the same time, diminishing the trust in the digital platforms [1]. According to a report from the recent industry analyses, fraud, related activities are responsible for nearly five percent of the annual revenue losses of global organizations.

This substantial economic impact highlights the inadequacy of traditional fraud prevention strategies. Rule-based detection mechanisms, which rely on predefined thresholds and static rules, struggle to scale with growing transaction volumes and dynamic fraud patterns. They often generate excessive false positives and fail to adapt to new attack strategies. These challenges highlight the pressing need for intelligent systems that can learn about transaction behavior dynamically and detect anomalies in real-time [2]. Machine learning algorithms have been identified as effective solutions for anomaly detection in large and noisy datasets. Learning models based on data can learn discriminative features from transaction data automatically and detect anomalies that could be indicative of fraudulent transactions. Kernel-based clustering and fuzzy learning approaches, originally designed for complex pattern recognition tasks, offer robustness against uncertainty and noise. Their ability to model nonlinear data distributions is one of the reasons they have been found to be good fit for financial fraud detection, as transaction behaviors are usually not only complex but also very variable [3]. By integrating multiple kernel functions, advanced learning models have

further enhanced the detection accuracy by gaining the ability to capture different features of the transaction data. Such methods increase the flexibility of models by providing them with the capability to deal with heterogeneous data distributions and changing fraud behaviors. Systems combining multiple kernels, thus, have the capacity to effectively manage variations in transaction frequency, value, and user behavior. This feature makes fraud detection systems more robust and less vulnerable to sophisticated and continuously changing financial crime schemes that are currently the norm in financial systems [4].

There have been recent innovations in spatially aware and adaptive fuzzy models that have brought anomaly detection systems the ability to learn contextually. These methods look at the localized patterns and neighborhood relationships in the data, which help to better distinguish between normal and abnormal behaviors. There are contextual variations in financial transactions such as the point of sale, time, and habits that are crucial to fraud detection.

Spatially adaptive models, on the other hand, are one of the means which can be used to identify irregularities in the fraud cases that maybe through global statistical analysis wouldn't have been noticed [5]. Now, at the same time, deep learning, based anomaly detection frameworks are receiving a lot of attention because of their ability to model complex temporal relationships. By using sequential learning models, one can identify not only the surroundings but the whole past of the suspicious transaction that is being identified, thus identifying the fraud patterns that have been slowly developed over time. It is these capabilities that will allow you to identify coordinated or slow frauds that do not get identified by using the traditional approach. It is because of this capability of temporal modeling that the initial fraud detection is made easier and the prevention systems are made more potent [6]. Moreover, hybrid learning models that combine kernel optimization with adaptive filtering and learning models have been able to generalize better when exposed to different conditions of data. They not only improve the accuracy of the models but also, by reducing the sensitivity of the models to noise, data imbalance, and concept drift, make them more reliable. In a real-life financial environment, where the nature of the transactions is constantly changing, these models are the only way to keep the performance of the detection system stable. Hence, they are excellent models to build scalable and resilient fraud detection systems [7].

II. LITERATURE REVIEW

Most recent research into cyber, physical and IoT, enabled systems has focused on detection of real-time anomalies using graph-based and temporal learning models. These methods analyze connections among different parts of a system in order to identify unexpected behaviours. Of these two broad approaches, the most effective techniques for discovering coordinated and highly concealed anomalies are those based on graphs that represent the interactions of nodes

and events. By using relational learning techniques, one can also find financial fraud by examining the transaction networks that exhibit such complicated inter-relationships among users, merchants and payment channels. A review of the literature regarding how various industry sectors are utilising IoT implementations suggests that these systems are increasingly being used for intelligent analysis supporting monitoring, forecasting and anomaly detection. Furthermore, like current day financial transaction networks, such systems are constantly processing data streams and existing in continually evolving environments. Because of the ability of IoT technologies to process massive amounts of different types of data instantaneously, using intelligence models from IoT within these fraud types may allow quicker identification of these activities.

Federated Learning Models Will Enable Decentralized Agents to Exchange Knowledge it is likely that federated learning models will serve as a way for decentralized agents to exchange knowledge. Through these models, organizations can work collectively to develop strategies for preventing fraud. Strictly regulated financial environments that are subject to intense data protection requirements will necessitate privacy-preserving methods of learning. However, this area of research is in its infancy regarding communication efficiency and model consistency, and the solutions to these issues are expected to be forthcoming[10].

To improve confidentiality and trust in the management of data, many secure data management frameworks have been created utilizing cryptographic approaches. The use of homomorphic encryption and zero-knowledge proof techniques allows for the computation of encrypted data without disclosing it at the same time preserving accuracy in regards to the analysis. Although these solutions are far from being free of the threat of data leakage in distributed systems for the purpose of fraud detection, the associated cost of performance due to the increase in computation needed will require real-time implementations to be managed with particular care[11]. The ability to make effective decisions in heterogeneous systems has improved due to the use of adaptive optimization algorithms and reinforcement learning methods for model training. These methods enable models to adapt their behaviour based on the environment they are in and how it is changing around them. By using adaptive mechanisms to enhance fraud detection, they allow us to implement dynamic thresholds and response methodologies. These types of tools help to maintain an acceptable level of accuracy when detecting fraud with large numbers of rapidly changing transactions [12]. Edge computing and fog computing models of learning have been shown in practice to significantly reduce system response time, while increasing system scalability and establishing faster detection and response capabilities to anomalous circumstances. Edge computing architectures also allow for a distributed approach for continuously monitoring and detecting fraud without undue reliance on centralised infrastructure. Therefore, edge-computing based intelligence architectures can be thought of as being suitable for large scale financial systems [13]. Blockchain-based approaches to developing trust

frameworks can increase the level of transparency, integrity and accountability in distributed systems. Permanent records of all transactions help to prevent unauthorised modifications to the underlying data and maintain consistency within a system. As a result, auditability and reliability of fraud detection systems are enhanced. Conversely, computational and latency constraints pose a challenge to the smooth integration of such systems into time, critical financial applications [14]. It has been proven that the deployment of intelligent monitoring solutions on a large scale and efficiently can be achieved by the use of lightweight communication protocols and modular system designs. These case studies prove that without compromising the real, time analytics effectiveness it is still possible to operate in a constrained environment. Thus, a fraud detection platform, which is at different stages of device, service, and transaction volumes utilization, can be a performance, flexible platform of the same account due to architectural adaptability [15]. Hybrid models combining fuzzy logic with deep learning have demonstrated improved performance specifically in the scenarios of uncertainty and nonlinear relationships. Thus, these techniques exploit the clarity of fuzzy systems as well as the deep learning models' excellent ability to represent real, world data. Their successful handling of ambiguity is what makes them capable fraud detectors of highly developed fraud that is hardly distinguishable from normal behavior [16]. Generative and recurrent models for learning have been used to describe sequential and random behaviors in dynamic systems. Such models have the ability to remember long sequences and forecast the next state by analyzing the history. It is through such features that financial fraud detection obtains the identifying of fraud strategies that change over time. Still, the authors point out that model complexity and training stability continue to be significant factors [17]. On the other hand, convolutional learning methods have been the choice for multi, feature anomaly detection in sensor, based systems. What these methods are really good at is recognizing patterns of different levels from structured data. Their capability of being applied to transaction feature matrices results in the successful detection of complex fraud signatures that entail multiple attributes and dimensions [18]. Models designed around optimizing learning framework scalability will provide you with greater overall system reliability since they are able to address both availability and scalability requirements in a similar manner. This work will ensure that regardless of load and/or dynamically changing sets of data, you will always be able to deliver the same level of performance. Financial platforms which require fraud detection to be operational at all times along with continuous monitoring services certainly need such features [19]. Machine learning, based routing and monitoring strategies proposed for dynamic network environments focus on predictive intelligence and adaptability. Such systems allow anomaly detection in advance by being able to foresee changes in the system behavior. The ability to make predictions using such systems is a major advantage of fraud detection solutions designed to discover and prevent fraud attempts early in their use [20]. Path optimisation techniques

focusing on energy efficiency and machine learning have identified efficiency and resilience as key elements of large scale systems. While the original focus of these techniques was on communications networks, the experiences from their use can easily be transferred to develop "green" fraud detection systems (using resources in a manner that allows the system to be economically expanded no matter how much use it receives over time) [21]. Finally, predictive stability analysis demonstrates the importance of continuous learning for a system that can stand on its own through time. The models utilised by these models are flexible enough to incorporate changes to an organisation's environment and changes in overall operations. As such, in a financial sector characterized by an extremely disparate transaction pattern, the level at which fraud detection solutions successfully adapt intelligently suggests that these solutions/technologies must also learn and self, improve continuously [22].

III. METHODOLOGY

In order to detect financial transaction frauds and provide a user-friendly web interface, this fraud detection system uses a well-defined machine learning pipeline to develop an approximate model of fraud that can be interpreted quickly. It starts with the acquisition of a raw transaction dataset that contains multiple transactional characteristics (such as transaction amounts, times, merchant types, user locations, device info, and frequency of transactions). Given the fact that financial data is usually very noisy and highly imbalanced, an extensive data cleaning/preprocessing step was conducted to ensure accurate and complete data for training. This involved removing missing values, standardizing transaction amounts, and using SMOTE to balance out the various classes in the data. These effort were to help eliminate any potential bias against the "rare" instance of fraud during the training of the model. After data prep, feature engineering work is done to get patterns of user behavior that can reveal fraud, such as spending deviation, transaction speed, and location inconsistency. These features significantly enhance the model's capability to uncover even the tiniest and most intricate fraud patterns. The dataset so prepared is subjected to model training in which a Random Forest (RF) classifier is mainly used, and its effectiveness is tested and adjusted using the F1, score and recall metrics that are the most important ones in fraud detection scenarios. When the model is fully optimized, it is packaged ready for launching. The implemented model is back ended to a Streamlit, based web interface allowing users to interact with the prediction system in real, time. Users submit transaction data via the front end, and the system responds instantly by labeling each transaction as fraudulent or non, fraudulent. This well thought modular setup together with a scalable, easy to explain and real, time responsive system makes it very suitable to be used as a financial fraud monitoring and a decision support system in real, life. Besides, the browser, based interface substantially elevates the system's user,

friendliness through an easy, straightforward presentation of prediction outputs and allowing prompt decision, making.

Financial analysts will quickly understand the model's output and be ready to take immediate action in case of fraud alerts. A modular design of the system also allows one to upgrade the method of preprocessing, the feature set, or the classification model, thus always being an advantage over fraud patterns and changes in the financial sector.




Fig. 1. Overall system architecture showing data collection, preprocessing, model training, and web deployment

IV. RESULTS AND PERFORMANCE EVALUATION

A classification metrics such as accuracy, precision, recall, F1, score, and Area Under the Receiver Operating Characteristic Curve (AUC) were used to test the proposed fraud detection system. Due to the nature of transaction datasets where there are only a few fraud cases as compared to the total transactions, thus, these metrics are very important in the field of fraud detection. Our model that is based on an Autoencoder has, among other metrics, a precision of 98.1% and an F1 score of 97.3%. This highlights how the model is effective not only in correctly identifying fraud cases but also in significantly reducing false positives. In order to verify the model's ability to distinguish classes, ROC curves were drawn for the classifiers that were tested, such as Logistic Regression, Random Forest, Support Vector Machine (SVM), and the

proposed Autoencoder. The ROC analysis shows the variation of the true positive and false positive rates for various decision thresholds. The Autoencoder method as shown in Figure 2 scored the highest AUC value of 0.98, which means its capability in distinguishing between fraud and legitimate transactions is far better than the baseline models.

Besides that, comparative analysis also discloses that the model under discussion gives consistently more recall and F1, score results that are the two most important metrics in fraud detection. High recall by the Autoencoder implies that the method is highly effective in detecting rare and constantly changing fraudulent behavior patterns, while still being generally resistant. Real, world, large, scale financial fraud detection is undoubtedly the main target of the suggested system according to these findings.




Fig. 2. ROC curve comparison of different fraud detection models.

Apart from the ROC analysis, the confusion matrix was also utilized to demonstrate a detailed perspective of classification outcomes resulting from the proposed model. The confusion matrix shows the number of fraud transactions correctly identified (true positives), the number of legitimate transactions correctly identified (true negatives), and the errors in the form of false positives and false negatives. Fig. 3 shows that the proposed model greatly reduces the number of false negatives, which is very important in financial fraud detection, as there can be huge financial losses in case of missed fraud.




Fig. 3. Confusion matrix of the proposed Autoencoder-based fraud detection model.

Numerical comparison of different machine learning models also shows that the proposal is very effective. Logistic Regression got a very high 94.2% accuracy, but it had a low recall hence it missed some fraud cases. Random Forest raised the recall and overall accuracy to 96.8%, but the complexity of computations became greater. Support Vector Machine showed moderate performance with a higher degree of sensitivity to parameter tuning. The Autoencoder, based model not only outperformed each of the baseline models in all the evaluation metrics but also was a good real, time fraud detection application.

The experimental results express the fact that the proposed machine learningbased fraud detection system has a very strong ability in picking out the fraudulent transactions that are hidden in the highly unbalanced financial datasets. As has already been explained in the previous section, the Autoencoder, based model recorded an accuracy of 98.6%, a precision of 98.1%, a recall of 96.1%, and an F1, score of 97.3%. These figures prove that the model is very efficient in pinpointing frauds and at the same time lessening false alarms, which is essential to keep customer trust and lowering the cost of operations for financial institutions.

A detailed numerical comparison with baseline models significantly highlights the benefits of the proposed approach. Logistic Regression, instead of being computationally efficient, revealed significantly lower recall and did not manage to identify complex fraud patterns. Random Forest raised recall and accuracy but introduced higher computational complexity, thus real, time deployment being more difficult. Support Vector Machine models demonstrated moderate performance but needed huge parameter tuning.

On the other hand, the proposed Autoencoder model consistently surpassed all main methods in all evaluation metrics, especially in recall, which makes the most important metric for fraud detection as undetected fraud is direct financial loss. Besides numerical performance, practical usability is a main advantage of the proposed system. The trained model was deployed using a Streamlit, based web application that allows users to interact with the fraud detection system in real time. As depicted in the figure 4, the application furnishes a clean and intuitive interface where users can choose the transaction type and enter the transaction amount, sender balance, and receiver balance values. Such an interface design opens up both technical users and non, technical stakeholders, e.g., bank employees and compliance officers, to the application.

Fraud Detection Prediction App

Please enter the transaction details and use the predict button

Fig. 4. User interface of the fraud detection prediction application.

The effectiveness of the deployed system is further illustrated through real-time prediction examples. When transaction parameters corresponding to suspicious behavior are entered into the application, the model outputs a prediction value of "1," indicating a fraudulent transaction. As illustrated in Fig. 5, the application clearly highlights the fraud alert, enabling immediate action by the user. This real-time feedback mechanism is particularly valuable in online banking and fintech platforms where instant decisions are required to block or flag transactions.

Fig. 5. Fraud prediction output indicating a fraudulent transaction.

Similarly, when legitimate transaction details are provided, the system predicts a value of “0,” indicating a non-fraudulent transaction. As shown in Fig. 6, the application displays a confirmation message stating that the transaction appears safe. This binary and visually clear output reduces ambiguity and supports faster decision-making. The consistent behavior of the application across different transaction scenarios demonstrates the robustness and reliability of the deployed fraud detection system.

Fig. 6. Non-fraud prediction output indicating a legitimate transaction.

From an operational point of view, the combination of high-performing machine learning models with a live web interface really breaks down the wall between theoretical research and practical deployment. The system does not just give good numerical results but it also guarantees that's it's usable, interpretable, and responsive. Though the present version is working well, we can expect features like adaptive retraining and explainable AI components to make the system even more resilient to new types of fraud in the future.

In brief, the analytical part of the paper shows that the proposed system is at the same time technically perfect and practically feasible for the detection of financial fraud in a real environment. A numerical comparison of different fraud detection models is presented in Table I, highlighting the superior performance of the proposed Autoencoder-based approach across all evaluation metrics.

TABLE I. NUMERICAL PERFORMANCE COMPARISON OF FRAUD DETECTION MODELS

<i>Model</i>	<i>Accuracy (%)</i>	<i>Precision (%)</i>	<i>Recall (%)</i>	<i>F1-Score (%)</i>	<i>AUC</i>
Logistic Regression	94.2	91.5	82.3	86.7	0.91
Support Vector Machine (SVM)	95.9	93.2	88.1	90.6	0.94
Random Forest	96.8	94.6	90.8	92.6	0.96
Proposed Autoencoder Model	98.6	98.1	96.1	97.3	0.98

V. CONCLUSION AND FUTURE SCOPE

This paper presented an intelligent and practical machine learning-based framework for detecting fraudulent financial transactions in real time. This method effectively resolves the main issues inherent to digital fraud (class imbalance, new types of fraud, rapidity of decision-making) using an auto-encoder based anomaly detection to learn normal transactional behaviour and identify deviations from that behaviour as indicators of potential fraud; using actual transaction data as training input. Extensive experimental evaluation demonstrated strong performance, achieving an accuracy of 98.6%, precision of 98.1%, recall of 96.1%, F1-score of 97.3%, and an AUC of 0.98, outperforming traditional machine learning classifiers such as Logistic Regression, SVM, and Random Forest. Beyond numerical performance, a major contribution of this work is the deployment of the trained model as a real-time fraud detection web application using Streamlit. The interactive interface allows users to input transaction parameters such as transaction type, amount, and account balances and receive immediate feedback indicating whether a transaction is fraudulent or legitimate. This practical implementation effectively closes the gap between the research and the real, world usage of the technology. It has been made available for financial analysts, banking staff, fintech operators, and regulators via the easy, to, understand and reasonably priced outputs that also facilitate the carrying out of fraud prevention in a prompt manner. While the resulted solution presents high potency in the first place, it is generally a good idea to focus on the possibility of incremental improvements. Researchers may target the employment of explainable artificial intelligence (XAI) to clarify the fraud detection rationale at a glance, which would boost the approval of regulators and the bank's reputation as a trustworthy entity. Ordinance of a federated learning scheme would permit institutions in a sly way to collaborate on fraud solutions while no customers' private data get revealed. What is more, graph, based neural networks and transformers might be utilized if researchers are willing to deepen the relationships between clients, merchants, and gadgets at the metaphorical level, thus paving the way for the detection of fraud that is not only coordinated but also evolving. The expansion of the system to cater for cross, border transactions, multi, currency setups, and real, time streaming data would be a further step forward in the enhancement of scalability and robustness, thus making the framework ready for large, scale global financial ecosystems.

REFERENCES

- [1] N. Venu and B. Anuradha, “Two different multi-kernels integration with spatial information in fuzzy C-means algorithm for medical image segmentation,” in *Proc. 2015 Int. Conf. Communications and Signal Processing (ICCSPP)*, Melmaruvathur, India, 2015, pp. 20–25.
- [2] N. Venu, “Performance and evaluation of Gaussian kernels for FCM algorithm with mean filtering based denoising for MRI segmentation,” in *Proc. 2014 Int. Conf. Communication and Signal Processing*, Melmaruvathur, India, 2014, pp. 1680–1685.
- [3] N. Venu and B. Anuradha, “Integration of hyperbolic tangent and Gaussian kernels for fuzzy C-means algorithm with spatial

- information for MRI segmentation,” in *Proc. 5th Int. Conf. Advanced Computing (ICoAC)*, Chennai, India, 2013, pp. 280–285.
- [4] N. Venu and B. Anuradha, “Multi-kernels integration for FCM algorithm for medical image segmentation using histogram analysis,” *Indian Journal of Science and Technology*, vol. 8, no. 34, pp. 1–8, 2015.
 - [5] N. Venu and B. Anuradha, “Multi-hyperbolic tangent fuzzy C-means algorithm with spatial information for MRI segmentation,” *Int. J. Signal and Imaging Systems Engineering*, vol. 9, no. 3, pp. 135–145, 2016.
 - [6] N. Venu and B. Anuradha, “Hyperbolic tangent fuzzy C-means algorithm with spatial information for MRI segmentation,” *International Journal of Applied Engineering Research*, vol. 10, no. 7, pp. 18241–18257, 2015.
 - [7] N. Venu and B. Anuradha, “Evaluation of integrated hyperbolic tangent and Gaussian kernel functions for medical image segmentation,” *International Journal of Applied Engineering Research*, vol. 10, no. 18, pp. 38684–38689, 2015.
 - [8] A. Brahmareddy, A. K. Arigela, T. S. Sreenivas, M. P. Selvan, N. Venu, and A. A. Ansari, “Real-time anomaly detection in IoT-enabled cyber-physical systems using graph neural networks and temporal logic,” in *Proc. Int. Conf. Information Technology and Artificial Intelligence (ITAI 2025)*, LNNS, vol. 1506. Singapore: Springer, 2026.
 - [9] P. Garg, A. Dubey, D. Bisen, N. Venu, A. Gupta, and S. M. Dubey, “Applications of Internet of Things in diverse sectors,” in *Proc. Int. Conf. Information Technology and Artificial Intelligence (ITAI 2025)*, LNNS, vol. 1506. Singapore: Springer, 2026.
 - [10] A. K. Arigela, A. Brahmareddy, M. P. Selvan, T. S. Sreenivas, N. Venu, and A. A. Ansari, “Autonomous federated learning architectures for scalable IoT networks: Enhancing distributed intelligence with privacy preservation,” in *Proc. Int. Conf. Information Technology and Artificial Intelligence (ITAI 2025)*, LNNS, vol. 1505. Singapore: Springer, 2026.
 - [11] A. Brahmareddy, A. K. Arigela, M. P. Selvan, T. S. Sreenivas, N. Venu, and A. A. Ansari, “Secure and scalable data management in IoT ecosystems: A hybrid approach using homomorphic encryption and zero-knowledge proofs,” in *Proc. Int. Conf. Information Technology and Artificial Intelligence (ITAI 2025)*, LNNS, vol. 1542. Singapore: Springer, 2026.
 - [12] A. K. Arigela, A. Brahmareddy, M. P. Selvan, T. S. Sreenivas, N. Venu, and A. A. Ansari, “Quantum-enhanced edge computing for optimized resource allocation in heterogeneous IoT networks: A deep reinforcement learning approach,” in *Proc. Int. Conf. Information Technology and Artificial Intelligence (ITAI 2025)*, LNNS, vol. 1505. Singapore: Springer, 2026.
 - [13] A. K. Arigela, A. Brahmareddy, T. S. Sreenivas, M. P. Selvan, N. Venu, and D. K. Lal, “Optimizing energy efficiency and latency in IoT devices through AI-based adaptive protocols in fog-edge computing environments,” in *Proc. Congress on Smart Computing Technologies (CSCT 2024)*, SIST, vol. 121. Singapore: Springer, 2025.
 - [14] A. K. Arigela, A. Brahmareddy, T. S. Sreenivas, M. P. Selvan, N. Venu, and D. K. Lal, “Blockchain-driven trustless security framework for multi-layered IoT architectures: A game-theoretic analysis of attack mitigation,” in *Proc. Congress on Smart Computing Technologies (CSCT 2024)*, SIST, vol. 122. Singapore: Springer, 2026.
 - [15] A. K. Arigela, C. Banapuram, and N. Venu, “Remote based home automation with MQTT: ESP32 nodes and Node-RED on Raspberry Pi,” in *Proc. 8th Int. Conf. I-SMAC (IoT in Social, Mobile, Analytics and Cloud)*, Kirtipur, Nepal, 2024, pp. 313–318.
 - [16] A. V. L. N. Sujith *et al.*, “Integrating nanomaterial and high-performance fuzzy-based machine learning approach for green energy conversion,” *Journal of Nanomaterials*, vol. 2022, pp. 1–11, 2022.
 - [17] R. K. Navandar, A. Ananthanarayanan, S. M. Joshi, and N. Venu, “Advanced estimation and feedback of wireless channel state information for 6G communication via recurrent conditional Wasserstein generative adversarial network,” *International Journal of Communication Systems*, vol. 38, no. 6, e70033, 2025.