

# Business Analytics - ETC3250 2017 - Lab 7

The bootstrap

*Souhaib Ben Taieb*


*6 September 2017*

Note: the online version of “An Introduction to Statistical Learning with Applications in R” (ISLR) is available at <http://www-bcf.usc.edu/~gareth/ISL/>.

## Assignment - Question 1

Do the exercise 2 in Section 5.4 of ISLR.

- $\frac{n-1}{n}$
- $\frac{n-1}{n}$
- probability that the  $j$ th observation is not in the bootstrap sample = probability that the  $j$ th observation is not in the  $i$ th position where  $i = 1, \dots, n$  = (probability that the  $j$ th observation is not in the  $i$ th position) <sup>$n$</sup>  and probability that the  $j$ th observation is not in the  $i$ th position is given above.
- probability that the  $j$ th observation is in the bootstrap sample = 1 - probability that the  $j$ th observation is not in the bootstrap sample =  $1 - (1 - 1/5)^5 = 1 - (4/5)^5 = 67.2\%$
- $1 - (99/100)^{100} = 63.4\%$
- $1 - (1 - 1/10000)^{10000} = 63.2\%$



- We can clearly see the convergence to  $1 - 1/e = 63.2\%$

```
store <- rep(NA, 10000)
for (i in 1:10000) {
  store[i] <- sum(sample(1:100, rep=TRUE) == 4) > 0
}
mean(store)
# [1] 0.6376
```

The same conclusion as above.

## Bootstrap confidence interval of the correlation coefficient

We will find a 95% confidence interval for the correlation coefficient of Median House value and average number of rooms in the Boston data set from the **MASS** package.

The functions `cor` and `cor.test` will compute the correlation and an asymptotic 95% confidence interval for it. This interval is based on Fisher's  $z$  transform

$$z = \frac{1}{2} \log \left( \frac{1+r}{1-r} \right)$$

which is approximately normally distributed with variance  $1/(n-3)$  where  $n$  is the number of observations. So if  $z_L$  and  $z_U$  are upper and lower limits for  $z$ , then

$$r_L = \frac{\exp(2z_L) - 1}{\exp(2z_L) + 1} \quad \text{and} \quad r_U = \frac{\exp(2z_U) - 1}{\exp(2z_U) + 1}$$

are upper and lower limits for  $r$ .

We will use the bootstrap to test if this is a good approximation in this case.

### Exercise 1

Check that the confidence interval returned by `cor.test` is computed using the above transformation.

```
library(MASS)

n <- nrow(Boston)
r <- cor(Boston$medv, Boston$rm)

# Fisher interval
cor.test(Boston$medv, Boston$rm)
#
# Pearson's product-moment correlation
#
# data: Boston$medv and Boston$rm
# t = 21.722, df = 504, p-value < 2.2e-16
# alternative hypothesis: true correlation is not equal to 0
# 95 percent confidence interval:
#  0.6474346 0.7378075
# sample estimates:
#      cor
# 0.6953599

z <- 0.5*log((1+r)/(1-r))
zint <- z + 1.96/sqrt(n-3)*c(-1,1)
rint <- (exp(2*zint)-1)/(exp(2*zint)+1)
print(rint)
# [1] 0.6474337 0.7378082
```

### Assignment - Question 2

Compute a 95% bootstrap confidence interval for the correlation. You will need to sample rows of the **Boston** matrix.

```

B <- 1000
rb <- numeric(B)
for(i in 1:B)
{
  bootstrapdata <- Boston[sample(n, replace=TRUE),]
  rb[i] <- cor(bootstrapdata$medv, bootstrapdata$rm)
}
quantile(rb, prob=c(0.025,0.975))
#      2.5%      97.5%
# 0.6130238 0.7682752

```

### Assignment - Question 3

Write a function that will return a bootstrap confidence interval for the correlation of any two numeric variables of the same length. Your function should take four arguments:

- x: a numeric vector of data
- y: a numeric vector of data
- level: the probability coverage of the confidence interval with default value of 0.95
- B: the number of bootstrap samples with default value of 1000.

```

bootstrap.cor.int <- function(x, y, level=0.95, B=1000)
{
  n <- length(x)
  rb <- numeric(B)
  for(i in 1:B)
  {
    j <- sample(n, replace=TRUE)
    rb[i] <- cor(x[j],y[j])
  }
  alpha = 1-level
  return(quantile(rb, prob=c(alpha/2, 1-alpha/2)))
}

bootstrap.cor.int(Boston$medv,Boston$rm,B=10000)
#      2.5%      97.5%
# 0.6090095 0.7691631

```

### TURN IN

- Your .Rmd file (which should knit without errors and without assuming any packages have been pre-loaded)
- Your Word (or pdf) file that results from knitting the Rmd.
- DUE: 10 September 11:55pm (late submissions not allowed), loaded into moodle