

Homework 3

DATA604 Simulation and Modeling

Daniel Dittenhafer

March 6, 2016

1

Starting with $X_0 = 1$, write down the entire cycle for $X_i = 11X_{i-1} \bmod(16)$

```
fn1 <- function(x0)
{
  df <- data.frame(X=c(), R=c())
  x <- x0
  continue <- TRUE

  while(continue)
  {
    xi <- (11 * x) %% 16
    df <- rbind(df, data.frame(X=x, R=xi))
    x <- xi

    if(xi == x0)
    {
      break
    }
  }

  return(df)
}

res <- fn1(1)
```

| X | R |
|----|----|
| 1 | 11 |
| 11 | 9 |
| 9 | 3 |
| 3 | 1 |

2

Using the LCG provided below: $X_i = (X_{i-1} + 12) \bmod(13)$, plot the pairs $(U_1, U_2), (U_2, U_3), \dots$ and observe the lattice structure obtained. Discuss what you observe.

```
fn2 <- function(x0, max=100)
{
  df <- data.frame(U1=c(), U2=c())
  x <- x0


  for(i in 1:max)
  {
    xi <- (x + 12) %% 13
    df <- rbind(df, data.frame(U1=x, U2=xi))
  }
}
```

```

  x <- xi
}

return(df)
}
# Call the function starting at x0=1
res <- fn2(25)

```



The chart above suggests there are only 13 points, but actually the LCG cycle period is 13 and numbers are repeating.

| U1 | U2 |
|----|----|
| 25 | 11 |
| 11 | 10 |
| 10 | 9 |
| 9 | 8 |
| 8 | 7 |
| 7 | 6 |
| 6 | 5 |
| 5 | 4 |
| 4 | 3 |
| 3 | 2 |
| 2 | 1 |
| 1 | 0 |
| 0 | 12 |
| 12 | 11 |

3

Implement the pseudo-random number generator:

$$X_i = 16807X_{i-1} \bmod(2^{31} - 1)$$

Using the seed 1234567, run the generator for 100,000 observations. Perform a chi-square goodness-of-fit test on the resulting PRN's. Use 20 equal-probability intervals and level $\alpha = 0.05$. Now perform a runs up-and-down test with $\alpha = 0.05$ on the observations to see if they are independent.

```

fnLCG3 <- function(seed = 1, n = 1)
{

```

```

rands <- rep(NA, n)
x <- seed
modVal <- (231 - 1)

for(i in 1:n)
{
  xi <- (16807 * x) %% (modVal)
  rands[i] <- xi
  x <- xi
}

return(rands)
}

n=100000
rn <- fnLCG3(1234567, n)

```

The first 6 generated numbers are shown below:

```

1422014746
456328559
849987676
681650688
1825340118
1687465831

```

Chi-Square Test

```

intervals <- 20
maxRn <- max(rn)
minRn <- min(rn)
intWidth <- (maxRn - minRn) / intervals
lwr <- minRn
dfCounts <- data.frame(intID=c(), count=c())
# Bin the data ourselves, I'd guess there
# is an easier way, but this will do.
for(i in 1:intervals)
{
  upr <- lwr + intWidth
  inRange <- rn[lwr <= rn & rn < upr]
  dfCounts <- rbind(dfCounts, data.frame(intID=i, count=length(inRange)))
  # setup for next interval range
  lwr <- upr
}
# Do our own Chi-Squared test
Expected <- (100000 / intervals)
chi2 <- sum((dfCounts$count - Expected)2 / Expected)
chi2

```

```
## [1] 14.7762
```

```

# Use built-in function to compare
chiTest <- chisq.test(dfCounts$count)
chiTest

```

```
##
```

```
## Chi-squared test for given probabilities
##
## data:  dfCounts$count
## X-squared = 14.776, df = 19, p-value = 0.7367
```

The p-value = 0.7367029 is not less than $\alpha = 0.05$, therefore we don't reject the null hypothesis that the distribution is uniform.

| intID | count |
|-------|-------|
| 1 | 5069 |
| 2 | 5028 |
| 3 | 5044 |
| 4 | 5087 |
| 5 | 4948 |
| 6 | 4953 |
| 7 | 4937 |
| 8 | 4933 |
| 9 | 4900 |
| 10 | 4957 |
| 11 | 5088 |
| 12 | 4994 |
| 13 | 5076 |
| 14 | 5019 |
| 15 | 5002 |
| 16 | 5067 |
| 17 | 4981 |
| 18 | 4914 |
| 19 | 5062 |
| 20 | 4940 |

Runs Up-and-Down Test

Using the `tseries` package, we execute the Runs test (Trapletti and Hornik, 2015). First we have to construct the +/- vector. Here we simply convert to boolean.

```
s <- rep(NA, n - 1)
for(i in 1:n - 1)
{
  s[i] <- rn[i] < rn[i + 1]
}

runsTest <- runs.test(as.factor(s))
runsTest
```

```
##
## Runs Test
##
## data:  as.factor(s)
## Standard Normal = 105.84, p-value < 2.2e-16
## alternative hypothesis: two.sided
```

Based on the p-value < 0.05, we reject the null hypothesis and conclude there is not evidence to support independence in the psuedo-random numbers.

4.

Give inverse-transforms, composition, and acceptance-rejection algorithms for generating from the following density:

$$f(x) = \begin{cases} \frac{3x^2}{2} & -1 \leq x \leq 1 \\ 0 & \text{otherwise} \end{cases}$$

Inverse-Transforms

First find the indefinite integral of the probability density function:

$$F(x) = \int \frac{3x^2}{2} dx = \frac{x^3}{2}$$

Next set $F(x) = R$ and solve for x in terms of R :

$$\frac{x^3}{2} = R$$

$$x^3 = 2R$$


$$F^{-1}(x) = \sqrt[3]{2R}$$

```
# Define a function of the F^-1(X)
invTfn4 <- function(r)
{
  vals <- (2 * r)^(1/3)
  return (vals)
}

# Generate the uniform psuedo-random vars
rVals <- runif(n, -1, 1)
# Convert to the desired distribution using the inverse transform method.
invTVals <- invTfn4(rVals)
```

```
## Warning: Removed 74997 rows containing non-finite values (stat_bin).
```

```
## Warning: Removed 2 rows containing missing values (geom_bar).
```



Acceptance-Rejection Method

```
# Helper function for the Accept/Reject approach
myRARmethod <- function(fun, min, max)
{
  M <- 2
  accepted <- FALSE
  while(!accepted)
  {
    # Get a random value from uniform distrubtion (g(x) for us)
    r <- runif(1, min, max)

    # Sample x from g(x) and u from U(0,1) (the uniform distribution over the unit interval)
    u <- runif(1, 0, 1)
    gx <- dunif(r, min, max)


    # Check whether or not u < f(x)/Mg(x).
    if(u < fun(r) / (M * gx))
    {
      accepted = TRUE
    }
  }

  return(r)
}

# Define a function for the PDF
Arfn4 <- function(x)
{
  if(-1 <= x && x <= 1)
  {
    val <- (3 * x^2) / 2
  }
  else
  {
    val = 0
  }
  return (val)
}

# Loop to generate the values
rarVals <- rep(NA, n)
for(i in 1:n)
{
  rarVals[i] <- myRARmethod(Arfn4, -1, 1)
}
```

```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```



Composition

Hmm...

5

Implement, test and compare different methods to generate from a $N(0,1)$ distribution.

$$f(x) = \frac{1}{\sqrt{2\pi}} e^{-\frac{x^2}{2}}$$

Inverse Transform Method

$$F(X) = \int \frac{1}{\sqrt{2\pi}} e^{-\frac{x^2}{2}} dx$$

It turns out the `qnorm` function is the inverse normal CDF function, so we'll use it.

```
normrandit <- function()
{
  u <- runif(1)
  return (qnorm(u))
}

itstats <- function(n)
{
  vals <- rep(NA, n)
  for(i in 1:n)
  {
    vals[i] <- normrandit()
  }

  return(list(values=vals, mean=mean(vals), sd=sd(vals)))
}


res <- itstats(10000)
res$mean
```

```
## [1] -0.005543553
```

```
res$sd
```

```
## [1] 1.003801
```

```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```



Box-Muller Method

```
normrandbm <- function()
{
  u2 <- runif(2)

  v1 <- (-2 * log(u2[1]))^(1/2) * cos(2 * pi * u2[2])
  v2 <- (-2 * log(u2[1]))^(1/2) * sin(2 * pi * u2[2])

  return (c(v1, v2))
}

bmstats <- function(n)
{
  vals <- rep(NA, n / 2)
  for(i in seq(1, n, by=2))
  {
    rs <- normrandbm()
    vals[i] <- rs[1]
    vals[i + 1] <- rs[2]
  }

  return(list(values=vals, mean=mean(vals), sd=sd(vals)))
}

resBm <- bmstats(10000)
length(resBm[[1]])
```

```
## [1] 10000
```




```
# Mean
resBm$mean
```

```
## [1] 0.00486827
```

```
# SD
resBm$sd
```

```
## [1] 1.009415
```



Accept Reject Method

```
normrandar <- function()
{
  continue <- TRUE
  while(continue)
  {
    u2 <- runif(2)
    eu2 <- - log(u2)

    if(eu2[2] >= ( (eu2[1] - 1)^2 / 2) )
    {
      break
    }
  }

  if(runif(1) > 0.5)
  {
    eu2 * -1
  }

  return(u2)
}

arstats <- function(n)
{
  vals <- rep(NA, n / 2)
```

```

for(i in seq(1, n, by=2))
{
  rs <- normrandar()
  vals[i] <- rs[1]
  vals[i + 1] <- rs[2]
}

return(list(values=vals, mean=mean(vals), sd=sd(vals)))
}

```

Compare

```

dfCompare <- data.frame(method=c(), N=c(), mean=c(), sd=c(), time=c())

perfTest <- function(fun)
{
  dfResult <- data.frame(method=c(), N=c(), mean=c(), sd=c(), time=c())
  Ns <- c(100, 1000, 10000, 100000)
  it <- 2

  for(n in Ns)
  {
    m <- rep(NA, it)
    s <- rep(NA, it)
    t <- rep(NA, it)
    for(i in 1:it)
    {
      st <- system.time({ret <- fun(n)})
      #print(st)
      m[i] <- ret$mean
      s[i] <- ret$sd
      t[i] <- st[[3]]
    }

    dfResult <- rbind(dfResult, data.frame(method=deparse(substitute(fun)),
                                           N=n,
                                           mean=mean(m),
                                           sd=mean(s),
                                           time=mean(t)))
  }

  return(dfResult)
}



# Force less use of scientific notation
# http://stackoverflow.com/questions/9397664/force-r-not-to-use-exponential-notation-e-g-e10
options("scipen"=100, "digits"=5)


dfCompare <- rbind(dfCompare, perfTest(itstats))
dfCompare <- rbind(dfCompare, perfTest(bmstats))
dfCompare <- rbind(dfCompare, perfTest(arstats))

```

| method | N | mean | sd | time |
|---------|--------|----------|---------|-------|
| itstats | 100 | 0.02481 | 0.90215 | 0.010 |
| itstats | 1000 | -0.01185 | 0.96086 | 0.020 |
| itstats | 10000 | 0.00391 | 1.00094 | 0.130 |
| itstats | 100000 | -0.00350 | 0.99954 | 1.240 |
| bmstats | 100 | -0.00982 | 0.96226 | 0.000 |

| method | N | mean | sd | time |
|---------|--------|----------|---------|--------|
| bmstats | 1000 | 0.00911 | 0.99064 | 0.015 |
| bmstats | 10000 | 0.00700 | 1.00040 | 0.295 |
| bmstats | 100000 | -0.00163 | 0.99798 | 30.380 |
| arstats | 100 | 0.47723 | 0.26306 | 0.010 |
| arstats | 1000 | 0.46741 | 0.25677 | 0.015 |
| arstats | 10000 | 0.47052 | 0.25735 | 0.320 |
| arstats | 100000 | 0.47091 | 0.25904 | 30.775 |





References

Trapletti, A. and K. Hornik. tseries: Time Series Analysis and Computational Finance. R package version 0.10-34. 2015.
URL: <http://CRAN.R-project.org/package=tseries>.