

WEEK 3: TEXT MINING I

SECU0057

BENNETT KLEINBERG

30 JAN 2020

Applied Data Science

WEEK 3: TEXT MINING 1

TODAY

- text quantification
- numerical representations



TEXT IS EVERYWHERE ...

- Practically all websites
- Emails
- Messaging
- Government reports
- Laws
- Police reports
- Uni coursework
- Newspapers

... AND EVERYTHING IS TEXT

- videos -> transcripts
- music -> lyrics
- conversations -> transcripts
- speeches -> transcripts

CORE IDEA

Text is a unique documentation of human activity.

We are obsessed with documenting.

TEXT EXAMPLE

How would you analyse the text?

EXAMPLE

All I ever wanted was to love women, and in turn to be loved by them back. Their behavior towards me has only earned my hatred, and rightfully so! I am the true victim in all of this. I am the good guy. Humanity struck at me first by condemning me to experience so much suffering. I didn't ask for this. I didn't want this. I didn't start this war. I wasn't the one who struck first. But I will finish it by striking back. I will punish everyone. And it will be beautiful. Finally, at long last, I can show the world my true worth.

CHALLENGE OF QUANTIFICATION

- text is not a numerical representation
- compare this to trading data, crime statistics, etc.
- text is just that, “a text”
- but: for quantitative analyses, we need numbers

Text → numerical representation?

FEATURES OF TEXT DATA

- meta dimension
- syntactic dimension
- semantic dimension
- text metrics

META DIMENSION

- no. of words
- no. of sentences

SYNTACTIC DIMENSION

- word frequencies
- verbs, nouns, persons, locations, ..
- structure of a sentence

SEMANTIC DIMENSION

- sentiment
- psycholinguistic features

TEXT METRICS

- readability
- lexical diversity

THE QUANTEDA PACKAGE

```
library(quanteda)
```

- quanteda: Quantitative Analysis of Textual Data
 - documentation
 - tutorials
 - examples

LEVELS OF TEXT DATA

- characters `c('h', 'a', 't', 'r', 'e', 'd')`
- words `hatred`
- sentences `I didn't ask for this.`
- documents: individual text files
- corpora: collection of documents

COUNTING META FEATURES IN R

text level	R function
characters	<code>nchar ()</code>
words	<code>quanteda::ntoken ()</code>
sentences	<code>quanteda::nsentence ()</code>

R EXAMPLES

```
#sentences  
no_of_sentences = nsentence(er)  
no_of_sentences
```

```
## text1  
##      13
```

```
#words 1  
no_of_words_1 = ntoken(er)  
no_of_words_1
```

```
## text1  
##      123
```

```
#words 2  
no_of_words_2 = ntype(er)  
no_of_words_2
```

```
## text1  
##      72
```

TYPE-TOKE RATIO

Note: often used metric for “lexical diversity” is the TTR (type-token ratio).

```
string_a = "I didn't ask for this. I didn't want this."  
string_b = "But I will finish it by striking back."
```

What are the type-token ratios of each string?

TYPE-TOKEN RATIO

```
ntype(string_a)/ntoken(string_a)
```

```
##      text1  
## 0.6363636
```

```
ntype(string_b)/ntoken(string_b)
```

```
## text1  
##      1
```

CHARACTERS PER WORD

```
nchar(er)/ntoken(er)
```

```
##      text1  
## 4.317073
```

WORDS PER SENTENCE

```
ntoken(er)/nsentence(er)
```

```
##      text1  
## 9.461538
```


TEXT REPRESENTATION

AIM

- representing a text by its tokens (terms)
- each text consists of a frequency of its tokens

```
"I think I believe him"
```

TEXT REPRESENTATION BY HAND

1. create a column for each token
2. count the frequency

text_id	I	think	believe	him
text1	2	1	1	1

TERM FREQUENCY

- frequency of each token in each document
- represented in a table (matrix)
- tokens are features of a document
- voilà: **Document Feature Matrix (= DFM)**

```
example_string_tok = tokens("I think I believe him")
```

DFM IN QUANTEDA

- from 'tokens' object, create a DFM table

```
dfm(example_string_tok)
```

```
## Document-feature matrix of: 1 document, 4 features (0% sparse).  
## 1 x 4 sparse Matrix of class "dfm"  
##           features  
## docs      i think believe him  
## text1 2      1          1    1
```

SPARSITY

Sparsity = % of zero-cells

- Why is sparsity = 0% here?
- What would you expect if we take additional documents, and why?

DFM WITH MULTIPLE DOCUMENTS

```
multiple_docs_tok = tokens(c("I think I believe him", "This is a cool fun
```

```
dfm(multiple_docs_tok)
```

```
## Document-feature matrix of: 2 documents, 9 features (50% sparse).  
## 2 x 9 sparse Matrix of class "dfm"  
##           features  
## docs      i think believe him this is a cool function  
## text1 2      1      1      1      0  0  0      0      0  
## text2 0      0      0      0      1  1  1      1      1
```


DFM WITH TWO LONE-ACTORS

All I ever wanted was to love women, and in turn to be loved by them back. Their behavior towards me has only earned my hatred, and rightfully so! I am the true victim in all of this. I am the good guy. Humanity struck at me first by condemning me to experience so much suffering. I didn't ask for this. I didn't want this. I didn't start this war. I wasn't the one who struck first. But I will finish it by striking back. I will punish everyone. And it will be beautiful. Finally, at long last, I can show the world my true worth.

DFM WITH TWO TEXTS

The Industrial Revolution and its consequences have been a disaster for the human race. They have greatly increased the life-expectancy of those of us who live in “advanced” countries, but they have destabilized society, have made life unfulfilling, have subjected human beings to indignities, have led to widespread psychological suffering (in the Third World to physical suffering as well) and have inflicted severe damage on the natural world. The continued development of technology will worsen the situation.

USING THE CORPUS METHOD

- Create a “mini corpus” for convenience
- makes using the quanteda pipeline easier

```
mini_corpus = corpus(c(er, ub))  
summary(mini_corpus)
```

```
## Corpus consisting of 2 documents:  
##  
##   Text  Types  Tokens  Sentences  
##   text1    72    123         13  
##   text2    63     88          3  
##  
## Source: /Users/bennettkleinberg/GitHub/UCL_SECU0057/lectures/week_3/*  
## Created: Thu Jan 30 06:39:31 2020  
## Notes:
```

DFM REPRESENTATION

```
corpus_tokenised = tokens(mini_corpus)
corpus_dfm = dfm(corpus_tokenised)
```

document	all	i	ever	wanted	was	to	love	women
text1	2	10	1	1	1	3	1	1
text2	0	0	0	0	0	3	0	0

document	am	the	true	victim	of	this	good	guy
text1	2	4	2	1	1	4	1	1
text2	0	7	0	0	3	0	0	0

Is this ideal?

WHAT ARE THE MOST FREQUENT “TERMS”?

```
topfeatures(corpus_dfm[1])
```

```
##      .      i      ,      the    this    to      and      by      me  didn't  
##     12     10      4       4      4      3       3       3       3      3
```

```
topfeatures(corpus_dfm[2])
```

```
##      the      have      ,      to      .      of      and  
##       7       7       4       3       3       3       2  
##     in suffering    world  
##      2       2       2
```

ZIPF'S LAW



THE OF AND TO A IN IS I THAT IT FOR YOU WAS WITH ON AS HAVE BUT BE THEY



The Zipf Mystery

13,315,384 views

340K 3.7K SHARE SAVE ...

WORD HIERARCHIES

- some words add more meaning than others
- stopwords = meaningless (?)
- in any case: too frequent words, don't tell much about the documents
- ideally: we want to get an *importance score* for each word

WORD IMPORTANCE

document	and	in	turn	be	loved	by
text1	3	2	1	2	1	3
text2	2	2	0	0	0	0

We want to “reward” words that are:

- important locally (for individual documents)
- but not ‘inflated’ globally (for the whole corpus)

METRIC FOR WORD IMPORTANCE: TERM FREQUENCY

- $tf(t, d) = \frac{\#_{t,d}}{nwords_d}$ (proportion)
- $tf(t, d) = \#_-(t, d)$ (count)

PROPORTIONS

document	and	in	turn	be	loved	by
text1	0.024	0.016	0.008	0.016	0.008	0.024
text2	0.023	0.023	0.000	0.000	0.000	0.000

COUNTS

document	and	in	turn	be	loved	by
text1	3	2	1	2	1	3
text2	2	2	0	0	0	0

DOUBLE-CHECK THE FORMULAE

- $tf(t, d) = \frac{\#_{t,d}}{nwords_d}$
- $tf(t, d) = \#_{-}(t, d)$

```
3/ntoken(mini_corpus[1])
```

```
##      text1  
## 0.02439024
```

Term frequency: *reward for words that occur often in a document*

PROBLEM


Some words just occur a lot anyway (e.g. “stop words”).

Global occurrence: document frequency

	x
and	2
in	2
turn	1
be	1
loved	1
by	1

$$df(t) = \# \text{ of docs with } t$$

DF



CORRECTING FOR TERM INFLATION


- we want: low values for common words
- and: higher values for *important* words

Trick: *inverse* document-frequency

INVERSE DF (IDF)


$$idf(t) = \frac{N}{df(t)}$$

IDF



PROBLEM?

- What happens if N becomes really large?



LOG IDF

- to avoid extreme values, we use the logarithm
- simple transformation: $idf(t) = \log(\frac{N}{df(t)+1})$

ABOUT LOGARITHMS

$$\log_b(a) = c \iff b^c = a$$


“the power to which {base b} would have to be raised to equal
a”

$$\log_2(8) = ? \rightarrow 2^? = 8$$


LOGARITHM BASES

- natural logarithm: base $e = 2.718281\dots$
- base 10 logarithm: $\log_{10}(x)$

Logarithm with base e, 2, and 10



LOG IDF



COMBINING TERM FREQUENCY AND DOCUMENT FREQUENCY

1. Local importance (TF)

document	and	in	turn
text1	3	2	1
text2	2	2	0

2. Correct for global occurrences (DF)

	x
and	-0.1760913
in	-0.1760913
turn	0.0000000

TF/IDF

```
#text1: "and"  
3/-0.1760913
```

```
#text2: "and"  
2/-0.1760913
```

TF-IDF

TF-IDF

TF-IDF is a measure of originality of a word by comparing the number of times a word appears in a doc with the number of docs the word appears in.

$$\text{TF-IDF} = \text{TF}(t, d) \times \text{IDF}(t)$$

Term frequency

Number of times term t appears in a doc, d

Inverse document frequency

$$\log \frac{1 + \overset{\text{\# of documents}}{n}}{1 + \underset{\text{Document frequency of the term } t}{df(d, t)}}$$

WORKING WITH TEXT AS DATA

RESEARCHER'S DEGREES OF FREEDOM

- stop word removal
- stemming

STOPWORD REMOVAL

- We know many words are “low in meaning”
- so-called stop words

x
i
me
my
myself
we
hers
herself
it
its
itself
they

WITHOUT STOPWORD REMOVAL

document	all	i	ever	wanted	was	to	love	women
text1	2	10	1	1	1	3	1	1
text2	0	0	0	0	0	3	0	0

WITH STOPWORD REMOVAL

document	ever	wanted	love	women	,	turn	loved	back
text1	1	1	1	1	4	1	1	2
text2	0	0	0	0	4	0	0	0

STEMMING

- some words originate from the same “stem”
- e.g. “love”, “loved”, “loving”, “lovely”
- but you might want to reduce all these to the stem

WORD STEMS

```
love_stem = c("love", "loved", "loving", "lovely")
```

document	love	loved	loving	lovely
text1	1	0	0	0
text2	0	1	0	0
text3	0	0	1	0
text4	0	0	0	1

AFTER STEMMING

document	love
text1	1
text2	1
text3	1
text4	1

OUR MINI CORPUS

Incl. stop words and without stemming:

document	all	i	ever	wanted	was	to	love	women
text1	2	10	1	1	1	3	1	1
text2	0	0	0	0	0	3	0	0

... TO

Without stop words and stemmed:

document	ever	want	love	women	,	turn	back	.
text1	1	2	2	1	4	1	2	12
text2	0	0	0	0	4	0	0	3

CONSIDERATIONS WITH TEXT DATA

- a lot of assumptions
- text == behaviour?
- produced text == displayed text?
- many decisions in your hand
 - stemming
 - stopwords
 - custom dictionary

WHAT'S NEXT?

- Today's tutorial: analysing speeches by US presidents, examining UK rap lyrics
- Homework: quanteda practice, text preprocessing

Next week: Text Mining 2