

# Network and Spatial Analyses

4. March 2020

## Lecture:

### Introduction to Graph Theory II.

- Random Networks
- Small World Networks
- Scale-free and Barabasi Model

## Seminar:


### Network measures and plots in R

Course Github page: [https://github.com/bokae/anet\\_course](https://github.com/bokae/anet_course)






## Eulerian and Hamiltonian path



Arokhlo et al. (2011).


[10.1007/978-3-642-23938-0\\_10](https://doi.org/10.1007/978-3-642-23938-0_10)



- Random Network Model
- Degree Distribution
- Small Worlds
- Power Laws and Scale-Free Networks
- Barabasi-Albert Model

Graphs, tables and pictures from Barabási, A. L. (2016). Network science. Cambridge university press. if we don't indicate differently!

# Random Network



# Random Network

$G(N,L)$ : have  $N$  number of nodes connected by  $L$  number of random connections.

Erdős-Rényi network

$G(N,p)$ : Between each pair of  $N_i$  and  $N_j$  there is a probability ( $p$ ) of connection.

Gilbert


$G(N,p)$  model fixes the probability of connections, while the  $G(N,L)$  fixes the total number of connections in the network.

In  $G(N,L)$  model the average degree easily calculable:  $\langle k \rangle = \frac{2L}{N}$ , but the number of connections are rarely fixed, so in other cases we use the  $G(N,p)$  model.

Pál Erdős

Alfréd Rényi

“A mathematician is a device for turning coffee into theorems”





Find the path between two authors:

Gergo Tóth

Paul Erdős

**Gergo Tóth**

co-authored 1 paper with

János Kertész

co-authored 3 papers with

András Kornai

co-authored 1 paper with

Zsolt Tuza

co-authored 7 papers with

**Paul Erdős**

**distance = 4**

How many handshakes away from Obama?



# Random Network

$G(N,p)$ : Between each pair of  $N_i$  and  $N_j$  there is a probability ( $p$ ) of connection.

Each random network will be different regardless they have the same parameter  $N$  and  $p$ . Not only the visualization of the graph changes, but so does the number of connections  $L$ .

The probability of  $L$  attempts resulted in a connection is  $p^L$ .

The probability of remaining  $N(N-1)/2 - L$  attempts have not resulted in a connection:  $(1-p)^{N(N-1)/2 - L}$

So, the number of different way we can replace  $L$  number of link between  $N(N-1)/2$  number of node pairs is:  $\binom{N(N-1)/2}{L}$



# Random Network

So we can add the probability of the realization of the a random network gives L number of links by:

$$p_L = \binom{\frac{N(N-1)}{2}}{L} p^L (1-p)^{\frac{N(N-1)}{2}-L}$$

Then the expected number of links in a random graph is:

$$\langle L \rangle = \sum_{L=0}^{\frac{N(N-1)}{2}} L p_L = p \frac{N(N-1)}{2}$$

Hence, the expected number of links is a produce of the probability and number of pairs we try to connect, which is  $L_{max} = N(N-1)/2$ .





Similarly, to get the average degree:  $\langle k \rangle = \frac{2\langle L \rangle}{N} = p(N-1)$

The binomial distribution has a form of:


$$p_x = \binom{N}{x} p^x (1-p)^{N-x}$$

The first moment of the distribution:


$$\langle x \rangle = \sum_{x=0}^N x p_x = Np$$



.....



.....



.....

# Random Network


How many different random graph can we describe with the same number of links?


Turn into a combinatorial question: how many ways can we put  $L$  number of connection on  $L_{max}$  places?

The first link of the sequence can be placed on  $L_{max}$  places, the second one  $L_{max}-1$ , the third one to  $L_{max}-2$  places...  $L_{max} > (L_{max}-1)(L_{max}-2)...(L_{max}-L+1)$ .

We have to divide the result by the number of different sequences, which is  $L!$

$$\frac{L_{max}(L_{max}-1)(L_{max}-2)...(L_{max}-L+1)}{L!} = \frac{L_{max}!}{L!(L_{max}-L)!} = \binom{L_{max}}{L}$$





# Real Networks are not Poisson


According to sociological estimations an average person knows ~1000 individuals on first name bases, so  $\langle k \rangle = 1000$ .

By using the random network properties we can estimate that, in this random society the estimated  $k_{\max} = 1185$ , while the  $k_{\min} = 816$ .

The dispersion of this random network is  $\sigma_k = \langle k \rangle^{1/2}$ , which for  $\langle k \rangle = 1000$  is  $\sigma_k = 31.62$ .

So friendships should ranging from 968 to 1032.  $\langle k \rangle \pm \sigma_k$

# Real Networks are not Poisson






Why are Hubs missing?

$k! \approx [\sqrt{2\pi k}] \left(\frac{k}{e}\right)^k$ , which allows us to rewrite the original approximation to:

$$p_k = \frac{e^{-\langle k \rangle}}{\sqrt{2\pi k}} \left(\frac{e\langle k \rangle}{k}\right)^k$$

, which predicts the chances of observing a node with high number connections decreases faster than exponentially!






# Evolution of a Random Network

We have two extreme cases:

- $p = 0$ , all the nodes are isolated, then the largest component  $N_G = 1$  and  $N_G/N$  tends to 0.
- $p = 1$ , therefore  $\langle k \rangle = N-1$ , then the network is a complete graph and all nodes belong to the giant component  $N_G = N$ , thus  $N_G/N = 1$ .



$$p > n^{-1}$$

The graph becomes a connected Giant Component

# Evolution of a Random Network

We have two extreme cases:

- $p = 0$ , all the nodes are isolated, then the largest component  $N_G = 1$  and  $N_G/N$  tends to 0.
- $p = 1$ , therefore  $\langle k \rangle = N-1$ , then the network is a complete graph and all nodes belong to the giant component  $N_G = N$ , thus  $N_G/N = 1$ .


Once  $\langle k \rangle$  exceeds a critical value  $N_G/N$  increases, which means that a large cluster - what we call as a Giant Component - emerges.

Critical point:  $\langle k \rangle = 1$

Subcritical regime :  $0 < \langle k \rangle < 1$

Supercritical:  $\langle k \rangle > 1$

Connected Regime:  $\langle k \rangle > \ln N$



# Real Networks are Supercritical

Critical point:  $\langle k \rangle = 1$


Subcritical regime :  $0 < \langle k \rangle < 1$

Supercritical:  $\langle k \rangle > 1$

Connected Regime:  $\langle k \rangle > \ln N$

Network	N	L	$\langle K \rangle$	$\ln N$
Internet	192,244	609,066	6.34	12.17
Power Grid	4,941	6,594	2.67	8.51
Science Collaboration	23,133	94,437	8.08	10.05
Actor Network	702,388	29,397,908	83.71	13.46
Protein Interactions	2,018	2,930	2.90	7.61

# Real Networks are Supercritical





# Small World Networks

Six degrees of separation.

The distance between two randomly chosen node is short.

- What does short mean?
- Short compare to what?

Consider a random network with average degree of  $\langle k \rangle$ , then a node has on average:

- $\langle k \rangle$  nodes at distance  $d=1$ ,
- $\langle k \rangle^2$  nodes at distance  $d=2$
- ...
- $\langle k \rangle^d$  nodes at distance  $d$ .
- 

So if we assume that a social network has a  $\langle k \rangle \sim 1000$ , then we know  $10^6$  people at  $d=2$ , and the whole earth population is at  $d=3$ .

# Small World Networks

The expected number of nodes in distance  $d$  from a randomly chosen node is:

$$N(d) = 1 + \langle k \rangle + \langle k^2 \rangle + \dots + \langle k^d \rangle = \frac{\langle k \rangle^{d+1}}{\langle k \rangle - 1}$$

$N(d)$  must be within the range of total number of nodes. Therefore we can identify the maximum distance in the network, which is the network's diameter:

$$N(d_{max}) \approx N$$


If we assume  $\langle k \rangle \gg 1$  then we can neglect the  $\pm 1$  in the fraction, obtaining:

$$\langle k \rangle^{d_{max}} \approx N$$

Therefore, the diameter of a random network can be approximated by:

$$d_{max} \approx \frac{\ln N}{\ln \langle k \rangle} \longmapsto \langle d \rangle \approx \frac{\ln N}{\ln \langle k \rangle}$$

Network	N	L	$\langle k \rangle$	$\langle d \rangle$	$d_{\max}$	$\ln N / \ln \langle k \rangle$
Internet	192,244	609,066	6.34	6.98	26	6.58
WWW	325,729	1,497,134	4.60	11.27	93	8.31
Power Grid	4,941	6,594	2.67	18.99	46	8.66
Mobile-Phone Calls	36,595	91,826	2.51	11.72	39	11.42
Email	57,194	103,731	1.81	5.88	18	18.4
Science Collaboration	23,133	93,437	8.08	5.35	15	4.81
Actor Network	702,388	29,397,908	83.71	3.91	14	3.04
Citation Network	449,673	4,707,958	10.43	11.21	42	5.55
E. Coli Metabolism	1,039	5,802	5.58	2.98	8	4.04
Protein Interactions	2,018	2,930	2.90	5.61	14	7.14



# Small World Networks

## Clustering Coefficient

Degree of a node does not include information about the neighbors of the node. Local clustering measures the density of connections between the immediate neighbors of the ego. In a random network to calculate  $C_i$ , first we need to know the expected number of a links of the ego network of  $i$ :


$$\langle L_i \rangle = p \frac{k_i(k_i-1)}{2}$$

Thus, the local clustering coefficient in a random network can be expressed by:


$$C_i = \frac{2\langle L_i \rangle}{k_i(k_i-1)} = p = \frac{\langle k \rangle}{N}$$

- If we fix  $\langle k \rangle$ , the larger the network, the smaller is the node's local clustering.
- Local clustering coefficient of a node is independent from the number of connections of the node.


**b. Internet**




**c. Science Collaboration**



**d. Protein Interactions**



**a. All Networks**



- Looking on real life networks,  $\langle C \rangle / \langle k \rangle$  does not decrease as  $N^{-1}$
- Real network has a much higher clustering coefficient than corresponding random  $G(N, L)$

# Small World Networks

## Watts-Strogatz Model

What gives the word *small* in Small World Networks?

In real networks the average distance between two points is a logarithmic function of  $N$ .


What makes it a real life network?

The average clustering coefficient of a real network is much higher than we would expect from a random network with the same properties of  $N$  and  $L$ .




**a.**

REGULAR




**b.**

SMALL-WORLD



**c.**

RANDOM




$p = 0$




$p = 1$

Increasing randomness





d.












# Scale-Free Networks

If the network of WWW was to be a random network then the degree distribution should follow Poisson distribution.

But it follows a power law distribution, with the exponent of gamma:  $p_k = k^{-\gamma}$   
Take the logarithm, we obtain:  $\log p_k = -\gamma \log k$



# Scale-Free Networks

In discrete formalization of the degree distribution we provide a probability the node has exactly  $k$  links:  $p_k = Ck^{-\gamma}$

,where  $C$  is a normalizing condition.  $\sum_{k=1}^{\infty} = 1 = C \sum_{k=1}^{\infty} k^{-\gamma}$

$$C = \frac{1}{\sum_{k=1}^{\infty} k^{-\gamma}} = \frac{1}{\zeta(\gamma)}$$

Thus, with  $k > 0$  case discrete power-law distribution can be expressed by:  $p_k = \frac{k^{-\gamma}}{\zeta(\gamma)}$

# Scale-Free Networks

In discrete formalization of the degree distribution we provide a probability the node has exactly  $k$  links:  $p_k = Ck^{-\gamma}$

,where  $C$  is a normalizing condition.  $\sum_{k=1}^{\infty} = 1 = C \sum_{k=1}^{\infty} k^{-\gamma}$

$$C = \frac{1}{\sum_{k=1}^{\infty} k^{-\gamma}} = \frac{1}{\zeta(\gamma)}$$

Thus, with  $k > 0$  case discrete power-law distribution can be expressed by:  $p_k = \frac{k^{-\gamma}}{\zeta(\gamma)}$





So let's assume that the degrees can form any positive real number, so we rewrite the power-law distribution as an integral:  $p(k) = Ck^{-\gamma}$


by normalizing we obtain the integrate of a continuum:  $\int_{k_{min}}^{\infty} p(k)dk = 1$

,where  $C = \frac{1}{\int_{k_{min}}^{\infty} k^{-\gamma} dk} = (\gamma - 1)k_{min}^{\gamma-1}$


Thus, in continuous case the degree distribution can be expressed as:  $\int_{k_1}^{k_2} p(k)dk$








**a.** POISSON



**b.**



**c.** POWER LAW



**d.**



# Scale-Free Networks - Why do we have Hubs?

## The Barabasi-Albert Model

*For to every one who has will more be given, and he will have abundance; but from him who has not, even what he has will be taken away.*

— Matthew 25:29, RSV.

### Growth

Real networks are getting larger and larger as a result of a growth process. While in random networks we usually have fixed  $N$ .

### Preferential Attachment


In real networks nodes tend to connect to the more connected nodes.




# Scale-Free Networks - Why do we have Hubs?

At each step we add new node to the network, with links connect to nodes already in the network.

The probability of that a link of a new node connected to a present node is depends on the degree of the node:  $\Pi(k_i) = \frac{k_i}{\sum_j k_j}$





The dashed line refers to the linear preferential attachment, while the solid lines shows the absence of preferential attachment.

Cumulative preferential attachment:

$$\pi(k) = \sum_{k_i=0}^k \Pi(k_i)$$

Likelihood to connect to a node depends on the degree of the node!